

Machine Learning for Probabilistic Robotics with Webots

Joan Gerard¹
Promotor: Prof. Gianluca Bontempi ¹

¹Université Libre de Bruxelles

March 9, 2019

Table of Contents

Probabilistic Robotics

Webots

Project Objectives

First Steps

Restuls

Table of Contents

Probabilistic Robotics

Webots

Project Objectives

First Steps

Restuls

Robot Positioning Problem

- ▶ A robot needs to deal with uncertainty most of the time.
- ▶ It needs to predict and preserve its current position and orientation within the environment.

Robot Positioning Problem

- ▶ Navigation is about controlling and operating the course of a robot and it is one of the most challenging skills that a mobile robot needs to master in order to successfully moving through the environment.
- ▶ Succeeding in navigation means to succeed likewise in:
 - ▶ Sense
 - ▶ Localization
 - ▶ Cognition
 - ▶ Control Action


Robot Positioning Problem

- ▶ Local Robot Positioning (position tracking): The robot knows its initial position.
- ▶ Global Robot Positioning: The robot does not know its initial position and it is able to estimate it even in a global uncertainty. Ex. Kidnapped robot problem.




Bayes Filter

▶ Prediction




▶ Error Correction



Particles Filter

- ▶ Each particle has a state (x, y, θ) and a weight.
- ▶ The weight is an indicator of how close the particle's state is to the real state.



Particles Filter Algorithm

- ▶ Train/test a prediction model: robot state → distance sensor data
- ▶ Compare it with the true sensor data and determine a weight for each particle
- ▶ More close to the real sensor data more weight will have

```
input : particles, controlAction, sensorData
output: nextParticles
1 nextParticles ← ∅
2 foreach particle ∈ particles do
3     particle.state ← predictState(particle.state, controlAction)
4     particle.weight ← calculateWeight(particle.state, sensorData)
5 end
6 for m = 1 to m = |particles| do
7     newParticle ← draw i from particles with probability ∝ particles[i].weight
8     nextParticles.add(newParticle)
9 end
```

Table of Contents

Probabilistic Robotics

Webots

Project Objectives

First Steps

Restuls

What is Webots?

- ▶ Tool for simulating robots in virtual environments
- ▶ Open Source
- ▶ Python, C++, Java, etc.
- ▶ 44 robot models
- ▶ Robot model creation/customization
- ▶ Robust documentation




Table of Contents

Probabilistic Robotics

Webots

Project Objectives

First Steps

Restuls

Main Objective

- ▶ The objective will be to exploit the simulation benefits of Webots to introduce Machine Learning techniques together with non-parametric filters (such as Particles Filter) for robot positioning estimation for in-door environments.

Table of Contents

Probabilistic Robotics

Webots



Project Objectives

First Steps

Restuls

Problem Formulation

- ▶ There is a robot with 8 laser sensors around it.
- ▶ The sensors measure the distance between the robot and the closest object.
- ▶ There is an arena of 2x1.5m with four walls.
- ▶ The robot has odometry data available.
- ▶ The robot is positioned at the middle of the arena and it knows its initial position.
- ▶ The robot needs to track its position.



Solution Approach

- ▶ Capture data with the simulator.
 - ▶ True robot position (x, y, θ) .
 - ▶ Sensor measurements (s_1, s_2, \dots, s_8) .
- ▶ Train ML Models
 - ▶ Train 8 neural networks that receives the true robot position as input and returns the estimated sensor measurements.
- ▶ Put the particles filter together with the ML Models to get the robot position estimation.
- ▶ Correct the position of the robot using the robot position estimation.

Capture data with the simulator

- ▶ Robot turns with a probability of 0.2; otherwise, it goes straight.
- ▶ Robot turns randomly to left or right maximum 30 degrees.
- ▶ Robot avoids colliding with the walls.
- ▶ Data is capture each 20 robot steps.

Train ML Models

- ▶ The data is normalized and shuffled.
- ▶ Many NN architectures were tested. The one that gave better results was:
 - ▶ Input Layer: 3 neurons
 - ▶ Intermediate Layer: Fully connected with 10 neurons
 - ▶ Intermediate Layer: Fully connected with 6 neurons
 - ▶ Intermediate Layer: Fully connected with 3 neurons
 - ▶ Output Layer: 1 neuron

Particles Filter + ML Model

input : robotState (deltaMove), sensorsData
output: particles

```
1 particles.state = particles.state + deltaMove
2 addRandomMove(particles.state)
3 foreach particle in particles do
4   |   particle.weight  $\leftarrow$  predictError(particle.state, sensorsData)
5 end
6 normalizeWeights(particles)
7 particles = resamplingBasedOnWeights(prob=particles.weight,
  replace=True)
8 return particles
```

Correction Step

- ▶ Take the average weighted state of all the particles.
- ▶ This value becomes the estimated state of the robot.
- ▶ Apply the correction step at each robot step.

Table of Contents

Probabilistic Robotics


Webots

Project Objectives

First Steps

Restuls


► 1000 particles used.



Drawbacks

- ▶ The problem requires to train 8 models which is time consuming.
- ▶ It does not generalize for unseen environments.
- ▶ The particle's filter algorithm works slow for a big amount of particles.

Any question?



(Suggestions and critics are also welcomed)