

Quantum Homomorphic Encryption

By

Joan Watiri Ngure (njoan@aims.ac.rw)
African Institute for Mathematical Sciences (AIMS), Rwanda

Supervised by: Professor Barry C Sanders
University of Calgary, Canada

June 2018

*AN ESSAY PRESENTED TO AIMS RWANDA IN PARTIAL FULFILMENT OF THE REQUIREMENTS FOR THE AWARD OF
MASTER OF SCIENCE IN MATHEMATICAL SCIENCES*



AIMS

African Institute for
Mathematical Sciences
RWANDA

7 **Contents**

8	1 Applications	1
9	1.1 The Airport Example	1

1. Applications

In this chapter we will discuss an example of a place where Quantum Homomorphic Encryption can be used.

1.1 The Airport Example

1.1.1 Problem Definition. We want to detect unauthorized personnel accessing distinguished places in the airport. We do not trust the server since it can be interfered with and information changed hence we are unable to detect the unauthorized personnel. The server may also decide to be malicious and relay the wrong information.

1.1.2 Requirements. We will require CCTV cameras, a client who is classical and requires to request services of a quantum computer.

1.1.3 How it works. The CCTV cameras relay images to the client on real time. The client encrypts the face images received. The encrypted images are sent to the server. The server has the face images of authorized persons which are also encrypted. The server performs face recognition on the encrypted images. The server knows the computation it is performing since in Homomorphic Encryption the computation is not encrypted. If an image does not match the images they have, then an encrypted intrusion message is produced. The server does not know what the output is. The message is sent to the doors and the security. The doors are supposed to automatically close and the security is supposed to immediately appear on the scene.

If a message is only sent when an intruder is detected then this may reveal some information to the server. A message has to be sent to the doors and security all the time. In case no intruder is detected then the doors should remain open and the security should not appear.

The CCTV should also be placed in locations where a face can be clearly captured and is unknown to the public since some clever people may decide to interfere with it. The output of the server should not also be a single quantum bit for example $|0\rangle$ when an intruder is detected and $|1\rangle$ for an authorized personnel. This same clever person could flip the bit when it is being relayed. As we saw earlier, a quantum state cannot be cloned because cloning involves measurement and measurement changes the state.

1.1.4 Why does the client require services of the server in this example. An airport is automatically large and the number of authorized personnel in different departments and sections are also many. The client requires storage facilities. The client does not have the capability of performing face recognition on a very large number of images. This computation requires high processing power and speed which the client does not possess.

Fig1.1 shows the model




Figure 1.1: The Airport Model

1.1.5 Assumptions made in this model.. There are few assumptions made while building this model. The server has the ability to perform face recognition on encrypted face images. Since the output options are two, whether an authorized person or an intruder then different encryptions to represent each of them are produced at different times.

1.1.6 Python code for the model. The following is a python code using face recognition module in Python. The code uses two images. One is the image of the authorized personnel while the other is relayed image. In the code the images are not encrypted but we assume in the quantum server they are encrypted. The program uses RSA a module that produces a private key and public key. The public key encrypts the message and the private key decrypts it. In the code the output is encrypted after performing face recognition. The encrypted code is the sent to the classical client operating the doors and to the security. They are prompted to enter their private codes known only to them. The message is then decrypted and they can act accordingly. In case a wrong code is entered then two more chances are given after which the system automatically blocks.

```
import dlib
```

```
58 import face_recognition
59 from Crypto.PublicKey import RSA
60 from Crypto import Random
61
62 #This is a face recognition model.
63
64 #Key generation.
65 rand = Random.new().read
66 private_key = RSA.generate(1280, rand)
67 public_key = private_key.publickey()
68
69 def face():
70
71 #The inputFace is compared with the target face to see whether they images represent sa
72
73 targetFace = face_recognition.load_image_file('/home/joan/joan/pythoncode/jj.jpg')
74 encodedFace = face_recognition.face_encodings(targetFace)[0]
75
76 inputFace = face_recognition.load_image_file("/home/joan/joan/pythoncode/DigitalPhoto.j
77 encodedInputFace = face_recognition.face_encodings(inputFace)[0]
78
79 outPut = face_recognition.compare_faces([encodedFace ], encodedInputFace)
80
81 u = "The face matches!"
82 l = "No match!"
83
84 if outPut [0] == True:
85 a = u
86 else:
87 a = l
88 return a
89
90 def encrypt():
91
92 #Here the message encryption is performed based on the results of face()
93
94 a = face()
95 k = public_key.encrypt('Intruder detected'.encode('utf-8'),10)
96 p = public_key.encrypt('Correct authentication'.encode('utf-8'),10)
97
98 if a == "The face matches":
99
100 enc_data = k
101
102 else:
```

```
103 enc_data = p
104
105 return enc_data
106
107
108 def decrypt():
109
110     #Decryption of the results from encrypt() are done.
111
112     b = encrypt()
113     privateKey = int(input('Please enter your password and press enter'))
114     attempts = 1
115     chances = 3
116
117     if privateKey == 3045:
118
119         raw_text = private_key.decrypt(b)
120         print (raw_text)
121     else:
122
123         print('Wrong password')
124
125     while attempts < 3 :
126         chances -=1
127         attempts +=1
128         att = int(input('Attempt %d, you have %d chances left : ' %(attempts, chances)))
129         if att == 3045:
130
131             raw_text = private_key.decrypt(b)
132             print (raw_text)
133         else :
134             print ('Wrong password')
135
136     print ('You have been blocked from the system!')
137
138     if __name__ == '__main__':
139
140         print('Recognizing face .....')
141         print (face())
142
143         print('Encrypting .....')
144         print(encrypt())
145
146         print('Decrypting .....')
147         print(decrypt())
```

148 **1.1.7 Limitation of this model.** This model poses one major limitation which is very vital. In
149 case a wrong code is entered three times the system automatically blocks. This implies that the
150 required action is not taken for example doors closing. If doors are not closed the intruder may
151 get away before the security get to the specific location.

References

- Stefanie Barz, Elham Kashefi, Anne Broadbent, Joseph F Fitzsimons, Anton Zeilinger, and Philip Walther. Demonstration of blind quantum computing. *Science*, 335(6066):303–308, 2012.
- Michael J Bremner, Richard Jozsa, and Dan J Shepherd. Classical simulation of commuting quantum computations implies collapse of the polynomial hierarchy. In *Proceedings of the Royal Society of London A: Mathematical, Physical and Engineering Sciences*. The Royal Society, 2010.
- Anne Broadbent and Stacey Jeffery. Quantum homomorphic encryption for circuits of low t-gate complexity. In *Annual Cryptology Conference*, pages 609–629. Springer, 2015.
- Anne Broadbent, Joseph Fitzsimons, and Elham Kashefi. Universal blind quantum computation. In *Foundations of Computer Science, 2009. FOCS’09. 50th Annual IEEE Symposium on*, pages 517–526. IEEE, 2009.
- Ran Canetti, Ben Riva, and Guy N Rothblum. Practical delegation of computation using multiple servers. In *Proceedings of the 18th ACM conference on Computer and communications security*, pages 445–454. ACM, 2011a.
- Ran Canetti, Ben Riva, and Guy N Rothblum. Two 1-round protocols for delegation of computation. *IACR Cryptology ePrint Archive*, 2011, 2011b.
- Joe Fitzsimons. Blind quantum computing and fully homomorphic encryption, 2012. Stackexchange.
- Joseph Fitzsimons, Li Xiao, Simon C Benjamin, and Jonathan A Jones. Quantum information processing with delocalized qubits under global control. *Physical review letters*, 99(3), 2007.
- Joseph F Fitzsimons. Private quantum computation: an introduction to blind quantum computing and related protocols. *npj Quantum Information*, 3(1):23, 2017.
- Craig Gentry. *A fully homomorphic encryption scheme*. Stanford University, 2009.
- Brian Hayes. Cloud computing. *Communications of the ACM*, 51(7):9–11, 2008.
- He-Liang Huang, Qi Zhao, Xiongfeng Ma, Chang Liu, Zu-En Su, Xi-Lin Wang, Li Li, Nai-Le Liu, Barry C Sanders, Chao-Yang Lu, et al. Experimental blind quantum computing for a classical client. *Physical review letters*, 119(5), 2017.
- Cescily Nicole Metzgar. *RSA Cryptosystem: An Analysis and Python Simulator*. PhD thesis, Appalachian State University, 2017.
- Michael Miller. *Cloud computing: Web-based applications that change the way you work and collaborate online*. Que publishing, 2008.
- Yingkai Ouyang, Si-Hui Tan, and Joseph Fitzsimons. Quantum homomorphic encryption from quantum codes. *arXiv preprint arXiv:1508.00938*, 2015.

- 186 Andrew Steane. Quantum computing. *Reports on Progress in Physics*, 61(2):117, 1998.
- 187 Craig Stuntz. What is homomorphic encryption, and why should i care?, 2010. Blog.
- 188 Subashini Subashini and Veeraruna Kavitha. A survey on security issues in service delivery models
189 of cloud computing. *Journal of network and computer applications*, 34(1):1–11, 2011.
- 190 Si-Hui Tan, Joshua A Kettlewell, Yingkai Ouyang, Lin Chen, and Joseph F Fitzsimons. A quantum
191 approach to homomorphic encryption. *Scientific reports*, 6, 2016.
- 192 Max Tillmann, Si-Hui Tan, Sarah E Stoeckl, Barry C Sanders, Hubert de Guise, René Heilmann,
193 Stefan Nolte, Alexander Szameit, and Philip Walther. Generalized multiphoton quantum in-
194 terference. *Physical Review X*, 5(4), 2015.
- 195 Yang Yang et al. *Evaluation of somewhat homomorphic encryption schemes*. PhD thesis, Mas-
196 sachusetts Institute of Technology, 2013.