



JS index.js × +



```
1 console.log(0.1 * 3 === 0.3);  
2 console.log(9007199254740993);  
3
```

Console

I/O

AI Agent

161 ms ✓

false

9007199254740992





main.py × +



```
1 p = "maçã"
2 print(len(p), len(p.encode()))
3
```

Console

I/O

AI Agent

140 ms ✓

4 6





main.go



```
1 package main
2
3 import "fmt"
4
5 func main() {
6     var b byte = 255
7     b++
8     fmt.Println(b) // 0: byte is an 8-bit unsigned integer, so it wraps around
9 }
```

Console

I/O

AI Agent

277 ms



0





Main.java × +

```
1 public class Main {  
2     public static void main(String[] args) {  
3         int[] v = new int[3];  
4         System.out.println(v[0]);  
5         System.out.println(v[2]);  
6     }  
7 }  
8
```

Console

I/O

AI Agent

849 ms ✓

0

0

HelloWorld.rs

```
1 let s = String::from("oi");
2 let t = s;
3 println!("{}", s, t);
4
```

Console

I/O

AI Agent

Exit 1

error: expected item, found keyword `let`

--> HelloWorld.rs:1:1

|

1 | let s = String::from("oi");

| ^^^

| |

| `let` cannot be used for global variables

| help: consider using `static` or `const` instead of `let`

|

= note: for a full list of items that can appear in modules, see

<<https://doc.rust-lang.org/reference/items.html>>

error: aborting due to 1 previous error

Debug this error



Main.c × +



```
1  #include <stdio.h>
2
3  int main(void) {
4      union { int i; float f; } u;
5
6      u.f = 1.0f;
7      printf("%d\n", u.i);
8
9      return 0;
10 }
```

Console

I/O

AI Agent

181 ms ✓

1065353216

