Nu Html Checker

This tool is an ongoing experiment in better HTML checking, and its behavior remains subject to change

Showing results for app.blade.php

Checker Input

Show ☐ source ☐ outline ☐ image report   [Options…]

Check by [file upload ⌄] [Escolher ficheiro] Nenhum ficheiro selecionado

Uploaded files with .xhtml or .xht extensions are parsed using the XML parser.

[Check]

Use the Message Filtering button below to hide/show particular messages, and to see total counts of errors and warnings.

[Message Filtering]

1. **Error** **Bad value** `{{ app()->getLocale() }}` **for attribute** `lang` **on element** `html` : **Subtags must not exceed 8 characters in length.**

   From line 1, column 16; to line 2, column 38

   ```
   TYPE html>↵<html lang="{{ app()->getLocale() }}">↵    <
   ```

2. **Error** **Bad value** `{{ url('css/app.css') }}` **for attribute** `href` **on element** `link` : **Illegal character in path segment:** `{` **is not allowed.**

   From line 17, column 9; to line 17, column 63

   ```
   >↵         <link href="{{ url('css/app.css') }}" rel="stylesheet">↵
   ```

3. **Warning** **The** `type` **attribute is unnecessary for JavaScript resources.**

   From line 18, column 9; to line 18, column 39

   ```
   >↵         <script type="text/javascript">↵
   ```

4. **Error** **Quote** `'` **in attribute name. Probable cause: Matching quote missing somewhere earlier.**

   At line 22, column 51

   ```
   pt" src={{ url('js/app.js') }}
   ```

5. **Error** **A slash was not immediately followed by** `>` **.**

   At line 22, column 55

   ```
   src={{ url('js/app.js') }} def
   ```

6. **Error** **Quote** `'` **in attribute name. Probable cause: Matching quote missing somewhere earlier.**

    At line 22, column 61

    ```
    url('js/app.js') }} defer>↵
    ```

7. **Warning** **Attribute** `url('js` **is not serializable as XML 1.0.**

    From line 22, column 9; to line 22, column 72

    ```
    >↵          <script type="text/javascript" src={{ url('js/app.js') }} defer>↵
    ```

8. **Warning** **Attribute** `app.js')` **is not serializable as XML 1.0.**

    From line 22, column 9; to line 22, column 72

    ```
    >↵          <script type="text/javascript" src={{ url('js/app.js') }} defer>↵
    ```

9. **Warning** **Attribute** `}}` **is not serializable as XML 1.0.**

    From line 22, column 9; to line 22, column 72

    ```
    >↵          <script type="text/javascript" src={{ url('js/app.js') }} defer>↵
    ```

10. **Error** **Bad value** `{{` **for attribute** `src` **on element** [script] **: Illegal character in path segment:** `{` **is not allowed.**

    From line 22, column 9; to line 22, column 72

    ```
    >↵          <script type="text/javascript" src={{ url('js/app.js') }} defer>↵
    ```

11. **Error** **Attribute** `url('js` **not allowed on element** [script] **at this point.**

    From line 22, column 9; to line 22, column 72

    ```
    >↵          <script type="text/javascript" src={{ url('js/app.js') }} defer>↵
    ```

    Attributes for element [script](#):
    - [Global attributes](#)
    - [src](#) — Address of the resource
    - [type](#) — Type of script
    - [nomodule](#) — Prevents execution in user agents that support [module scripts](#)
    - [async](#) — Execute script when available, without blocking while fetching
    - [defer](#) — Defer script execution
    - [crossorigin](#) — How the element handles crossorigin requests
    - [integrity](#) — Integrity metadata used in *Subresource Integrity* checks [SRI]
    - [referrerpolicy](#) — [Referrer policy](#) for [fetches](#) initiated by the element
    - [blocking](#) — Whether the element is [potentially render-blocking](#)
    - [fetchpriority](#) — Sets the [priority](#) for [fetches](#) initiated by the element

12. **Error** **Attribute** `app.js')` **not allowed on element** [script] **at this point.**

    From line 22, column 9; to line 22, column 72

```
>↵             <script type="text/javascript" src={{ url('js/app.js') }} defer>↵
```

Attributes for element [script](#):

    [Global attributes](#)

    [src](#) — Address of the resource

    [type](#) — Type of script

    [nomodule](#) — Prevents execution in user agents that support [module scripts](#)

    [async](#) — Execute script when available, without blocking while fetching

    [defer](#) — Defer script execution

    [crossorigin](#) — How the element handles crossorigin requests

    [integrity](#) — Integrity metadata used in *Subresource Integrity* checks [[SRI]](#)

    [referrerpolicy](#) — [Referrer policy](#) for [fetches](#) initiated by the element

    [blocking](#) — Whether the element is [potentially render-blocking](#)

    [fetchpriority](#) — Sets the [priority](#) for [fetches](#) initiated by the element

---

13.   **Error**   **Attribute** `}}` **not allowed on element** `script` **at this point.**

From line 22, column 9; to line 22, column 72

```
>↵             <script type="text/javascript" src={{ url('js/app.js') }} defer>↵
```

Attributes for element [script](#):

    [Global attributes](#)

    [src](#) — Address of the resource

    [type](#) — Type of script

    [nomodule](#) — Prevents execution in user agents that support [module scripts](#)

    [async](#) — Execute script when available, without blocking while fetching

    [defer](#) — Defer script execution

    [crossorigin](#) — How the element handles crossorigin requests

    [integrity](#) — Integrity metadata used in *Subresource Integrity* checks [[SRI]](#)

    [referrerpolicy](#) — [Referrer policy](#) for [fetches](#) initiated by the element

    [blocking](#) — Whether the element is [potentially render-blocking](#)

    [fetchpriority](#) — Sets the [priority](#) for [fetches](#) initiated by the element

---

14.   **Warning**   **The** `type` **attribute is unnecessary for JavaScript resources.**

From line 22, column 9; to line 22, column 72

```
>↵             <script type="text/javascript" src={{ url('js/app.js') }} defer>↵
```

---

15.   **Error**   **Bad value** `{{ url('/welcome') }}` **for attribute** `href` **on element** `a` **:**

Illegal character in path segment: `{` **is not allowed.**

From line 29, column 46; to line 29, column 77

```
es-title"><a href="{{ url('/welcome') }}">FEUP T
```

16. **Error** **Bad value** `{{ url('/logout') }}` **for attribute** `href` **on element** `a`:
Illegal character in path segment: `{` **is not allowed.**

From line 34, column 29; to line 34, column 78

```
        <a class="nav-option" href="{{ url('/logout') }}">Logout
```

17. **Error** **Bad value** `{{ route('profile.show', ['id' => Auth::user()->id]) }}` **for attribute** `href` **on element** `a`: **Illegal character in path segment:** `{` **is not allowed.**

From line 36, column 29; to line 36, column 113

```
        <a class="nav-option" href="{{ route('profile.show', ['id' =>
Auth::user()->id]) }}">Profil
```

18. **Error** **Bad value** `{{ route('userManagement.showUsers') }}` **for attribute** `href` **on element** `a`: **Illegal character in path segment:** `{` **is not allowed.**

From line 38, column 33; to line 38, column 101

```
        <a class="nav-option" href="{{ route('userManagement.showUsers')
}}">User M
```

19. **Warning** **Section lacks heading. Consider using** `h2` - `h6` **elements to add identifying headings to all sections, or else use a** `div` **element instead for any cases where no heading is needed.**

From line 45, column 13; to line 45, column 34

```
        <section id="content">↵
```

20. **Error** **Bad value** `{{ url('js/app.js') }}` **for attribute** `src` **on element** `script`: **Illegal character in path segment:** `{` **is not allowed.**

From line 50, column 9; to line 50, column 45

```
>↵        <script src="{{ url('js/app.js') }}"></scri
```

Document checking completed.

Used the HTML parser.

Total execution time 15 milliseconds.

[About this checker](#) • [Report an issue](#) • Version: 23.11.28