

Exercise

Using the following code:

```
const names=['João','Maria','Andreia','Hugo','Ana']
const grades=[10,12,8,16,6]
const persons=[];
const positives=[];
let failed = 0;
let numberOfStudents = 0;
const BuildPersonsObject=()=>{
}
BuildPersonsObject();
console.log(positives);
console.log(failed);
console.log(numberOfStudents)
```

Create the code for function BuildPersonsObject to fulfill the

following objectives:

1 –Fill the persons array with objects. You must have an object

for each person, and it needs to have to properties (name and grade). This values provided need to

come from the names and grades arrays

2-Fill the positive variable with just the name of the students

which grade is equal or bigger then 10

3-Fill the variable failed with the number of students which

grade is lower than 10

4-Fill the variable numberOfStudents with the

number of
students that begin with the letter A

5-Create a new function that receives,a name and
a grade in a
argument,and according to the grade
it should return a message(NAME and GRADE
should be
replaced with the arguments received):

-NAME had GRADE, so it was a negative result- 0
to 10 (10
doesn't count)

-NAME had GRADE, so it is a ok result– 10 to
13(13 doesn't
count)

-NAME had GRADE, so it was a good result -13 to
16 (16
doesn't count)

-NAME had GRADE, so it is a very good result –
16 to 18(18
doesn't count)

-NAME had GRADE, so it is an excelent result –
18 to 20

6 – Call this previous function with a name of your
choice, and a
random number between 0 and 20