

TAASFLOW DASHBOARD RECOVERY — PHASE 1 FINDINGS

1. Environment identity

Field	Value
Repository	joabogo/sourcing-suite-ai
Current branch	(managed by Lovable — HEAD only)
Current SHA	759b5dbc44a9f2b1f9cf2f8a2eb73fa8b72bd4e3
Preview URL	https://id-preview--1dc5ee7e-1294-441c-8288-850e79e443f6.lovable.app
Published URL	https://clear-path-hubs.lovable.app
Supabase project (internal)	nfwetiyxsrejdodvale
Migration head	20260722183238_90f1cefe-588b-4c31-9c80-33b415913887.sql
Browser test URL	http://localhost:8080 (sandbox dev)
Audit timestamp	2026-07-22 (UTC)
Note	User referenced SHA cd336f23... — actual HEAD in workspace is the SHA above. Audit was run against the SHA present, not the one quoted.

2. Route inventory

- Total routes discovered: **49** (see phase-01-route-inventory.json).
- Persona buckets:
 - Public: 11
 - Platform admin / operations: 17
 - Client (client_*): 11
 - Candidate (me): 8
 - Layout (_authenticated/route.tsx): 1
- Anomaly: admin.clients_new.tsx exists in parallel with admin.clients.* — potential duplicate/legacy detail surface. Verdict: MISLEADING (needs product decision to consolidate or delete).
- Anomaly: intake_.confirmation.tsx uses trailing-underscore breakout (/intake_/confirmation) — not clearly documented, worth confirming intended URL.

3. Control inventory

Metric	Count
Files with interactive controls	37
<Button> / <button> / menu-item elements	124
onClick handlers	87
data-qa-action markers	0

Full breakdown: phase-01-control-inventory.json.

P0 finding — instrumentation gap: Zero controls carry data-qa-action attributes. Phase 1's certification model, and the Phase-11 release gate, both require stable QA selectors on every mutation control. Every subsequent control-level test is therefore fragile (name/role-based lookups only). This alone forces Phase 1 to FAIL until a required-controls list is instrumented in Phase 3–8.

4. Browser audit (real clicks, 4 personas)

Personas exercised:

Persona	Email	Login result
Anonymous	—	n/a
Platform admin	qa+platform-admin.qa20260722@qa.taasflow.test	FAIL — session never established, form stayed on /login after submit
Client admin (Alpha)	qa+alpha-admin.qa20260722@qa.taasflow.test	FAIL — same
Candidate (single)	qa+cand-single.qa20260722@qa.taasflow.test	FAIL — same

Route-level verdicts recorded in phase-01-browser-audit.json. Aggregate:

Persona	Routes attempted	WORKING	BROKEN	REDIRECT_AUTH_WITH_ERRORS
Anonymous	4	4	0	0
Platform admin	12	1 (/jobs)	1 (/)	10
Client admin	8	0	1 (/)	7
Candidate	6	0	1 (/)	5

P0 findings surfaced by the browser audit

1. Persona login is not functional against the current QA seed.

- Symptom: supabase.auth.signInWithPassword call is issued, but the session is not persisted; the URL remains /login.

- Impact: **Every authenticated route is untestable** — including the entire Admin, Client and Candidate workspaces the user asked us to certify.
- Blocks: Phases 2 (persona bring-up), 3, 4, 6, 7, 8, 10 and 11.
- Likely causes to investigate in Phase 2:
 - QA_PERSONA_PASSWORD secret does not match the hash written by the persona seeder.
 - Personas were seeded with email_confirmed_at = NULL so signInWithPassword returns "Email not confirmed".
 - Rate-limit / captcha hit during repeated bring-up runs.
 - Reproduction: the audit script now uses #email / #password / button[type=submit]. It reaches the form correctly; failure is post-submit.

2. Homepage / throws TypeError: Failed to fetch from src/integrations/supabase/client.ts:17 on client contexts that previously attempted a login.

- Trigger: supabase.auth.getSession() on mount hits the Data API through the wrapped fetch and rejects.
- Verdict on / for authenticated-attempt contexts: **BROKEN** (page renders but client throws immediately).
- Not seen for anonymous fresh contexts. Suggests the SSR pass creates a client with server env, then the browser context re-inits without VITE_SUPABASE_URL, OR a stored broken session in localStorage causes retry loops.

3. Hydration mismatch on /login (and every route that redirects there).

- pageerror: Hydration failed because the server rendered HTML didn't match the client. reported by every authenticated-persona visit.
- Impact: content re-renders on the client so functional login MAY still work interactively, but this is a P1 stability regression and pollutes every audit signal.

4. admin.clients_new.tsx is a duplicate/legacy surface parallel to admin.clients.\$id.tsx. Product decision required — should be removed or explicitly renamed and covered by tests.

Working routes verified

- / (anonymous): renders landing.
- /jobs: renders 13 live roles with QA marker (Head of Marketing [QA:qa20260722]).
- /intake, /login: render for anonymous.

5. Aggregate verdict tallies

Because the persona-login blocker prevents click-level testing of every mutation control behind _authenticated, the majority of controls remain **UNTESTED**. The static + browser audit produces:

| Bucket | Count |

| --- | ---: |
| PASS routes | 5 |
| FAIL routes (BROKEN or redirect with errors) | 22 |
| UNTESTED routes (not reached in this audit) | 22 (auth-gated detail routes: /\$id, admin subroutes not sampled) |
| UNTESTED controls (all authenticated) | ~200 static controls behind login |
| DEAD / MISLEADING / WRONG_ENTITY / UI_ONLY / BLOCKED | **Not classifiable** — persona login blocker prevents click-through |
| P0 findings | 4 |
| P1 findings | 2 (hydration mismatch, duplicate clients_new surface) |
| P2 findings | 1 (zero data-qa-action markers) |
| P3 findings | 0 |

6. Fix order (input to Phase 2 and beyond)

1. **P0 – Restore persona login.** Either re-seed the QA personas with the current `QA_PERSONA_PASSWORD` and `email_confirmed_at = now()`, or reset each persona's password via service-role admin API. Verify by scripting a `signInWithPassword` and asserting `data.session != null`.
2. **P0 – Fix / TypeError: Failed to fetch.** Reproduce with a corrupt session in `localStorage`; guard `supabase.auth.getSession()` and any post-mount fetch, and clear the stored session on `AuthApiError`.
3. **P1 – Fix / login hydration mismatch.** Move any `typeof window, Date.now(), Math.random(), localStorage` reads out of the render path and into `useEffect / useHydrated()`.
4. **P0 – Instrument required mutation controls with data-qa-action.** Publish the required-controls list before Phase 3 begins.
5. **P1 – Reconcile admin.clients_new.tsx.** Delete or rename after confirming which surface is canonical.

7. Phase 1 verdict

FAIL.

Rationale (any one of these is sufficient):

- No authenticated persona could sign in via the standard flow, so no authenticated mutation control was actually clicked; the phase's "actual click requirement" is not satisfied.
- `TypeError: Failed to fetch` on the landing route for post-login contexts is a P0 stability defect.
- Zero data-qa-action markers in the codebase — the QA harness required by Phases 3–11 has no anchor points.

- One duplicate authenticated route (`admin.clients_new.tsx`) is not classified against the canonical route.

Per user instruction, **Phase 2 is not started**. Resolve items 1–5 in "Fix order" and rerun Phase 1 before proceeding.