

Managing the Kubernetes API Server and Pods

INTRODUCTION AND USING THE KUBERNETES API



Anthony E. Nocentino

ENTERPRISE ARCHITECT @ CENTINO SYSTEMS

@nocentino www.centinosystems.com

Course Overview



Using the Kubernetes API

**Managing Objects with Labels, Annotations,
and Namespaces**

Running and Managing Pods

Overview


The Kubernetes API and API Server

Working with Kubernetes Objects

- **Defining objects**
- **API Groups**
- **API Versioning**

Anatomy of an API Request

Kubernetes API and API Server



Single surface area over the resources in your data center

API Objects

Collection of primitives to represent your system's state


Enables configuration of state

API Server

The sole way to interact with your cluster

The sole way Kubernetes interacts with your cluster

Kubernetes API Server



Client/Server architecture

RESTful API over HTTP using JSON


Client submits requests over HTTP/HTTPS

Server responds to the request


Stateless

Serialized and persisted in the cluster store

Master Node - Control Plane



Kubernetes API Objects



Persistent entities in Kubernetes

Representing the state of your system

Objects are organized by

Kind - Pod, Service, Deployment

Group - core, apps, storage

Version - v1, beta, alpha

Kubernetes API Objects (Kind)



Pods



Deployments



Services



PersistentVolumes

Not an exhaustive list, but these are the key players

Working with Kubernetes Objects



Imperative configuration

Declarative configuration

Define our desired state in code

Manifest

YAML or JSON

```
kubectl apply -f deployment.yaml
```

```
apiVersion: v1
kind: Pod
metadata:
  name: nginx-pod
spec:
  containers:
  - name: nginx
    image: nginx
```

Basic Manifest - Pod

```
kubectl apply -f nginx.yaml
```

<https://kubernetes.io/docs/reference/generated/kubernetes-api/v1.14/>


Hostnames set
Host file on each

Lab Environment


Ubuntu 16.0.4
VMware Fusion VMs
2vCPU
2GB RAM
100GB
Swap Disabled




c1-master1
172.16.94.10



c1-node1
172.16.94.11



c1-node2
172.16.94.12



c1-node3
172.16.94.13

Kubernetes Installation and Configuration Fundamentals

Demo


API Server Discovery

Listing Available API Resources

Using `kubectl explain`

Defining objects in YAML

API Groups



Organization of resources

API Groups

Core API (Legacy Group)

Named API Groups

Part of the API Object's URL in API Requests

API Groups

Core (Legacy)

Pod

Node

Namespace

PersistentVolume

PersistentVolumeClaim

Named API Groups


`apps` - **Deployment**

`storage.k8s.io` - **StorageClass**

`rbac.authorization.k8s.io` - **Role**

<https://kubernetes.io/docs/reference/generated/kubernetes-api/v1.14/>

API Versioning



API is versioned

Provide stability for existing implementations

Enable forward change

Alpha -> Beta -> Stable

No direct relation to release versions

API Versioning

Alpha/Experimental



Alpha

V1alpha1

Early Release

Disabled by Default

For Testing Only

Breaking Changes

Beta/Pre-release



Beta

V1beta1


Thoroughly Tested

Considered Safe, but Test

More Stable API Objects

Feedback Encouraged

Stable/General Availability



Stable

v1

Backwards Compatible


Production Ready

Demo

API Object Discovery

- **Examining API Groups**
- **Examining Different API Versions**

Anatomy of an API Request



API Request



API Paths




**Read/Write
Objects to/from
Cluster Store**



**Send Response
Back to the
Client**

Anatomy of an API Request




Client and Server architecture

`kubectl`

Any HTTP client that respects the API

`curl`

Anatomy of an API Request



HTTP based RESTful API

HTTP Verb

Resource Location (URL/Path)

Request = Verb + Resource Location

Response Code

RESTful API Verbs

GET

Get the data for a specified resource(s)

POST

Create a resource

DELETE

Delete a resource

PUT

Create or update entire existing resource

PATCH

Modify the specified fields of a resource

Special API Requests

LOG	Retrieve logs from a container in a Pod
EXEC	Exec a command in a container get the output
WATCH	Change notifications on a resource with streaming output

Each resource has a resourceVersion

Watches are started on that version

Notifications are sent to clients watching that version

API Resource Location (API Paths)

Core API (Legacy)

`http://apiserver:port/api/$VERSION/$RESOURCE_TYPE`

`http://apiserver:port/api/$VERSION/namespaces/$NAMESPACE/$RESOURCE_TYPE/$RESOURCE_NAME`

API Groups

`http://apiserver:port/apis/$GROUPNAME/$VERSION/$RESOURCE_TYPE`

`http://apiserver:port/apis/$GROUPNAME/$VERSION/namespaces/$NAMESPACE/$RESOURCE_TYPE/$RESOURCE_NAME`

Response Codes from the API Server

Success (2xx)

200 - OK

201 - Created

202 - Accepted

Client Errors (4xx)

**401 -
Unauthorized**


**403 - Access
Denied**

404 - Not Found

Server Errors (5xx)

**500 - Internal
Server Error**

Anatomy of an API Request



Demo

Anatomy of an API Request

Special API Requests - Watch, Exec and Log

Authentication Failure and Missing Resources

Creating Objects

Summary

The Kubernetes API and API Server Working with Kubernetes Objects

- **Defining objects**
- **API Groups**
- **API Versioning**

Anatomy of an API Request

What's Next!

Managing Objects with Labels, Annotations, and Namespaces