

Configuration as Data - Environment Variables, Secrets and ConfigMaps



Anthony E. Nocentino

ENTERPRISE ARCHITECT @ CENTINO SYSTEMS

@nocentino www.centinosystems.com

Course Overview



**Configuring and Managing Storage in
Kubernetes**

**Configuration as Data - Environment
Variables, Secrets and ConfigMaps**

**Managing and Controlling the
Kubernetes Scheduler**

Overview

Configuring Pods with Environment Variables

Working with Sensitive Data Using Secrets

**Managing Application Configuration with
ConfigMaps**

Why Do we Need Configuration as Data?


Abstraction

**Container Images are
Immutable**


Service Discovery

Sensitive Information

Configuring Applications in Pods



**Command Line
Arguments**




**Environment
Variables**



ConfigMaps

Environment Variables Inside Pods



User defined

Pod Spec for each container

Defined inside the container image

Defined in `name/value` or `valueFrom`

System defined

Names of all Services available at the time the Pod was created

Defined at container startup

Cannot be updated once the Pod is created

Defining Environment Variables

spec:

containers:

- name: hello-world

image: gcr.io/google-samples/hello-app:1.0

env:

- name: DATABASE_SERVERNAME

value: "sql.example.local"

- name: BACKEND_SERVERNAME

value: "be.example.local"

Demo

**Passing configuration into containers
using Environment Variables**

Secrets




Store sensitive information as Objects



Retrieve for later use




Passwords, API tokens, keys and certificates



Safer and more flexible configurations (Pod Specs and Images)

Properties of Secrets



base64 encoded

Encryption can be configured

Stored in etcd

Namespaced and can only be referenced by Pods in the same Namespace

Unavailable Secrets will prevent a Pods from starting up

<https://kubernetes.io/docs/tasks/administer-cluster/encrypt-data/>

Creating Secrets

```
kubectl create secret generic app1 \  
  --from-literal=USERNAME=app1login \  
  --from-literal=PASSWORD='S0methingS@Str0ng!'
```

Using Secrets in Pods

Environment Variables

Volumes or Files

**Referenced Secret must be created and accessible
for the Pod to start up**

Using Secrets in Environment Variables

```
spec:
  containers:
  - name: hello-world
    ...
  env:
  - name: app1username
    valueFrom:
      secretKeyRef:
        name: app1
        key: USERNAME
  - name: app1password
    valueFrom:
      secretKeyRef:
        name: app1
        key: PASSWORD
```

```
spec:
  containers:
  - name: hello-world
    ...
  envFrom:
  - secretRef:
      name: app1
```

Using Secrets as Files

```
spec:
  volumes:
    - name: appconfig
      secret:
        secretName: app1
        /etc/appconfig/USERNAME
        /etc/appconfig/PASSWORD
  containers:
    ...
    volumeMounts:
      - name: appconfig
        mountPath: "/etc/appconfig"
```

Demo

Creating and accessing Secrets

Accessing Secrets inside a Pod

- **Environment variables**
- **Files and Volumes**

Accessing a Private Container Registry



Secrets for application configuration

Use Secrets to access a private container registry

Want to access registries over the Internet

Docker Hub

Cloud based container registries

Create a Secret of type docker-registry

Enabling Kubernetes (kubelet) to pull the images from the private registry

Demo

**Pulling a container image from a
private container repository**

ConfigMaps



Key value pairs exposed into a Pod used application configuration settings

Defining application or environment specific settings

Decouple application and Pod configurations

Maximizing our container image's portability

Environment Variables or Files

Using ConfigMaps in Pods



Environment variables

`valueFrom` and `envFrom`

Volumes and Files

Volume mounted inside a container

Single file or directory

Many files or directories

Volume ConfigMaps can be updated

Defining ConfigMaps

```
kubectl create configmap appconfigprod \  
  --from-literal=DATABASE_SERVERNAME=sql.example.local \  
  --from-literal=BACKEND_SERVERNAME=be.example.local
```

```
kubectl create configmap appconfigqa \  
  --from-file=appconfigqa
```

```
apiVersion: v1  
kind: ConfigMap  
metadata:  
  name: appconfigprod  
data:  
  BACKEND_SERVERNAME: be.example.local  
  DATABASE_SERVERNAME: sql.example.local
```

Using ConfigMaps in Environment Variables

```
spec:
  containers:
  - name: hello-world
    ...
  env:
  - name: DATABASE_SERVERNAME
    valueFrom:
      configMapKeyRef:
        name: appconfigprod
        key: DATABASE_SERVERNAME
  - name: BACKEND_SERVERNAME
    valueFrom:
      configMapKeyRef:
        name: appconfigprod
        key: BACKEND_SERVERNAME
```

```
containers:
- name: hello-world
  ...
  envFrom:
  - configMapRef:
      name: appconfigprod
```

Using ConfigMaps as Files

```
spec:
  volumes:
    - name: appconfig
      configMap:
        name: appconfigqa
  containers:
    - name: hello-world
      ...
      volumeMounts:
        - name: appconfig
          mountPath: "/etc/appconfig"
```

Demo

Creating ConfigMaps

Using ConfigMaps in Pods

Review

Configuring Pods with Environment Variables

Working with Sensitive Data Using Secrets

**Managing Application Configuration with
ConfigMaps**

What's Next!

Managing and Controlling the Kubernetes Scheduler