

Configuring and Managing Kubernetes Storage and Scheduling

CONFIGURING AND MANAGING STORAGE IN KUBERNETES



Anthony E. Nocentino

ENTERPRISE ARCHITECT @ CENTINO SYSTEMS

@nocentino www.centinosystems.com

Course Overview



**Configuring and Managing Storage in
Kubernetes**

**Configuration as Data - Environment
Variables, Secrets and ConfigMaps**

**Managing and Controlling the
Kubernetes Scheduler**

Overview

Persistent Storage in Containers

Kubernetes Storage Objects


Storage Lifecycle

Using Storage in Kubernetes

Persistent Storage and Containers



Containers are ephemeral



A container's Writable Layer is deleted when the container is deleted



When a Pod is deleted, its container(s) is deleted from the Node




How can we persist data across a Pod's lifecycle?

Storage API Objects in Kubernetes




Volume



**Persistent
Volume**




**Persistent
Volume Claim**



Storage Class


Storage in Kubernetes



**Persistent
Volume**



**Persistent
Volume Claim**



Volumes



Persistent storage deployed as part of the Pod spec

Implementation details for your storage


This can be challenging...

Sharing code

Same lifecycle as Pod

We can do better...

Persistent Volumes



Administrator defined storage in the Cluster

Implementation details for your storage

Lifecycle independent of the Pod

Managed by the Kubelet

Maps the storage in the Node

Exposes PV as a mount inside the container

<https://kubernetes.io/docs/concepts/storage/persistent-volumes/>

Types of Persistent Volumes

Networked	Block	Cloud
NFS	Fibre Channel	awsElasticBlockStore
azureFile	iSCSI	azureDisk
		gcePersistentDisk

<https://kubernetes.io/docs/concepts/storage/persistent-volumes/#types-of-persistent-volumes>

Persistent Volumes Claims



A request for storage by a user

Size

Access Mode

Storage Class

Enable portability of your application configurations

The Cluster will map a PVC to a PV

Access Modes

ReadWriteOnce
(RWO)

ReadWriteMany
(RWX)

ReadOnlyMany
(ROX)



Node level access, not Pod access

Static Provisioning Workflow

Create a
PersistentVolume

Create a
PersistentVolumeClaim

Define Volume in
Pod Spec



Storage Lifecycle

Binding

PVC Created

Control Loop

Matches PVC->PV

Using

Pod's Lifetime


Reclaim

PVC Deleted

Delete (default)

Retain

Defining a Persistent Volume



```
type { nfs, fc, azureDisk, ... }
```

```
capacity
```

```
accessModes
```

```
persistentVolumeReclaimPolicy
```

```
Labels
```

Defining a Persistent Volume

```
apiVersion: v1
kind: PersistentVolume
metadata:
  name: pv-nfs-data
spec:
  capacity:
    storage: 10Gi
  accessModes:
    - ReadWriteMany
  nfs:
    server: 172.16.94.5
    path: "/export/volumes/pod"
```

Defining a Persistent Volume Claim



accessModes

resources

storageClassName

selector

Defining a Persistent Volume Claim

```
apiVersion: v1
kind: PersistentVolumeClaim
metadata:
  name: pvc-nfs-data
spec:
  accessModes:
    - ReadWriteMany
resources:
  requests:
    storage: 10Gi
```

Using Persistent Volumes in Pods

```
...
spec:
  volumes:
    - name: webcontent
      persistentVolumeClaim:
        claimName: pvc-nfs-data
  containers:
    - name: nginx
      ...
      volumeMounts:
        - name: webcontent
          mountPath: "/usr/share/nginx/html/web-app"
```

mountPath


volumeMounts

volumes




PersistentVolumeClaim

PersistentVolume

Lab Environment



c1-storage
172.16.94.5



c1-master1
172.16.94.10

c1-node1
172.16.94.11

c1-node2
172.16.94.12

c1-node3
172.16.94.13

Kubernetes Installation and Configuration Fundamentals


Demo

Storage Server Overview - NFS

Static Provisioning Persistent Volumes

Storage Lifecycle and Reclaim Policy

Storage Class



Define tiers/classes of storage

Enables Dynamic Provisioning

Define infrastructure specific parameters

Reclaim Policy



Dynamic Provisioning Workflow

Create a
StorageClass

Create a
PersistentVolumeClaim

Define Volume in Pod
Spec

Creates a
PersistentVolume



Defining a StorageClass

```
apiVersion: storage.k8s.io/v1
kind: StorageClass
metadata:
  name: managed-premium
parameters:
  kind: Managed
  storageaccounttype: Premium_LRS
provisioner: kubernetes.io/azure-disk
```

Dynamic Provisioning

```
apiVersion: v1
kind: PersistentVolumeClaim
metadata:
  name: pvc-azure-managed
spec:
  accessModes:
    - ReadWriteOnce
  storageClassName: managed-premium
  resources:
    requests:
      storage: 10Gi
```


Demo

Dynamic Provisioning in the Cloud

Defining a custom StorageClass

Review

Persistent Storage in Containers

Kubernetes Storage Objects

Storage Lifecycle

Using Storage in Kubernetes

What's Next!

Configuration as Data - Environment Variables, Secrets and ConfigMaps