

CA320 - Computability & Complexity

Context-Sensitive Languages

Dr. David Sinclair

CA320

Dr. David Sinclair

Context-Sensitive Grammars

An *unrestricted grammar* is a 4-tuple $G = (V, \Sigma, S, P)$, where V and Σ are disjoint sets of variables and terminals respectively. $S \in V$ is called the *start symbol* and P is a set of production rules of the form $\alpha \rightarrow \beta$.

A *Context-Sensitive Grammar* (CSG) is an *unrestricted grammar* in which every production is of the form $\alpha \rightarrow \beta$ and $|\beta| \geq |\alpha|$, i.e. no production rule is length-decreasing.

An Example CSG

An example CSG is:

$$\begin{aligned}
 S &\rightarrow aBCT|aBC \\
 T &\rightarrow ABCT|ABC \\
 BA &\rightarrow AB \\
 CA &\rightarrow AC \\
 CB &\rightarrow BC \\
 aA &\rightarrow aa \\
 aB &\rightarrow ab \\
 bB &\rightarrow bb \\
 bC &\rightarrow bc \\
 cC &\rightarrow cc
 \end{aligned}$$

How a variable is derived depends on the context!

CA320

Dr. David Sinclair

An Example CSG (2)

Here are some derivations from this CSG.

$$\begin{aligned}
 S &\Rightarrow aBC & L(G) = \{a^n b^n c^n | n \geq 1\} \\
 &\Rightarrow abC \\
 &\Rightarrow abc
 \end{aligned}$$

We have already shown that $AnBnCn$ is not a context-free language using the CFG pumping lemma. But it is a context-sensitive language.

$$\begin{aligned}
 S &\Rightarrow aBCT \\
 &\Rightarrow aBCABC \\
 &\Rightarrow aBACBC \\
 &\Rightarrow aABCBC \\
 &\Rightarrow aABBCC \\
 &\Rightarrow aaBBCC \\
 &\Rightarrow aabBCC \\
 &\Rightarrow aabbCC \\
 &\Rightarrow aabbcC \\
 &\Rightarrow aabbcc
 \end{aligned}$$

CSLs are not a generalisation of CFGs as CSLs cannot have any Λ -productions.

Linear Bounded Automata

A *linear bounded automaton* (LBA) is a finite state machine with a finite length data store called a *tape*. The tape consists of a sequence of cells, where each cell can store a symbol from the machine's alphabet. Symbols can be written or read from any position on this tape and therefore the LBA has a *read-write head* that can be moved left or right one cell.

The tape is used both to store the input and any ongoing calculations. There are 2 special symbols, [and], that are used to mark the finite bounds of the tape. The read-write head cannot move beyond either of these symbols and it cannot overwrite these symbols.

CA320

Dr. David Sinclair

Linear Bounded Automata (2)

At each step the LBA read the symbol under the read-write head, replaces the by another symbol (could be the same symbol) and then perform one of four possible actions $\mathcal{A} \in \{Y, N, L, R\}$, where:

- Y** denotes “Yes”, accept the input string
- N** denotes “No”, reject the input string
- L** denotes “Left”, move the read-write head one cell to the left
- R** denotes “Right”, move the read-write head one cell to the right

Linear Bounded Automata (2)

Formally, a linear bounded automaton is a 5-tuple

$M = \{Q, \Sigma, \Gamma, q_0, \delta\}$ where:

- Q is a finite set of *states*;
- Σ is a finite alphabet (*input symbols*);
- Γ is a finite alphabet (*store symbols*);
- $q_0 \in Q$ is the *initial state*; and
- $\delta : Q \times (\Gamma \cup \{[,]\}) \rightarrow Q \times (\Gamma \cup \{[,]\}) \times \mathcal{A}$, is the *transition function*.

If $((q, \sigma), (q', \psi, \mathcal{A})) \in \delta$ then when in state q with σ at the current read-write head position, M will replace σ by ψ and perform action \mathcal{A} and enter state q' .

M accepts $w \in \Sigma^*$ iff it starts with configuration $(q_0, [w])$ and the action Y is taken.


Linear Bounded Automaton Example

An LBA to accept $AnBnCn = \{a^n b^n c^n | n \geq 0\}$ is:

$$\begin{aligned}
 Q &= \{s, t, u, v, w\} \\
 \Sigma &= \{a, b, c\} \\
 \Gamma &= \{a, b, c, x\} \\
 q_0 &= s \\
 \delta &= \{((s, []), (t, [, R)), \\
 &\quad ((t, []), (t, [, Y)), ((t, x), (t, x, R)), ((t, a), (u, x, r)), \\
 &\quad ((u, a), (u, a, R)), ((u, x), (u, x, R)), ((u, b), (v, x, R)) \\
 &\quad ((v, b), (v, b, R)), ((v, x), (v, x, R)), ((v, c), (w, x, L)) \\
 &\quad ((w, c), (w, c, L)), ((w, b), (w, b, L)), ((w, a), (w, a, L)) \\
 &\quad ((w, x), (w, x, L)), ((w, []), (t, [, R)) \\
 &\quad \}
 \end{aligned}$$

Linear Bounded Automaton Example (2)

Or as a transition diagram;



where $\sigma/\psi/\mathcal{A}$ denotes reading symbol σ , writing symbol ψ and performing action \mathcal{A} .

CA320

Dr. David Sinclair

Linear Bounded Automaton Example (3)

Intuitively the previous LBA behaves as follows.

- The LBA performs multiple passes over the input string.
- On each pass (from left to right) starting at the start symbol $[$ in state t , the LBA converts the first a into an x , and then the first b into an x and finally the first c into an x .
- After converting a c into an x (after matching it with an a and b) the LBA moves right to left until it reaches the start symbol $[$ and goes into state t .
- If the LBA in state t only encounters x symbols from the start symbol $[$ to the end symbol $]$, then the LBA performs a Y action.
- the LBA gets stuck in either state u , v or w if there is not a “matching” a , b or c symbol respectively.

Can you design a better version of this LBA that actually rejects string that are not in the language $AnBnCn$?

CA320

Dr. David Sinclair