

# R-intro - Session 3 exercise solutions

*João Gonçalves*

*27 de Julho de 2018*

## Contents

<b>List objects</b>	<b>1</b>
Exercise 1 . . . . .	1
Exercise 2 . . . . .	2
QUICK-EXERCISE 1 . . . . .	3
<b>User-defined functions</b>	<b>4</b>
Exercise 3 . . . . .	4
<b>If conditionals</b>	<b>7</b>
Exercise 4 . . . . .	7
<b>For loops</b>	<b>9</b>
Exercise 5 . . . . .	9

## List objects

---

### Exercise 1

1a.

```
my_list <- list(a = 1:5,  
               b = matrix(1:20, nrow = 5, ncol = 4))
```

1b.

```
# Extracting a from the list  
my_list$a
```

```
## [1] 1 2 3 4 5
```

```
# Extracting the first column of b  
my_list$b[,1]
```

```
## [1] 1 2 3 4 5
```

```
# Multiply the two vectors (element-by-element) and attribute  
# this to a new list element called "mult"  
my_list[["mult"]] <- my_list$a * my_list$b[,1]  
  
print(my_list$mult)
```

```
## [1] 1 4 9 16 25
```

1c.

```
# Using the dollar $ operator
my_list$mult[3]
```

```
## [1] 9
```

```
# Equivalent to before but using the [[]] operator
my_list[["mult"]][3]
```

```
## [1] 9
```

```
# Concatenation can be used to extract more than one element, for example:
my_list[["mult"]][c(1,3,5)]
```

```
## [1] 1 9 25
```

## Exercise 2

2.

```
set.seed(123) # Used to make random numbers always the same
```

```
# Now define the list that will be used for the exercise
nestList <- list(
```

```
  x = list(
    a1 = 1:10,
    a2 = rnorm(10)
  ),
```

```
  y = list(
    b1 = 1:10,
    b2 = rnorm(10)
  )
)
```

2a.

```
# Using the $ operator
nestList$x
```

```
## $a1
```

```
## [1] 1 2 3 4 5 6 7 8 9 10
```

```
##
```

```
## $a2
```

```
## [1] -0.56047565 -0.23017749 1.55870831 0.07050839 0.12928774
```

```
## [6] 1.71506499 0.46091621 -1.26506123 -0.68685285 -0.44566197
```

```
# The same as before but with the [[]] operator
nestList[["x"]]
```

```
## $a1
```

```
## [1] 1 2 3 4 5 6 7 8 9 10
```

```
##
```

```
## $a2
```

```
## [1] -0.56047565 -0.23017749 1.55870831 0.07050839 0.12928774
```

```
## [6] 1.71506499 0.46091621 -1.26506123 -0.68685285 -0.44566197
```

2b.

```

# the third element of `a1`
nestList$x$a1[3]

## [1] 3
# equivalent to:
nestList[["x"]][["a1"]][3]

## [1] 3
# the second to fifth elements of `b2`
nestList$y$b2[2:5]

## [1] 0.3598138 0.4007715 0.1106827 -0.5558411
# equivalent to:
nestList[["y"]][["b2"]][2:5]

## [1] 0.3598138 0.4007715 0.1106827 -0.5558411
2c.
nestList$x$a2 * nestList$y$b1

## [1] -0.5604756 -0.4603550 4.6761249 0.2820336 0.6464387
## [6] 10.2903899 3.2264134 -10.1204899 -6.1816757 -4.4566197
# the same as:
nestList[["x"]][["a2"]] * nestList[["y"]][["b1"]]

## [1] -0.5604756 -0.4603550 4.6761249 0.2820336 0.6464387
## [6] 10.2903899 3.2264134 -10.1204899 -6.1816757 -4.4566197

```

## QUICK-EXERCISE 1

QE-1) a)

```

# Extract columns to atemporary vectors
ozone <- airquality$Ozone
temp <- airquality$Temp

# Calculate correlation
aq_cor <- cor.test(x = ozone, y = temp, method="pearson")

# Equivalent to before but without specifically declaring
# the x and y in cor.test. This way we are defining function
# arguments by their positions
aq_cor <- cor.test(ozone, temp)

# Also equivalent but not using temp vectors, instead
# using directly indexation to pull data
aq_cor <- cor.test(airquality$Ozone, airquality$Temp)

```

QE-1) b)

```

# Get object structure
str(aq_cor)

```

```
## List of 9
```

```
## $ statistic : Named num 10.4
##   ..- attr(*, "names")= chr "t"
## $ parameter : Named int 114
##   ..- attr(*, "names")= chr "df"
## $ p.value    : num 2.93e-18
## $ estimate   : Named num 0.698
##   ..- attr(*, "names")= chr "cor"
## $ null.value : Named num 0
##   ..- attr(*, "names")= chr "correlation"
## $ alternative: chr "two.sided"
## $ method     : chr "Pearson's product-moment correlation"
## $ data.name  : chr "airquality$Ozone and airquality$Temp"
## $ conf.int   : atomic [1:2] 0.591 0.781
##   ..- attr(*, "conf.level")= num 0.95
## - attr(*, "class")= chr "htest"

# Get correlation value
aq_cor$estimate

##          cor
## 0.6983603

# Get correlation p-value
aq_cor$p.value

## [1] 2.931897e-18
```

## User-defined functions

---

### Exercise 3

3a.

```
Celsius2Kelvin <- function(tempCelsius){

  tempKelvin <- tempCelsius + 273.15

  return(tempKelvin)
}

a <- 20.5
Celsius2Kelvin(a)
```

```
## [1] 293.65
```

3b.

```
Celsius2Fahrenheit <- function(tempCelsius){

  return(tempCelsius * 9/5 + 32)
}
```

```
b <- 16.7
Celsius2Fahrenheit(b)
```

```
## [1] 62.06
```

3c.

```
recode2NA <- function(x){
  # Modify x values to NA
  x[x < 10 | x > 100] <- NA
  # return the modified x
  return(x)
}

v <- c(1, 5, 10, 15, 25, 78, 90, 34, 55, 120, 100, 105, 103, 12, 101)
recode2NA(v)
```

```
## [1] NA NA 10 15 25 78 90 34 55 NA 100 NA NA 12 NA
```

3d.

```
standardize.me <- function(x){
  # A temp variable with the standardized x
  x.std <- (x - mean(x)) / sd(x)
  return(x.std)
}

d <- rnorm(100, 100, 5)
standardize.me(d)
```

```
## [1] -1.20092019 -0.23629559 -1.15345306 -0.81621339 -0.69833577
## [6] -1.90337085 0.96205166 0.18520463 -1.28072953 1.43426593
## [11] 0.49517789 -0.32380438 1.02713411 1.00784707 0.94365701
## [16] 0.79276194 0.63984446 -0.05915536 -0.33616647 -0.42073748
## [21] -0.77741241 -0.22487962 -1.42517589 2.47300079 1.38222037
## [26] -1.26367153 -0.44617840 -0.51856141 0.89642063 -0.08351063
## [31] 0.29864809 -0.02128432 -0.03754250 1.56455583 -0.24514455
## [36] 1.73239442 -1.74680087 0.67468620 0.15169910 0.25622323
## [41] 0.44202926 -0.55904664 -0.36709071 -1.14502066 -1.20542354
## [46] 0.35563932 0.51986028 0.07128048 1.05794154 2.33807543
## [51] -0.54622928 -2.60991448 1.15268573 -0.79386364 -0.76980940
## [56] 1.17519709 -0.31211505 -1.37446320 0.21690711 -0.14653145
## [61] 0.01766046 0.44843201 -0.40960150 0.74252023 -0.23914644
## [66] 0.38770837 1.25608974 0.50507246 -0.35883228 1.31507693
## [71] 1.13879871 0.63357818 0.28209130 -0.70158975 1.55553234
## [76] -0.67020948 2.49385972 1.75071422 -0.25641493 -1.15392575
## [81] -0.79523229 0.30269478 -0.26889090 -0.38336195 -1.06902104
## [86] -0.03999112 -0.87979147 -1.88208702 -0.42045998 1.05422894
## [91] -0.64193230 0.70119037 -1.82526708 -0.05194805 0.60067323
## [96] 0.35294325 0.13106603 -0.71611837 -0.95334285 -1.15132408
```

3e.

```
CoeffVar <- function(x){
  cv <- mean(x) / sd(x)
  return(cv)
}
```

```

}

e <- rnorm(100)
CoeffVar(e)

## [1] -0.02338485

3f.
mult2 <- function(x){

  x.sort <- sort(x, decreasing = TRUE)
  highest2 <- x.sort[1:2]

  return((highest2[1] * highest2[2]) / 2)
}

f <- rnorm(1000, 100, 10)
mult2(f)

## [1] 8459.032


3g.
myHist <- function(x, ...){

  # Calculate the 25%, 50% and the 50% quantiles
  qts <- quantile(x, probs = c(0.25, 0.50, 0.75))
  # Make the histogram with the input x vector
  hist(x, ...)
  # Add the vertical lines using abline function
  abline(v = qts, lwd=1, lty=2, col="red")
}

g <- rnorm(1000, 10, 3)

myHist(g, main="Distribution of values",
  col = "light grey",
  border = "white")

```



```
# To save the result to a file use (for example) png()
# followed by the function that makes the plot
# then close the file by using dev.off()
png(filename = "myHist.png", width = 1200, height = 900, res = 300)
myHist(g, main="Distribution of values",
      col = "light grey",
      border = "white")
dev.off()
```

```
## pdf
## 2
```

## If conditionals

---

### Exercise 4

4a.

```
isPositive <- function(x){
  # The test condition of an if goes inside the ( ) what happens
```

```

# if the condition is TRUE goes within the { }
if(x > 0){
  TRUE
}else{
  FALSE
}
}

isPositive(10)

```

```
## [1] TRUE
```

```
isPositive(-10)
```

```
## [1] FALSE
```

4b.

```

checkCorrValue <- function(x, y){

  absCorrValue <- abs(cor.test(x, y)$estimate)

  if(absCorrValue > 0.6){
    return(TRUE)
  }else{
    return(FALSE)
  }
}

# Test with vectors Ozone and Temp from airquality dataset
checkCorrValue(x = airquality$Ozone, y = airquality$Temp)

```

```
## [1] TRUE
```

```
# Two additional tests
```

```
checkCorrValue(x = rnorm(10), y = rnorm(10))
```

```
## [1] FALSE
```

```
checkCorrValue(x = 1:10, y = 1:10)
```

```
## [1] TRUE
```

4c.

```

significanceSymbol <- function(x, y, ...){

  corTest <- cor.test(x,y,...)
  pvalue <- corTest$p.value

  if(pvalue >= 0.1){
    print("n.s.")
  }else if(pvalue < 0.001){
    print("***")
  }else if(pvalue < 0.01){
    print("**")
  }else if(pvalue < 0.05){
    print("*")
  }
}

```



```

    }else if(pvalue < 0.1){
      print("-")
    }
  }

significanceSymbol(x = airquality$Ozone, y = airquality$Temp)

## [1] "***"

```

## For loops

---

### Exercise 5

5a.

```

# Use na.rm = TRUE by default to avoid missing values
# in mean and sd calculation
#
# In addition let's define a number of decimal plates to
# round the output values (ndigits argument)
#
printMeanStd <- function(x, na.rm=TRUE, ndigits=2, ...){

  # Check if x is a matrix or a dataframe
  # If not stop the function execution
  #
  if(!is.matrix(x) & !is.data.frame(x)){
    stop("x must be a matrix or data frame")
  }

  # Calculate the mean and stdev for each column i
  # and print it to the console
  #
  for(i in 1:ncol(x)){ # let's iterate from 1 to ncol(x)

    # Paste is used to concatenate the text that is
    # outputed
    #
    print(paste("Column nr", i, colnames(x)[i], ":"))

    print(paste("Mean =",
                round(mean(x[,i], na.rm = na.rm), ndigits)))

    print(paste("Std-dev. =",
                round(sd(x[,i], na.rm = na.rm), ndigits)))
  }
}

printMeanStd(airquality)

```

```
## [1] "Column nr 1 Ozone :"
```

```
## [1] "Mean = 42.13"
```

```
## [1] "Std-dev. = 32.99"
```

```
## [1] "Column nr 2 Solar.R :"
```

```
## [1] "Mean = 185.93"
```

```
## [1] "Std-dev. = 90.06"
```

```
## [1] "Column nr 3 Wind :"
```

```
## [1] "Mean = 9.96"
```

```
## [1] "Std-dev. = 3.52"
```

```
## [1] "Column nr 4 Temp :"
```

```
## [1] "Mean = 77.88"
```

```
## [1] "Std-dev. = 9.47"
```

```
## [1] "Column nr 5 Month :"
```

```
## [1] "Mean = 6.99"
```

```
## [1] "Std-dev. = 1.42"
```

```
## [1] "Column nr 6 Day :"
```

```
## [1] "Mean = 15.8"
```

```
## [1] "Std-dev. = 8.86"
```

5b.

```
calcCorrelation <- function(xvec, ymat, thresh){

  # Check if xvec is a numeric vector
  # If not stop the function execution
  if(!is.numeric(xvec)){
    stop("xvec must be a numeric vector")
  }

  # Check if ymat is a matrix or a dataframe
  # stop if not
  if(!is.matrix(ymat) & !is.data.frame(ymat)){
    stop("ymat must be a matrix or data frame")
  }

  for(i in 1:ncol(ymat)){
    # Calculate the correlation
    corTest <- cor.test(xvec, ymat[,i])
    corValue <- corTest$estimate

    if(abs(corValue) > thresh){
      print(colnames(ymat)[i]) # Print the i-th variable name
      print(corTest) # print the cor.test result
    }
  }
}

# Let's test the function
calcCorrelation(airquality$Ozone, airquality[, -1], thresh = 0.6)

## [1] "Wind"
##
## Pearson's product-moment correlation
##
## data:  xvec and ymat[, i]
```

```

## t = -8.0401, df = 114, p-value = 9.272e-13
## alternative hypothesis: true correlation is not equal to 0
## 95 percent confidence interval:
## -0.7063918 -0.4708713
## sample estimates:
##      cor
## -0.6015465
##
## [1] "Temp"
##
## Pearson's product-moment correlation
##
## data:  xvec and ymat[, i]
## t = 10.418, df = 114, p-value < 2.2e-16
## alternative hypothesis: true correlation is not equal to 0
## 95 percent confidence interval:
##  0.5913340 0.7812111
## sample estimates:
##      cor
## 0.6983603

```