



Hands-on Lab : Create Tables and Load Data in PostgreSQL using pgAdmin

Estimated time needed: 20 minutes

In this lab, you will learn how to create tables and load data in the PostgreSQL database service using the pgAdmin graphical user interface (GUI) tool. The pgAdmin GUI provides an alternative to the command line for interacting with a PostgreSQL database using a graphical interface. This provides a number of key features for interacting with a PostgreSQL database in an easy to use format.

Software Used in this Lab

In this lab, you will use [PostgreSQL Database](#). PostgreSQL is a Relational Database Management System (RDBMS) designed to efficiently store, manipulate, and retrieve data.



To complete this lab you will utilize the PostgreSQL relational database service available as part of IBM Skills Network Labs (SN Labs) Cloud IDE. SN Labs is a virtual lab environment used in this course.

Database Used in this Lab

Books database has been used in this lab.

The following diagram shows the structure of the myauthors table from the Books database:

myauthors	
author_id	int
first_name	varchar(100)
middle_name	varchar(50)
last_name	varchar(100)

Objectives

After completing this lab, you will be able to use pgAdmin with PostgreSQL to:

- Create databases and tables in a PostgreSQL instance
- Load data into tables manually using the pgAdmin GUI
- Load data into tables from a text/script file


Lab Structure

In this lab, you will complete several tasks in which you will learn how to create tables and load data in the PostgreSQL database service using the pgAdmin graphical user interface (GUI) tool.


Task A: Create a database

First, to create a database on a PostgreSQL server instance, you'll first want to actually launch a PostgreSQL server instance on Cloud IDE and open up the pgAdmin Graphical User Interface.


1. Click on the Skills Network extension button on the left side of the window.
2. Open the "DATABASES" drop down menu and click on "PostgreSQL"
3. Click on the "Start" button. PostgreSQL may take a few moments to start.



4. Next, open the pgAdmin Graphical User Interface by clicking the "pgAdmin" button in the Cloud IDE interface.




5. Once the pgAdmin GUI opens, click on the **Servers** tab on the left side of the page. You will be prompted to enter a password.




6. To retrieve your password, click on the "PostgreSQL" tab near the top of the interface.

7. Click on the Copy icon to the left of your password to copy the session password onto your clipboard.



8. Navigate back to the "pgAdmin" tab and paste in your password, then click **OK**

9. You will then be able to access the pgAdmin GUI tool.



10. In the tree-view, expand **Servers** > **postgres** > **Databases**. If prompted, enter your PostgreSQL service session password. Right-click on **Databases** and go to **Create** > **Database**. In the **Database** box, type **Books** as the name for your new database, and then click **Save**. Proceed to Task B.

pgAdmin

File ▾Object ▾Tools ▾Help ▾

Browser

1

2

3

Servers (1)

postgres

Databases (1)

postgres

Cast

Catal

Event Triggers

Extensions

Foreign Data Wrappers

Languages

Publications

Schemas

Subscriptions

Login/Group Roles

Tablespaces

Create

Refresh...

Dashboard

Properties

SQL

Statistics

Server sessions

7

4

3

2

1

0

Tuples in

1

Inse

Create - Database

General

Definition

Security

Parameters

Advanced

SQL

Database

Books

Owner

postgres

Comment

i

?

Cancel

Reset

Save

Task B: Create tables

Now that you have your PostgreSQL service active and have created the **Books** database using pgAdmin, let's go ahead and create a few tables to populate the database and store the data that we wish to eventually upload into it.

1. In the tree-view, expand **Books** > **Schemas** > **public**. Right-click on **Tables** and go to **Create** > **Table**.

pgAdmin

File ▾ Object ▾ Tools ▾ Help ▾

Browser

Database sessions

Tuples in

Server activity

▼ Servers (1)

▼ postgres

▼ Databases (2)

▼ Books 1

▼ Schemas (1) 2

▼ public 3

▼ Tables 4

▼ Triggers

▼ Types

▼ Views

▼ Subscriptions

▼ postgres

▼ Login/Group Roles

▼ Tablespaces

Collations

Domains

FTS Configurations

FTS Dictionaries

FTS Parsers

FTS Templates

Foreign Tables

Functions

Materialized Views

Procedures

Sequences

Create >

Refresh...

Grant Wizard...

Search Objects...

Query Tool

Database sessions

Tuples in

Server activity

Sessions Locks Prepared Transactions

PID

User

Applic

pgAdi

2. On the **General** tab, in the **Name** box, type **myauthors** as name of the table. Don't click Save, proceed to the next step.

Create - Table

General

Columns

Advanced

Constraints

Partitions

Parameters

Security

SQL

Name

myauthors

Owner

postgres

Schema

public

Tablespace

Select an item...

Partitioned table?

No

Comment

i

?

Cancel

Reset

Save

3. Switch to tab **Columns** and click the **Add new row** button four times to add **4** column placeholders. Don't click Save, proceed to the next step.

Create - Table

General

Columns

Advanced

Constraints

Partitions

Parameters

Security

SQL

Inherited from table(s)

Select to inherit from...

Columns

		Name ▲	Data type	Length/Precision	Scale	Not NULL?	Primary key?
<div></div>	<div></div>	<div></div>	<div>Select an item...</div>			<div>No</div>	<div>No</div>
<div></div>	<div></div>	<div></div>	<div>Select an item...</div>			<div>No</div>	<div>No</div>
<div></div>	<div></div>	<div></div>	<div>Select an item...</div>			<div>No</div>	<div>No</div>
<div></div>	<div></div>	<div></div>	<div>Select an item...</div>			<div>No</div>	<div>No</div>

i

?

Cancel

Reset

Save

4. Enter the **myauthors** table definition structure information as shown in the image below in the highlighted boxes. Then click **Save**. Proceed to Task C.

Create - Table

General

Columns

Advanced

Constraints

Partitions

Parameters

Security

SQL

Inherited from table(s)

Select to inherit from...

Columns

author_id

integer

Yes

Yes

first_name

character varying

100

No

No

middle_name

character varying

50

No

No

last_name

character varying

100

No

No

i

?

Cancel


Reset

Save

Task C: Load data into tables manually using the pgAdmin GUI

Great! You now have a database and have created tables within it. With the pgAdmin GUI, you can insert values into the tables manually. This is useful if you have a few new entries you wish to add to the database. Let's see how to do it.

1. In the tree-view, expand **Tables**. Right-click on **myauthors** and go to **View/Edit Data > All Rows**.



2. You will insert 2 rows of data into the **myauthors** table. In the lower **Data Output** pane, enter **myauthors** table data information for 2 rows as shown in the highlighted boxes in the image below. Then click the **Save Data Changes** button. Proceed to Task D.





[illegible]


Task D: Load data into tables using a text/script file


In the previous task, you entered some data entries into a table manually with pgAdmin. While this method can be useful for small additions, if you wish to upload large amounts of data at once, that process becomes far too tedious. An alternative is to load data into tables from a text or script file containing the data you wish to enter. Let's take a look at how to do this.

1. Finally, you will import the remainder of the **myauthors** table data from a csv text file. Download the csv file below to your local computer:
 - [myauthors.csv](#)
2. In the tree-view, right-click on **myauthors** and go to **Import/Export**.

pgAdmin File ▾ Object ▾ Tools ▾ Help ▾

Browser     Dashboard Pr

▾  Servers (1)



3. Follow the instructions below to import:

- Make sure Import/Export is set to **Import**, Format = **csv** and Header = **Yes**. Then click on the **Select file** button by the Filename box.

Import/Export data - table 'myauthors'

Options

Columns

Import/Export

Import

1

File Info

4

Filename

...

Format

csv

2

Encoding

Select an item...

Miscellaneous

OID

No

Header

Yes

3

Delimiter

Select from list...

Specifies the character that separates columns within each row (line) of the file. The default is a tab character in text format, a comma in CSV format. This must be a single one-byte character. This option is not allowed when using binary format.

Cancel

OK

Click the **Upload File** button.

Select file

Home

Up

/var/lib/pgadmin/

Refresh

Edit

Upload File

Create Folder

Grid View

List View

Name	Size	Modified
sessions	4.0 kB	Mon Mar 22 02:15:08 2021
storage	4.0 kB	Mon Mar 22 02:11:24 2021

Show hidden files and folders?


Format

csv


Cancel

Select

- Double-click on the drop files area and load the **myauthors.csv** you downloaded earlier from your local computer storage.



- When the upload is complete, close the drop files area clicking the **X** button.



- Select the uploaded **myauthors.csv** file from the list and click the **Select** button.

Select file

/var/lib/pgadmin/myauthors.csv

Name	Size	Modified
myauthors.csv	26.0 kB	Mon Mar 22 08:19:26 2021
sessions	4.0 kB	Mon Mar 22 02:15:08 2021
storage	4.0 kB	Mon Mar 22 02:11:24 2021

Show hidden files and folders?☐

Format

csv

Cancel

Select

- Click **OK** and notification of import success should appear.

Import/Export data - table 'myauthors'

Options

Columns

Import/Export

Import

File Info

Filename

/var/lib/pgadmin/myauthors.csv

...

Format

csv

Encoding

Select an item...

Miscellaneous

OID

No

Header

Yes

Delimiter

Select from list...

Specifies the character that separates columns within each row (line) of the file. The default is a tab character in text format, a comma in CSV format. This must be a single one-byte character. This option is not allowed when using binary format.

✕ Cancel

✓ OK

Import - Copying table data

✕

Copying table data 'public.myauthors' on database 'Books' and server (postgres:5432)

Mon Mar 22 2021 02:26:40 GMT-0600 (Mountain Daylight Time)

🕒 0.02 seconds

📄 More details...

✕ Stop Process

✓

Successfully completed.

4. Repeat Task C Step 1 to check that the newly imported data rows appear along with your previously inserted 2 rows.

Other Contributors

- [David Pasternak](#)

Changelog

Date	Version	Changed by	Change Description
2021-03-15	1.0	Sandip Saha Joy	Created initial version
2021-10-18	1.1	David Pasternak	Updated lab instructions

© IBM Corporation 2021. All rights reserved.