

Π -Ware: An Embedded Hardware Description Language using Dependent Types

Author: João Paulo Pizani Flor
<joaopizani@uu.nl>

Supervisor: Wouter Swierstra
<w.s.swierstra@uu.nl>

Department of Information and Computing Sciences
Utrecht University

Tuesday 26th August, 2014

Introduction

What is Π -Ware

Background

Research Question

Research Question /
Methodology

DTP / Agda

Big picture

Agda

Π -Ware

Syntax

Semantics

Proofs

Conclusions

Limitations

Future work



Universiteit Utrecht

Table of Contents

Introduction

What is Π -Ware

Background

Research Question

Research Question / Methodology

DTP / Agda

Big picture

Agda

Π -Ware

Syntax

Semantics

Proofs

Conclusions

Limitations

Future work

Introduction

What is Π -Ware

Background

Research Question

Research Question /
Methodology

DTP / Agda

Big picture

Agda

Π -Ware

Syntax

Semantics

Proofs

Conclusions

Limitations

Future work



Universiteit Utrecht

What is Π -Ware

► Π -Ware är en...

Introduction

What is Π-Ware

Background

Research Question

Research Question /
Methodology

DTP / Agda

Big picture

Agda

Π-Ware

Syntax

Semantics

Proofs

Conclusions

Limitations

Future work



Universiteit Utrecht

Hardware design is hard(er)

- ▶ Strict(er) correctness requirements
 - You can't simply *update* a full-custom chip after production
 - Intel FDIIV
 - Expensive verification / validation (up to 50% of development costs)
- ▶ Low-level details (more) important
 - Layout / area
 - Power consumption / fault tolerance

Introduction

What is Π -Ware

Background

Research Question

Research Question /
Methodology

DTP / Agda

Big picture

Agda

Π -Ware

Syntax

Semantics

Proofs

Conclusions

Limitations

Future work



Universiteit Utrecht

Hardware design is growing

- ▶ Moore's law will still apply for some time
 - We can keep packing more transistors into same silicon area
- ▶ **But** optimizations in CPUs display diminishing returns
 - Thus, more algorithms *directly* in hardware

Introduction

What is Π -Ware

Background

Research Question

Research Question / Methodology

DTP / Agda

Big picture

Agda

Π -Ware

Syntax

Semantics

Proofs

Conclusions

Limitations

Future work



Universiteit Utrecht

Hardware Description Languages

- ▶ All started in the 1980s
- ▶ *De facto* industry standards: VHDL and Verilog
- ▶ Were intended for *simulation*, not modelling or synthesis
 - *Unsynthesizable* constructs
 - Widely variable tool support

Introduction

What is Π -Ware

Background

Research Question

Research Question / Methodology

DTP / Agda

Big picture

Agda

Π -Ware

Syntax

Semantics

Proofs

Conclusions

Limitations

Future work



Universiteit Utrecht

Functional Programming

- ▶ Easier to *reason* about program properties
- ▶ Inherently *parallel* and *stateless* semantics
 - In contrast to imperative programming

Introduction

What is Π-Ware

Background

Research Question

Research Question /
Methodology

DTP / Agda

- Big picture
- Agda

Π-Ware

- Syntax
- Semantics
- Proofs

Conclusions

Limitations

Future work



Universiteit Utrecht

Functional Hardware Description

- ▶ A functional program describes a circuit
- ▶ Several *functional* Hardware Description Languages (HDLs) during the 1980s
 - For example, μ FP [Sheeran, 1984]
- ▶ Later, *embedded* hardware Domain-Specific Languages (DSLs)
 - For example, Lava (Haskell) [Bjesse et al., 1998]

Introduction

What is Π -Ware

Background

Research Question

Research Question / Methodology

DTP / Agda

Big picture

Agda

Π -Ware

Syntax

Semantics

Proofs

Conclusions

Limitations

Future work



Universiteit Utrecht

Dependently-Typed Programming

Dependently-Typed Programming (DTP) är en
programmationstechnik...

Introduction

What is Π -Ware

Background

Research Question

Research Question /
Methodology

DTP / Agda

Big picture

Agda

Π -Ware

Syntax

Semantics

Proofs

Conclusions

Limitations

Future work



Universiteit Utrecht

Research Question / Methodology

► **Question:**

- “What are the improvements that DTP can bring to hardware design?”

► **Methodology:**

- Develop a hardware DSL, *embedded* in a dependently-typed language (Agda)
 - Called **Π -Ware**
 - allowing simulation, synthesis and verification

Introduction

What is Π-Ware

Background

Research Question

Research Question /
Methodology

DTP / Agda

Big picture

Agda

Π-Ware

Syntax

Semantics

Proofs

Conclusions

Limitations

Future work



Universiteit Utrecht

Dependently-Typed Programming

- ▶ **Disclaimer:** Suspend disbelief in syntax
 - Examples are in *Agda*
 - Syntax similar to Haskell, details further ahead
- ▶ Types can depend on values
 - Example: `data Vec (α : Set) : $\mathbb{N} \rightarrow$ Set where...`
 - Compare with Haskell (GADT style):
`data List :: * -> * where...`
- ▶ Types of arguments can depend on *values of previous arguments*
 - Ensure a “safe” domain
 - `take : (m : \mathbb{N}) \rightarrow Vec α ($m + n$) \rightarrow Vec α m`

Introduction

What is Π -Ware

Background

Research Question

Research Question /
Methodology

DTP / Agda

Big picture

Agda

Π -Ware

Syntax

Semantics

Proofs

Conclusions

Limitations

Future work



Universiteit Utrecht

Dependently-Typed Programming

- ▶ Type checking requires *evaluation* of functions
 - We want `Vec Bool (2 + 2)` to unify with `Vec Bool 4`
- ▶ Consequence: all functions must be *total*
- ▶ Termination checker (heuristics)
 - Structurally-decreasing recursion
 - This passes the check:

```
add : ℕ → ℕ → ℕ
add zero    y = y
add (suc x') y = suc (add x' y)
```
 - This does not:

```
silly : ℕ → ℕ
silly zero    = zero
silly (suc n') = silly [ n' / 2]
```

Introduction

What is Π -Ware

Background

Research Question

Research Question /
Methodology

DTP / Agda

Big picture

Agda

Π -Ware

Syntax

Semantics

Proofs

Conclusions

Limitations

Future work



Universiteit Utrecht

Dependently-Typed Programming

- ▶ Dependent pattern matching can *rule out* impossible cases

- Classic example: *safe head* function

$$\text{head} : \text{Vec } \alpha \ (\text{suc } n) \rightarrow \alpha$$
$$\text{head } (x :: xs) = x$$

- The **only** constructor returning $\text{Vec } \alpha \ (\text{suc } n)$ is $_::_$

Introduction

What is Π-Ware

Background

Research Question

Research Question /
Methodology

DTP / Agda

Big picture

Agda

Π-Ware

Syntax

Semantics

Proofs

Conclusions

Limitations

Future work



Universiteit Utrecht

Dependent types as logic

- ▶ Programming language / Theorem prover
 - Types as propositions, terms as proofs [Wadler, 2014]

- ▶ Example:

- Given the relation:

```
data __≤__ : ℕ → ℕ → Set where
  z≤n : ∀ {n}                → zero ≤ n
  s≤s  : ∀ {m n} → m ≤ n → suc m ≤ suc n
```

- Proposition:

```
twoLEQFour : 2 ≤ 4
```

- Proof:

```
twoLEQFour = s≤s (s≤s z≤n)
s≤s (s≤s (z≤n : 0 ≤ 4) : 1 ≤ 4) : 2 ≤ 4
```

Introduction

What is Π -Ware

Background

Research Question

Research Question /
Methodology

DTP / Agda

Big picture

Agda

Π -Ware

Syntax

Semantics

Proofs

Conclusions

Limitations

Future work



Universiteit Utrecht

Agda syntax for Haskell programmers

- ▶ Liberal identifier lexing (Unicode **everywhere**)
 - $a \equiv b + c$ is a valid identifier, $a \equiv b + c$ an expression
 - Used a lot in Agda's standard library: \times , \uplus , \wedge
 - And in Π -Ware: \mathbb{C} , $\llbracket c \rrbracket$, \Downarrow , \Uparrow
- ▶ *Mixfix* notation
 - $_[_] := _$ is the vector update function: $v \ [\# \ 3 \] := \text{true}$.
 - $_[_] := _ \ v \ (\# \ 3) \ \text{true} \iff v \ [\# \ 3 \] := \text{true}$
- ▶ Almost nothing built-in
 - $_+_ \ : \mathbb{N} \rightarrow \mathbb{N} \rightarrow \mathbb{N}$ defined in `Data.Nat`
 - $\text{if_then_else_} : \text{Bool} \rightarrow \alpha \rightarrow \alpha \rightarrow \alpha$ defined in `Data.Bool`

Introduction

What is Π -Ware

Background

Research

Question

Research Question /
Methodology

DTP / Agda

Big picture

Agda

Π -Ware

Syntax

Semantics

Proofs

Conclusions

Limitations

Future work



Universiteit Utrecht

Agda syntax for Haskell programmers

► Implicit arguments

- Don't have to be passed if Agda can **guess** it
- Syntax: $\epsilon : \{\alpha : \text{Set}\} \rightarrow \text{Vec } \alpha \text{ zero}$

► “For all” syntax: $\forall n \iff (n : _)$

- Where $_$ means: guess this type (based on other args)
- Example:
 - $\forall n \rightarrow \text{zero} \leq n$
 - $\text{data } _ \leq _ : \mathbb{N} \rightarrow \mathbb{N} \rightarrow \text{Set}$

► It's common to combine both:

- $\forall \{\alpha\} n \rightarrow \text{Vec } \alpha (\text{suc } n) \rightarrow \alpha \iff$
 $\{\alpha : _ \} \{n : _ \} \rightarrow \text{Vec } \alpha n \rightarrow \alpha$

Introduction

What is Π -Ware

Background

Research Question

Research Question / Methodology

DTP / Agda

Big picture

Agda

Π -Ware

Syntax

Semantics

Proofs

Conclusions

Limitations

Future work



Universiteit Utrecht

Low-level circuits

- Structural representation
- Untyped but *sized*

data $\mathbb{C}' : \mathbb{N} \rightarrow \mathbb{N} \rightarrow \text{Set}$

data \mathbb{C}' where

Nil : $\mathbb{C}' \text{ zero zero}$

Gate : $(g\# : \text{Gates}\#) \rightarrow \mathbb{C}' (|\text{in}| g\#) (|\text{out}| g\#)$

Plug : $\forall \{i\ o\} \rightarrow (f : \text{Fin } o \rightarrow \text{Fin } i) \rightarrow \mathbb{C}' i\ o$

DelayLoop : $(c : \mathbb{C}' (i + l) (o + l)) \{\text{comb}'\ c\} \rightarrow \mathbb{C}' i\ o$

$_ \gg' _ : \mathbb{C}' i\ m \rightarrow \mathbb{C}' m\ o \rightarrow \mathbb{C}' i\ o$

$_ |' _ : \mathbb{C}' i_1\ o_1 \rightarrow \mathbb{C}' i_2\ o_2 \rightarrow \mathbb{C}' (i_1 + i_2) (o_1 + o_2)$

$_ |+' _ : \mathbb{C}' i_1\ o \rightarrow \mathbb{C}' i_2\ o \rightarrow \mathbb{C}' (\text{succ } (i_1 \sqcup i_2))\ o$

Introduction

What is Π -Ware

Background

Research Question

Research Question / Methodology

DTP / Agda

Big picture

Agda

Π -Ware

Syntax

Semantics

Proofs

Conclusions

Limitations

Future work



Universiteit Utrecht

Atoms

- ▶ How to carry values of an Agda type in *one* wire
- ▶ Defined by the `Atomic` type class in `PiWare.Atom`

`record Atomic` : `Set1` `where`
`field`

`Atom` : `Set`

`|Atom|−1` : \mathbb{N}

`n→atom` : `Fin` (`suc` `|Atom|−1`) \rightarrow `Atom`

`atom→n` : `Atom` \rightarrow `Fin` (`suc` `|Atom|−1`)

`inv−left` : $\forall i \rightarrow \text{atom} \rightarrow n \ (n \rightarrow \text{atom} \ i) \equiv i$

`inv−right` : $\forall a \rightarrow n \rightarrow \text{atom} \ (\text{atom} \rightarrow n \ a) \equiv a$

`|Atom|` = `suc` `|Atom|−1`

`Atom#` = `Fin` `|Atom|`

Introduction

What is Π -Ware

Background

Research Question

Research Question /
Methodology

DTP / Agda

Big picture

Agda

Π -Ware

Syntax

Semantics

Proofs

Conclusions

Limitations

Future work



Universiteit Utrecht

Atomic instances

- ▶ Examples of types that can be **Atomic**
 - Bool, std_logic, other multi-valued logics
 - Predefined in the library: **PiWare.Atom.Bool**
- ▶ First, define how many atoms we are interested in
 - Need at least 1 (later why)

$|B|-1 = 1$

$|B| = \text{suc } |B|-1$

- ▶ Friendlier names for the indices (elements of **Fin 2**)

pattern **False#** = Fz

pattern **True#** = Fs Fz

Introduction

What is Π -Ware

Background

Research Question

Research Question / Methodology

DTP / Agda

Big picture

Agda

Π -Ware

Syntax

Semantics

Proofs

Conclusions

Limitations

Future work



Universiteit Utrecht

Atomic instance (Bool)

- Bijection between $\{n \in \mathbb{N} \mid n < 2\}$ (Fin 2) and Bool

$$n \rightarrow B = \lambda \{ \text{False\#} \rightarrow \text{false}; \text{True\#} \rightarrow \text{true} \}$$
$$B \rightarrow n = \lambda \{ \text{false} \rightarrow \text{False\#}; \text{true} \rightarrow \text{True\#} \}$$

- Proof that $n \rightarrow B$ and $B \rightarrow n$ are inverses

$$\text{inv-left-B} = \lambda \{ \text{False\#} \rightarrow \text{refl}; \text{True\#} \rightarrow \text{refl}; \}$$
$$\text{inv-right-B} = \lambda \{ \text{false} \rightarrow \text{refl}; \text{true} \rightarrow \text{refl} \}$$

- With all pieces at hand, we construct the instance

$$\begin{aligned} \text{Atomic-B} = \text{record} \{ & \text{Atom} = B \\ & ; |\text{Atom}|-1 = |B|-1 \\ & ; n \rightarrow \text{atom} = n \rightarrow B \\ & ; \text{atom} \rightarrow n = B \rightarrow n \\ & ; \text{inv-left} = \text{inv-left-B} \\ & ; \text{inv-right} = \text{inv-right-B} \} \end{aligned}$$

Introduction

What is Π -Ware

Background

Research Question

Research Question / Methodology

DTP / Agda

Big picture

Agda

Π -Ware

Syntax

Semantics

Proofs

Conclusions

Limitations

Future work



Universiteit Utrecht

The Gates type class

$W : \mathbb{N} \rightarrow \text{Set}$

$W = \text{Vec Atom}$

record Gates : Set where

field

|Gates| : \mathbb{N}

|in| |out| : Fin |Gates| $\rightarrow \mathbb{N}$

spec : $(g : \text{Fin } |Gates|)$
 $\rightarrow (W (|in| \ g) \rightarrow W (|out| \ g))$

Gates# = Fin |Gates|

Introduction

What is Π -Ware

Background

Research Question

Research Question /
Methodology

DTP / Agda

Big picture

Agda

Π -Ware

Syntax

Semantics

Proofs

Conclusions

Limitations

Future work



Universiteit Utrecht

Gates instances

- ▶ Example: `PiWare.Gates.BoolTrio`
- ▶ First, how many gates are there in the library

`|BoolTrio| = 5`

- ▶ Then the friendlier names for the indices

```
pattern FalseConst# = Fz
pattern TrueConst#  = Fs Fz
pattern Not#         = Fs (Fs Fz)
pattern And#         = Fs (Fs (Fs Fz))
pattern Or#          = Fs (Fs (Fs (Fs Fz)))
```

Introduction

What is Π -Ware

Background

Research Question

Research Question /
Methodology

DTP / Agda

Big picture

Agda

Π -Ware

Syntax

Semantics

Proofs

Conclusions

Limitations

Future work



Universiteit Utrecht

Gates instance (BoolTrio)

- ▶ Defining the *interfaces* of the gates

```
[in] FalseConst# = 0
```

```
|in| TrueConst# = 0
```

```
|in| Not# = 1
```

$$|in|_{And\#} = 2$$
$$|in|_{Or\#} = 2$$
$$|out|_{-} = 1$$

- And the specification function for each gate

```
spec=false == [ false ]
```

```
spec-true      _      = [ true  ]
```

$$\text{spec-not} \quad (x :: \varepsilon) \quad = \text{[not } x \text{]}$$

spec-and $(x :: y :: \varepsilon) = [x \wedge y]$

spec-or $(x :: y :: \varepsilon) = [x \vee y]$

Introduction

What is Π-Ware

Background

Research

Question

Research Question /
Methodology

DTP / Agda

Big picture

Agda

Π-Ware

Syntax

Semantics

Proofs

Conclusions

Limitations

Future work



Universiteit Utrecht

Gates instance (BoolTrio)

- Mapping each gate index to its respective specification

```
specs-BoolTrio FalseConst# = spec-false
```

```
specs-BoolTrio TrueConst# = spec-true
```

$$\text{specs} - \text{BoolTrio } \text{Not\#} = \text{spec} - \text{not}$$

```
specs-BoolTrio And# = spec-and
```

```
specs-BoolTrio Or# = spec-or
```

- With all pieces at hand, we construct the instance

BoolTrio : Gates

```

BoolTrio = record { |Gates| = |BoolTrio|
                    ; |in|   = |in|
                    ; |out|  = |out|
                    ; spec   = specs-BoolTrio }

```

Introduction

What is Π-Ware

Background

Research Question

Research Question / Methodology

DTP / Agda

Big picture

Agda

П-Ware

Syntax

Semantics

Proofs

Conclusions

Limitations

Future work



High-level circuits

- ▶ User is not supposed to describe circuits at low level (\mathbb{C}')
- ▶ The high level circuit type (\mathbb{C}) allows for *typed* circuit interfaces

- Input and output indices are Agda types

```
data  $\mathbb{C}$  ( $\alpha \beta : \text{Set}$ )  $\{i j : \mathbb{N}\} : \text{Set}$  where
  Mk $\mathbb{C} : \{ \{s\alpha : \Downarrow W \Uparrow \alpha \{i\} \} \} \{ \{s\beta : \Downarrow W \Uparrow \beta \{j\} \} \}$ 
     $\rightarrow \mathbb{C}' i j \rightarrow \mathbb{C} \alpha \beta \{i\} \{j\}$ 
```

- ▶ Mk \mathbb{C} takes:

- Low level description (\mathbb{C}')
- Information on how to *synthesize* elements of α and β
 - Passed as *instance arguments* (class constraints)

Introduction

What is Π -Ware

Background

Research Question

Research Question /
Methodology

DTP / Agda

Big picture

Agda

Π -Ware

Syntax

Semantics

Proofs

Conclusions

Limitations

Future work



Universiteit Utrecht

Synthesizable

- ▶ $\Downarrow W \Uparrow$ type class (pronounced Synthesizable)
 - Describes how to synthesize a given Agda type (α)
 - Two fields: from element of α to a *word* and back

```
record  $\Downarrow W \Uparrow$  ( $\alpha$  : Set) { $i$  :  $\mathbb{N}$ } : Set where
  constructor  $\Downarrow W \Uparrow$  [ $\_$ ,  $\_$ ]
  field
```

$$\Downarrow : \alpha \rightarrow W\ i$$
$$\Uparrow : W\ i \rightarrow \alpha$$

Introduction

What is Π -Ware

Background

Research Question

Research Question /
Methodology

DTP / Agda

Big picture

Agda

Π -Ware

Syntax

Semantics

Proofs

Conclusions

Limitations

Future work



Universiteit Utrecht

$\Downarrow W \Uparrow$ instances

- ▶ Any *finite* type can have such an instance
- ▶ Predefined in the library: `Bool`; `_×_`; `_⊔_`; `Vec`
- ▶ Example: instance for products (`_×_`)

$$\Downarrow W \Uparrow - \times : \{ \mid s\alpha : \Downarrow W \Uparrow \alpha \{i\} \} \{ \mid s\beta : \Downarrow W \Uparrow \beta \{j\} \} \\ \rightarrow \Downarrow W \Uparrow (\alpha \times \beta)$$

$$\Downarrow W \Uparrow - \times \{ \alpha \} \{ i \} \{ \beta \} \{ j \} \{ \mid s\alpha \} \{ \mid s\beta \} = \Downarrow W \Uparrow [\text{down} , \text{up}]$$

where $\text{down} : (\alpha \times \beta) \rightarrow W (i + j)$
 $\text{down} (a , b) = (\Downarrow a) ++ (\Downarrow b)$

$$\text{up} : W (i + j) \rightarrow (\alpha \times \beta)$$

$$\text{up } w \text{ with splitAt } i \text{ } w$$

$$\text{up } .(\Downarrow a ++ \Downarrow b) \mid \Downarrow a , \Downarrow b , \text{refl} = \Uparrow \Downarrow a , \Uparrow \Downarrow b$$

Introduction

What is Π -Ware

Background

Research

Question

Research Question /
Methodology

DTP / Agda

Big picture

Agda

Π -Ware

Syntax

Semantics

Proofs

Conclusions

Limitations

Future work



Universiteit Utrecht

Synthesizable

- Both fields \downarrow and \uparrow should be inverses of each other

Introduction

What is Π-Ware

Background

Research Question

Research Question / Methodology

DTP / Agda

Big picture

Agda

Π-Ware

Syntax

Semantics

Proofs

Conclusions

Limitations

Future work



Universiteit Utrecht


Synthesis semantics

- ▶ Netlist: digraph with *gates* as nodes and *buses* as edges
- ▶ Synthesis semantics: given netlists of subcircuits, build combination

$\text{Nil} : \mathbb{C} \ 0 \ 0$

$$\frac{i \ o : \mathbb{N} \quad f : \text{Fin } o \rightarrow \text{Fin } i}{\text{Plug } f : \mathbb{C} \ i \ o}$$

$$\frac{g\# : \text{Gate}\#}{\text{Gate } g\# : \mathbb{C} \ (\text{ins } g\#) \ (\text{outs } g\#)}$$

$$\frac{c : \mathbb{C} \ (i+1) \ (o+1)}{\text{DelayLoop} : \mathbb{C} \ i \ o}$$


Introduction

What is Π -Ware

Background

Research Question

Research Question / Methodology

DTP / Agda

Big picture

Agda

Π -Ware

Syntax

Semantics

Proofs


Conclusions

Limitations


Future work

Synthesis semantics


$$\frac{c_1 : \mathbb{C} \, i \, m \quad c_2 : \mathbb{C} \, m \, o}{c_1 \gg' c_2 : \mathbb{C} \, i \, o}$$



$$\frac{c_1 : \mathbb{C} \, i_1 \, o_1 \quad c_2 : \mathbb{C} \, i_2 \, o_2}{c_1 \mid' c_2 : \mathbb{C} \, (i_1 + i_2) \, (o_1 + o_2)}$$



$$\frac{c_1 : \mathbb{C} \, i_1 \, o \quad c_2 : \mathbb{C} \, i_2 \, o}{c_1 \mid + c_2 : \mathbb{C} \, (1 + (i_1 \sqcup i_2)) \, o}$$



Introduction

What is Π -Ware

Background

Research Question

Research Question / Methodology

DTP / Agda

Big picture

Agda

Π -Ware

Syntax

Semantics

Proofs

Conclusions

Limitations

Future work



Universiteit Utrecht

Synthesis semantics

Missing “pieces”:

► Adapt **Atomic**

- New field: a **VHDLTypeDecl**
 - Such as: **type** ident **is** (elem1, elem2);
 - Enumerations, integers (ranges), records.
- New field: **atomVHDL** : **Atom#** \rightarrow **VHDLExpr**

► Adapt **Gates**

- For each gate, a corresponding **VHDLEntity**
- **netlist** : (**g#** : **Gates#**) \rightarrow **VHDLEntity** (**|in| g#**) (**|out| g#**)
 - The VHDL entity has the *interface* of corresponding gate

Introduction

What is Π -Ware

Background

Research Question

Research Question / Methodology

DTP / Agda

Big picture

Agda

Π -Ware

Syntax

Semantics

Proofs

Conclusions

Limitations

Future work



Universiteit Utrecht

Simulation semantics

► Two levels of abstraction

- High-level simulation ($\llbracket _ \rrbracket$) for high-level circuits (\mathbb{C})
- Low-level simulation ($\llbracket _ \rrbracket'$) for low-level circuits (\mathbb{C}')

► Two kinds of simulation

- Combinational simulation ($\llbracket _ \rrbracket$) for stateless circuits
- Sequential simulation ($\llbracket _ \rrbracket^*$) for stateful circuits

► High level defined in terms of low level

$$\llbracket _ \rrbracket : \forall \{ \alpha \ i \ \beta \ j \} \rightarrow (c : \mathbb{C} \ \alpha \ \beta \ \{ i \} \ \{ j \}) \rightarrow (\alpha \rightarrow \beta)$$
$$\llbracket \text{MkC} \ \{ s\alpha \} \ \{ s\beta \} \ c' \rrbracket = \uparrow \circ \llbracket c' \rrbracket' \circ \downarrow$$

Introduction

What is Π -Ware

Background

Research Question

Research Question / Methodology

DTP / Agda

Big picture

Agda

Π -Ware

Syntax

Semantics

Proofs

Conclusions

Limitations

Future work



Universiteit Utrecht

Combinational simulation (excerpt)

$$\llbracket _ \rrbracket' : \forall \{i\ o\} \rightarrow (c : \mathbb{C}'\ i\ o) \{p : \text{comb}'\ c\} \rightarrow (\mathbb{W}\ i \rightarrow \mathbb{W}\ o)$$
$$[\text{Ni}]' = \text{const } \varepsilon$$
$$\llbracket \text{Gate } g^\# \rrbracket' = \text{spec } g^\#$$
$$[\![\text{Plug } p \]\!] = \text{plugOutputs } p$$
$$\llbracket \text{DelayLoop } c \rrbracket' \{ () \} v$$
$$\llbracket c_1 \gg' c_2 \rrbracket' \{p_1, p_2\} = \llbracket c_2 \rrbracket' \{p_2\} \circ \llbracket c_1 \rrbracket' \{p_1\}$$
$$\llbracket _ + _ \rrbracket' \{i_1\} \ c_1 \ c_2 \rrbracket' \{p_1, p_2\} =$$

$$\llbracket \llbracket c_1 \rrbracket' \{p_1\}, \llbracket c_2 \rrbracket' \{p_2\} \rrbracket' \circ \text{untag} \{i_1\}$$

► Remarks:

- Proof requires c to be combinational
- **Gate** case uses specification function
- **DelayLoop** case can be *discharged*

Introduction

What is Π-Ware

Background

Research Question

Research Question /
Methodology

DTP / Agda

Big picture

Agda

Π-Ware

Syntax

Semantics

Proofs

Conclusions

Limitations

Future work



Universiteit Utrecht

Sequential simulation

- ▶ Inputs and outputs become **Streams**
 - $C' i o \implies \text{Stream } (W i) \rightarrow \text{Stream } (W o)$
 - **Stream**: infinite list
- ▶ We can't write a recursive evaluation function over **Streams**
 - *Sum* case ($_|_ + _|_$) needs $(\text{Stream } (\alpha \uplus \beta) \rightarrow \text{Stream } \alpha \times \text{Stream } \beta)$
 - What if there are no *lefts* (or *rights*)?
- ▶ A stream function is not an accurate model for hardware
 - A function of type $(\text{Stream } \alpha \rightarrow \text{Stream } \beta)$ can “look ahead”
 - For example, $\text{tail } (x_0 :: x_1 :: x_2 :: xs) = x_1 :: x_2 :: xs$

Introduction

What is Π -Ware

Background

Research Question

Research Question /
Methodology

DTP / Agda

Big picture

Agda

Π -Ware

Syntax

Semantics

Proofs

Conclusions

Limitations

Future work



Universiteit Utrecht

Causal stream functions

Solution: sequential simulation based on a *causal* stream function

Some definitions:

- ▶ Causal context: past + present values

$$\Gamma c : (\alpha : \text{Set}) \rightarrow \text{Set}$$

$$\Gamma c \alpha = \alpha \times \text{List } \alpha$$

- ▶ Causal stream function: produces **one** (current) output

$$_ \Rightarrow^c _ : (\alpha \beta : \text{Set}) \rightarrow \text{Set}$$

$$\alpha \Rightarrow^c \beta = \Gamma c \alpha \rightarrow \beta$$

Introduction

What is Π -Ware

Background

Research Question

Research Question /
Methodology

DTP / Agda

Big picture

Agda

Π -Ware

Syntax

Semantics

Proofs

Conclusions

Limitations

Future work



Universiteit Utrecht

Sequential simulation

- ▶ We can then “run” the step-by-step function to produce a whole **Stream**
 - Idea from “The Essence of Dataflow Programming” [Uustalu and Vene, 2005]

$$\text{runc}' : (\alpha \Rightarrow_{\text{c}} \beta) \rightarrow (\Gamma_{\text{c}} \alpha \times \text{Stream } \alpha) \rightarrow \text{Stream } \beta$$

$$\text{runc}' f ((x^0, x^-), (x^1 :: x^+)) = f (x^0, x^-) :: \# \text{runc}' f ((x^1, x^0 :: x^-), x^+)$$

$$\text{runc} : (\alpha \Rightarrow_{\text{c}} \beta) \rightarrow (\text{Stream } \alpha \rightarrow \text{Stream } \beta)$$

$$\text{runc } f \ (x^0 :: x^+) = \text{runc}' \ f \ ((x^0, []), b \ x^+)$$

- Obtaining the stream-based simulation function:

$$\llbracket *' \rrbracket : \forall \{i\ o\} \rightarrow \mathbb{C}'\ i\ o \rightarrow (\text{Stream}\ (W\ i) \rightarrow \text{Stream}\ (W\ o))$$


$$[_] *' = \text{runc} \circ [_] \text{c}$$

Future work



Universiteit Utrecht

Sample circuit: XOR



$\underline{VC} : \mathbb{C} (B \times B) B$

$\underline{VC} = \text{pForkX}$

$\gg (\neg C \parallel \text{idC} \gg \wedge C) \parallel (\text{idC} \parallel \neg C \gg \wedge C)$
 $\gg \vee C$

Introduction

What is Π -Ware

Background

Research

Question

Research Question /
Methodology

DTP / Agda

Big picture

Agda

Π -Ware

Syntax

Semantics

Proofs

Conclusions

Limitations

Future work



Universiteit Utrecht

Specification of XOR

- ▶ To define *correctness* we need a *specification function*
 - Listing all possibilities (truth table)
 - Based on pre-existing functions (standard library)
- ▶ Truth table

$\underline{\text{VC}}\text{-spec-table} : (B \times B) \rightarrow B$

$\underline{\text{VC}}\text{-spec-table} \text{ (false , false) } = \text{false}$

$\underline{\text{VC}}\text{-spec-table} \text{ (false , true) } = \text{true}$

$\underline{\text{VC}}\text{-spec-table} \text{ (true , false) } = \text{true}$

$\underline{\text{VC}}\text{-spec-table} \text{ (true , true) } = \text{false}$

Introduction

What is Π -Ware

Background

Research Question

Research Question /
Methodology

DTP / Agda

Big picture

Agda

Π -Ware

Syntax

Semantics

Proofs

Conclusions

Limitations

Future work



Universiteit Utrecht

Proof of XOR (truth table)

$$\text{vC-proof-table} : \llbracket \text{vC} \rrbracket (a, b) \equiv \text{vC-spec-table} (a, b)$$

```
VC-proof-table  false  false  = refl
```

```
VC-proof-table  false  true  = refl
```

```
VC-proof-table  true  false = refl
```

```
VC-proof-table  true  true  = refl
```

► Proof by *case analysis*

- Could be automated (reflection)

Introduction

What is Π-Ware

Background

Research

Question

Research Question /
Methodology

DTP / Agda

Big picture

Agda

Π-Ware

Syntax

Semantics

Proofs

Conclusions

Limitations

Future work



Universiteit Utrecht

Specification of XOR

- Based (`_xor_`) from `Data.Bool`

`_xor_` : $B \rightarrow B \rightarrow B$

`true xor b` = `not b`

`false xor b` = `b`

- Adapted interface to match exactly `⊔C`

`⊔C-spec-subfunc` : $(B \times B) \rightarrow B$

`⊔C-spec-subfunc` = `uncurry' _xor_`

Introduction

What is Π -Ware

Background

Research Question

Research Question /
Methodology

DTP / Agda

Big picture

Agda

Π -Ware

Syntax

Semantics

Proofs

Conclusions

Limitations

Future work



Universiteit Utrecht

Proof of XOR (pre-existing)

- Proof based on $\underline{\text{VC}}\text{-spec-subfunc}$

$$\underline{\text{VC}}\text{-proof-subfunc} : \llbracket \underline{\text{VC}} \rrbracket (a, b) \equiv \underline{\text{VC}}\text{-spec-subfunc} (a, b)$$
$$\underline{\text{VC}}\text{-proof-subfunc} = \underline{\text{VC}}\text{-xor-equiv}$$

- Need a lemma to complete the proof
 - Circuit is defined using {NOT, AND, OR}
 - $\underline{\text{xor}}$ is defined directly by pattern matching

$$\underline{\text{VC}}\text{-xor-equiv} : (\text{not } a \wedge b) \vee (a \wedge \text{not } b) \equiv (a \text{ xor } b)$$

Introduction

What is Π -Ware

Background

Research

Question

Research Question /
Methodology

DTP / Agda

Big picture

Agda

Π -Ware

Syntax

Semantics

Proofs

Conclusions

Limitations

Future work



Universiteit Utrecht

Circuit “families”

- ▶ We can also prove properties of circuit “families”
- ▶ Example: an AND gate definition with generic number of inputs

$\text{andN}' : \forall n \rightarrow \mathbb{C}' \ n \ 1$

$\text{andN}' \ \text{zero} = \text{TC}'$

$\text{andN}' \ (\text{suc } n) = \text{idC}' \mid' \text{andN}' \ n \ \gg' \wedge \mathbb{C}'$

- ▶ Example proof: when all inputs are **true**, output is **true**
 - For *any* number of inputs
 - Proof by induction on n (number of inputs)

Introduction

What is Π -Ware

Background

Research Question

Research Question / Methodology

DTP / Agda

Big picture

Agda

Π -Ware

Syntax

Semantics

Proofs

Conclusions

Limitations

Future work



Universiteit Utrecht

Problems

- This proof is done at the *low level*

$$\begin{aligned}\text{proof-andN}' &: \forall n \rightarrow \llbracket \text{andN}' n \rrbracket' (\text{replicate true}) \equiv [\text{true}] \\ \text{proof-andN}' \text{ zero} &= \text{refl} \\ \text{proof-andN}' (\text{suc } n) &= \text{cong } (\text{spec-and} \circ (_ :: _ \text{ true})) \\ &\quad (\text{proof-andN}' n)\end{aligned}$$

- Still problems with inductive proofs in the high level
 - Guess: definition of \mathbb{C} and $\llbracket _ \rrbracket$ prevent goal reduction

Introduction

What is Π -Ware

Background

Research

Question

Research Question /
Methodology

DTP / Agda

Big picture

Agda

Π -Ware

Syntax

Semantics

Proofs

Conclusions

Limitations


Future work



Universiteit Utrecht

Sequential proofs

- Example of sequential circuit: a *register*



- Respective Π -Ware circuit description

$\text{reg} : \mathbb{C} (B \times B) B$

$\text{reg} = \text{delayC} (\text{arr} \gg \text{mux2to1} \gg \times \mathbb{C})$

where $\text{arr} = (\uparrow \mathbb{C} \parallel \text{idC}) \gg \text{ALRC} \gg (\text{idC} \parallel \uparrow \mathbb{C})$

Introduction

What is Π -Ware

Background

Research

Question

Research Question /
Methodology

DTP / Agda

Big picture

Agda

Π -Ware

Syntax

Semantics

Proofs

Conclusions

Limitations

Future work



Universiteit Utrecht

Register example

- ▶ Example (test case) of register behaviour

loads inputs : Stream Bool

loads = true :: # (true :: # (false :: # repeat false))

inputs = true :: # (false :: # (true :: # repeat false))

actual = take 42 ([reg] * \$ zipWith _,_ inputs loads)

test-reg = actual \equiv true \triangleleft false \triangleleft replicate false

- ▶ Still problems with *infinite* expected vs. actual comparisons
 - Normal Agda equality ($_ \equiv _$) does not work
 - Need to use *bisimilarity*

Introduction

What is Π -Ware

Background

Research Question

Research Question / Methodology

DTP / Agda

Big picture

Agda

Π -Ware

Syntax

Semantics

Proofs

Conclusions

Limitations

Future work



Universiteit Utrecht

Current limitations / trade-offs

- ▶ Interface of generated netlists is always *flat*
 - One input, one output

```
entity fullAdd8 is
port (
  inputs   : in  std_logic_vector(16 downto 0);
  outputs  : out std_logic_vector(8  downto 0)
);
end fullAdd8;
```

- ▶ Due to the indices of \mathbb{C}' (naturals)
 - Can't distinguish $\mathbb{C}'\ 17\ 9$ from $\mathbb{C}'\ (1 + 8 + 8)\ (8 + 1)$

Introduction

What is Π -Ware

Background

Research Question

Research Question / Methodology

DTP / Agda

Big picture

Agda

Π -Ware

Syntax

Semantics

Proofs

Conclusions

Limitations

Future work



Universiteit Utrecht

Current limitations / trade-offs

- ▶ Proofs on high-level families of circuits
 - Probably due to definitions of \mathbb{C} and $\llbracket _ \rrbracket$
- ▶ Proofs with infinite comparisons (sequential circuits)

Introduction

What is Π -Ware

Background

Research Question

Research Question / Methodology

DTP / Agda

Big picture

Agda

Π -Ware

Syntax

Semantics

Proofs

Conclusions

Limitations

Future work



Universiteit Utrecht

Thank you!

Questions?

Mede mogelijk gemaakt door:

Utrechts
Universiteitsfonds



Universiteit Utrecht



Universiteit Utrecht

References I



Lava: hardware design in Haskell.

Sheeran, M. (1984).

In *Proceedings of the 1984 ACM Symposium on LISP and Functional Programming*, LFP '84, pages 104–112, New York, NY, USA. ACM.



The essence of dataflow programming.

In *Proceedings of the Third Asian Conference on Programming Languages and Systems, APLAS'05*, pages 2–18, Berlin, Heidelberg. Springer-Verlag.

Future work



References II



Wadler, P. (2014).

Propositions as types.

Unpublished note, <http://homepages.inf.ed.ac.uk/wadler/papers/propositions-as-types/propositions-as-types.pdf>.

Introduction

What is Π -Ware

Background

Research Question

Research Question /
Methodology

DTP / Agda

Big picture

Agda

Π -Ware

Syntax

Semantics

Proofs

Conclusions

Limitations

Future work



Universiteit Utrecht