

ATIVIDADE I
RELATIONAL DATABASE E ADVANCED SQL
PROFESSOR LUCIANO INÁCIO DE MELO
29ABD
JOAO PAULO MARTINS RODRIGUES
RM 364668

```
1)
INSERT ALL
  WHEN salary > 20000 THEN
    INTO special_sal (employee_id, salary) VALUES (employee_id, salary)
  ELSE
    INTO sal_history (employee_id, hire_date, salary) VALUES (employee_id, hire_date, salary)
    INTO mgr_history (employee_id, manager_id, salary) VALUES (employee_id, manager_id, salary)
SELECT employee_id, hire_date, manager_id, salary
FROM employees
WHERE employee_id < 125;

2)
INSERT INTO sales_info (employee_id, week, sales)
SELECT employee_id, week_id, sales
FROM sales_source_data
UNPIVOT (sales FOR dia IN (sales_mon, sales_tue, sales_wed, sales_thur, sales_fri));

3)
SELECT manager_id, job_id, SUM(salary) AS total_salarios
FROM employees
WHERE manager_id < 120
GROUP BY ROLLUP (manager_id, job_id);

4)
SELECT manager_id, job_id, SUM(salary) AS total_salarios
FROM employees
WHERE manager_id < 120
GROUP BY CUBE (manager_id, job_id);

5)
MERGE INTO bonificacoes b
USING bonificacoes_temp t
ON (b.id_funcionario = t.id_funcionario)
WHEN MATCHED THEN UPDATE SET
  b.nome = t.nome,
  b.valor_bonificacao = t.valor_bonificacao
WHERE (b.nome <> t.nome OR b.valor_bonificacao <> t.valor_bonificacao)
WHEN NOT MATCHED THEN INSERT (id_funcionario, nome, valor_bonificacao)
VALUES (t.id_funcionario, t.nome, t.valor_bonificacao);

6)
SELECT last_name, job_id
FROM (
  SELECT last_name, job_id, LEVEL AS lvl
  FROM employees
  START WITH last_name = 'Lorentz'
  CONNECT BY PRIOR employee_id = manager_id
)
WHERE lvl > 1;

7a) -- JOIN
SELECT c.country_name,
       ROUND(AVG(e.salary), 2) AS media_salarial
FROM employees e
JOIN departments d ON e.department_id = d.department_id
JOIN locations l ON d.location_id = l.location_id
JOIN countries c ON l.country_id = c.country_id
GROUP BY c.country_name
HAVING AVG(e.salary) > 8000
ORDER BY media_salarial DESC;
```

```

7b) -- WITH
WITH emp_country AS (
    SELECT e.salary, c.country_name
    FROM employees e
    JOIN departments d ON e.department_id = d.department_id
    JOIN locations l ON d.location_id = l.location_id
    JOIN countries c ON l.country_id = c.country_id
)
SELECT country_name, ROUND(AVG(salary), 2) AS media_salarial
FROM emp_country
GROUP BY country_name
HAVING AVG(salary) > 8000
ORDER BY media_salarial DESC;

```

```

8)
WITH emp_country AS (
    SELECT e.employee_id, e.salary, c.country_name
    FROM employees e
    JOIN departments d ON e.department_id = d.department_id
    JOIN locations l ON d.location_id = l.location_id
    JOIN countries c ON l.country_id = c.country_id
),
changed AS (
    SELECT DISTINCT employee_id FROM job_history
)
SELECT ec.country_name,
    COUNT(*) AS quantidade_funcionarios,
    ROUND(AVG(ec.salary), 2) AS media_salarial
FROM emp_country ec
JOIN changed ch ON ec.employee_id = ch.employee_id
GROUP BY ec.country_name
HAVING COUNT(*) > 2
    AND AVG(ec.salary) > 9000
ORDER BY media_salarial DESC;

```