



TÉCNICO
LISBOA

Algorithms for Computational Logic

Overview of Satisfiability Modulo Theories

based on slides of João Marques-Silva and Mikoláš Janota

IST, ULisboa

Context

- Propositional satisfiability (SAT)
 - Modern SAT algorithms – CDCL
- Propositional encodings
 - Cardinality constraints, PB constraints, etc.

Context

- Propositional satisfiability (SAT)
 - Modern SAT algorithms – CDCL
- Propositional encodings
 - Cardinality constraints, PB constraints, etc.
- Overconstrained problems
 - Optimization
 - Minimal sets

Context

- Propositional satisfiability (SAT)
 - Modern SAT algorithms – CDCL
- Propositional encodings
 - Cardinality constraints, PB constraints, etc.
- Overconstrained problems
 - Optimization
 - Minimal sets
- Duality

Context

- Propositional satisfiability (SAT)
 - Modern SAT algorithms – CDCL
- Propositional encodings
 - Cardinality constraints, PB constraints, etc.
- Overconstrained problems
 - Optimization
 - Minimal sets
- Duality
- Satisfiability Modulo Theories (SMT)
- Other topics:
 - Answer Set Programming (ASP)

Outline

What is SMT?

Application Examples

A Glimpse of SMT

Eager Encodings

Lazy Solving

Outline

What is SMT?

Application Examples

- Encoding a scheduling problem

- Encoding symbolic execution

A Glimpse of SMT

Eager Encodings

Lazy Solving

FOL and Terminology

- FOL: functions, predicates, quantifiers, e.g. $(\forall x \exists y)(f(x, y))$

FOL and Terminology

- FOL: functions, predicates, quantifiers, e.g. $(\forall x \exists y)(f(x, y))$
- FOL is generally **undecidable** but it is **semi-decidable**.

FOL and Terminology

- FOL: functions, predicates, quantifiers, e.g. $(\forall x \exists y)(f(x, y))$
- FOL is generally **undecidable** but it is **semi-decidable**.
- SMT: satisfiability of **fragments of FOL**

FOL and Terminology

- FOL: functions, predicates, quantifiers, e.g. $(\forall x \exists y)(f(x, y))$
- FOL is generally **undecidable** but it is **semi-decidable**.
- SMT: satisfiability of **fragments of FOL**
- Example fragment: *integer linear arithmetic*

FOL and Terminology

- FOL: functions, predicates, quantifiers, e.g. $(\forall x \exists y)(f(x, y))$
- FOL is generally **undecidable** but it is **semi-decidable**.
- SMT: satisfiability of **fragments of FOL**
- Example fragment: *integer linear arithmetic*
- these fragments are called **theories**

FOL and Terminology

- FOL: functions, predicates, quantifiers, e.g. $(\forall x \exists y)(f(x, y))$
- FOL is generally **undecidable** but it is **semi-decidable**.
- SMT: satisfiability of **fragments of FOL**
- Example fragment: *integer linear arithmetic*
- these fragments are called **theories**
- e.g. $(d - c = 1) \wedge ((d < 5) \vee (c > 10))$ is satisfiable with example solutions $\{c = 11, d = 12\}, \{c = 1, d = 2\}$.

FOL and Terminology

- FOL: functions, predicates, quantifiers, e.g. $(\forall x \exists y)(f(x, y))$
- FOL is generally **undecidable** but it is **semi-decidable**.
- SMT: satisfiability of **fragments of FOL**
- Example fragment: *integer linear arithmetic*
- these fragments are called **theories**
- e.g. $(d - c = 1) \wedge ((d < 5) \vee (c > 10))$ is satisfiable with example solutions $\{c = 11, d = 12\}, \{c = 1, d = 2\}$.
- **interpreted** functions, predicates, and constants, e.g. $+, -, =, <, 5$.

FOL and Terminology

- FOL: functions, predicates, quantifiers, e.g. $(\forall x \exists y)(f(x, y))$
- FOL is generally **undecidable** but it is **semi-decidable**.
- SMT: satisfiability of **fragments of FOL**
- Example fragment: *integer linear arithmetic*
- these fragments are called **theories**
- e.g. $(d - c = 1) \wedge ((d < 5) \vee (c > 10))$ is satisfiable with example solutions $\{c = 11, d = 12\}, \{c = 1, d = 2\}$.
- **interpreted** functions, predicates, and constants, e.g. $+, -, =, <, 5$.
- **uninterpreted** functions, predicates, and constants, e.g. f, c .

FOL and Terminology

- FOL: functions, predicates, quantifiers, e.g. $(\forall x \exists y)(f(x, y))$
- FOL is generally **undecidable** but it is **semi-decidable**.
- SMT: satisfiability of **fragments of FOL**
- Example fragment: *integer linear arithmetic*
- these fragments are called **theories**
- e.g. $(d - c = 1) \wedge ((d < 5) \vee (c > 10))$ is satisfiable with example solutions $\{c = 11, d = 12\}, \{c = 1, d = 2\}$.
- **interpreted** functions, predicates, and constants, e.g. $+, -, =, <, 5$.
- **uninterpreted** functions, predicates, and constants, e.g. f, c .
- e.g. $f(c) > c$ is satisfied by $\{f(x) = x + 1, c = 100\}$

FOL and Terminology

- FOL: functions, predicates, quantifiers, e.g. $(\forall x \exists y)(f(x, y))$
- FOL is generally **undecidable** but it is **semi-decidable**.
- SMT: satisfiability of **fragments of FOL**
- Example fragment: *integer linear arithmetic*
- these fragments are called **theories**
- e.g. $(d - c = 1) \wedge ((d < 5) \vee (c > 10))$ is satisfiable with example solutions $\{c = 11, d = 12\}, \{c = 1, d = 2\}$.
- **interpreted** functions, predicates, and constants, e.g. $+, -, =, <, 5$.
- **uninterpreted** functions, predicates, and constants, e.g. f, c .
- e.g. $f(c) > c$ is satisfied by $\{f(x) = x + 1, c = 100\}$
- **term**: $f(c)$, **atom**: $f(c) > d$, **literal**: $\neg(f(c) > d)$, **proposition**: $(c < d) \vee (d > z)$

FOL and Terminology

- FOL: functions, predicates, quantifiers, e.g. $(\forall x \exists y)(f(x, y))$
- FOL is generally **undecidable** but it is **semi-decidable**.
- SMT: satisfiability of **fragments of FOL**
- Example fragment: *integer linear arithmetic*
- these fragments are called **theories**
- e.g. $(d - c = 1) \wedge ((d < 5) \vee (c > 10))$ is satisfiable with example solutions $\{c = 11, d = 12\}, \{c = 1, d = 2\}$.
- **interpreted** functions, predicates, and constants, e.g. $+, -, =, <, 5$.
- **uninterpreted** functions, predicates, and constants, e.g. f, c .
- e.g. $f(c) > c$ is satisfied by $\{f(x) = x + 1, c = 100\}$
- **term**: $f(c)$, **atom**: $f(c) > d$, **literal**: $\neg(f(c) > d)$, **proposition**: $(c < d) \vee (d > z)$
- **congruence**: $(t_1 = s_1 \wedge t_2 = s_2) \rightarrow f(t_1, t_2) = f(s_1, s_2)$

An example

- All variables `integer`

An example

- All variables integer
- Solve:

$$\begin{aligned} & ((x_4 - x_2 \leq 3) \vee (x_4 - x_3 \geq 5)) \wedge (x_4 - x_3 \leq 6) \wedge \\ & (x_1 - x_2 \leq -1) \wedge (x_1 - x_3 \leq -2) \wedge (x_1 - x_4 \leq -1) \wedge \\ & (x_2 - x_1 \leq 2) \wedge (x_3 - x_2 \leq -1) \wedge \\ & ((x_3 - x_4 \leq -2) \vee (x_4 - x_3 \geq 2)) \end{aligned}$$

An example

- All variables integer
- Solve:

$$\begin{aligned} & ((x_4 - x_2 \leq 3) \vee (x_4 - x_3 \geq 5)) \wedge (x_4 - x_3 \leq 6) \wedge \\ & (x_1 - x_2 \leq -1) \wedge (x_1 - x_3 \leq -2) \wedge (x_1 - x_4 \leq -1) \wedge \\ & (x_2 - x_1 \leq 2) \wedge (x_3 - x_2 \leq -1) \wedge \\ & ((x_3 - x_4 \leq -2) \vee (x_4 - x_3 \geq 2)) \end{aligned}$$

- Integer difference logic (with Boolean structure)

An example

- All variables integer
- Solve:

$$\begin{aligned} & ((x_4 - x_2 \leq 3) \vee (x_4 - x_3 \geq 5)) \wedge (x_4 - x_3 \leq 6) \wedge \\ & (x_1 - x_2 \leq -1) \wedge (x_1 - x_3 \leq -2) \wedge (x_1 - x_4 \leq -1) \wedge \\ & (x_2 - x_1 \leq 2) \wedge (x_3 - x_2 \leq -1) \wedge \\ & ((x_3 - x_4 \leq -2) \vee (x_4 - x_3 \geq 2)) \end{aligned}$$

- Integer difference logic (with Boolean structure)
- Unsatisfiable (**Why?**)
- How to solve formulas like the above?

Outline

What is SMT?

Application Examples

- Encoding a scheduling problem

- Encoding symbolic execution

A Glimpse of SMT

Eager Encodings

Lazy Solving

A scheduling example

- Standard job-shop scheduling formulation: [Moura&Bjorner'11]
 - n jobs, each composed of m tasks to be performed chronologically on m machines
 - ▶ $d_{i,j}$: duration of task j for job i

A scheduling example

- Standard **job-shop scheduling** formulation: [Moura&Bjorner'11]
 - n jobs, each composed of m tasks to be performed chronologically on m machines
 - ▶ $d_{i,j}$: duration of task j for job i
 - Types of constraints:
 - ▶ **Precedence**: between two tasks in the same job
 - ▶ **Resource**: No two different tasks requiring the same machine can execute simultaneously
 - ▶ All jobs **must** terminate by a time limit max

A scheduling example

- Standard **job-shop scheduling** formulation: [Moura&Bjorner'11]
 - n jobs, each composed of m tasks to be performed chronologically on m machines
 - ▶ $d_{i,j}$: duration of task j for job i
 - Types of constraints:
 - ▶ **Precedence**: between two tasks in the same job
 - ▶ **Resource**: No two different tasks requiring the same machine can execute simultaneously
 - ▶ All jobs **must** terminate by a time limit max
 - An example (task has number of time units and assigned machine):

$d_{i,j}$	Machine 1	Machine 2
Job 1	2	1
Job 2	3	1
Job 3	2	3

with $max = 8$

A scheduling example (Cont.)

- An SMT model for job-shop scheduling:
 - $t_{i,j}$: start time for task j of job i
 - Example:

$d_{i,j}$	Machine 1	Machine 2
Job 1	2	1
Job 2	3	1
Job 3	2	3


with $\max = 8$

A scheduling example (Cont.)

- An SMT model for job-shop scheduling:
 - $t_{i,j}$: start time for task j of job i
 - Example:

$d_{i,j}$	Machine 1	Machine 2
Job 1	2	1
Job 2	3	1
Job 3	2	3

with $\max = 8$



A scheduling example (Cont.)

- An SMT model for job-shop scheduling:
 - $t_{i,j}$: start time for task j of job i
 - Example:

$d_{i,j}$	Machine 1	Machine 2
Job 1	2	1
Job 2	3	1
Job 3	2	3

with $\text{max} = 8$

- Formulation:

$$\begin{aligned} & (t_{1,1} \geq 0) \wedge (t_{1,2} \geq t_{1,1} + 2) \wedge (t_{1,2} + 1 \leq 8) \wedge \\ & (t_{2,1} \geq 0) \wedge (t_{2,2} \geq t_{2,1} + 3) \wedge (t_{2,2} + 1 \leq 8) \wedge \\ & (t_{3,1} \geq 0) \wedge (t_{3,2} \geq t_{3,1} + 2) \wedge (t_{3,2} + 3 \leq 8) \wedge \\ & ((t_{1,1} \geq t_{2,1} + 3) \vee (t_{2,1} \geq t_{1,1} + 2)) \wedge \\ & ((t_{1,1} \geq t_{3,1} + 2) \vee (t_{3,1} \geq t_{1,1} + 2)) \wedge \\ & ((t_{2,1} \geq t_{3,1} + 2) \vee (t_{3,1} \geq t_{2,1} + 3)) \wedge \\ & ((t_{1,2} \geq t_{2,2} + 1) \vee (t_{2,2} \geq t_{1,2} + 1)) \wedge \\ & ((t_{1,2} \geq t_{3,2} + 3) \vee (t_{3,2} \geq t_{1,2} + 1)) \wedge \\ & ((t_{2,2} \geq t_{3,2} + 3) \vee (t_{3,2} \geq t_{2,2} + 1)) \end{aligned}$$

A scheduling example (Cont.)

- An SMT model for job-shop scheduling:

- $t_{i,j}$: start time for task j of job i
- Example:

$d_{i,j}$	Machine 1	Machine 2
Job 1	2	1
Job 2	3	1
Job 3	2	3

with $\max = 8$

- Formulation:

$$\begin{aligned} & (t_{1,1} \geq 0) \wedge (t_{1,2} \geq t_{1,1} + 2) \wedge (t_{1,2} + 1 \leq 8) \wedge \\ & (t_{2,1} \geq 0) \wedge (t_{2,2} \geq t_{2,1} + 3) \wedge (t_{2,2} + 1 \leq 8) \wedge \\ & (t_{3,1} \geq 0) \wedge (t_{3,2} \geq t_{3,1} + 2) \wedge (t_{3,2} + 3 \leq 8) \wedge \\ & ((t_{1,1} \geq t_{2,1} + 3) \vee (t_{2,1} \geq t_{1,1} + 2)) \wedge \\ & ((t_{1,1} \geq t_{3,1} + 2) \vee (t_{3,1} \geq t_{1,1} + 2)) \wedge \\ & ((t_{2,1} \geq t_{3,1} + 2) \vee (t_{3,1} \geq t_{2,1} + 3)) \wedge \\ & ((t_{1,2} \geq t_{2,2} + 1) \vee (t_{2,2} \geq t_{1,2} + 1)) \wedge \\ & ((t_{1,2} \geq t_{3,2} + 3) \vee (t_{3,2} \geq t_{1,2} + 1)) \wedge \\ & ((t_{2,2} \geq t_{3,2} + 3) \vee (t_{3,2} \geq t_{2,2} + 1)) \end{aligned}$$

- Integer difference logic with Boolean structure

► Model: $t_{1,1} = 5; t_{1,2} = 7; t_{2,1} = 2; t_{2,2} = 6; t_{3,1} = 0; t_{3,2} = 3;$

Software testing with symbolic execution

- Example C program:

[E.g. Moura&Bjorner'11]

```
int GCD(int x, int y) {  
    while (true) {  
        int m = x % y;  
        if (m == 0) return y;  
        x = y;  
        y = m;  
    }  
}
```

Software testing with symbolic execution

- Example C program:

[E.g. Moura&Bjorner'11]

```
int GCD(int x, int y) {  
    while (true) {  
        int m = x % y;  
        if (m == 0) return y;  
        x = y;  
        y = m;  
    }  
}
```

- Can the while loop test be executed exactly **twice**?
 - If so, **which inputs** allow this to happen?

Software testing with symbolic execution (Cont.)

- Problem formulation as SMT formula:

Software testing with symbolic execution (Cont.)

- Problem formulation as SMT formula:

First build SSA Program

by loop unrolling

(now variables do not change)

```
int GCD(int x0, int y0) {  
    int m0 = x0 % y0;  
    assert(m0 != 0);  
    int x1 = y0;  
    int y1 = m0;  
    int m1 = x1 % y1;  
    assert(m1 == 0);  
}
```

Software testing with symbolic execution (Cont.)

- Problem formulation as SMT formula:

First build SSA Program

by loop unrolling

(now variables do not change)

```
int GCD(int x0, int y0) {  
    int m0 = x0 % y0;  
    assert(m0 != 0);  
    int x1 = y0;  
    int y1 = m0;  
    int m1 = x1 % y1;  
    assert(m1 == 0);  
}
```

Path Formula in SMT

$$\begin{aligned}(m_0 = x_0 \% y_0) & \wedge \\ \neg(m_0 = 0) & \wedge \\ (x_1 = y_0) & \wedge \\ (y_1 = m_0) & \wedge \\ (m_1 = x_1 \% y_1) & \wedge \\ (m_1 = 0) & \end{aligned}$$

Software testing with symbolic execution (Cont.)

- Problem formulation as SMT formula:

First build SSA Program

by loop unrolling

(now variables do not change)

```
int GCD(int x0, int y0) {  
    int m0 = x0 % y0;  
    assert(m0 != 0);  
    int x1 = y0;  
    int y1 = m0;  
    int m1 = x1 % y1;  
    assert(m1 = 0);  
}
```

Path Formula in SMT

$$\begin{aligned}(m_0 = x_0 \% y_0) & \wedge \\ \neg(m_0 = 0) & \wedge \\ (x_1 = y_0) & \wedge \\ (y_1 = m_0) & \wedge \\ (m_1 = x_1 \% y_1) & \wedge \\ (m_1 = 0) & \end{aligned}$$

- **Note:** SSA denotes static single assignment form

Software testing with symbolic execution (Cont.)

- Problem formulation as SMT formula:

C Program

```
int GCD(int x, int y) {  
    while (true) {  
        int m = x % y;  
        if (m == 0) return y;  
        x = y;  
        y = m;  
    }  
}
```

Software testing with symbolic execution (Cont.)

- Problem formulation as SMT formula:

C Program

```
int GCD(int x, int y) {  
    while (true) {  
        int m = x % y;  
        if (m == 0) return y;  
        x = y;  
        y = m;  
    }  
}
```

Solution

- Model:
 $x_0 = 2; y_0 = 4; m_0 = 2;$
 $x_1 = 4; y_1 = 2; m_1 = 0;$
- Function call: $\text{GCD}(2,4)$

Software testing with symbolic execution (Cont.)

- Problem formulation as SMT formula:

C Program

```
int GCD(int x, int y) {  
    while (true) {  
        int m = x % y;  
        if (m == 0) return y;  
        x = y;  
        y = m;  
    }  
}
```

Solution

- Model:
 $x_0 = 2; y_0 = 4; m_0 = 2;$
 $x_1 = 4; y_1 = 2; m_1 = 0;$
- Function call: **GCD(2,4)**

- **Recall:** This testing approach is known as **dynamic symbolic execution**
 - Example tools: CUTE, Klee, DART, SAGE, Pex, Yogi

Remark on SW Verification and Testing

- SW verification & testing one of the main driving forces behind SMT
- **Testing:** Increasing test coverage (which input reaches a given path?)
- **Verification:** proving correctness, absence of crashes, security, etc.
- Implications for **security**: prove that your program/protocol is secure

Outline

What is SMT?

Application Examples

- Encoding a scheduling problem

- Encoding symbolic execution

A Glimpse of SMT

Eager Encodings

Lazy Solving

Example Theories – EUF

- Equality with Uninterpreted Functions (EUF)
- Is this formula satisfiable?

$$[a \times (f(b) + f(c)) = d] \wedge [b \times (f(a) + f(c)) \neq d] \wedge [a = b]$$

Example Theories – EUF

- Equality with Uninterpreted Functions (EUF)
- Is this formula satisfiable?

$$[a \times (f(b) + f(c)) = d] \wedge [b \times (f(a) + f(c)) \neq d] \wedge [a = b]$$

- Formula is **unsatisfiable**

Example Theories – EUF

- Equality with Uninterpreted Functions (EUF)
- Is this formula satisfiable?

$$[a \times (f(b) + f(c)) = d] \wedge [b \times (f(a) + f(c)) \neq d] \wedge [a = b]$$

– Formula is **unsatisfiable**

- And this formula?

$$[h(a, g(f(b), f(c))) = d] \wedge [h(b, g(f(a), f(c))) \neq d] \wedge [a = b]$$

Example Theories – EUF

- Equality with Uninterpreted Functions (EUF)
- Is this formula satisfiable?

$$[a \times (f(b) + f(c)) = d] \wedge [b \times (f(a) + f(c)) \neq d] \wedge [a = b]$$

– Formula is **unsatisfiable**

- And this formula?

$$[h(a, g(f(b), f(c))) = d] \wedge [h(b, g(f(a), f(c))) \neq d] \wedge [a = b]$$

– Formula is also **unsatisfiable**

Example Theories – EUF

- Equality with Uninterpreted Functions (EUF)
- Is this formula satisfiable?

$$[a \times (f(b) + f(c)) = d] \wedge [b \times (f(a) + f(c)) \neq d] \wedge [a = b]$$

– Formula is **unsatisfiable**

- And this formula?

$$[h(a, g(f(b), f(c))) = d] \wedge [h(b, g(f(a), f(c))) \neq d] \wedge [a = b]$$

– Formula is also **unsatisfiable**

- **Useful**: Abstract non-supported operations (functions)
 - E.g. multiplication; ALUs in circuits; etc.

Example Theories – Arithmetic

- Wide range of applications
- Variables are either **integers** or **reals**
- Fragments can be solved with more efficient methods
 - **Bounds**
 - ▶ $x \bowtie k, \bowtie \in \{<, >, \leq, \geq, =\}$
 - **Difference Logic**
 - ▶ $x - y \bowtie k, \bowtie \in \{<, >, \leq, \geq, =\}$
 - **UTVPI** (Unit Two-Variable Per Inequality)
 - ▶ $\pm x \pm y \bowtie k, \bowtie \in \{<, >, \leq, \geq, =\}$
 - **Linear Arithmetic**
 - ▶ $\sum a_i x_i \bowtie k, \bowtie \in \{<, >, \leq, \geq, =\}$
 - **Non-Linear Arithmetic**
 - ▶ E.g. $3xy - 4x^2z - 4y \leq 10$

- Bit vectors

Other Theories

- Bit vectors
- Arrays

Other Theories

- Bit vectors
- Arrays
- Pointer logic

Other Theories

- Bit vectors
- Arrays
- Pointer logic
- Quantified theories, e.g. quantified linear integer arithmetic is decidable

Algorithms for SMT

- Eager approaches

- Eager approaches
 - Encode problem to CNF and solve with SAT solver (1 SAT call)

Algorithms for SMT

- Eager approaches
 - Encode problem to CNF and solve with SAT solver (1 SAT call)
- Lazy approaches

Algorithms for SMT

- Eager approaches
 - Encode problem to CNF and solve with SAT solver (1 SAT call)
- Lazy approaches
 - Embed SAT solver with theory solver(s) (many SAT calls); theory solvers are responsible for deciding conjunctions of literals

Outline

What is SMT?

Application Examples

- Encoding a scheduling problem

- Encoding symbolic execution

A Glimpse of SMT

Eager Encodings

Lazy Solving

Eager Approaches (among others)

- Bounded integers encoded as Boolean variables (log variables)

Eager Approaches (among others)

- Bounded integers encoded as Boolean variables (log variables)
- Encode AtMost- k , AtLeast- k , and pseudo-Boolean constraints to CNF.

Eager Approaches (among others)

- Bounded integers encoded as Boolean variables (log variables)
- Encode AtMost- k , AtLeast- k , and pseudo-Boolean constraints to CNF.
- **Recall:** Can encode arbitrary propositional constraints to CNF.

Eager Approaches (among others)

- Bounded integers encoded as Boolean variables (log variables)
- Encode AtMost- k , AtLeast- k , and pseudo-Boolean constraints to CNF.
- **Recall:** Can encode arbitrary propositional constraints to CNF.
- Terms replaced by constants and encode congruence explicitly

Eager Approaches (among others)

- Bounded integers encoded as Boolean variables (log variables)
- Encode AtMost- k , AtLeast- k , and pseudo-Boolean constraints to CNF.
- **Recall:** Can encode arbitrary propositional constraints to CNF.
- Terms replaced by constants and encode congruence explicitly
 - E.g. replace $f(a), f(b), f(c)$ with A, B, C

Eager Approaches (among others)

- Bounded integers encoded as Boolean variables (log variables)
- Encode AtMost- k , AtLeast- k , and pseudo-Boolean constraints to CNF.
- **Recall:** Can encode arbitrary propositional constraints to CNF.
- Terms replaced by constants and encode congruence explicitly
 - E.g. replace $f(a), f(b), f(c)$ with A, B, C
 - Generate implications capturing congruence.

$$a = b \rightarrow A = B$$

$$a = c \rightarrow A = C$$

$$b = c \rightarrow B = C$$

Eager Approaches (among others)

- Bounded integers encoded as Boolean variables (log variables)
- Encode AtMost- k , AtLeast- k , and pseudo-Boolean constraints to CNF.
- **Recall:** Can encode arbitrary propositional constraints to CNF.
- Terms replaced by constants and encode congruence explicitly
 - E.g. replace $f(a), f(b), f(c)$ with A, B, C
 - Generate implications capturing congruence.

$$\begin{aligned}a &= b \rightarrow A = B \\a &= c \rightarrow A = C \\b &= c \rightarrow B = C\end{aligned}$$

- Formula with only equality and n constants is satisfiable iff it has a model of size at most n . (small model property). [E.g. Pnueli et al.'02].
Constants encoded as bounded integers $1..n$.

Finite Models with Booleans

- Finding a model of finite size n can be encoded as SAT.

Finite Models with Booleans

- Finding a model of finite size n can be encoded as SAT.
- **log-encoding**: elements of the universe are represented by $k = \lceil \log_2 n \rceil$ Boolean variables.

Finite Models with Booleans

- Finding a model of finite size n can be encoded as SAT.
- **log-encoding**: elements of the universe are represented by $k = \lceil \log_2 n \rceil$ Boolean variables.
- equality: $(a_k, \dots, a_0) = (b_k, \dots, b_0) \rightsquigarrow \bigwedge_{i \in 0..k} (a_i \Leftrightarrow b_i)$

Finite Models with Booleans

- Finding a model of finite size n can be encoded as SAT.
- **log-encoding**: elements of the universe are represented by $k = \lceil \log_2 n \rceil$ Boolean variables.
- equality: $(a_k, \dots, a_0) = (b_k, \dots, b_0) \rightsquigarrow \bigwedge_{i \in 0..k} (a_i \Leftrightarrow b_i)$
- inequality: $(a_k, \dots, a_0) < (b_k, \dots, b_0) \rightsquigarrow$
 $(\neg a_k \wedge b_k) \vee ((a_k \Leftrightarrow b_k) \wedge (a_{k-1}, \dots, a_0) < (b_{k-1}, \dots, b_0))$

Finite Models with Booleans

- Finding a model of finite size n can be encoded as SAT.
- **log-encoding**: elements of the universe are represented by $k = \lceil \log_2 n \rceil$ Boolean variables.
- equality: $(a_k, \dots, a_0) = (b_k, \dots, b_0) \rightsquigarrow \bigwedge_{i \in 0..k} (a_i \Leftrightarrow b_i)$
- inequality: $(a_k, \dots, a_0) < (b_k, \dots, b_0) \rightsquigarrow$
 $(\neg a_k \wedge b_k) \vee ((a_k \Leftrightarrow b_k) \wedge (a_{k-1}, \dots, a_0) < (b_{k-1}, \dots, b_0))$
- Other operations can be encoded, e.g. summation and multiplication by school method.

Finite Models with Booleans

- Finding a model of finite size n can be encoded as SAT.
- **log-encoding**: elements of the universe are represented by $k = \lceil \log_2 n \rceil$ Boolean variables.
- equality: $(a_k, \dots, a_0) = (b_k, \dots, b_0) \rightsquigarrow \bigwedge_{i \in 0..k} (a_i \Leftrightarrow b_i)$
- inequality: $(a_k, \dots, a_0) < (b_k, \dots, b_0) \rightsquigarrow$
 $(\neg a_k \wedge b_k) \vee ((a_k \Leftrightarrow b_k) \wedge (a_{k-1}, \dots, a_0) < (b_{k-1}, \dots, b_0))$
- Other operations can be encoded, e.g. summation and multiplication by school method.
- **unary-encoding**: elements are represented by n Boolean variables with $a_i \Rightarrow a_{i-1}$ for $i \in 1..n$.

Finite Models with Booleans

- Finding a model of finite size n can be encoded as SAT.
- **log-encoding**: elements of the universe are represented by $k = \lceil \log_2 n \rceil$ Boolean variables.
- equality: $(a_k, \dots, a_0) = (b_k, \dots, b_0) \rightsquigarrow \bigwedge_{i \in 0..k} (a_i \Leftrightarrow b_i)$
- inequality: $(a_k, \dots, a_0) < (b_k, \dots, b_0) \rightsquigarrow$
 $(\neg a_k \wedge b_k) \vee ((a_k \Leftrightarrow b_k) \wedge (a_{k-1}, \dots, a_0) < (b_{k-1}, \dots, b_0))$
- Other operations can be encoded, e.g. summation and multiplication by school method.
- **unary-encoding**: elements are represented by n Boolean variables with $a_i \Rightarrow a_{i-1}$ for $i \in 1..n$.
- equality: $(a_n, \dots, a_0) = (b_n, \dots, b_0) \rightsquigarrow \bigwedge_{i \in 0..n} (a_i \Leftrightarrow b_i)$

Finite Models with Booleans

- Finding a model of finite size n can be encoded as SAT.
- **log-encoding**: elements of the universe are represented by $k = \lceil \log_2 n \rceil$ Boolean variables.
- equality: $(a_k, \dots, a_0) = (b_k, \dots, b_0) \rightsquigarrow \bigwedge_{i \in 0..k} (a_i \Leftrightarrow b_i)$
- inequality: $(a_k, \dots, a_0) < (b_k, \dots, b_0) \rightsquigarrow (\neg a_k \wedge b_k) \vee ((a_k \Leftrightarrow b_k) \wedge (a_{k-1}, \dots, a_0) < (b_{k-1}, \dots, b_0))$
- Other operations can be encoded, e.g. summation and multiplication by school method.
- **unary-encoding**: elements are represented by n Boolean variables with $a_i \Rightarrow a_{i-1}$ for $i \in 1..n$.
- equality: $(a_n, \dots, a_0) = (b_n, \dots, b_0) \rightsquigarrow \bigwedge_{i \in 0..n} (a_i \Leftrightarrow b_i)$
- inequality: $(a_n, \dots, a_0) < (b_n, \dots, b_0) \rightsquigarrow \bigvee_{i \in 0..n} (\neg a_i \wedge b_i)$

Finite Models with Booleans

- Finding a model of finite size n can be encoded as SAT.
- **log-encoding**: elements of the universe are represented by $k = \lceil \log_2 n \rceil$ Boolean variables.
- equality: $(a_k, \dots, a_0) = (b_k, \dots, b_0) \rightsquigarrow \bigwedge_{i \in 0..k} (a_i \Leftrightarrow b_i)$
- inequality: $(a_k, \dots, a_0) < (b_k, \dots, b_0) \rightsquigarrow$
 $(\neg a_k \wedge b_k) \vee ((a_k \Leftrightarrow b_k) \wedge (a_{k-1}, \dots, a_0) < (b_{k-1}, \dots, b_0))$
- Other operations can be encoded, e.g. summation and multiplication by school method.
- **unary-encoding**: elements are represented by n Boolean variables with $a_i \Rightarrow a_{i-1}$ for $i \in 1..n$.
- equality: $(a_n, \dots, a_0) = (b_n, \dots, b_0) \rightsquigarrow \bigwedge_{i \in 0..n} (a_i \Leftrightarrow b_i)$
- inequality: $(a_n, \dots, a_0) < (b_n, \dots, b_0) \rightsquigarrow \bigvee_{i \in 0..n} (\neg a_i \wedge b_i)$
- **Note**: log-encoding smaller but unary tends to give better behavior in SAT solvers.

Small Model Property

- **Idea:** in some theories, satisfiability can be encoded into finding a finite model.

Small Model Property

- **Idea:** in some theories, satisfiability can be encoded into finding a finite model.
- A formula with only equality and n variables is satisfiable iff it has a model of at most size n .

Small Model Property

- **Idea:** in some theories, satisfiability can be encoded into finding a finite model.
- A formula with only equality and n variables is satisfiable iff it has a model of at most size n .
- **Why?** For any larger model \mathcal{A}' construct \mathcal{A} by considering only elements used to interpret the variables in the formula.

Small Model Property

- **Idea:** in some theories, satisfiability can be encoded into finding a finite model.
- A formula with only equality and n variables is satisfiable iff it has a model of at most size n .
- **Why?** For any larger model \mathcal{A}' construct \mathcal{A} by considering only elements used to interpret the variables in the formula.
- $(x_1 = x_2) \vee (x_1 = x_3) \wedge (x_3 \neq x_2)$ is decided by looking for a model up to size 3.

Small Model Property: IDL

- What about Integer Difference Logic?

Small Model Property: IDL

- What about Integer Difference Logic?
- Let s be the sum of absolute values of weights and n number of variables.

Small Model Property: IDL

- What about Integer Difference Logic?
- Let s be the sum of absolute values of weights and n number of variables.
- It is sufficient to look for a model with integers in $0..(s + n)$.

Small Model Property: IDL

- What about Integer Difference Logic?
- Let s be the sum of absolute values of weights and n number of variables.
- It is sufficient to look for a model with integers in $0..(s + n)$.
- **Why?**

Small Model Property: IDL

- What about Integer Difference Logic?
- Let s be the sum of absolute values of weights and n number of variables.
- It is sufficient to look for a model with integers in $0..(s + n)$.
- **Why?**
 - Any solution can be shifted so it starts at 0.

Small Model Property: IDL

- What about Integer Difference Logic?
- Let s be the sum of absolute values of weights and n number of variables.
- It is sufficient to look for a model with integers in $0..(s + n)$.
- **Why?**
 - Any solution can be shifted so it starts at 0.
 - “Compress” any solution while preserving the satisfiability of the same literals.

IDL: Compressing Model Example


- $\neg(x_1 - x_0 \leq 4) \wedge (x_1 - x_2 \leq -2)$,
model: $x_0 = -2, x_1 = 5, x_2 = 8$

IDL: Compressing Model Example

- $\neg(x_1 - x_0 \leq 4) \wedge (x_1 - x_2 \leq -2)$,
model: $x_0 = -2, x_1 = 5, x_2 = 8$
- rewrite as: $x_1 - x_0 \geq 5, x_2 - x_1 \geq 2$


IDL: Compressing Model Example

- $\neg(x_1 - x_0 \leq 4) \wedge (x_1 - x_2 \leq -2)$,
model: $x_0 = -2, x_1 = 5, x_2 = 8$
- rewrite as: $x_1 - x_0 \geq 5, x_2 - x_1 \geq 2$




IDL: Compressing Model Example

- $\neg(x_1 - x_0 \leq 4) \wedge (x_1 - x_2 \leq -2)$,
model: $x_0 = -2, x_1 = 5, x_2 = 8$
- rewrite as: $x_1 - x_0 \geq 5, x_2 - x_1 \geq 2$




IDL: Compressing Model Example

- $\neg(x_1 - x_0 \leq 4) \wedge (x_1 - x_2 \leq -2)$,
model: $x_0 = -2, x_1 = 5, x_2 = 8$
- rewrite as: $x_1 - x_0 \geq 5, x_2 - x_1 \geq 2$




IDL: Compressing Model Example

- $\neg(x_1 - x_0 \leq 4) \wedge (x_1 - x_2 \leq -2)$,
model: $x_0 = -2, x_1 = 5, x_2 = 8$
- rewrite as: $x_1 - x_0 \geq 5, x_2 - x_1 \geq 2$



IDL: Compressing Model Example

- $\neg(x_1 - x_0 \leq 4) \wedge (x_1 - x_2 \leq -2)$,
model: $x_0 = -2, x_1 = 5, x_2 = 8$
- rewrite as: $x_1 - x_0 \geq 5, x_2 - x_1 \geq 2$



- Max number: $0 + 5 + 2$
- Note that: $5 = 4 + 1$, that is why we add 1 for each variable since original constraints may be negated

Uninterpreted Functions: Ackerman's Reduction

- For each application $f(\vec{a})$ introduce a fresh variable f_a

Uninterpreted Functions: Ackerman's Reduction

- For each application $f(\vec{a})$ introduce a fresh variable f_a
- For each pair of applications $f(\vec{a}), f(\vec{c})$ add the implication $\vec{a} = \vec{c} \Rightarrow f_{\vec{a}} = f_{\vec{c}}$.

Uninterpreted Functions: Ackerman's Reduction

- For each application $f(\vec{a})$ introduce a fresh variable f_a
- For each pair of applications $f(\vec{a}), f(\vec{c})$ add the implication $\vec{a} = \vec{c} \Rightarrow f_{\vec{a}} = f_{\vec{c}}$.

Example

Uninterpreted Functions: Ackerman's Reduction

- For each application $f(\vec{a})$ introduce a fresh variable f_a
- For each pair of applications $f(\vec{a}), f(\vec{c})$ add the implication $\vec{a} = \vec{c} \Rightarrow f_{\vec{a}} = f_{\vec{c}}$.

Example

- $f(a) \neq f(c) \wedge (a = c \vee f(a) = c)$

Uninterpreted Functions: Ackerman's Reduction

- For each application $f(\vec{a})$ introduce a fresh variable f_a
- For each pair of applications $f(\vec{a}), f(\vec{c})$ add the implication $\vec{a} = \vec{c} \Rightarrow f_{\vec{a}} = f_{\vec{c}}$.

Example

- $f(a) \neq f(c) \wedge (a = c \vee f(a) = c)$
- $f_a \neq f_c \wedge (a = c \vee f_a = c) \wedge (a = c \Rightarrow f_a = f_c)$

Uninterpreted Functions: Ackerman's Reduction Contd.

Careful: Need to consider also sub-terms.

Example

Uninterpreted Functions: Ackerman's Reduction Contd.

Careful: Need to consider also sub-terms.

Example

- $f(f(a)) = f(a) \wedge f(f(f(a))) \neq f(a)$

Uninterpreted Functions: Ackerman's Reduction Contd.

Careful: Need to consider also sub-terms.

Example

- $f(f(a)) = f(a) \wedge f(f(f(a))) \neq f(a)$
- Applications: $\{f(a), f(f(a)), f(f(f(a)))\}$

Uninterpreted Functions: Ackerman's Reduction Contd.

Careful: Need to consider also sub-terms.

Example

- $f(f(a)) = f(a) \wedge f(f(f(a))) \neq f(a)$
- Applications: $\{f(a), f(f(a)), f(f(f(a)))\}$
- Reduction:

$$\begin{aligned} & f_{f(a)} = f_a \wedge f_{f(f(a))} \neq f_a \\ \wedge \quad & a = f_a \Rightarrow f_a = f_{f(a)} \\ \wedge \quad & a = f_{f(a)} \Rightarrow f_a = f_{f(f(a))} \\ \wedge \quad & f_a = f_{f(a)} \Rightarrow f_{f(a)} = f_{f(f(a))} \end{aligned}$$

Uninterpreted Functions: Ackerman's Reduction Contd.

Careful: Need to consider also sub-terms.

Example

- $f(f(a)) = f(a) \wedge f(f(f(a))) \neq f(a)$
- Applications: $\{f(a), f(f(a)), f(f(f(a)))\}$
- Reduction:

$$\begin{aligned} & f_{f(a)} = f_a \wedge f_{f(f(a))} \neq f_a \\ \wedge \quad & a = f_a \Rightarrow f_a = f_{f(a)} \\ \wedge \quad & a = f_{f(a)} \Rightarrow f_a = f_{f(f(a))} \\ \wedge \quad & f_a = f_{f(a)} \Rightarrow f_{f(a)} = f_{f(f(a))} \end{aligned}$$

- Propagate $f_{f(a)} = f_a$ in last implication $\rightsquigarrow f_{f(a)} = f_{f(f(a))}$

Uninterpreted Functions: Ackerman's Reduction Contd.

Careful: Need to consider also sub-terms.

Example

- $f(f(a)) = f(a) \wedge f(f(f(a))) \neq f(a)$
- Applications: $\{f(a), f(f(a)), f(f(f(a)))\}$
- Reduction:

$$\begin{aligned} & f_{f(a)} = f_a \wedge f_{f(f(a))} \neq f_a \\ \wedge \quad & a = f_a \Rightarrow f_a = f_{f(a)} \\ \wedge \quad & a = f_{f(a)} \Rightarrow f_a = f_{f(f(a))} \\ \wedge \quad & f_a = f_{f(a)} \Rightarrow f_{f(a)} = f_{f(f(a))} \end{aligned}$$

- Propagate $f_{f(a)} = f_a$ in last implication $\rightsquigarrow f_{f(a)} = f_{f(f(a))}$
- Transitivity of $f_{f(a)} = f_a$ and $f_{f(a)} = f_{f(f(a))}$ $\rightsquigarrow f_a = f_{f(f(a))}$

Uninterpreted Functions: Ackerman's Reduction Contd.

Careful: Need to consider also sub-terms.

Example

- $f(f(a)) = f(a) \wedge f(f(f(a))) \neq f(a)$
- Applications: $\{f(a), f(f(a)), f(f(f(a)))\}$
- Reduction:

$$\begin{aligned} & f_{f(a)} = f_a \wedge f_{f(f(a))} \neq f_a \\ \wedge \quad & a = f_a \Rightarrow f_a = f_{f(a)} \\ \wedge \quad & a = f_{f(a)} \Rightarrow f_a = f_{f(f(a))} \\ \wedge \quad & f_a = f_{f(a)} \Rightarrow f_{f(a)} = f_{f(f(a))} \end{aligned}$$

- Propagate $f_{f(a)} = f_a$ in last implication $\rightsquigarrow f_{f(a)} = f_{f(f(a))}$
- Transitivity of $f_{f(a)} = f_a$ and $f_{f(a)} = f_{f(f(a))}$ $\rightsquigarrow f_a = f_{f(f(a))}$
- Contradiction $f_a = f_{f(f(a))}$ and $f_a \neq f_{f(f(a))}$ \rightsquigarrow **unsatisfiable**

Outline

What is SMT?

Application Examples

- Encoding a scheduling problem

- Encoding symbolic execution

A Glimpse of SMT

Eager Encodings

Lazy Solving

Lazy solving

- Use SAT for Boolean structure.

Lazy solving

- Use SAT for Boolean structure.
- Use **theory solver** for conjunctions of literals.

Lazy solving

- Use SAT for Boolean structure.
- Use **theory solver** for conjunctions of literals.
- Conceptually the following is needed:

Lazy solving

- Use SAT for Boolean structure.
- Use **theory solver** for conjunctions of literals.
- Conceptually the following is needed:
 - $\mathcal{T2B}$: abstracts theory formula to Boolean formula, e.g.

$$\mathcal{T2B}((x < y) \vee \neg(z > y)) \rightsquigarrow e_{x < y} \vee \neg e_{z > y}$$

Lazy solving

- Use SAT for Boolean structure.
- Use **theory solver** for conjunctions of literals.
- Conceptually the following is needed:
 - $\mathcal{T2B}$: abstracts theory formula to Boolean formula, e.g.
$$\mathcal{T2B}((x < y) \vee \neg(z > y)) \rightsquigarrow e_{x < y} \vee \neg e_{z > y}$$
 - $\mathcal{B2T}$: converts Boolean literal to theory literal, e.g.
$$\mathcal{B2T}(\neg e_{z > y}) \rightsquigarrow \neg(z > y)$$

Lazy solving

- Use SAT for Boolean structure.
- Use **theory solver** for conjunctions of literals.
- Conceptually the following is needed:
 - $\mathcal{T}2\mathcal{B}$: abstracts theory formula to Boolean formula, e.g.
$$\mathcal{T}2\mathcal{B}((x < y) \vee \neg(z > y)) \rightsquigarrow e_{x < y} \vee \neg e_{z > y}$$
 - $\mathcal{B}2\mathcal{T}$: converts Boolean literal to theory literal, e.g.
$$\mathcal{B}2\mathcal{T}(\neg e_{z > y}) \rightsquigarrow \neg(z > y)$$
 - $\mathcal{T}\text{-SAT}(\mathcal{L})$: **theory solver** for set of literals \mathcal{L} determines whether \mathcal{T} -satisfiable or \mathcal{T} -unsatisfiable.

Lazy solving

- Use SAT for Boolean structure.
- Use **theory solver** for conjunctions of literals.
- Conceptually the following is needed:
 - $\mathcal{T}2\mathcal{B}$: abstracts theory formula to Boolean formula, e.g.
$$\mathcal{T}2\mathcal{B}((x < y) \vee \neg(z > y)) \rightsquigarrow e_{x < y} \vee \neg e_{z > y}$$
 - $\mathcal{B}2\mathcal{T}$: converts Boolean literal to theory literal, e.g.
$$\mathcal{B}2\mathcal{T}(\neg e_{z > y}) \rightsquigarrow \neg(z > y)$$
 - $\mathcal{T}\text{-SAT}(\mathcal{L})$: **theory solver** for set of literals \mathcal{L} determines whether \mathcal{T} -satisfiable or \mathcal{T} -unsatisfiable.
 - If unsatisfiable, provides **explanation** $\mathcal{L}' \subseteq \mathcal{L}$ so that \mathcal{L}' is also \mathcal{T} -unsatisfiable.

Lazy solving

- Use SAT for Boolean structure.
- Use **theory solver** for conjunctions of literals.
- Conceptually the following is needed:
 - $\mathcal{T2B}$: abstracts theory formula to Boolean formula, e.g.
$$\mathcal{T2B}((x < y) \vee \neg(z > y)) \rightsquigarrow e_{x < y} \vee \neg e_{z > y}$$
 - $\mathcal{B2T}$: converts Boolean literal to theory literal, e.g.
$$\mathcal{B2T}(\neg e_{z > y}) \rightsquigarrow \neg(z > y)$$
 - $\mathcal{T}\text{-SAT}(\mathcal{L})$: **theory solver** for set of literals \mathcal{L} determines whether \mathcal{T} -satisfiable or \mathcal{T} -unsatisfiable.
 - If unsatisfiable, provides **explanation** $\mathcal{L}' \subseteq \mathcal{L}$ so that \mathcal{L}' is also \mathcal{T} -unsatisfiable.
 - $\text{SAT}(\alpha)$: **SAT solver** for formula α determines if SAT or UNSAT. If SAT, provides **model** as a set of true literals.

Lazy approaches – example

- Example SMT formula:

$$g(a) = c \wedge (f(g(a)) \neq f(c) \vee g(a) = d) \wedge c \neq d$$

- Represent Boolean structure as CNF formula:

$$(x) \wedge (\neg y \vee z) \wedge (\neg w)$$

- Interaction between SAT solver & theory solver (EUF):

SAT Outcome	Bool Model	EUF Outcome	Explanation clause (sent to SAT solver)
<hr/>			

Lazy approaches – example

- Example SMT formula:

$$g(a) = c \wedge (f(g(a)) \neq f(c) \vee g(a) = d) \wedge c \neq d$$

- Represent Boolean structure as CNF formula:

$$(x) \wedge (\neg y \vee z) \wedge (\neg w)$$

- Interaction between SAT solver & theory solver (EUF):

SAT Outcome	Bool Model	EUF Outcome	Explanation clause (sent to SAT solver)
SAT	$\{x, \neg y, \neg w\}$	UNSAT	$(\neg x \vee y \vee w)$

Lazy approaches – example

- Example SMT formula:

$$g(a) = c \wedge (f(g(a)) \neq f(c) \vee g(a) = d) \wedge c \neq d$$

- Represent Boolean structure as CNF formula:

$$(x) \wedge (\neg y \vee z) \wedge (\neg w)$$

- Interaction between SAT solver & theory solver (EUF):

SAT Outcome	Bool Model	EUF Outcome	Explanation clause (sent to SAT solver)
SAT	$\{x, \neg y, \neg w\}$	UNSAT	$(\neg x \vee y \vee w)$
SAT	$\{x, y, z, \neg w\}$	UNSAT	$(\neg x \vee \neg y \vee \neg z \vee w)$

Lazy approaches – example

- Example SMT formula:

$$g(a) = c \wedge (f(g(a)) \neq f(c) \vee g(a) = d) \wedge c \neq d$$

- Represent Boolean structure as CNF formula:

$$(x) \wedge (\neg y \vee z) \wedge (\neg w)$$

- Interaction between SAT solver & theory solver (EUF):

SAT Outcome	Bool Model	EUF Outcome	Explanation clause (sent to SAT solver)
SAT	$\{x, \neg y, \neg w\}$	UNSAT	$(\neg x \vee y \vee w)$
SAT	$\{x, y, z, \neg w\}$	UNSAT	$(\neg x \vee \neg y \vee \neg z \vee w)$
UNSAT	$(x) \wedge (\neg y \vee z) \wedge (\neg x \vee y \vee w) \wedge (\neg w) \wedge (\neg x \vee \neg y \vee \neg z \vee w)$		

Lazy solving

input : formula ϕ in theory \mathcal{T}

output: truth value

```
1  $\alpha \leftarrow \mathcal{T}2\mathcal{B}(\phi)$  // abstract input formula
2 while true do
3    $(\text{res}, \tau) \leftarrow \text{SAT}(\alpha)$  // Boolean model
4   if  $\text{res} = \text{false}$  then return false
5    $\mathcal{L} \leftarrow \bigcup_{l \in \tau} \mathcal{B}2\mathcal{T}(l)$  // convert to theory model
6    $(\text{res}, \mathcal{L}') \leftarrow \mathcal{T}\text{-SAT}(\mathcal{L})$  // theory check
7   if  $\text{res} = \text{true}$  then return true
8    $\alpha \leftarrow \alpha \wedge \bigvee_{l \in \mathcal{L}'} \neg \mathcal{T}2\mathcal{B}(l)$  // block explanation
9 end
```

Theory Solver: Equality — Congruence closure

- Divide the set of literals \mathcal{L} into positive E and negative D .

Theory Solver: Equality — Congruence closure

- Divide the set of literals \mathcal{L} into positive E and negative D .
- Build a set of all **sub-terms** S in \mathcal{L} .

Theory Solver: Equality — Congruence closure

- Divide the set of literals \mathcal{L} into positive E and negative D .
- Build a set of all sub-terms S in \mathcal{L} .
- Build congruence closure as a partitioning of S .

Theory Solver: Equality — Congruence closure

- Divide the set of literals \mathcal{L} into positive E and negative D .
- Build a set of all sub-terms S in \mathcal{L} .
- Build congruence closure as a partitioning of S .
 - Put each term $t \in S$ in its own partition.

Theory Solver: Equality — Congruence closure

- Divide the set of literals \mathcal{L} into positive E and negative D .
- Build a set of all sub-terms S in \mathcal{L} .
- Build congruence closure as a partitioning of S .
 - Put each term $t \in S$ in its own partition.
 - For each $(s = t) \in E$, merge partitions of s and t .

Theory Solver: Equality — Congruence closure

- Divide the set of literals \mathcal{L} into positive E and negative D .
- Build a set of all sub-terms S in \mathcal{L} .
- Build congruence closure as a partitioning of S .
 - Put each term $t \in S$ in its own partition.
 - For each $(s = t) \in E$, merge partitions of s and t .
 - For s_1, \dots, s_k and t_1, \dots, t_k s.t. s_i is in the same partition as t_i , merge partitions of $f(s_1, \dots, s_k)$ and $f(t_1, \dots, t_k)$.

Theory Solver: Equality — Congruence closure

- Divide the set of literals \mathcal{L} into positive E and negative D .
- Build a set of all sub-terms S in \mathcal{L} .
- Build congruence closure as a partitioning of S .
 - Put each term $t \in S$ in its own partition.
 - For each $(s = t) \in E$, merge partitions of s and t .
 - For s_1, \dots, s_k and t_1, \dots, t_k s.t. s_i is in the same partition as t_i , merge partitions of $f(s_1, \dots, s_k)$ and $f(t_1, \dots, t_k)$.
 - Repeat until no congruence applies.

Theory Solver: Equality — Congruence closure

- Divide the set of literals \mathcal{L} into positive E and negative D .
- Build a set of all sub-terms S in \mathcal{L} .
- Build congruence closure as a partitioning of S .
 - Put each term $t \in S$ in its own partition.
 - For each $(s = t) \in E$, merge partitions of s and t .
 - For s_1, \dots, s_k and t_1, \dots, t_k s.t. s_i is in the same partition as t_i , merge partitions of $f(s_1, \dots, s_k)$ and $f(t_1, \dots, t_k)$.
 - Repeat until no congruence applies.
- If there is a $s \neq t \in D$, s.t. s and t are in the same partition, return unsatisfiable otherwise satisfiable.

Example

$$f(a, b) = a \wedge f(f(a, b), b) \neq a$$

Example

$$f(a, b) = a \wedge f(f(a, b), b) \neq a$$

- Congruence closure algorithm – iteratively merge equivalence classes:

Example

$$f(a, b) = a \wedge f(f(a, b), b) \neq a$$

- Congruence closure algorithm – iteratively merge equivalence classes:

$$\{\{a\}, \{b\}, \{f(a, b)\}, \{f(f(a, b), b)\}\}$$

Example

$$f(a, b) = a \wedge f(f(a, b), b) \neq a$$

- Congruence closure algorithm – iteratively merge equivalence classes:

$$\{\{a\}, \{b\}, \{f(a, b)\}, \{f(f(a, b), b)\}\}$$

$$\{\{a, f(a, b)\}, \{b\}, \{f(f(a, b), b)\}\}$$

Example

$$f(a, b) = a \wedge f(f(a, b), b) \neq a$$

- **Congruence closure** algorithm – iteratively merge equivalence classes:

$$\{\{a\}, \{b\}, \{f(a, b)\}, \{f(f(a, b), b)\}\}$$

$$\{\{a, f(a, b)\}, \{b\}, \{f(f(a, b), b)\}\}$$

$$\{\{a, f(a, b), f(f(a, b), b)\}, \{b\}\}$$

Example

$$f(a, b) = a \wedge f(f(a, b), b) \neq a$$

- **Congruence closure** algorithm – iteratively merge equivalence classes:

$$\{\{a\}, \{b\}, \{f(a, b)\}, \{f(f(a, b), b)\}\}$$

$$\{\{a, f(a, b)\}, \{b\}, \{f(f(a, b), b)\}\}$$

$$\{\{a, f(a, b), f(f(a, b), b)\}, \{b\}\}$$

- But $f(f(a, b), b) \neq a$.

Example

$$f(a, b) = a \wedge f(f(a, b), b) \neq a$$

- Congruence closure algorithm – iteratively merge equivalence classes:

$$\{\{a\}, \{b\}, \{f(a, b)\}, \{f(f(a, b), b)\}\}$$

$$\{\{a, f(a, b)\}, \{b\}, \{f(f(a, b), b)\}\}$$

$$\{\{a, f(a, b), f(f(a, b), b)\}, \{b\}\}$$

- But $f(f(a, b), b) \neq a$.
- Formula is **unsatisfiable**.

Integer Difference Logic: Theory Solver

- Integer variables
- **Conjunction** of linear inequalities of the form $x_i - x_j \leq k$

Integer Difference Logic: Theory Solver

- Integer variables
- **Conjunction** of linear inequalities of the form $x_i - x_j \leq k$
- Algorithm:
 - Add edge between x_j and x_i with weight k , for inequality $x_i - x_j \leq k$

Integer Difference Logic: Theory Solver


- Integer variables
- **Conjunction** of linear inequalities of the form $x_i - x_j \leq k$
- Algorithm:
 - Add edge between x_j and x_i with weight k , for inequality $x_i - x_j \leq k$
 - Add additional source vertex x_0
 - Add edge from x_0 to x_i , for each other vertex x_i
 - Use Bellman-Ford algorithm to check for **negative cycles**
 - ▶ **Negative cycle:** Elimination of variables in (some) inequalities yields $0 \leq -k, k > 0$

Integer Difference Logic (Cont.)

$$\begin{aligned} & (x_4 - x_2 \leq 3) \wedge (x_4 - x_3 \leq 6) \wedge (x_1 - x_2 \leq -1) \wedge \\ & (x_1 - x_3 \leq -2) \wedge (x_1 - x_4 \leq -1) \wedge (x_3 - x_2 \leq -1) \wedge \\ & (x_3 - x_4 \leq -2) \end{aligned}$$


Integer Difference Logic (Cont.)

$$\begin{aligned} & (x_4 - x_2 \leq 3) \wedge (x_4 - x_3 \leq 6) \wedge (x_1 - x_2 \leq -1) \wedge \\ & (x_1 - x_3 \leq -2) \wedge (x_1 - x_4 \leq -1) \wedge (x_3 - x_2 \leq -1) \wedge \\ & (x_3 - x_4 \leq -2) \end{aligned}$$



Integer Difference Logic (Cont.)

$$(x_4 - x_2 \leq 3) \wedge (x_4 - x_3 \leq 6) \wedge (x_1 - x_2 \leq -1) \wedge \\ (x_1 - x_3 \leq -2) \wedge (x_1 - x_4 \leq -1) \wedge (x_3 - x_2 \leq -1) \wedge \\ (x_3 - x_4 \leq -2)$$



Satisfiable:

$$x_1 = -4$$

$$x_2 = 0$$

$$x_3 = -2$$

$$x_4 = 0$$


$$x_i = \text{dist}(x_0, x_i)$$

Integer Difference Logic (Cont.)

$$\begin{aligned} & (x_4 - x_2 \leq 3) \wedge (x_4 - x_3 \leq 6) \wedge (x_1 - x_2 \leq -1) \wedge \\ & (x_1 - x_3 \leq -2) \wedge (x_1 - x_4 \leq -1) \wedge (x_2 - x_1 \leq 2) \wedge \\ & (x_3 - x_2 \leq -1) \wedge (x_3 - x_4 \leq -2) \end{aligned}$$


Integer Difference Logic (Cont.)

$$\begin{aligned} & (x_4 - x_2 \leq 3) \wedge (x_4 - x_3 \leq 6) \wedge (x_1 - x_2 \leq -1) \wedge \\ & (x_1 - x_3 \leq -2) \wedge (x_1 - x_4 \leq -1) \wedge (x_2 - x_1 \leq 2) \wedge \\ & (x_3 - x_2 \leq -1) \wedge (x_3 - x_4 \leq -2) \end{aligned}$$



Integer Difference Logic (Cont.)

$$\begin{aligned} & (x_4 - x_2 \leq 3) \wedge (x_4 - x_3 \leq 6) \wedge (x_1 - x_2 \leq -1) \wedge \\ & (x_1 - x_3 \leq -2) \wedge (x_1 - x_4 \leq -1) \wedge (x_2 - x_1 \leq 2) \wedge \\ & (x_3 - x_2 \leq -1) \wedge (x_3 - x_4 \leq -2) \end{aligned}$$



Unsatisfiable

$$x_2 - x_1 \leq 2$$

$$x_3 - x_2 \leq -1$$

$$x_1 - x_3 \leq -2$$

$$\text{Sum: } 0 \leq -1$$

Note: Cycle serves as *explanation*, UNSAT as long as present.

- Convert all literals to positive (i.e. remove negations):

- Convert all literals to positive (i.e. remove negations):
 - $\neg(x - y \leq c)$

- Convert all literals to positive (i.e. remove negations):
 - $\neg(x - y \leq c)$
 - $\rightsquigarrow x - y > c$

- Convert all literals to positive (i.e. remove negations):
 - $\neg(x - y \leq c)$
 - $\rightsquigarrow x - y > c$
 - $\rightsquigarrow y - x < -c$

- Convert all literals to positive (i.e. remove negations):
 - $\neg(x - y \leq c)$
 - $\rightsquigarrow x - y > c$
 - $\rightsquigarrow y - x < -c$
 - $\rightsquigarrow y - x \leq -c - 1$

- Convert all literals to positive (i.e. remove negations):
 - $\neg(x - y \leq c)$
 - $\rightsquigarrow x - y > c$
 - $\rightsquigarrow y - x < -c$
 - $\rightsquigarrow y - x \leq -c - 1$
- **Note:** Also possible on reals/rationals but care is needed because we cannot directly convert strict inequalities to non-strict ones.

Recap example for IDL

- Example SMT formula:

$$\begin{aligned} & ((x_4 - x_2 \leq 3) \vee (x_4 - x_3 \geq 5)) \wedge (x_4 - x_3 \leq 6) \wedge \\ & (x_1 - x_2 \leq -1) \wedge (x_1 - x_3 \leq -2) \wedge (x_1 - x_4 \leq -1) \wedge (x_2 - x_1 \leq 2) \wedge \\ & (x_3 - x_2 \leq -1) \wedge ((x_3 - x_4 \leq -2) \vee (x_4 - x_3 \geq 2)) \end{aligned}$$

- Represent Boolean structure as CNF formula:

$$(a \vee b) \wedge (c) \wedge (d) \wedge (e) \wedge (f) \wedge (g) \wedge (h) \wedge (i \vee j)$$

- Interaction between SAT solver & theory solver (IDL):

SAT Outcome	Boolean model	IDL Outcome	Explanation clause (sent to SAT solver)
<hr/>			

Recap example for IDL

- Example SMT formula:

$$\begin{aligned} & ((x_4 - x_2 \leq 3) \vee (x_4 - x_3 \geq 5)) \wedge (x_4 - x_3 \leq 6) \wedge \\ & (x_1 - x_2 \leq -1) \wedge (x_1 - x_3 \leq -2) \wedge (x_1 - x_4 \leq -1) \wedge (x_2 - x_1 \leq 2) \wedge \\ & (x_3 - x_2 \leq -1) \wedge ((x_3 - x_4 \leq -2) \vee (x_4 - x_3 \geq 2)) \end{aligned}$$

- Represent Boolean structure as CNF formula:

$$(a \vee b) \wedge (c) \wedge (d) \wedge (e) \wedge (f) \wedge (g) \wedge (h) \wedge (i \vee j)$$

- Interaction between SAT solver & theory solver (IDL):

SAT Outcome	Boolean model	IDL Outcome	Explanation clause (sent to SAT solver)
SAT	$\{a, c, \dots, h, i\}$	UNSAT	$(\neg e \vee \neg g \vee \neg h)$

Recap example for IDL

- Example SMT formula:

$$\begin{aligned} & ((x_4 - x_2 \leq 3) \vee (x_4 - x_3 \geq 5)) \wedge (x_4 - x_3 \leq 6) \wedge \\ & (x_1 - x_2 \leq -1) \wedge (x_1 - x_3 \leq -2) \wedge (x_1 - x_4 \leq -1) \wedge (x_2 - x_1 \leq 2) \wedge \\ & (x_3 - x_2 \leq -1) \wedge ((x_3 - x_4 \leq -2) \vee (x_4 - x_3 \geq 2)) \end{aligned}$$

- Represent Boolean structure as CNF formula:

$$(a \vee b) \wedge (c) \wedge (d) \wedge (e) \wedge (f) \wedge (g) \wedge (h) \wedge (i \vee j)$$

- Interaction between SAT solver & theory solver (IDL):

SAT Outcome	Boolean model	IDL Outcome	Explanation clause (sent to SAT solver)
SAT	$\{a, c, \dots, h, i\}$	UNSAT	$(\neg e \vee \neg g \vee \neg h)$
UNSAT	$(e) \wedge (g) \wedge (h) \wedge (\neg e \vee \neg g \vee \neg h)$		

Lazy approaches – remarks

- Why are they called **lazy**?
 - Theory solver called only as needed, to check T-consistency
- Key properties:
 - Avoiding large encodings
 - Modular implementation
 - ▶ Easy to add theory solvers
 - Currently, the most efficient algorithms
 - **Clear** separation between Boolean and theory domains
- Widely used by modern SMT solvers
 - Z3, Yices, OpenSMT, MathSAT, CVC, Barcelogic, etc.

Lazy approaches – Key Techniques

- Key techniques in all efficient SMT solvers:
 - Check T-consistency of **partial** assignments
 - Given T-inconsistent assignment M , compute $M' \subseteq M$ and add $\neg M'$ as a clause
 - Given T-inconsistent assignment, **backtrack** to where assignment is T-consistent

DPLL(T)

- What is $\text{DPLL}(T)$?

DPLL(T)

- What is $\text{DPLL}(T)$?

$$\text{DPLL}(T) = \text{DPLL}(X) + T\text{-Solver}$$

DPLL(T)

- What is $\text{DPLL}(T)$?

$$\text{DPLL}(T) = \text{DPLL}(X) + T\text{-Solver}$$

- $\text{DPLL}(X)$
 - SAT solver capable of enumerating models

DPLL(T)

- What is $\text{DPLL}(T)$?

$$\text{DPLL}(T) = \text{DPLL}(X) + T\text{-Solver}$$

- $\text{DPLL}(X)$
 - SAT solver capable of enumerating models
 - Preferable: partial model detection

DPLL(T)

- What is $\text{DPLL}(T)$?

$$\text{DPLL}(T) = \text{DPLL}(X) + T\text{-Solver}$$

- $\text{DPLL}(X)$
 - SAT solver capable of enumerating models
 - Preferable: partial model detection
 - **Cannot use:** pure literals, blocked literals, etc.

DPLL(T)

- What is $\text{DPLL}(T)$?

$$\text{DPLL}(T) = \text{DPLL}(X) + T\text{-Solver}$$

- $\text{DPLL}(X)$
 - SAT solver capable of enumerating models
 - Preferable: partial model detection
 - **Cannot use**: pure literals, blocked literals, etc.
- T -Solver:

DPLL(T)

- What is $DPLL(T)$?

$$DPLL(T) = DPLL(X) + T\text{-Solver}$$

- $DPLL(X)$
 - SAT solver capable of enumerating models
 - Preferable: partial model detection
 - **Cannot use:** pure literals, blocked literals, etc.
- T -Solver:
 - Checks T -consistency of **conjunctions** of literals
 - Performs theory propagation
 - Computes **explanations** of inconsistency
 - **Note:** T -propagation should be **incremental** and **backtrackable**