Piezoresistive Ink

InkPR02NP®

InkPR02NP® is a piezoresistive ink that changes its electrical resistance when subjected to mechanical deformation. It is designed for face-to-face printing on flexible substrates and sensor applications.

SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/ UNDERTAKING

1.1 Product identifier

Product name: InkPR02NP®

1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the Substance/Mixture: Industrial and research

1.3 Details of the supplier of the safety data sheet

Company: Nanopaint, Lda
Address: CIIES – Sala 23/28, Avenida de Tibães, 1199, 4770-568 Vale de São Cosme, Portugal

1.4 Emergency telephone number

+351 253 601 681

SECTION 2: HAZARDS IDENTIFICATION

2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008)

H225: Líquido e vapor facilmente inflamáveis.

H319: Provoca irritação ocular grave.

H336: Pode provocar sonolência ou vertigens.

2.2 Label elements

Warning Pictograms: GHS07 (Exclamation mark), GHS02 (Flame)



NanoPaint, Lda.
CIIES – Sala 23/28
Avenida de Tibães, 1199
4770-568 Vale de São Cosme, Portugal

www.nanopaint-tech.com
info@nanopaint-tech.com

© 2026 NanoPaint Lda. All rights reserved. This Technical Data Sheet is generated from product records in NanopaintHub. Values shown reflect stored product data with optional batch overlay.

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

3.2 Mixtures

Dangerous Components:

Identifiers	Chemical Name	Classification (1272/2008)	% Weight
CAS: 67-64-1 EC: 200-662-2	Acetone	H225; H319; H336	20%

SECTION 4: FIRST AID MEASURES

4.1 Description of first aid measures

General advice: Consult a physician. Show this safety data sheet to the doctor in attendance.
If inhaled: If breathed in, move person into fresh air. If not breathing, give artificial respiration. Consult a physician.
In case of skin contact: Wash off with soap and plenty of water. Consult a physician if irritation develops.
In case of eye contact: Rinse thoroughly with plenty of water for at least 15 minutes and consult a physician.
If swallowed: Rinse mouth with water.

SECTION 5: FIREFIGHTING MEASURES

5.1 Extinguishing media

Suitable extinguishing media: Use water spray, alcohol-resistant foam, dry chemical or carbon dioxide.

5.2 Special hazards arising from the substance or mixture

Carbon oxides, Nitrogen oxides (NOx).

5.3 Advice for firefighters

Wear self-contained breathing apparatus for firefighting if necessary.

SECTION 6: ACCIDENTAL RELEASE MEASURES

6.1 Personal precautions, protective equipment and emergency procedures

Use personal protective equipment. Avoid breathing vapours, mist or gas. Ensure adequate ventilation.

6.2 Environmental precautions

Prevent further leakage or spillage if safe to do so. Do not let product enter drains.

6.3 Methods and materials for containment and cleaning up

NanoPaint, Lda.
CIIES – Sala 23/28
Avenida de Tibães, 1199
4770-568 Vale de São Cosme, Portugal

www.nanopaint-tech.com
info@nanopaint-tech.com

© 2026 NanoPaint Lda. All rights reserved. This Technical Data Sheet is generated from product records in NanopaintHub. Values shown reflect stored product data with optional batch overlay.

Soak up with inert absorbent material and dispose of as hazardous waste. Keep in suitable, closed containers for disposal.

SECTION 7: HANDLING AND STORAGE

7.1 Precautions for safe handling

Avoid contact with skin and eyes. Avoid inhalation of vapour or mist.

Keep away from sources of ignition - No smoking. Take measures to prevent the build up of electrostatic charge.

7.2 Conditions for safe storage, including any incompatibilities

Store in cool place. Keep container tightly closed in a dry and well-ventilated place.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1 Control parameters

Components with workplace control parameters: No data available.

8.2 Exposure controls

Appropriate engineering controls: Handle in accordance with good industrial hygiene and safety practice.
Personal protective equipment: Safety glasses with side-shields, chemical resistant gloves, protective clothing.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

9.1 Information on basic physical and chemical properties

Physical state: Paste

Colour: Black

Viscosity: 80–100 KU

Odour: Characteristic

Flash point: No data available

SECTION 10: STABILITY AND REACTIVITY

10.1 Reactivity: No data available

10.2 Chemical stability: Stable under recommended storage conditions.

10.3 Possibility of hazardous reactions: No data available

10.4 Conditions to avoid: Heat, flames and sparks (if flammable).

NanoPaint, Lda.
CIIES – Sala 23/28
Avenida de Tibães, 1199
4770-568 Vale de São Cosme, Portugal

www.nanopaint-tech.com
info@nanopaint-tech.com

© 2026 NanoPaint Lda. All rights reserved. This Technical Data Sheet is generated from product records in NanopaintHub. Values shown reflect stored product data with optional batch overlay.

10.5 Incompatible materials: Strong oxidizing agents.

SECTION 11: TOXICOLOGICAL INFORMATION

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity: Classified based on available ingredients data.

Skin corrosion/irritation: Refer to Section 2.

Serious eye damage/eye irritation: Refer to Section 2.

SECTION 12: ECOLOGICAL INFORMATION

12.1 Toxicity: No data available.

12.2 Persistence and degradability: No data available.

12.3 Bioaccumulative potential: No data available.

SECTION 13: DISPOSAL CONSIDERATIONS

13.1 Waste treatment methods

Product: Offer surplus and non-recyclable solutions to a licensed disposal company.
Contaminated packaging: Dispose of as unused product.

SECTION 14: TRANSPORT INFORMATION

Regulated under ADR/RID, IMDG, IATA. Hazard Classes: ADR3 (Flammable Liquid)



SECTION 15: REGULATORY INFORMATION

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

This safety datasheet complies with the requirements of Regulation (EC) No. 1907/2006.

SECTION 16: OTHER INFORMATION

Full text of H-Statements referred to under sections 2 and 3:

H225 Líquido e vapor facilmente inflamáveis.

NanoPaint, Lda.
CIIES – Sala 23/28
Avenida de Tibães, 1199
4770-568 Vale de São Cosme, Portugal

www.nanopaint-tech.com
info@nanopaint-tech.com

© 2026 NanoPaint Lda. All rights reserved. This Technical Data Sheet is generated from product records in NanopaintHub. Values shown reflect stored product data with optional batch overlay.

H319 Provoca irritação ocular grave.

H336 Pode provocar sonolência ou vertigens.

The information contained herein is based on the present state of our knowledge and does not therefore guarantee certain properties. Recipients of our product must take responsibility for observing existing laws and regulations.

NanoPaint, Lda.
CIIES – Sala 23/28
Avenida de Tibães, 1199
4770-568 Vale de São Cosme, Portugal

www.nanopaint-tech.com
info@nanopaint-tech.com

© 2026 NanoPaint Lda. All rights reserved. This Technical Data Sheet is generated from product records in NanopaintHub. Values shown reflect stored product data with optional batch overlay.