

1 Title

Terahertz Sensors for In-Situ Soil Characterization and Imaging

2 Directorates

This research is proposed as an EAGER submission and goes under the ENG directorate.

3 Proposed Research

Depth-varying soil properties such as moisture, nutrient levels, organic matter, and texture are critical for efficient crop management. Precision agriculture, in which parameters such as these are used for efficient application of irrigation, fertilizer, and pesticides and herbicides, relies on reliable measurement of these properties. Additionally, plant root structure aids in crop modeling, used to predict how changes in crop management affect yield. Presently, there is a lack of sensors for in-situ measurement of these properties. This research proposes a new application of two sensing modalities that have distinct advantages of low power, small size, and ease of installation: surface plasmon resonance (SPR) in the near-infrared (NIR) and millimeter wave imaging using beamforming radar. Both could be considered terahertz (THz) sensors, a sensing regime still largely unexplored in agricultural and environmental applications.

Current soil profile sensing techniques involve either taking samples from the field, for lab analysis of properties, or difficult installation in the field. For instance, time-domain reflectometry (TDR) [9] or capacitance measurement [1] both can determine soil moisture and electrical conductivity through electromagnetic characterization of soil in the megahertz regime. However, to measure the soil profile, this requires digging a pit and installing sensors, then back-filling. Moreover, operation in this frequency ranges necessitates larger sensors and larger electrical components.

In the past decade, researchers have sought to examine soil properties using near-infrared spectroscopy (NIRS), in which the reflectance or transmittance of a soil sample is measured over a range of NIR frequencies, a technique also used for brain activity measurement [5]. This is in the THz regime and makes use of small, low power, optical components. While soil would typically be considered too lossy at these high frequencies, particular resonances associated with water's and organic compounds' O-H and C-H bonds make it amenable to measurement by NIRS; there is a transmission window in the mid-infrared and a strong water absorption in the short-infrared [4, 6].

This research proposes exploiting measurement at very high frequencies to characterize soil moisture, organic matter, nutrients, and root structure. The proposed work is to employ NIRS using surface plasmon resonance (SPR) for chemical and textural analysis. The proposed technique have the distinct advantages of small size, low power, and variety of measurements. The developed sensor would use SPR, in which the NIR pulse is guided into the soil medium through a thin metal layer with a negative refractive index on top of an optical wave guide [7]. This allows NIR transmission underground at a range of depths by a pencil-thin rod carrying multiple optical waveguides, directing NIR pulses to the desired locations. Such a sensor is easily installable by drilling a narrow hole. Further, while NIR alone can elucidate texture, nitrogen, and organic matter [2, 8], functionalized coatings that bind to specific nutrients or pollutants can expand the range of chemometric analysis.

There are potential pitfalls. Primarily, soil electromagnetic properties are relatively ill-defined above 3 GHz, making modeling for either approach very difficult. Further, the variety of soil types and moisture levels makes either approach challenging; decades have gone into making TDR work across a range of soils, while THz/NIR is still very new. Further, the small size of the sensors makes them prone to damage in the real environment. The delicate nature of SPR coatings (such as gold) may make them prone to damage on insertion in the soil. Finally, there are infrastructural challenges, in that to make an NIR-SPR sensor requires some new analytical equipment for development [3], namely an NIR spectrometer.

In our proposed sensor, THz pulses are coupled to small electromagnetic structures along a thin cylinder. The proposed work has three parts: design of the electromagnetic structure of the sensors; design of the circuitry for applying the THz pulses to the structures; and design of the microfabrication process for their construction. Over the course of a two-year investigation, we plan to start with theoretical design using fundamental principles combined with computer simulation, move to prototype construction and laboratory testing, and end with small-scale field trials. The researchers involved include PI Joaquin Casanova, with an established history in agricultural engineering and electromagnetic sensor design, including soil moisture and computer vision sensors; Co-PI Changzhi Li, with a strong research history in high-frequency radar techniques and circuit design; and Co-PI YK Yoon, who has been long involved in design and fabrication of micro-scale sensors, including millimeter wave antennas and SPR sensors.

4 Researchers and Contact Information

PI - Joaquin Casanova - University of Florida - jcasa@ufl.edu - 352-246-9649

Co-PI - Changzhi Li - Texas Tech University - changzhi.li@ttu.edu - 806-834-8682

Co-PI - Yong-Kyu Yoon - University of Florida - ykyoon@ufl.edu - 352-392-5985

References Cited

- [1] J Robert Birchak, C Gerald Gardner, Jackie E Hipp, and Joe M Victor. High dielectric constant microwave probes for sensing soil moisture. *Proceedings of the IEEE*, 62(1):93–98, 1974.
- [2] Cheng-Wen Chang, David A Laird, Maurice J Mausbach, and Charles R Hurburgh. Near-infrared reflectance spectroscopy–principal components regression analyses of soil properties. *Soil Science Society of America Journal*, 65(2):480–490, 2001.
- [3] Akifumi Ikehata, Tamitake Itoh, and Yukihiro Ozaki. Surface plasmon resonance near-infrared spectroscopy. *Analytical chemistry*, 76(21):6461–6469, 2004.
- [4] RA Lewis. Invited review terahertz transmission, scattering, reflection, and absorption the interaction of thz radiation with soils. *Journal of Infrared, Millimeter, and Terahertz Waves*, 38(7):799–807, 2017.
- [5] Hiroshi Matsuyama, Hajime Asama, and Mihoko Otake. Design of differential near-infrared spectroscopy based brain machine interface. In *Robot and Human Interactive Communication, 2009. RO-MAN 2009. The 18th IEEE International Symposium on*, pages 775–780. IEEE, 2009.
- [6] Andrei Rodionov, Stefan Pätzold, Gerhard Welp, Lutz Damerow, Wulf Amelung, et al. Sensing of soil organic carbon using visible and near-infrared spectroscopy at variable moisture and surface roughness. *Soil Science Society of America Journal*, 78(3):949–957, 2014.
- [7] Jun Shibayama, Keisuke Shimizu, Junji Yamauchi, and Hisamatsu Nakano. Surface plasmon resonance waveguide sensor in the terahertz regime. *Journal of Lightwave Technology*, 34(10):2518–2525, 2016.
- [8] LK Sørensen and S Dalsgaard. Determination of clay and other soil properties by near infrared spectroscopy. *Soil Science Society of America Journal*, 69(1):159–167, 2005.
- [9] G Clarke Topp, JL Davis, and AP Annan. Electromagnetic determination of soil water content: Measurements in coaxial transmission lines. *Water resources research*, 16(3):574–582, 1980.