

Datasheets

Temperature/Humidity (HDC1080):

https://www.ti.com/lit/ds/symlink/hdc1080.pdf?ts=1738555810034&ref_url=https%253A%252F%252Fwww.ti.com%252Fproduct%252FHDC1080

CO2 (SCD41) :

<https://download.mikroe.com/documents/datasheets/SCD41%20Datasheet.pdf>

Ammonia (MQ-137):

<https://www.sparkfun.com/ammonia-gas-sensor-mq-137.html>

Methane (MQ-4):

<https://www.sparkfun.com/methane-cng-gas-sensor-mq-4.html>

Hydrogen Sulfide (MQ-136):

<https://www.sparkfun.com/hydrogen-sulfide-gas-sensor-mq-136.html>

AD7718:

https://www.analog.com/media/en/technical-documentation/data-sheets/ad7708_7718.pdf

Microcontroller pins:

I2C:

SCL - IO4

SDA - IO6

SPI:

MOSI - IO21

MISO - IO19

CLK - IO18

CS* - IO5

RESET - IO7

RDY - IO9

Sensor IDs:

Temperature and Humidity Sensor:

0x40

CO2 Sensor:

0x62

Formula:

SPI:

```
adc_value = 2*(((adc_code / pow(2,23) -1)*2.5) + .0278177268);
```


Using I2C for digital sensors, I need to write a function that can access both (HDC1080 and SCD41) of the sensors from the SCL - IO4 and SDA - IO6.

Using SPI to interface with the AD7718 to read the 3 analog sensor values as shown below:


- **I2C Sensors (Temperature & CO2)**
 - **HDC1080 (Temperature & Humidity) @ 0x40**
 - **SCD41 (CO2 Sensor) @ 0x62**
 - **I2C Pins on ESP32-S3:**
 - **SCL → GPIO 4**
 - **SDA → GPIO 6**
- **Analog Sensors (Interfaced via SPI ADC)**
 - **MQ-137 (Ammonia)**
 - **MQ-4 (Methane)**
 - **MQ-136 (H2S)**
 - **SPI ADC (AD7718)**
 - **MOSI → GPIO 21**
 - **MISO → GPIO 19**
 - **CLK → GPIO 18**
 - **CS → GPIO 5**
 - **RESET → GPIO 7**
 - **RDY → GPIO 9**

Header Connections and Buttons:


Connector on the left:



Connector on the right:



Left side is power. Right side is the test voltages. H2S 2 sends voltage directly to ADC analog input 1. NH3 2 sends to ADC analog input 2.



SW1 is the reset button. SW2 is the boot button.

I2C Test:

Power 3.3V. No test voltage needed.

SPI/ADC Test:

Power 5V and 3.3V. Test voltage H2S 2 needed. Use NH3 2 if you want to test chip select.