

Note: To access the complete submission files for a given filing, please see the [SEC EDGAR website](http://www.sec.gov/Archives/edgar/data/{cik}/{accession}/). The SEC website folder <http://www.sec.gov/Archives/edgar/data/{cik}/{accession}/> will always contain all the data sets for a given submission. To assemble the folder address to any filing referenced in the SUB data set, simply substitute {cik} with the cik field and replace {accession} with the adsh field (after removing the dash character). The following sample SQL Query provides an example of how to generate a list of addresses for filings contained in the SUB data set:

- ```
select name,form,period, 'http://www.sec.gov/Archives/edgar/data/' +
ltrim(str(cik,10))+ '/' + replace(adsh,'-','')+ '/' +instance as url from SUBM subm order by
period desc, name
```

## 5.2 TAG (Tags)

The TAG data set contains all standard taxonomy tags, not just those appearing in submissions to date, and also includes all custom taxonomy tags defined in the submissions. The source is the “as filed” XBRL filer submissions. The standard tags are derived from taxonomies in <http://www.sec.gov/info/edgar/edgartaxonomies.shtml>.

**Figure 3. Fields in the TAG data set**

| Field Name      | Field Description                                                                                                                                                                                                        | Field Type                         | Max Size | May be NULL | Key |
|-----------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|------------------------------------|----------|-------------|-----|
| <b>tag</b>      | The unique identifier (name) for a tag in a specific taxonomy release.                                                                                                                                                   | ALPHANUMERIC                       | 256      | No          | *   |
| <b>version</b>  | For a standard tag, an identifier for the taxonomy; otherwise the accession number where the tag was defined.                                                                                                            | ALPHANUMERIC                       | 20       | No          | *   |
| <b>custom</b>   | 1 if tag is custom (version=adsh), 0 if it is standard. <i>Note: This flag is technically redundant with the version and adsh columns.</i>                                                                               | BOOLEAN (1 if true and 0 if false) | 1        | No          |     |
| <b>abstract</b> | 1 if the tag is not used to represent a numeric fact.                                                                                                                                                                    | BOOLEAN (1 if true and 0 if false) | 1        | No          |     |
| <b>datatype</b> | If abstract=1, then NULL, otherwise the data type (e.g., monetary) for the tag.                                                                                                                                          | ALPHANUMERIC                       | 20       | Yes         |     |
| <b>iord</b>     | If abstract=1, then NULL; otherwise, “I” if the value is a point-in time, or “D” if the value is a duration.                                                                                                             | ALPHANUMERIC                       | 1        | No          |     |
| <b>crdr</b>     | If datatype = monetary, then the tag’s natural accounting balance (debit or credit); if not defined, then NULL.                                                                                                          | ALPHANUMERIC (“C” or “D”)          | 1        | Yes         |     |
| <b>tlabel</b>   | If a standard tag, then the label text provided by the taxonomy, otherwise the text provided by the filer. A tag which had neither would have a NULL value here.                                                         | ALPHANUMERIC                       | 512      | Yes         |     |
| <b>doc</b>      | The detailed definition for the tag (truncated to 2048 characters). If a standard tag, then the text provided by the taxonomy, otherwise the text assigned by the filer. Some tags have neither, and this field is NULL. | ALPHANUMERIC                       | 2048     | Yes         |     |