CTL DECISION SHEET (DSH)

Standard(s):	Subclause(s):	No.	Year
IEC 60730-1/2010 IEC 60335-1/2010 IEC 60598-1/2008 IEC 60950-1/2006	General	DSH 1055	2014
Category:			
VARIOUS			
Subject:	**Key words:**	**Developed by**	**Approved at**
Chemical solvent used for the scrub test	- IEC TC 72 – 61 – 108 – IEC SC 34D - Chemical solvent - Scrub test	WG4	2014 CTL Plenary Meeting

Question

For the Standard IEC 60730-1 4th Ed. there is required:
The solvents used are:
– neutral liquid detergent blended from alkyl benzene sulphonate and non-ionic detergents;
– petroleum spirit (aliphatic solvent hexane with a content of aromatics of maximum 0,1 volume %, a Kauributanol value of 29, initial boiling point of approximately 65 ℃ and dry point approximately 69 ℃, and specific gravity of approximately 0,68 g/cm3); and water.

For the standard IEC 60335-1 5th Ed. There is now required:
The petroleum spirit to be used for the test is aliphatic solvent hexane.

- For the standard IEC 60598-1 7th Ed. There is required:

NOTE The petroleum spirit used should consist of a solvent hexane with a content of aromatics of maximum 0,1 % by volume, a value of 29 % for kauri-butanol, an initial boiling-point of approximately 65 ℃, a dry-point of approximately 69 ℃ and a densit y of approximately 0,68 g/cm3.

- For the standard IEC 60950-1 2nd Ed. There is required:

The petroleum spirit to be used for the test is aliphatic solvent hexane having a maximum aromatics content of 0,1 % by volume, a kauributenol value of 29, an initial boiling point of approximately 65 °C, a dry point of approximately 69 ℃ and a mass per unit vo lume of approximately 0,7 kg/l.
As an alternative, it is permitted to use a reagent grade hexane with a minimum of 85 % as n-hexane.

NOTE The designation “n-hexane” is chemical nomenclature for a "normal" or straight chain hydrocarbon. This petroleum spirit may further be identified as a certified ACS (American Chemical Society) reagent grade hexane
(CAS# 110-54-3).

The exact chemical solvent formula is difficult to find in the marketplace.
The various TCs are kindly requested to consider "harmonizing" the solvent accordingly.

© IEC – IECEE 2012

Decision
The petroleum spirit to be used for the test is aliphatic solvent hexane. As an alternative, it is permitted to use a reagent grade hexane with a minimum of 85% as n-hexane. Note: the designation “n-hexane” is chemical nomenclature for a “normal” or straight chain hydrocarbon. This petroleum spirit may further be identified as a certified ACS (American Chemical Society) reagent grade hexane (CAS# 110-54-3).
Explanatory notes

© IEC – IECEE 2012