■ CTL Provisional DECISION SHEET (PDSH)
☐ CTL DECISION SHEET (DSH)

Standard(s) (incl. year)	**Subclause(s)**	**Tracking No.**
IEC 62196-1: 2022 IEC 62196-3: 2022	11	PDSH 2301
Category		
ELVH		
Subject	**Keywords**	**Developed by**
The minimum cross-sectional area requirements for earthing conductors in EE/FF vehicle connectors	Earthing conductor Isolated system	ETF 14

Question

What are the minimum cross-sectional area requirements for the earthing conductor of EE/FF vehicle connectors when used in isolated systems? Is the earthing conductor of the EE/FF connector can be considered as functional earth conductor? Is the short-time current test in cl. 12.3 applicable to these connectors?

Decision

1. When used in isolated systems, the minimum cross-sectional area of the earthing conductor of EE/FF vehicle connectors shall be 6 mm^2.

2. 12.3 short-time current test is not applicable for EE/FF vehicle connectors used in isolated systems.

Explanatory notes

Enquiry:
Date: 2025-04-02

PDSH:
Year of publication:
To be approved at CTL plenary:

DSH
Publication date:

Click here to enter text.

Disclaimer: This document is controlled and has been released electronically.
Only the version on the IECEE Website is the current document version.