DECISION SHEET

Standard(s):	**Sub clause(s):**	No.	Year
IEC 60950-1:2001 **IEC 60950-1:2005**	**1.5.2, 4.5**	737	2009
		Developed by ETF 2	
Subject: **Application of IEC 60320-1 type appliance inlet**	**Key words:** **- Appliance inlet** **- Thermal limit** **- Building-in power supply**	**Decision approved at the 46th CTL Plenary Meeting 2009**	

Question:

Does DSH-548 apply to end products only, or to other equipment, such as built-in power supplies, where the appliance inlet is likely to serve as (PLUGGABLE EQUIPMENT TYPE A) means for connection to the AC MAINS SUPPLY?

Decision:

DSH-548 applies to all PLUGGABLE EQUIPMENT TYPE A where the appliance inlet is used as means for connection to an AC MAINS SUPPLY.

Explanatory Notes:

DSH-548 discusses the specific case of an adapter. Appliance inlets however are frequently used in built-in power supplies. Built-in equipment requires re-evaluation of several safety aspects after integration into a final product or system. The appliance inlet will often serve in built-in power supplies (e.g. ATX power supplies for PC) as means for connection to an AC MAINS SUPPLY. Therefore, an exceeding of thermal limits for appliance inlets during TYPE TEST of a built-in power supply should not be permitted, as this specific condition would not improve after integration into the final product or system.