

1 Eye-tracking on the web: lessons learned from replicating 5 experiments

2 Josh de Leeuw¹ & et al.^{1,2}

3 ¹ Vassar College

4 ² XX

5 Author Note

6 Add complete departmental affiliations for each author here. Each new line herein
7 must be indented, like this line.

8 Enter author note here.

9 The authors made the following contributions. Josh de Leeuw: Conceptualization,
10 Writing - Original Draft Preparation, Writing - Review & Editing; et al.: Writing - Review
11 & Editing.

12 Correspondence concerning this article should be addressed to Josh de Leeuw, Postal
13 address. E-mail: my@email.com

14

Abstract

15

ADD LATER

16

Keywords: keywords

17

Word count: X

Eye-tracking on the web: lessons learned from replicating 5 experiments

Intro stuff:

- Eye-tracking as a key method in cognitive science research
- Online data collection is more and more popular & let's us ask new questions, test more diverse populations
- But, concerns over quality + little known about eye-tracking online

Present work

In the present work, we attempted to replicate five eye-tracking studies from the cognitive science literature using the eye-tracking plug-in from `jsPsych`, a Javascript library for running behavioral experiments in a web browser (de Leeuw, 2015). The plug-in relies on the `webgazer.js` library for webcam eye-tracking (Papoutsaki et al., 2016). The goal was to examine the strengths and weaknesses of webcam eye-tracking for common paradigms in cognitive science. The studies were chosen to cover a variety of topic areas (e.g., memory, decision-making, psycholinguistics) and paradigms (two halves of the screen, visual world paradigm with four quadrants, visual world paradigm with “natural” scenes). . . .

General Methods

Participants

Participants completed the experiment remotely and were recruited through the Prolific platform. In order to have access to the experiment, participants had to meet the following criteria: 18 years of age or older, fluency in English, and access to a webcam. All participants provided informed consent. The studies were approved by the Vassar College Institutional Review Board.

41 Eye-tracking Calibration and Validation

42 When participants began the experiment, they were notified the webcam would be
43 used for eye tracking but no video would be saved. They were asked to remove glasses if
44 possible, close any other tabs or apps, turn off notifications, and make sure their face was
45 lit from the front. The webcam's view of the participant popped up on the screen, and
46 participants were asked to center their face in the box and keep their head still. The
47 experiment window then expanded to full screen, and participants began the eye-tracking
48 calibration.

49 During the calibration, dots appeared on the screen one at a time in different
50 locations, and the participants had to fixate them and click on each one. Once they clicked
51 on a dot, it would disappear and a new one would appear in a different location on the
52 screen. The locations of calibration dots were specific to each experiment (details below)
53 and appeared in the areas of the screen where the visual stimuli would appear during the
54 main task in order to ensure that eye movements were accurately recorded in the relevant
55 regions of interest. After the calibration was completed, the validation began. Participants
56 were asked to go through the same steps as the calibration, except that they only fixated
57 the dots as they appeared in different locations on the screen. If accuracy on the validation
58 was too low (fewer than 50% of looks landed within a 200 px radius of the validation
59 points), participants were given an opportunity to re-start the calibration and validation
60 steps. If the second attempt also lead to low validation accuracy, participants were
61 informed that they could not participate in the study.

62 Data pre-processing

63 We used R [Version 4.1.2; R Core Team (2021)] and the R-packages *afex* [Version
64 1.0.1; Singmann, Bolker, Westfall, Aust, and Ben-Shachar (2021)], *broom.mixed* [Version
65 0.2.7; Bolker and Robinson (2020)], *dplyr* [Version 1.0.7; Wickham, François, Henry, and

Müller (2021)], *forcats* [Version 0.5.1; Wickham (2021a)], *ggplot2* [Version 3.3.5; Wickham (2016)], *jsonlite* [Version 1.7.2; Ooms (2014)], *lme4* [Version 1.1.27.1; Bates, Mächler, Bolker, and Walker (2015)], *lmerTest* [Version 3.1.3; Kuznetsova, Brockhoff, and Christensen (2017)], *Matrix* [Version 1.3.4; Bates and Maechler (2021)], *papaja* [Version 0.1.0.9997; Aust and Barth (2020)], *readr* [Version 2.1.1; Wickham and Hester (2020)], *shiny* [Version 1.7.1; Chang et al. (2021)], *stringr* [Version 1.4.0; Wickham (2019)], *tidyr* [Version 1.1.4; Wickham (2021b)], and *tinylabels* (Barth, 2022) for all our analyses.

Experiment 1

The first study was a replication attempt of Altmann and Kamide (1999). Altmann and Kamide used the visual world eye-tracking paradigm (Tanenhaus, Spivey-Knowlton, Eberhard, & Sedivy, 1995) to show that meanings of verbs rapidly constrain the set of potential subsequent referents in sentence processing. For example, when looking at the display in Figure XX and listening to a sentence like “The boy will eat the . . .,” participants are more likely to look at the cake than when they hear “The boy will move the . . .,” in which case they tend to look at the train, presumably because cakes are edible and trains are not. Semantic information available at the verb is used to anticipate upcoming linguistic input.

Methods

All stimuli, experiment scripts, data, analysis scripts, and pre-registration are available on the Open Science Framework at <https://osf.io/s82kz>.

Participants. 60 participants were paid \$XX for their participation. Our sample size of participants was determined by the total run time of our experiment, ~10 minutes, and the allotted funding from the Vassar College Cognitive Science Department. From this information, we calculated a reasonable number of participants we could afford to

compensate on Prolific. Note that the sample size of the original study was 24. For unknown reasons, 2 of the subjects' results were not recorded, so in the analysis, we worked with data collected from 58 participants.

Procedure. The task began with an -point eye-tracker calibration and validation. During the experiment, the participants were simultaneously presented with a visual image and a corresponding audio recording of a spoken sentence. Participants had to input a keyboard response indicating “yes” or “no” as to whether the sentence they heard was feasible given the visual image. There were two practice trials to ensure that participants had a sound understanding of the instructions before they undertook the main portion of the experiment. Participants' reaction times, keyboard responses, and looks to objects in the scene were recorded for each trial.

Materials & Design. The visual stimuli were created through Canva and depicted an agent accompanied by four to five objects in the scene (see Figure XX). On critical trials, participants heard one of two sentences associated with the scene. In the restrictive condition, the sentence (e.g., “The boy will eat the cake”) contained a verb (e.g., “eat”) which restricts the set of possible subsequent referents (e.g., to edible things). Only the target object (e.g., the cake) was semantically consistent with the verb's meaning. In the non-restrictive condition, the sentence (e.g., “The boy will move the cake”) contained a verb (e.g., “move”) which does not restrict the set of possible subsequent referents. The target object (e.g., the cake) as well as the distractor objects (e.g., the train, the ball, etc.) were semantically consistent with the verb's meaning. Both sentences were compatible with the scene, such that the correct keyboard response for the critical trials was “yes.” Filler trials consisted of scenes that looked similar to critical scenes but were paired with inappropriate sentences. The correct keyboard response for the filler trials was “no.”

Each participant was presented with sixteen critical trials (eight in the restrictive condition, eight in the non-restrictive condition) and sixteen fillers for a total of 32 trials. The order of trials and the assignment of critical scene to condition was random on a

subject-by-subject basis.

TO DO: add figure

Data pre-processing and analysis. Looks to the objects in the scene were time-locked to the onset of the verb, the offset of the verb, onset of the post-verbal determiner, and onset of the target noun.

Results

Replication.

- here we will describe the analyses that are as close as possible to the original paper with a minimal validation cutoff
- same analysis but with stricter validation cutoff

Comparison to in-lab data.

- here we will describe a direct comparison to data collected in the lab

Calibration.

- here we will describe the analyses that correlate calibration quality with effect size at the individual level

Discussion

Experiment 2

The second study was a replication attempt of Johansson and Johansson (2014), which examined how visuospatial information is integrated into memory for objects. They found that, during memory retrieval, learners spontaneously look to blank screen locations where pictures were located during encoding (see Spivey & Geng, 2001) and that this spatial reinstatement facilitates retrieval of the picture.

Methods

Participants. 60 participants were paid \$XX for their participation . The sample size was motivated in part by budget constraints, but was nonetheless 2.5x larger than the original sample size of 24, as suggested by Simonsohn (2015). Data from 1 participant were not properly recorded due to unknown technical issues, so data from 59 participants were included in all analyses to follow.

Procedure. The experiment consisted of two blocks each composed of an encoding phase and a recall phase. During the encoding phase, participants saw a grid indicating the four quadrants of the screen. Each quadrant contained six images of items belonging to the same category (see Figure XX). The four categories were humanoids, household objects, animals, and methods of transportation. Participants were asked to remember the contents of the four quadrants. Different images were used in each block.

Each of the four quadrants was presented one at a time. First, a list of the items in the quadrant were shown, then the items in the actual quadrant were shown (??). For each item, an audio file would play (“???”) asking the participant to use their arrow keys to identify which direction each item was facing (every item was facing either left or right (right??)). After the participant identified the direction of each item, they would have an additional 30 seconds to encode the name and orientation of each item in the quadrant. Then, after all four quadrants were presented in this way, the participant was shown the full grid of 24 items and had 60 seconds to further encode the name and orientation of each item.

During the recall phase, participants listened to statements and responded by pressing the ‘F’ key for false statements and ‘T’ for true ones. Each statement fell into either an interobject or intraobject condition. Interobject statements were those that compared two different items in the grid (e.g. “The skeleton is to the left of the robot”), while intraobject statements were those that asked about the orientation of a single item

(e.g. “The bus is facing right”). There were 48 total statements, with 24 interobject and 24 intraobject statements split evenly among the four quadrants. While listening to these statements, in the free-viewing block, participants saw a blank screen and were allowed to freely gaze around the screen. During the fixed-viewing block, participants were asked to fixate a small cross in the center of the screen throughout the recall phase. In both cases, the mouse was obscured from the screen. Participants were randomly assigned to see the fixed-viewing or free-viewing block first.

After completing both encoding-recall blocks, participants were asked to answer a few survey questions (such as whether they wore glasses or encountered any distractions).

The primary methodological difference between this replication and Johansson and Johansson’s study was that the original study included two additional viewing conditions that were omitted from this replication due to time constraints. In those two conditions, participant were prompted to look to a specific quadrant (rather than free viewing or central fixation) which either matched or mismatched the original location of the to-be-remembered item.

Data analysis.

Results

Replication. Eye-gaze. Looks during the retrieval period were categorized as belonging to one of four quadrants based on the x,y coordinates. The critical quadrant was the one in which the to-be-retrieved object had been previously located during encoding. The other three quadrants were semi-randomly labeled “first,” “second,” third” (e.g., when the critical quadrant was in the top left, the “first” quadrant was the top right quadrant, but when the critical quadrant was in the top right, “first” corresponded to bottom right, etc.). In both the fixed- and free-viewing condition, participants directed a larger proportion of looks to the critical quadrant (see Figure 1). This bias appeared larger in the

190 free-viewing condition, suggesting that the manipulation was (somewhat) effective.




Figure 1. Proportion of eye-gaze to critical quadrant and other three quadrants during memory retrieval in a) fixed and b) free viewing conditions.

191 The proportion of looks across quadrants in the free-viewing condition was analyzed
 192 in linear mixed-effects model with quadrant as the predictor (critical as the reference level).
 193 The model included random intercepts and slopes for participants¹ Proportions of looks
 194 were significantly higher for the critical quadrant compared to the other three (first: $b =$
 195 -0.06 , $SE = 0.01$, $p < 0.001$, second: $b = -0.08$, $SE = 0.01$, $p < 0.001$, third: $b = -0.05$, $SE =$
 196 0.01 , $p < 0.001$)

¹ lme4 syntax: `lmer(proportion ~ quadrant + (1+quadrant|subject_id))`. Among other limitations, this approach violates the independence assumptions of the linear model because looks to the four locations are not independent. This analysis was chosen because it is analogous to the ANOVA analysis




Figure 2. Accuracy and response times during memory retrieval.

Response Time and Accuracy. Participants' response times and accuracies on memory questions are summarized in Figure 2. Both dependent variables were analyzed with linear mixed-effects model with relation type (interobject = -0.5, intraobject=0.5) and viewing_condition (fixed = -0.5, free=0.5) and their interaction as the predictors. The model included random intercepts for participants². Accuracy did not differ significantly between interobject and intraobject questions ($b = -0.05$, $SE = 0.03$, $p=0.05$). Participants were less accurate in the free viewing condition than the fixed condition ($b = -0.06$, $SE = 0.03$, $p=0.03$). Response times were slower for interobject (e.g., "The train is to the right of the taxi.") than intraobject (e.g., "The train is facing right.") questions ($b = -555.60$, $SE =$

conducted in the original paper.

² lme4 syntax: `lmer(DV ~ relation_type*viewing_condition + (1|subject_id))`

105.24, $p < 0.001$). Response times were slower in the free viewing condition than the fixed condition ($b = 260.98$, $SE = 105.24$, $p < 0.001$). The interaction was not a significant predictor for response times or accuracy. These behavioral results are inconsistent with the original findings.

One possibility is that in-lab participants were much more compliant with the instruction to keep their gaze on central fixation (though these data are not reported in the original paper). When analyzing results from the subset of participants ($N = 25$) who were most compliant during the fixed-viewing block (at least 25% of their looks fell within 20% of the center of the display), the viewing condition effects and the interactions were not significant. Given the smaller sample size we do not interpret these results further.

Q: Can we recover item IDs to do crossed random effects?

Calibration. Participants' calibration quality, measured as the mean percentage of fixations that landed within **XX** pixels of the calibration point, varied substantially (between 17.78 and 100 %). The quality of a participant's calibration was not significantly correlated with the participant's effect size (*Pearson's* $r = 0.20$, $p = 0.14$) as measured by the difference between the proportion of looks to the critical quadrant minus the average proportion of looks to the average of the other three quadrants.

Discussion

Experiment 3

The third study was a replication attempt of Manns, Stark, and Squire (2000) which aimed to show that the visual paired-comparison task, widely used in the patient literature, tapped into declarative memory. In the visual paired-comparison task, two identical pictures were presented side by side for a brief viewing period. After a delay, one of the previously viewed pictures was presented along with a new picture. Individuals looked more at the new picture than the old picture and the time spent looking was correlated

with later recognition memory performance. On the other hand perceptual priming, thought to recruit non-declarative memory, was not linked to later recognition. (The perceptual priming arm of the design was not included in this replication.)

Methods

Participants. Our initial sample size was 51 participants for the first day of our experiment and 48 of them came back for the second day. Following Manns et al., we excluded 3 participants due to perfect performance on the recognition memory test. Our final sample size was 45 participants.

Procedure. The task began with a 7-point eye-tracker calibration (each point was presented 3 times in a random order) and validation with 3 points (each presented once). The point locations were designed to focus calibration on the center of the screen and the middle of the left and right halves of the screen. The experiment was administered over the course of two consecutive days. It consisted of three sections: a presentation phase, a test phase, and a recognition test. The first two phases occurred on the first day, while the recognition test occurred on the second day.

During the presentation phase, participants viewed 24 pairs of identical color photographs depicting common objects. Each pair was presented for 5 seconds and an interval of 5 seconds elapsed before the next pair was shown. The order of the photographs was randomized and different for each participant. After completion of the presentation phase, participants were given a 5-minute break during which they could look away from the screen.

After the break, they were prompted to complete the eye-tracking calibration again before beginning the test phase. During this phase, participants again viewed 24 pairs of photographs with an interstimulus duration of 5 seconds. In each pair, one photograph was previously seen during the presentation phase, while the other was new. Which pictures

were old or new was counterbalanced across participants. For half of the participants in each counterbalancing group, the new and old photographs were reversed.

Approximately 24 hours after completing the first session, with a leeway interval of 12 hours to accommodate busy schedules, participants were given the recognition test. It consisted of 48 photographs, presented one at a time. Each was shown on the screen for 1 second, followed by a 1 second interstimulus interval. Half of the photographs had been viewed twice on the previous day and were deemed the “targets.” The other half depicted an object with the same name as an object in one of the old photographs, but had not been viewed before, deemed “foils.” Each photograph remained on the screen until the participants indicated whether or not they had seen it before by pressing ‘y’ for yes and ‘n’ for no. After they pressed one of the two keys, a prompt on the screen asked them to rate their confidence in their answer from 1 as a “pure guess” to 5 as “very sure.” by clicking on the corresponding number on the screen. No feedback on their responses was given during the test.

The experimental design is visually depicted in Figure XX

Materials. Images were selected XXX...

There were two modifications we made to the methods of the original experiment. As we are only replicating the declarative memory component of the original experiment, we did not have a “priming group.” Therefore, we followed only the procedure for the “looking group.” Additionally, for each section of the study, the stimuli was presented on a single screen instead of two screens due to the constraints of the online experiment format.

Data analysis.

Results

Discussion

Experiment 4

The fourth study was a replication attempt of Experiment 1 in Ryskin, Qi, Duff, and Brown-Schmidt (2017), which was closely modeled on Snedeker and Trueswell (2004). These studies used the visual world paradigm to show that listeners use knowledge of the co-occurrence statistics of verbs and syntactic structures to resolve ambiguity. For example, in a sentence like “Feel the frog with the feather,” the phrase “with the feather” could be describing the frog, or it could be describing the instrument that should be used to do the “feeling.” When both options (a frog holding a feather and a feather by itself) are available in the visual display, listeners rely on the verb’s “bias” (statistical co-occurrence either in norming or corpora) to rapidly choose an action while the sentence is unfolding.

Methods

The stimuli, experimental code, and data and analysis scripts can be found on the Open Science Framework at the following link, <https://osf.io/x3c49/> (<https://osf.io/x3c49/>). The pre-registration for the study can be found at <https://osf.io/3v4pg> (<https://osf.io/3v4pg>).

Participants. 58 (??) participants were paid \$XX for their participation. A sample size of 58 was chosen because we wanted to replicate the experiment with greater statistical power. Note that the original study had a sample size of 24.

Procedure.

- *TO DO:* add details of calibration point locations

After the eye-tracking calibration, participants went through an audio test so they could adjust the audio on their computer to a comfortable level. Before beginning the experiment, they were given instructions that four objects would appear, an audio prompt would play, and they should do their best to use their mouse to act out the instructions. They then went through three practice trials which were followed by 54 critical trials and 24 filler trials presented in a random order.

During a trial, four pictures were displayed (target animal, target instrument, distractor animal, distractor instrument), one in each corner of the screen, and participants heard an audio prompt that contained instructions about the action they needed to act out (e.g., “Rub the butterfly with the crayon”; see Figure XX)³. Using their cursor, participants could act out the instructions by clicking on objects and moving them or motioning over the objects⁴. After the action was completed, the participants were instructed to press the space bar which led to a screen that said “Click Here” in the middle in order to remove bias in the eye and mouse movements from the previous trial. The experiment only allowed the participants to move on to the next trial once the audio was completely done playing and the mouse had been moved over at least one object.

TO DO: ADD FIGURES Figure 1: An example of a critical trial for the sentence “Rub the butterfly with the crayon.” The butterfly is the target animal, the panda is the distractor animal, the crayon is the target instrument, and the violin is the distractor instrument.

Materials. The images and audios presented to the participants were the same stimuli used in the original study (available here). The critical trials were divided into

³ In the original study, the pictures appeared one by one on the screen and their names were played as they appeared. We removed this introductory portion of the trial to save time

⁴ As opposed to the original study we recorded mouse movement instead of clicking behavior since not all of the audio prompts required clicking. For example, the sentence “locate the camel with the straw” may not involve any clicking but rather only mousing over the camel.

modifier-biased, instrument-biased, and equibiased conditions, and the filler trials did not contain ambiguous instructions. Two lists of critical trials were made with different verb and instrument combinations (e.g., “rub” could be paired with “panda” and “crayon” in one list and “panda” and “violin” in the second list). Within each list, the same verb was presented twice but each time with a different target instrument and animal. The lists were randomly assigned to the participants to make sure the effects were not caused by the properties of the animal or instrument images used. The list of verbs used can be found in Appendix A of the original study.

Results

Replication. The location of initial mouse movements was used to assess whether the final interpretation of ambiguous sentences was biased by the verb. Figure 3 suggests that listeners were more likely to move their mouse first over the target instrument when the verb was equi-biased than when the verb was modifier-biased and even more so when the verb was instrument-biased. The opposite graded pattern can be observed for mouse movements over the target animal.

A mixed-effects logistic regression model was used to predict whether the first movement was on the target instrument with the verb bias condition as an orthogonally contrast-coded (instrument vs. equi & modifier: inst = -2/3, equi = 1/3, mod = 1/3; equi vs. modifier: inst = 0, equi = -1/2, mod = 1/2) fixed effect. Participants and items were entered as varying intercepts with by-participant varying slopes for verb bias condition⁵. Participants were more likely to first move their mouse over target instruments in the instrument-biased condition relative to the equi-biased and modifier-biased condition ($b = -1.50$, $SE = 0.25$, $p < 0.01$). Further, participants were more likely to first move their

⁵ lme4 syntax: `glmer(is.mouse.over.instrument ~ verb_bias + (1 + verb_bias | participant) + (1 | item), family="binomial", data=d)`




Figure 3. Proportion of first mouse movements by location and verb bias.

mouse over target instruments in the equi-biased condition relative to the modifier-biased condition ($b = -1.10$, $SE = 0.29$, $p < 0.01$)

Gaze fixations were time-locked to the auditory stimulus on a trial by trial basis and categorized as being directed towards one of the four items in the display if the x, y coordinates fell within a rectangle containing the image. Figure 4 suggests that the participants made more fixations to the target animal when the verb was modifier-biased compared to when the the verb was equi-biased and they looked at the target animal least when the verb was instrument-biased. The pattern was reversed for looks to the target instrument.

In order to assess how verb bias impacted sentence disambiguation as the sentence unfolded, the proportion of fixations was computed in three time windows: the




Figure 4. Timecourse of eye-gaze to target animal and target instrument by verb bias condition. Vertical lines indicate average onsets of animal and instrument offset by 200ms.

verb-to-animal window (from verb onset + 200 ms to animal onset + 200 ms), the animal-to-instrument window (from animal onset + 200 ms to instrument onset + 200 ms), and the post-instrument window (from instrument onset + 200 ms to instrument onset + 1500ms + 200 ms). Mixed-effects linear regression models were used to predict the proportions of fixations to the target animal within each time window with the verb bias condition as an orthogonally contrast-coded (instrument vs. equi & modifier: $inst = -2/3$, $equi = 1/3$, $mod = 1/3$; equi vs. modifier: $inst = 0$, $equi = -1/2$, $mod = 1/2$) fixed effect. Participants and items were entered as varying intercepts⁶. In the *verb-to-noun* window,

⁶ lme4 syntax: `lmer(prop.fix.target.animal ~ verb_bias + (1 + verb_bias | participant) + (1 | item), data=d)`. A model with by-participant varying slopes for verb bias condition was first attempted

participants did not look more at the target animal in any of the verb bias conditions (Instrument vs. Equi and Modifier: $b = -0.01$, $SE = 0.02$, $p = 0.59$; Equi vs. Modifier: $b = 0$, $SE = 0.02$, $p = 1$). In the *noun-to-instrument* window, participants looked more at the target animal in the modifier-biased condition and equi-biased conditions relative to the instrument-biased condition ($b = 0.03$, $SE = 0.01$, $p < 0.01$) and in the modifier biased relative to the equi-biased condition ($b = 0.02$, $SE = 0.01$, $p < 0.05$). In the *post-instrument* window, participants looked more at the target animal in the modifier-biased condition and the equi-biased conditions relative to the instrument-biased condition ($b = 0.08$, $SE = 0.02$, $p < 0.01$) but not significantly so in the modifier biased condition relative to the equi-biased condition ($b = 0.03$, $SE = 0.02$, $p = 0.15$).

Comparison to in-lab data. The web version of the study qualitatively replicates the action and eye-tracking results of the original dataset (Ryskin et al., 2017). The mouse click results from both studies are summarized in Figure 5. The quantitative patterns of clicks were similar to those observed in the original dataset, though for Instrument-biased verbs, clicks were closer to evenly split between the animal and the instrument relative to the in-lab study where they were very clearly biased toward the instrument.

The eye-tracking results from both studies are summarized in Figure 6. For simplicity, and to reflect the dependent variable used in analyses, we average the proportion of fixations to the target animal within each time window. Though the qualitative patterns are replicated, proportions of fixations to the target animal were much lower in the web version of the study. This may reflect the fact that participants in the web study are less attentive and/or the quality of the webgazer eye-tracking system is lower, relative to the Eyelink 1000 which was used for the original study.

Calibration. Participants' calibration quality, measured as the mean percentage of fixations that landed within **XX** pixels of the calibration point, varied substantially

but did not converge.




Figure 5. Proportion of first mouse movements by location and verb bias in the original dataset (Ryskin et al., 2017) and the current data collected online.

(between 2.22 and 97.36 %). The quality of a participant’s calibration significantly correlated with the participant’s effect size (*Pearson’s* $r = 0.29$, $p < 0.05$). The difference in target animal fixation proportions between modifier and instrument conditions was higher for participants with better calibration

Replicating the linear mixed-effects analysis (in the post-instrument onset time window only) on a subset of 35 participants with calibration quality $>50\%$ suggests that the effect of verb bias condition was larger in this subset than in the full dataset. Participants looked more at the target animal in the modifier-biased condition and the equi-biased conditions relative to the instrument-biased condition ($b = 0.10$, $SE = 0.02$, $p < 0.001$) but not significantly so in the modifier biased condition relative to the equi-biased




Figure 6. Proportion of target fixations by verb bias in the original dataset (Ryskin et al., 2017) and the current data collected online. Error bars reflect bootstrapped 95% CIs over subject means

condition ($b = 0.02$, $SE = 0.02$, $p = 0.29$).

Replicating the linear mixed-effects analysis (in the post-instrument onset time window only) on a subset of 19 participants with calibration quality $>75\%$ suggests that the effect of verb bias condition was larger in this subset than in the full dataset. Participants looked more at the target animal in the modifier-biased condition and the equi-biased conditions relative to the instrument-biased condition ($b = 0.11$, $SE = 0.03$, $p < 0.001$) but not significantly so in the modifier biased condition relative to the equi-biased condition ($b = 0.05$, $SE = 0.03$, $p = 0.13$).

Effects of ROIs. Eye-tracking on the web differs critically from in-lab eye-tracking in that the size of the display differs across participants. Thus the size of the ROIs differs across participants. The current version of the web experiment used a bounding box around each image to determine the ROI. This approach is flexible and accomodates variability in image size, but may exclude looks that are directed at the image but fall outside of the image (due to participant or eye-tracker noise) as show in Figure 7a. Alternatively, The display can be split into 4 quadrants which jointly cover the entire screen (see Figure 7b).




Figure 7. Example participant's gaze coordinates categorized into ROIs based on a) image bounding boxes and b) screen quadrants. Magenta points indicate looks that were not categorized into an ROI

Categorizing gaze location based on which of the four quadrants of the screen the coordinates fell in, increases the overall proportions of fixations (see Figure 8). In the




Figure 8. Timecourse of eye-gaze to target animal and target instrument by verb bias condition with gaze categorized based on which quadrant of the screen the coordinates fall in (as opposed to a bounding box around the image). Vertical lines indicate average onsets of animal and instrument offset by 200ms.

416 *post-instrument* window, participants looked more at the target animal in the
 417 modifier-biased condition and the equi-biased conditions relative to the instrument-biased
 418 condition ($b = 0.08$, $SE = 0.02$, $p < 0.01$) and marginally so in the modifier biased
 419 condition relative to the equi-biased condition ($b = 0.04$, $SE = 0.02$, $p = 0.05$). Effect size
 420 estimates appeared somewhat larger and noise was somewhat reduced when using the
 421 quadrant categorization relative to the bounding box-based ROIs.

Discussion

Experiment 5

The fifth study was a replication attempt of Shimojo, Simion, Shimojo, and Scheier (2003), which found that human gaze is actively involved in preference formation. Participants were shown pairs of human faces and were asked to choose the face which they found more attractive. Prior to making their explicit selection, participants spent more time looking at the face that was ultimately judged more attractive. This bias was not as large when the task was face shape discrimination rather than a preference-based choice.

Methods

All stimuli, experiment scripts, data, and analysis scripts are available on the Open Science Framework at <https://osf.io/eubsc/> (<https://osf.io/eubsc/>). The study pre-registration is available at <https://osf.io/tv57s> (<https://osf.io/tv57s>).

Participants. 27 participants were recruited on Prolific to participate in stimulus norming (for attractiveness). They were paid \$XX for completing the experiment. Data from 3 participants was excluded because their mode response made up more than 50% of their total responses, for a total of 24 participants in the norming.

50 participants for the main task were recruited on Prolific and were paid \$XX. 8 subjects, 4 from the attractiveness task group and 4 from the roundness task group, were excluded for incorrect validations. After this data exclusion, we ended up with 21 participants each for the attractiveness task and the roundness task. The original sample size in Shimojo et al. (2003) was 10 participants total.

Procedure and Design. At the beginning of the experimental task, participants completed a 9-point eye-tracker calibration (each point appeared 3 times in random order)

and 3-point validation. The validation point appeared once at center, middle left, and middle right locations in random order.

During each trial of the main task, two faces were displayed on the two halves of the screen, one on the left and one on the right (as in Figure XX). Participants were randomly assigned to one of two tasks: attractiveness or shape judgment. In the attractiveness task, participants were asked to choose the more attractive face in the pair and in the shape judgment task participants were asked to pick the face that appeared rounder. They pressed the “a” key on their keyboard to select the face on the left and the “d” key to select the face on the right. A fixation cross appeared in the center of the screen between each set of faces. Participants were asked to look at this fixation cross in order to reset their gaze in between trials (???). The order of the 19 face pairs was random for each participant.

Materials and Norming. The faces in our replication were selected from a set of 1,000 faces within the Flickr-Faces-HQ Dataset. (The face images used in Shimojo et al. were from the Ekman face database and the AR face database.) These images were chosen because the person in each image was looking at the camera with a fairly neutral facial expression and appeared to be over the age of 18. Participants in the norming study viewed 172 faces and were asked to rate them on a scale from 1 (less attractive) to 7 (more attractive) using a slider. Faces were presented one at a time and in a random order for each participant. Following Shimojo et al., 19 face pairs were made by matching two faces that had a difference in mean attractiveness ratings that was 0.25 points or lower and that matched in gender, race, and age group (young adult, adult, or older adult).

Data analysis. In the original study, a video-based eye tracker was used. The eye movements of participants were recorded with a digital camera, and eye position was then tracked using MediaAnalyzer software. This eye tracker was able to collect 30 samples per second. In our study, the camera on the device used by the participant and the jsPsych WebGazer package were used to determine where a participant’s gaze was directed. Since our eye tracking method did not have the same sample collection rate as the eye tracker in

Shimojo et al., time windows of 50 milliseconds were used when looking at the likelihood of gazing at the chosen face at a given point between a cutoff time and when the decision was made.

Results

Discussion

Combined Analyses

- Pooling data from all experiments we can look at patterns in the calibration and validation data

General Discussion

References

- Altmann, G. T. M., & Kamide, Y. (1999). Incremental interpretation at verbs: Restricting the domain of subsequent reference. *Cognition*, 73(3), 247–264. [https://doi.org/10.1016/S0010-0277\(99\)00059-1](https://doi.org/10.1016/S0010-0277(99)00059-1)
- Aust, F., & Barth, M. (2020). *papaja: Create APA manuscripts with R Markdown*. Retrieved from <https://github.com/crsh/papaja>
- Barth, M. (2022). *tinylabls: Lightweight variable labels*. Retrieved from <https://cran.r-project.org/package=tinylabls>
- Bates, D., Mächler, M., Bolker, B., & Walker, S. (2015). Fitting linear mixed-effects models using lme4. *Journal of Statistical Software*, 67(1), 1–48. <https://doi.org/10.18637/jss.v067.i01>
- Bates, D., & Maechler, M. (2021). *Matrix: Sparse and dense matrix classes and methods*. Retrieved from <https://CRAN.R-project.org/package=Matrix>
- Bolker, B., & Robinson, D. (2020). *Broom.mixed: Tidying methods for mixed models*. Retrieved from <https://CRAN.R-project.org/package=broom.mixed>
- Chang, W., Cheng, J., Allaire, J., Sievert, C., Schloerke, B., Xie, Y., ... Borges, B. (2021). *Shiny: Web application framework for r*. Retrieved from <https://CRAN.R-project.org/package=shiny>
- de Leeuw, J. R. (2015). jsPsych: A JavaScript library for creating behavioral experiments in a Web browser. *Behavior Research Methods*, 47(1), 1–12. <https://doi.org/10.3758/s13428-014-0458-y>
- Johansson, R., & Johansson, M. (2014). Look Here, Eye Movements Play a Functional Role in Memory Retrieval. *Psychological Science*, 25(1), 236–242. <https://doi.org/10.1177/0956797613498260>
- Kuznetsova, A., Brockhoff, P. B., & Christensen, R. H. B. (2017). lmerTest package: Tests in linear mixed effects models. *Journal of Statistical Software*, 82(13), 1–26. <https://doi.org/10.18637/jss.v082.i13>

- Manns, J. R., Stark, C. E. L., & Squire, L. R. (2000). The visual paired-comparison task as a measure of declarative memory. *Proceedings of the National Academy of Sciences*, 97(22), 12375–12379. <https://doi.org/10.1073/pnas.220398097>
- Ooms, J. (2014). The jsonlite package: A practical and consistent mapping between JSON data and r objects. *arXiv:1403.2805 [Stat.CO]*. Retrieved from <https://arxiv.org/abs/1403.2805>
- Papoutsaki, A., Sangkloy, P., Laskey, J., Daskalova, N., Huang, J., & Hays, J. (2016). WebGazer: Scalable webcam eye tracking using user interactions. In *Proceedings of the 25th international joint conference on artificial intelligence (IJCAI)* (pp. 3839–3845). AAAI.
- R Core Team. (2021). *R: A language and environment for statistical computing*. Vienna, Austria: R Foundation for Statistical Computing. Retrieved from <https://www.R-project.org/>
- Ryskin, R., Qi, Z., Duff, M. C., & Brown-Schmidt, S. (2017). Verb biases are shaped through lifelong learning. *Journal of Experimental Psychology: Learning, Memory, and Cognition*, 43(5), 781–794. <https://doi.org/10.1037/xlm0000341>
- Shimojo, S., Simion, C., Shimojo, E., & Scheier, C. (2003). Gaze bias both reflects and influences preference. *Nature Neuroscience*, 6(12), 1317–1322. <https://doi.org/10.1038/nn1150>
- Singmann, H., Bolker, B., Westfall, J., Aust, F., & Ben-Shachar, M. S. (2021). *Afex: Analysis of factorial experiments*. Retrieved from <https://CRAN.R-project.org/package=afex>
- Snedeker, J., & Trueswell, J. C. (2004). The developing constraints on parsing decisions: The role of lexical-biases and referential scenes in child and adult sentence processing. *Cognitive Psychology*, 49(3), 238–299. <https://doi.org/10.1016/j.cogpsych.2004.03.001>
- Spivey, M. J., & Geng, J. J. (2001). Oculomotor mechanisms activated by imagery

and memory: Eye movements to absent objects. *Psychological Research*, 65(4),
235–241. <https://doi.org/10.1007/s004260100059>

Tanenhaus, M. K., Spivey-Knowlton, M. J., Eberhard, K. M., & Sedivy, J. C.
(1995). Integration of visual and linguistic information in spoken language
comprehension. *Science*, 268(5217), 1632–1634.

Wickham, H. (2016). *ggplot2: Elegant graphics for data analysis*. Springer-Verlag
New York. Retrieved from <https://ggplot2.tidyverse.org>

Wickham, H. (2019). *Stringr: Simple, consistent wrappers for common string
operations*. Retrieved from <https://CRAN.R-project.org/package=stringr>

Wickham, H. (2021a). *Forcats: Tools for working with categorical variables
(factors)*. Retrieved from <https://CRAN.R-project.org/package=forcats>

Wickham, H. (2021b). *Tidyr: Tidy messy data*. Retrieved from
<https://CRAN.R-project.org/package=tidyr>

Wickham, H., François, R., Henry, L., & Müller, K. (2021). *Dplyr: A grammar of
data manipulation*. Retrieved from <https://CRAN.R-project.org/package=dplyr>

Wickham, H., & Hester, J. (2020). *Readr: Read rectangular text data*. Retrieved
from <https://CRAN.R-project.org/package=readr>