



Raven Scanner *Standard USB*

User Manual



Copyrights and Trademarks

Microsoft, Windows, Windows XP, Windows Vista, Windows 7, Windows 8, and Windows 10 are registered trademarks of Microsoft Corporation in the United States and/or other countries.

Other product names used herein are for identification purposes only and may be trademarks of their respective companies. We disclaim any and all rights to those marks.

Warranty

Hardware Warranty

Machine: The Raven Scanner ("Machine" or "Hardware"); Duration: 1 Year ("Warranty Period"); Warranty for Machines: Starfish Technologies, LLC dba Raven ("Manufacturer" or "Raven") warrants that each Machine is free from defects in materials and workmanship and conforms to the manufacturer's published specifications. The warranty period for each Machine is a specified, fixed period commencing on its date of purchase, as evidenced by your original or digital sales receipt; Extent of Warranty: In addition to the limitations and exclusions set forth in the "Disclaimer of Warranties" below, the warranty does not cover the repair or exchange of a Machine resulting from misuse, accident, modification, unsuitable physical or operating environment, improper maintenance or failure caused by a product for which the Manufacturer is not responsible or for cosmetic defects as long as such defects do not interfere with the functionality or performance of the Machine. The warranty is voided by removal or alteration of Machine parts or identification labels; Items not covered by the warranty: Owner computer operating system, application programs other than Raven software or hardware configurations; Return Policy: Machines can be returned within 30 days with proof of purchase (original or digital receipt) in its original packaging. After 30 days from the original date of purchase, a Machine cannot be returned. A Machine cannot be returned if it is damaged as a result of misuse, accident, modification, unsuitable physical or operating environment, improper maintenance or failure caused by a product for which the manufacturer is not responsible. The return policy is voided by removal or alteration of machine parts or identification labels.

Disclaimer of Warranties

YOU EXPRESSLY ACKNOWLEDGE AND AGREE THAT USE OF THE RAVEN SOFTWARE AND HARDWARE IS AT YOUR SOLE RISK AND THAT THE ENTIRE RISK AS TO SATISFACTORY QUALITY, PERFORMANCE, ACCURACY AND EFFORT IS WITH YOU. EXCEPT FOR THE LIMITED WARRANTY ON MEDIA AND HARDWARE SET FORTH ABOVE AND TO THE MAXIMUM EXTENT PERMITTED BY APPLICABLE LAW, THE RAVEN SOFTWARE AND HARDWARE ARE PROVIDED "AS IS", WITH ALL FAULTS AND

WITHOUT WARRANTY OF ANY KIND, AND RAVEN AND RAVEN'S LICENSORS HEREBY DISCLAIM ALL WARRANTIES AND CONDITIONS WITH RESPECT TO THE SOFTWARE AND HARDWARE, EITHER EXPRESS, IMPLIED OR STATUTORY, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES AND/OR CONDITIONS OF MERCHANTABILITY, OF SATISFACTORY QUALITY, OF FITNESS FOR A PARTICULAR PURPOSE, OF ACCURACY, OF QUIET ENJOYMENT, AND NON-INFRINGEMENT OF THIRD PARTY RIGHTS. RAVEN DOES NOT WARRANT AGAINST INTERFERENCE WITH YOUR ENJOYMENT OF THE RAVEN SOFTWARE AND HARDWARE, THAT THE FUNCTIONS CONTAINED IN THE RAVEN SOFTWARE AND HARDWARE WILL MEET YOUR REQUIREMENTS, THAT THE OPERATION OF THE RAVEN SOFTWARE AND HARDWARE WILL BE UNINTERRUPTED OR ERROR-FREE, OR THAT DEFECTS IN THE RAVEN SOFTWARE AND HARDWARE WILL BE CORRECTED. NO ORAL OR WRITTEN INFORMATION OR ADVICE GIVEN BY RAVEN OR A RAVEN AUTHORIZED REPRESENTATIVE SHALL CREATE A WARRANTY. AFTER THE END OF THE WARRANTY PERIOD, SHOULD THE RAVEN SOFTWARE AND HARDWARE PROVE DEFECTIVE, YOU ASSUME THE ENTIRE COST OF ALL NECESSARY SERVICING, REPAIR OR CORRECTION. SOME JURISDICTIONS DO NOT ALLOW THE EXCLUSION OF IMPLIED WARRANTIES OR LIMITATIONS ON APPLICABLE STATUTORY RIGHTS OF A CONSUMER, SO THE ABOVE EXCLUSION AND LIMITATIONS MAY NOT APPLY TO YOU.

RAVEN'S LIMITED WARRANTY DOES NOT APPLY TO A RAVEN PRODUCT THAT HAS BEEN SUBJECTED TO PHYSICAL DAMAGE AFTER PURCHASE, CAUSED, FOR EXAMPLE, BY CASUALTY, ACCIDENT, ACTS OF GOD OR TRANSPORTATION, INCLUDING (A) BY A FAILURE TO PROPERLY PACKAGE AND SHIP THE IMAGING PRODUCT BACK TO RAVEN FOR WARRANTY SERVICE IN ACCORDANCE WITH RAVEN'S THEN CURRENT PACKAGING AND SHIPPING GUIDELINES, INCLUDING FAILURE TO REPLACE THE SHIPPING RESTRAINT PRIOR TO SHIPPING, OR BY A FAILURE TO REMOVE THE SHIPPING RESTRAINT PRIOR TO USE; (B) RESULTING FROM THE USER'S INSTALLATION, SYSTEM INTEGRATION, PROGRAMMING, RE-INSTALLATION OF USER OPERATING SYSTEMS OR APPLICATIONS SOFTWARE, SYSTEMS ENGINEERING, RELOCATION, RECONSTRUCTION OF DATA, OR REMOVAL OF THE PRODUCT OR ANY COMPONENT (INCLUDING BREAKAGE OF A CONNECTOR, COVER, GLASS, PINS, OR SEAL); (C) FROM SERVICE, MODIFICATION OR REPAIR NOT PERFORMED BY RAVEN OR A SERVICE PROVIDER AUTHORIZED BY RAVEN OR BY TAMPERING, USE OF COUNTERFEIT OR OTHER NON-RAVEN COMPONENTS, ASSEMBLIES, ACCESSORIES, OR MODULES; (D) BY MISUSE, UNREASONABLE HANDLING OR MAINTENANCE, MISTREATMENT, OPERATOR ERROR, FAILURE TO PROVIDE PROPER SUPERVISION OR MAINTENANCE INCLUDING USE OF CLEANING PRODUCTS OR OTHER ACCESSORIES NOT APPROVED BY RAVEN OR USE IN CONTRAVENTION OF RECOMMENDED PROCEDURES OR SPECIFICATIONS; (E) BY ENVIRONMENTAL CONDITIONS (SUCH AS EXCESSIVE HEAT OR OTHER UNSUITABLE PHYSICAL OPERATING ENVIRONMENT), CORROSION, STAINING, ELECTRICAL WORK EXTERNAL TO THE PRODUCT OR FAILURE TO PROVIDE ELECTRO-STATIC DISCHARGE (ESD) PROTECTION; (F) BY FAILURE TO INSTALL FIRMWARE UPDATES OR RELEASES AVAILABLE FOR THE PRODUCT AND (G)

BY SUCH OTHER SUPPLEMENTAL EXCLUSIONS PUBLISHED FROM TIME TO TIME ONLINE AT [HTTPS://WWW.RAVEN.COM/WARRANTY](https://www.raven.com/warranty).

PURCHASERS OF PRODUCTS FROM FOREIGN DISTRIBUTION CHANNELS MUST SEEK WARRANTY COVERAGE, IF ANY, THROUGH THE ORIGINAL SOURCE OF PURCHASE. RAVEN PROVIDES NO LIMITED WARRANTY FOR PRODUCTS THAT ARE PURCHASED AS PART OF A THIRD PARTY MANUFACTURER'S PRODUCT, COMPUTER SYSTEM OR OTHER ELECTRONIC DEVICE. ANY WARRANTY FOR THESE PRODUCTS IS PROVIDED BY THE OEM (ORIGINAL EQUIPMENT MANUFACTURER) AS PART OF THAT MANUFACTURER'S PRODUCT OR SYSTEM. THE REPLACEMENT PRODUCT ASSUMES THE REMAINDER OF THE LIMITED WARRANTY PERIOD APPLICABLE TO THE DEFECTIVE PRODUCT OR THIRTY (30) DAYS, WHICHEVER IS LONGER.

If any provision of this Limited Warranty is legally invalid, the warranty shall endure except for the invalid provision. This Limited Warranty constitutes the entire agreement between the parties with respect to the use of the Machine.

IN NO EVENT WILL MANUFACTURER BE LIABLE FOR ANY LOST REVENUE, PROFIT, DATA OR FOR SPECIAL, CONSEQUENTIAL, INDIRECT, INCIDENTAL OR PUNITIVE DAMAGES HOWEVER CAUSED AND REGARDLESS OF THE THEORY OF LIABILITY ARISING OUT OF THE USE OR INABILITY TO USE THE MACHINES EVEN IF MANUFACTURER HAS BEEN ADVISED OF THE POSSIBILITY OF SUCH DAMAGES. IN NO EVENT WILL MANUFACTURER'S LIABILITY, WHETHER IN CONTRACT, TORT OR OTHERWISE, EXCEED THE PRICE PAID BY CUSTOMER.

The laws of your country or state may require a warranty term longer than one (1) year, in which case the Manufacturer will provide the minimum warranty term required by applicable law.

HOW TO OBTAIN LIMITED WARRANTY SERVICE

Raven Scanners are supplied with information on unpacking, setup, installation and operation. Careful reading of the materials will answer most of the questions the end user might have regarding proper installation, operation and maintenance of the product. However, should additional technical support be required, you may visit our website at: <https://www.raven.com/faq> or contact: 1-800-713-9009

In order to properly service you, please be prepared to describe your issue and provide the Raven account email address, scanner model, serial number and proof of purchase.

For more Raven Scanner information, visit our website at: <https://www.raven.com/>

Safety Information

When using this machine, the following safety precautions should always be followed.

Safety During Operation

In this manual, the following important symbols are used:

- **WARNING:**

Indicates potentially hazardous situations, which if instructions are not followed, could result in death or serious injury.

- **CAUTION:**

Indicates a potentially hazardous situation which, if instructions are not followed, may result in minor or moderate injury or damage to property.

Important:

Indicates operational requirements and restrictions. Please read and follow these instructions to ensure a proper operation and to avoid damage to the hardware.

Note:

Indicates further explanation or clarification. Reading this is highly recommended.

- **WARNING:**

To avoid hazardous electric shock or fire, do not remove any covers or screws other than those specified in this manual.

- **CAUTION:**

- ✓ To reduce the risk of fire, use only no.26AWG or larger telecommunication line cord.
- ✓ Disconnect the power plug by pulling the plug, not the cable.
- ✓ Do not touch the metal fingers of the ADF pad module. The edges are sharp and touching them may result in injury.

Precautions

- Do not install the hardware near heating or air conditioning units.
- Do not install the hardware in a humid or dusty place.
- Place the hardware securely on an even, flat surface. Tilted or uneven surfaces may cause mechanical or paper-feeding problems.
- Retain the box and packing materials for shipping purposes.

Federal Communications Commission (FCC) compliance information statement

Part 15

This hardware has been tested and found to comply with the limits for a Class B digital device, pursuant to Part 15 of the FCC Rules. These limits are designed to provide reasonable protection against harmful interference in a residential installation. This hardware generates, uses and can radiate radio frequency energy and, if not installed and used in accordance with the instructions, may cause harmful interference to radio communications. However, there is no guarantee that interference will not occur in a particular installation. If this hardware does cause harmful interference to radio or television reception, which can be determined by turning the hardware off and on. The user is encouraged to try to correct the interference by one of the following measures:

- Reorient or relocate the receiving antenna.
- Increase the separation between the hardware and receiver.
- Connect the hardware into an outlet on a circuit different from that to which the receiver is connected.
- Consult the dealer or an experienced radio/TV technician for help.

This device complies with Part 15 of the FCC Rules. Operation is subject to the following

two conditions: (1) This device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation.

FCC Caution:

Any changes or modifications not expressly approved by the party responsible for compliance could void the user's authority to operate this hardware.

This device is intended only for OEM integrators under the following conditions:

- 1) The antenna must be installed such that 20 cm is maintained between the antenna and users.
- 2) The transmitter module may not be co-located with any other transmitter or antenna.

FCC Radiation Exposure Statement:

This hardware complies with FCC radiation exposure limits set forth for an uncontrolled environment. This hardware should be installed and operated with minimum distance 20cm between the radiator & your body. To maintain compliance with FCC RF exposure compliance requirements, please avoid direct contact to the transmitting antenna during transmitting.

"Contains FCC ID: YAI2213"

Product Safety Guide

Please clearly read all these instructions and follow all instructions and warnings before installing and using the device.

The following indications are used in this document to obviate any chance of accident or damage to you and/or the device.

● WARNING	Indicates potentially hazardous situations, which if instructions are not followed, could result in death or serious injury.
● CAUTION	Indicates a potentially hazardous situation which, if instructions are not followed, may result in minor or moderate injury or damage to property.

- **WARNING**
 - Use only the AC power adapter that came with your device. Using any other AC power adapter could cause fire, electrical shock, or injury.
 - Use only the AC power cord and USB cable that came with your device and avoid abrasions, cuts, fraying, crimping, and kinking. Using any other AC power cord and USB cable could cause fire, electrical shock, or injury.
 - Do not place objects on top of the AC power cord, and do not allow the AC power adapter or the AC power cord to be stepped on or run over.
 - Place the device and its AC power adapter near an electrical outlet where the AC power adapter can easily be unplugged.
 - If you use an extension cord with the device, make sure that the total ampere rating of the devices plugged into the extension cord does not exceed the cord's ampere rating.
 - Place the device close enough to the computer so that the interface cable can easily reach between the device and the computer.
 - Do not place or store the device or its AC power adapter:
 - Outdoors
 - Near excessive dirt or dust, water, or heat sources
 - In locations subject to shocks, vibrations, high temperature or humidity, direct sunlight, strong light sources, or rapid changes in temperature or humidity
 - Do not use the device with wet hands.
 - Never disassemble, modify, or attempt to repair the AC power adapter, device, or device option by yourself, except as specifically explained in the device's documentation. This could cause fire, electrical shock, or injury.
 - Do not insert objects into any opening, as they may touch dangerous voltage points or short-out components. Beware of electrical shock hazards.

- Unplug the device and the AC power adapter, and refer servicing to qualified service personnel under the following conditions:
 - The AC power adapter or plug is damaged.
 - Liquid has entered the device or the AC power adapter.
 - Object has entered the device or the AC power adapter.
 - The device or the AC power adapter has been dropped, or the case has been damaged.
 - The device or the AC power adapter does not operate normally (i.e. appearance of smoke, strange smell, odd noise, etc.), or exhibits a distinct change in performance
- Unplug the device and the AC power adapter before cleaning.
- **CAUTION**
 - Do not locate the device on rickety or aslope tables. Do not locate the device on unstable surface. The device may fall down and this may result in injury.
 - Do not place heavy objects on the unit. It may cause unbalance and the device may fall down. This may result in injury.
 - Store the AC Power cord/USB cable bundled out of the reach of children to avoid the risk of injury.
 - Keep plastic bags bundled out of the reach of children to avoid the danger of suffocation.
 - If you are not going to use the device for a long period, unplug the AC power adapter from the electrical outlet.

Disposal of Waste Equipment by Users in Private Union




This symbol on the product or on its packaging indicates that the product cannot be disposed of with your other household waste. Instead it should be sent to appropriate facilities for recovery and recycling in an effort to protect human health and the environment. For more information about where you can drop off your waste equipment for recycling, please contact your local city office, your household waste disposal service or the shop where you purchased the product.

Getting Started


Introduction

Thank you for purchasing the Raven Standard Document Scanner. With the Raven Scanner, you can instantly scan single-sided or double-sided document(s) and deliver the electronic images to various destinations including your desktop, e-mail addresses, fax, and cloud services such as Raven Cloud, Dropbox, Google Drive or Evernote.


Package Items




Raven Standard Scanner



USB Cable



Power Cord




Quick Guide

Note:


1. Only use the AC adapter included in the machine. Using other AC adapters may damage the machine and void the warranty.
2. Please unpack the packing carefully, and check the contents against the checklist. If any items are missing or damaged, please contact us immediately by emailing support@raven.com or calling +1-800-713-9009.


Front View



Part Name	Function
Paper Guide	Slides to paper edges to keep paper in place.
ADF Paper Tray	Keeps paper in place while scanning. Extend for longer pages.
Cancel / Home Button	Cancels scan from the scanner and returns to home screen.
Scan Button	Starts scan from Raven Scanner Standard.
Power Button	Press and hold to turn the power on or off.
Output Tray	Open to collect the document after scanning.
Extension	Extend to hold documents ejected from the ADF to the tray.
Screen with Up/Down Buttons	Sort through different workflows to select for scanning.

Control Panel



Part Name	Function
	- Displays the scanning and error status. - Displays the list of workflows available.
	- Used to scroll up and down to view available workflows in Raven Desktop. - Used to select an item.
	- Press to start a scan. - Press to confirm a selection.
	- Short press to cancel a scanning job during scanning. - Short press to go back to the previous screen. - Long press to return to the home screen.
	- Short press to turn on the power. - Long press to turn off the power.
	USB icon will appear when there is a successful USB connection between the computer and scanner
	Refresh icon can be selected to refresh connection status
	Settings icon can be selected to view settings and scanner information

Rear View




Part Name	Function
USB Port	Connects the scanner via USB to your computer.
Power Connector	Connect the AC adapter to the scanner.

Removable Parts



Friction Roller



ADF Roller


Setting Up Your Scanner

1 Precautions


- Keep the scanner out of direct sunlight. Direct exposure to the sun or excessive heat may cause damage to the unit.
- Do not install the scanner in a humid or dusty place.
- Be sure to use the proper AC power source.
- Place the scanner securely on an even, flat surface. Tilted or uneven surfaces may cause mechanical or paper-feeding problems.
- Retain the scanner box and packing materials for shipping purposes.

2 Connect to Power

2.1 Connect one end of the power cable to the power receptacle of the scanner. Connect the other end to an appropriate power outlet.



2.2 Press the Power Switch button on the front panel, the Power LED will flash. When it is finished and ready to scan, the LED indicator will stop flashing and become steadily on. To turn off the scanner, press the Power Switch button for about 3 seconds, the Power LED will be off.




3 Install Raven Desktop

- 3.1 Visit Raven.com/Desktop to download the latest version of Raven Desktop.
- 3.2 Complete the download and installation of Raven Desktop on your computer.
- 3.3 Sign up for a free Raven account, or log in with existing Raven account credentials.

4 Connecting to Computer

- 4.1 Connect the **square end** of the USB cable to the USB port of your scanner. Connect the **rectangle end** to the USB port at the rear side of your computer.

Note: The scanner is designed with a USB 3.2 Gen 1x1 interface to ensure the optimal speed. If your computer comes with a USB 3.2 Gen 1x1 port, make sure to connect the scanner to your computer to the USB 3.2 Gen 1x1 port which is distinguished in blue color at the back of your computer. The USB 3.2 Gen 1x1 port enhances your scanning speed and is also compatible with USB 2.0 and USB 1.1.



- 4.2 The computer should detect a new USB device and prompt a “New Hardware Found” message.

- 4.3 Open Raven Desktop and click to Connect a new scanner, then choose Raven Standard and the USB connection method to proceed through the steps to finishing installing drivers and connecting the scanner to your computer. Be sure the scanner is powered on and connected to the computer by USB cable.

Scanning with Raven Desktop

1 Ensure that the scanner shows as Connected in the bottom left corner of Raven Desktop

- If the scanner is not connected, click “Connect Scanner” to reconnect or reinstall drivers

2 Configure Workflows and Scan Settings

2.1 A default workflow is available and can be customized by adjusting the scan settings and destination selections on the right and then clicking “Save Default Settings”.

2.2 Additional custom workflows can be created by clicking the  icon next to Workflows, then naming your workflow and saving with your custom settings. Workflows can be dragged to be reorganized and reordered on the left view.

2.3 To choose local folders on your computer or desktop, click  and then  Folder

3 Scanning

3.1 Select your desired workflow, then press the SCAN button on the bottom right. Workflows can also be selected on the scanner screen and started using the scan button on the scanner when Raven Desktop is open and connected.

3.2 Make any desired changes by double clicking the preview pages, or using the buttons on the preview page.

3.3 Click SEND to send the document to the chosen destinations.

3.4 A final status for each cloud destination will be displayed, but can be viewed for 30 days by clicking “HISTORY” on the top navigation.

Adjusting Scanner Settings

Item	Description
Sides	Auto-detect: Automatically scan both sides and remove any blank pages without content. One-sided (Face Down): Choose to scan a single side of your document with the first page facing down against the feeder. Two-sided (Face Down): If you have a double-sided document, choose to scan both sides of your document with the first page facing down against the feeder.
Size	Auto: Scanner will auto detect page size and crop to the edges of the document (max page size of 8.5 in. x 14 in.) Letter: Fixed letter page size of 8.5 in x 11 in Legal: Fixed legal page size of 8.5 in x 14 in Extra Long: Allows scanning long documents up to 40" in length (e.g. receipts). Note: limited to one-sided, 200dpi
Quality	Excellent: Choose to scan at 600dpi (much slower scanning) Great: Choose to scan at 400 dpi (slower scanning) Better: Choose to scan at 300 dpi (slower scanning) Good: Choose to scan at 200dpi (good for most documents)
Color	Color: The original is scanned in full color. This mode is best for full color originals such as pictures. Black & White: Colors in the original are scanned as black or white. This mode is best for text-only originals. Grayscale: The colors in the original are scanned in black and white as shades of gray (grayscale). Most common setting.
Document Name	Enter a custom file name for the document or click the pencil icon to adjust the default document name.
File Type	PDF or JPEG
Save File As	Separated: Choose to scan each page as its own digital document. Combined: Choose to scan all document pages as a single digital document.
Destinations	Choose one or more destinations where your scanned documents should be sent. Raven Cloud: Scan to your Raven Cloud document management account for searchable filing & organization. Google Drive: Scan to your Google Drive account (login required). SharePoint: Scan to your SharePoint account (login required) OneDrive: Scan to your OneDrive account (login required) Dropbox: Scan to your Dropbox account (login required). Evernote: Scan to your Evernote account (login required).

	Box: Scan to your Box account (login required). Quickbooks Online: Scan your Quickbooks Online account attachments (login required). Email: Scan to one or more email addresses. USB Drive: Scan to a USB flash drive attached to the side of the scanner. Folder: Click Manage and then add local folders on your computer to view as destination options.
Blank Page Removal	On: Scanned pages that do not contain content (blank) will be automatically removed from the final document. Off: Scanned pages that do not contain content (blank) will be retained as pages in your final document.
AI Cloud OCR	On: documents will have optical character recognition (OCR) applied to the PDF documents generated, making them fully searchable (internet required) Off: no optical character recognition (OCR) will be applied
Scan Brightness	Adjust the brightness of all scans. Note that adjusting the brightness too much could result in white or black pages.
Scan Contrast	Adjust the contrast of all scans. Note that adjusting the contrast too much could result in poor image quality.
File Compression	High: high compression, smallest file size Medium: medium compression, medium file size (recommended) Low: low compression, large file size None: no compression applied

Operation

Document Loading Tips


Before using the ADF (Auto Document Feeder), please make sure that your paper meets the following specifications:

- Document(s) can range in size from 74 x 52 mm (2.9 x 2 in.) (A8) to 216 x 356 mm (8.5 x 14 in.) (Legal).
- Document(s) can range in weight from 12 to 110 lbs (50 ~ 413 g/m2)
- ID cards up to 1.25 mm (0.05 in.) thick
- Plastic cards compliant with the ISO7810 ID-1 type
- Document(s) should be square or rectangular and in good condition (not fragile or worn).
- Document(s) should be free of curl, wrinkle, tears, wet ink, or punch holes.
- Document(s) should be free of staples, paper clips, paper sticky notes.


Loading Document(s) in the ADF Paper Tray

Document Feeding

1. Unfold the document feeder and its extension.
2. Unfold the output tray and raise the paper stopper.



3. Raise the paper guide and slide to the edge of your documents to hold your multi-page document.



4. Load the stack of documents **face down** with the top of the pages pointing into the feeder.



5. Verify that the paper guides are aligned with the edges of the stack by sliding the paper feed guides in the automatic feeder tray.

Feeding Tips

To avoid occasional multi-feeds or paper jams, please fan your documents and align the top edges before feeding them into the scanner.


1. Hold both ends of the documents and fan them a few times.
2. Rotate the documents by 90 degrees and fan them in the same manner.
3. Align the edges of the documents in a step-like pattern (see picture).




Scanning a Stack of Document with Various Sizes and Weights

When scanning a batch of documents with different sizes and weights, be sure to follow the following guidelines to avoid a skewed image or a paper jam:


1. Align the documents TOP EDGE first in the sequence of paper size from large to small.




2. If two pages are of the same size yet with different weight, arrange these pages in the sequence of paper weight from heavyweight to lightweight.



3. Align the edges of the documents by tapping the bottom of the stack against the table top.



4. Center these pages in the document feeder and make sure that the edges of page of the largest size slightly touch the Paper Guide.



Scanning and Sending Your Document to Raven Cloud

1. Load the stack of documents with the top of the pages pointing into the feeder.
2. Verify that the paper guides are aligned with the edges of the stack by sliding the paper feed guides in the automatic feeder tray.
3. Select "Raven Cloud" as a Destination in your desired Raven Desktop workflow.
4. Click "SCAN".
5. Preview thumbnails of the scanned pages and make any necessary edits.

Scanning Your Document to E-mail Addresses

1. Load the stack of documents with the top of the pages pointing into the feeder.
2. Verify that the paper guides are aligned with the edges of the stack by sliding the paper feed guides in the automatic feeder tray.
3. Select "Email" as a Destination in your desired Raven Desktop workflow.
4. Enter email address or addresses to receive the scan, or select from saved contacts in the drop down menu.
5. Click "SCAN".
6. Preview thumbnails of the scanned pages and make any necessary edits.

Scanning Your Document to USB Flash Drives

1. Insert a USB Flash Drive or External USB Hard Drive into the USB port on the left side of the scanner. Note: the USB drive must be formatted to FAT32 format.
2. Load the stack of documents with the top of the pages pointing into the feeder.
3. Verify that the paper guides are aligned with the edges of the stack by sliding the paper feed guides in the automatic feeder tray.
4. Select "USB" as a Destination in your desired Raven Desktop workflow.
5. Click "SCAN".
6. Preview thumbnails of the scanned pages and make any necessary edits.

Scanning Your Document to Google Drive

1. Connect your Google Drive account within your account settings by visiting <https://app.raven.com/connect>
2. Load the stack of documents with the top of the pages pointing into the feeder.
3. Verify that the paper guides are aligned with the edges of the stack by sliding the paper feed guides in the automatic feeder tray.
4. Select "Google Drive" as a Destination in your desired Raven Desktop workflow.
5. Click "SCAN".
6. Preview thumbnails of the scanned pages and make any necessary edits.

Scanning Your Document to SharePoint

1. Connect your SharePoint account within your account settings by visiting <https://app.raven.com/connect>
2. Load the stack of documents with the top of the pages pointing into the feeder.
3. Verify that the paper guides are aligned with the edges of the stack by sliding the paper feed guides in the automatic feeder tray.
4. Select "SharePoint" as a Destination in your desired Raven Desktop workflow.
5. Click "SCAN".
6. Preview thumbnails of the scanned pages and make any necessary edits.

Scanning Your Document to OneDrive

1. Connect your OneDrive account within your account settings by visiting <https://app.raven.com/connect>
2. Load the stack of documents with the top of the pages pointing into the feeder.
3. Verify that the paper guides are aligned with the edges of the stack by sliding the paper feed guides in the automatic feeder tray.
4. Select "OneDrive" as a Destination in your desired Raven Desktop workflow.
5. Click "SCAN".
6. Preview thumbnails of the scanned pages and make any necessary edits.

Scanning Your Document to Dropbox

1. Connect your Dropbox account within your account settings by visiting <https://app.raven.com/connect>
2. Load the stack of documents with the top of the pages pointing into the feeder.
3. Verify that the paper guides are aligned with the edges of the stack by sliding the paper feed guides in the automatic feeder tray.
4. Select "Dropbox" as a Destination in your desired Raven Desktop workflow.
5. Click "SCAN".
6. Preview thumbnails of the scanned pages and make any necessary edits.

Scanning Your Document to Box

1. Connect your Box account within your account settings by visiting <https://app.raven.com/connect>
2. Load the stack of documents with the top of the pages pointing into the feeder.
3. Verify that the paper guides are aligned with the edges of the stack by sliding the paper feed guides in the automatic feeder tray.
4. Select "Box" as a Destination in your desired Raven Desktop workflow.
5. Click "SCAN".
6. Preview thumbnails of the scanned pages and make any necessary edits.

Scanning Your Document to Evernote

1. Connect your Evernote account within your account settings by visiting <https://app.raven.com/connect>
2. Load the stack of documents with the top of the pages pointing into the feeder.
3. Verify that the paper guides are aligned with the edges of the stack by sliding the paper feed guides in the automatic feeder tray.
4. Select "Evernote" as a Destination in your desired Raven Desktop workflow.
5. Click "SCAN".
6. Preview thumbnails of the scanned pages and make any necessary edits.

Scanning Your Document to Quickbooks Online Attachments

1. Connect your Quickbooks Online account within your account settings by visiting <https://app.raven.com/connect>
2. Load the stack of documents with the top of the pages pointing into the feeder.
3. Verify that the paper guides are aligned with the edges of the stack by sliding the paper feed guides in the automatic feeder tray.
4. Select "Quickbooks Online" as a Destination in your desired Raven Desktop workflow.
5. Click "SCAN".
6. Preview thumbnails of the scanned pages and make any necessary edits.
7. Locate your documents in Quickbooks Online as PDF attachments to be used with invoice or expense transactions

Scanning and Sending to Multiple Destinations

1. Load the stack of documents with the top of the pages pointing into the feeder.
2. Verify that the paper guides are aligned with the edges of the stack by sliding the paper feed guides in the automatic feeder tray.
3. Select the "Destination" option on the home screen and choose your destinations by tapping the destination rows individually until you have selected all destinations where you would like to send your document, then choose "Save".

Saving Contacts

1. Click "CONTACTS" on the top navigation menu
2. Select "Add Contact"
3. Input the contact name
4. Input the contact email address and/or fax number
5. Select "Save"

Using As A TWAIN Scanner With a Third Party Application


To use your Raven Standard Scanner with 3rd party applications, you must first install Raven Desktop onto your computer and complete the driver installation. After installation of Raven Desktop is completed and you have connected to your scanner, you can close Raven Desktop and the Raven Standard should be available for use with other applications that are TWAIN compatible.

Troubleshooting

Clearing Paper Jams

In the event of a paper jam, follow the procedures below to remove the paper:

1. Press the ADF release button on the right side.
2. Gently open the front door.
3. Carefully pull the paper out of the ADF unit.
4. Close the front door. Your Scanner is now ready to use.



Error Conditions

If there is error during scanning, the LED light will be flashing in red color and error drawing will be displayed. Refer to the following table to clear the error conditions.

Error Drawing / Meaning	Cause	Solution
Paperjam 	1. Original has become stuck in the feeder. 2. Original exceeds max. length.	Open the feeder cover and pull the original out of the feeder.
Cover Open 	Feeder cover is open.	Close the feeder cover.
Multi-Feed 	More than one piece of paper fed into the feeder.	1. Remove the paper. 2. Fan the paper for several times. 3. Make sure the edge of paper near the paper guide and try again.

Miss Feed 	Failed to pick up paper.	1. Fan the documents. 2. Load the document with its edges slightly touch the paper guides.
No USB Cable Connection 	No USB cable connection.	Connect scanner to the computer with a USB cable.
Firmware Download Fail 	Firmware installation failed.	Download the firmware and try again.

Questions and Answers

Question:	Paper becomes jammed during scanning.
Answer:	1. Open the front door. 2. Pull out the jammed paper carefully. 3. Close the front door
Question:	More than one sheet of paper are fed into the scanner.
Answer:	1. Open the scanner front door. 2. Remove the multi-fed sheets. 3. Close the front door. 4. Flatten the corners and edges. Loosen the paper before putting it into the paper guide again. 5. Check the feeding roller condition. If necessary, follow the cleaning directions and perform the cleaning.
Question:	Paper becomes skewed in the scanner.
Answer:	1. Use the slide guide to keep the paper path straight. 2. Check the condition of the feeding roller. If necessary, follow the cleaning directions and perform the cleaning.
Question:	Receipts are not being detected as fed into the scanner.
Answer:	1. Slide the feeder paper guides to the edge of the receipt or smallest position. 2. Align the receipt to the right edge of the feeder paper guides. 3. Ensure the receipt is down into the ADF before scanning.

Maintenance

Your scanner is designed to be maintenance-free. However, constant care and maintenance can keep your scanner working smoothly.


Cleaning the ADF

After using the scanner for a long period of time, the rollers and glass inside the scanner may become contaminated with ink, toner particles or paper dust. It is necessary to perform routine cleaning to ensure the optimum image quality and performance. As a guideline, please clean the rollers and glass after first 4,000 to 5,000 scans and then perform the cleaning on a weekly basis. Note that the guideline varies according to the type of documents you are scanning.

Tip! If documents do not feed easily, if several documents feed at the same time or if streaks appear on the scanned images, it is time to clean your scanner.

Cleaning Procedures


1. Soak a clean cloth with some isopropyl alcohol (95%).
2. Open the front door slightly to the left. Wipe the feeding rollers until the surfaces are cleaned.



3. Close the scanner front cover. Your scanner is now ready for use.

Cleaning The Glass

1. Press the ADF Release button. Open the front door to the left.
2. Wet a clean cloth with some isopropyl alcohol. (95%). Do not spray the glass cleaner directly on the glass. If too much glass cleaner is applied, the cleaner could leak under the glass and damage the scanner.
3. Wipe the glass and the white area as illustrated in below to rid the dust or dirt.




Replacing the ADF Reverse Roller


After scanning approximately 100,000 pages through the ADF, the ADF Reverse Roller may be worn out and you may experience problems with document feeding. In this case, you may need to replace a new ADF reverse roller. For ordering the ADF roller, please visit <https://www.raven.com/accessories>, email Raven support at support@raven.com or call 1-800-713-9009 to order a replacement.

Disassembling Procedure

1. Press the ADF Release button.
2. Gently open the ADF Front Cover to the left.
3. Hold the mylar assembly with your fingers and then lift it up as illustrated below




4. Locate the white wheel to the right, and gently pull the roller at an angle towards




5. Press the right end of the Friction Roller externally to detach it from the slot and then detach the left end from its hole.

Reassembling Procedure


1. Insert the left end of the Friction Roller to the hole of its original place. Make sure the flat side is up as shown.



2. Insert the right end of the Friction Roller to its slot.



3. Press down the mylar assembly.



4. Close the ADF Front Cover.

Note:


- Consumables must be replaced regularly. It is recommended to purchase new consumables in advance so that they can be replaced before the end of their life.
- The replacement cycle is based on the use of A4 (80 g/m2 [20 lb]) wood-free paper or plain paper. The actual cycle varies according to the type of used paper and how frequently the scanner is used and cleaned.
- Use only the specified consumables.
- Visit <https://www.raven.com/accessories>, email Raven support at support@raven.com or call 1-800-713-9009 to order any consumables.

Replacing the ADF Roller

After scanning approximately 200,000 pages through the ADF, the ADF rollers may be worn out and you may experience problems with document feeding. In this case, you may need to replace a new ADF roller. For ordering the ADF roller, please email Raven support at support@raven.com or call 1-800-713-9009 to order a replacement.


Disassembling Procedure

1. Gently open the ADF Front Door.
2. Use both hands to pull the roller cover to open it.




- 3.

4. Move the tab of the ADF roller UP as indicated.




5. Detach the right end of the ADF roller from the scanner and remove the ADF roller.



Reassembling Procedure

1. Insert the left end of the ADF roller first to its slot and place the ADF roller to its proper position.
2. Move the tab of the ADF roller DOWN.



3. Close the ADF roller cover. A snap-in sound could be heard if correctly installed

Specifications

Description	Raven Scanner Select Standard
Scanner Type	ADF (Automatic Document Feeder), Duplex scanning
Multifeed Detection	Ultrasonic Sensor
Image Sensor Technology	Color Contact Image Sensor (CIS) x 2 (front x 1, back x 1)
Light Source	LED
Optical Resolution (dpi)	600
Document Feeder Capacity	Maximum 50 sheets (413 g/m ² or 110 lb)
Document Feeder Paper Sizes	Maximum : 8.5 x 40 in. Minimum : 2.9 x 2 in.
Daily Scanning Capability	8,000 sheets
Scanning Modes	Color, Grayscale, Monochrome (Black & White)
Long Page Scanning Capability	Up to 200 dpi Color Duplex 236 in. Up to 300 dpi Color Duplex 218 in. Up to 600 dpi Color Duplex 59 in.
ID Card Scanning	Minimum Size : 2 x 2 in., Maximum Thickness : 1.25 mm
Scanning Speed	Simplex : 40 ppm b&w/grayscale, 40 ppm color Duplex : 40 ppm b&w/grayscale, 40 ppm color
Scanner Size	11.1 x 6 x 6.5 in.
Scanner Weight	5.51 lb.
USB Computer Port*	USB3.2 Gen1x1
Power Requirement	100-240V ~ 50-60Hz, 1.2A Max
Power Source	24Vdc, 2.0A
Power Consumption	Operation < 17 W, Ready < 6 W, Sleep < 1.9 W, Off < 0.2 W
Environmental Compliance	ENERGY STAR®
Operating Environment	Temperature (50°F~95°F), Humidity (10%~85% RH)
Driver	TWAIN for Win XP / Vista / Win 7 / Win 8 / Win 10 / Mac OS

Included Items: Raven Scanner Select Standard, AC Cable, AC Adaptor, USB Cable, Quick Guide
For more Raven Scanner information, visit our website at: <https://www.raven.com/>

Safety Precautions 	Be sure to carefully read all safety precautions prior to using this product and use this device as instructed.	Do not place this device in wet, moist, steamy, dusty or oily areas. Using this product under such conditions may result in electrical shock, fire or damage to this product.
--	---	---

Specifications are subject to change without notice.

Technical Support

Raven
11150 S Wilcrest Drive
Suite 200
Houston, Texas 77099

1-800-713-9009

support@raven.com

www.Raven.com