

HIGH-LEVEL PROGRAMMING 2

Scoped Enumerations

by Prasanna Ghali

Summary of C Enumerations

2

- Quite often, you might want to assign integer codes to different items in your program, e.g.,

```
int month; // Jan = 1, Feb = 2, ...  
month = 5; // May
```

- Someone reading your program that does not know your integer code will be confused, e.g.,

```
int team; // Ferrari = 1,  
          // McLaren = 2, ...  
team = 6; // What does this mean?
```

- C enumeration types do this in a better way

Declaring C Enumerations

3

In enumeration declaration, identifiers or *enumerators* are given for each possible value that enumeration type can contain

Enumeration specifies set of *integer* values of type `int`. Enumeration declarations have similar syntax to structure, only difference is use of keyword `enum`.

②
①
`enum Team {
 FERRARI, MCLAREN,
 BMW, WILLIAMS,
 RENAULT, TOYOTA
};`

`my_team` is variable of type `enum Team` and is initialized with value BMW
③

`enum Team my_team = BMW;`

Values of Enumerators (1 / 3)

4

- By default, enumerators are assigned values 0, 1, 2, ... in order

```
enum Suit {SPADE, HEART, CLUB, DIAMOND};
```

0

1

2

3

Values of Enumerators (2/3)

5

- Enumerators can be explicitly specified values:

```
enum Suit {  
    SPADE = 4, HEART = 3,  
    CLUB = 2, DIAMOND = 1  
};
```

Values of Enumerators (3/3)

6

- Unspecified values are assigned value of previous member plus one

If 1st enumerator value is unspecified, by default, it has value of zero

```
enum Suit {  
    SPADE, HEART = 8,  
    CLUB = 2, DIAMOND  
};
```

DIAMOND has value 3 – the value of previous member SPADE plus one

Enumerations: Use Cases (1 / 3)

7

- Since enumerators are **ints**, you can use **enum** variable anywhere an **int** is legal:

```
enum Fish { trout, bass, carp, salmon };

enum Fish myfish = bass;
if (myfish == trout)
    grill_fish(myfish);
else
    bake_fish(myfish);
```

Enumerations: Use Cases (2/3)

8

- Since enumerators are **ints**, you can use **enum** variable anywhere an **int** is legal:

```
enum Suit {SPADE, HEART, CLUB, DIAMOND};

void fs(enum Suit);
void fi(int);

enum Suit s = CLUB;

int i = DIAMOND; // i is 3
s = SPADE;       // s is 0 (SPADE)
s++;             // s is 1 (HEART)
i += s;          // i is 4
fi(s);           // argument is 1
fs(2);           // argument is DIAMOND
```


Enumerations: Use Cases (3/3)

9

Enumerators are compile-time constants and therefore can be used to define array sizes.

This is preferable to preprocessor macros!!!

```
// not preferred  
#define ARRAYSIZE 10  
int arr[ARRAYSIZE];
```

```
// preferred!!!  
enum {ARRAYSIZE = 15};  
int arr[ARRAYSIZE];
```

Unnamed Enumerations

10

Unnamed **enum** is used when all we need is set of integer constants, rather than a type for defining integer variables

enum declaration
need not have
enumeration tag

②
①
enum {trout = 2, bass = 5,
carp = 10, salmon = 15};

```
int myfish = carp;  
if (myfish == trout)  
    grill_fish(myfish);  
else  
    bake_fish(myfish);
```

Summary of C Enumerations

11

- Enumeration can be used to give identifiers to integer codes
- Enumeration type variable is `int` and can be used in similar ways
- Type qualifier `const` and `enum` type can satisfy all symbolic constant operations for which `#define` might be used

C++ Plain Enumerations

12

- Similar to C enumerations with some exceptions

C++ Plain Enumerations:

Differences with C Enumerations (1)

13

- C++ allows programmers to be explicit about size and signedness of enumerations

```
enum Shape : int {Circle, Rectangle, Square};
```

- ▣ If `int` is too wasteful, we could instead use `char`

```
enum Shape : char {Circle, Rectangle, Square};
```

- ▣ Default type is implementation specified

```
enum Shape {Circle, Rectangle, Square};
```

C++ Plain Enumerations:

Differences with C Enumerations (2)

14

- C++ plain enumerations are more type safe
 - ▣ Implicit conversion from integer value to enumeration is not allowed
 - ▣ However, implicit conversion from enumeration to integer value is still allowed [as in C]

```
enum Fish { trout, carp, salmon, halibut };  
  
void ff(Fish);  
void fi(int);  
  
Fish f{salmon};  
ff(2);           // error!!!  
fi(salmon);      // ok!!!
```

C++ Plain Enumerations:

Differences with C Enumerations (3)

15

- C++ plain enumerations are more type safe
 - ▣ Enumeration of one type doesn't convert to enumeration value of different enumeration type

```
enum Fish { trout, carp, salmon, halibut };  
enum Color { red, green, blue };  
  
Fish f {salmon};  
Color c {blue};  
f = green; // error: cannot assign f a Color enumerator
```

C++ Plain Enumerations:

Disadvantages (1 / 2)

16

- Since enumerator names are in same scope as the `enum`, name collisions can occur

```
enum Color { red, green, blue };  
enum TrafficLight { red, yellow, green }; // error
```


C++ Plain Enumerations:

Disadvantages (2/2)

17

- Having a plain enumeration value convert to **int** can lead to nasty surprises:

```
enum Fish { trout, carp, salmon, halibut };  
enum Color { red, green, blue };
```

```
Fish f = salmon;  
if (f == 2) { // oops!!! comparing fish and int  
    std::cout << "salmon are blue\n";  
} else {  
    std::cout << "salmon are not blue\n";  
}
```

C++ Scoped Enumerations

18

- Considered as simple user-defined types [since C++11] to address type safety and name collision problems associated with plain enumerations:

```
enum class Color { red, green, blue };  
enum struct Assets { equity, bond, future };
```

- Keyword **class** or **struct** keyword in definition means enumerators are in scope of enumeration

```
enum class TrafficLight { red, yellow, green };  
enum class FireAlert {green, yellow, orange, red}; // ok
```

C++ Scoped Enumerations: Strongly Typed

19

- Scoped enumerations are strongly typed – values of scoped enumerations no longer convert implicitly to integral value!!!

```
enum class TrafficLight : int { red, yellow, green };  
enum class FireAlert     : int { green, yellow, orange, red };
```

```
void ffa(FireAlert);  
void fi(int);
```

```
FireAlert w1 = 7; // error: no int to FireAlert conversion  
int w2 = green;   // error: green not in scope  
ffa(2);           // error: no int to FireAlert conversion  
int w3 = FireAlert::green; // error: no FireAlert to int conversion  
FireAlert w4{FireAlert::green}; // OK  
fi(w4);           // error: no FireAlert to int conversion
```

```
void foo(TrafficLight x) {  
    if (x == 9) { /* ... */ } // error: 9 is not TrafficLight  
    if (x == red) { /* ... */ } // error: no red in scope  
    if (x == FireAlert::red) { /* ... */ } // error: x is not FireAlert  
    if (x == TrafficLight::red) { /* ... */ } // OK  
}
```

C++ Enumerations: Overloading Operators (1 / 2)

20

- By default, **enum** has only assignment, initialization, and comparisons
- Since **enum** is user-defined type, we can define functions that overload operators on it

C++ Enumerations: Overloading Operators (2/2)

21

```
enum Weekday { Mon = 1, Tue, Wed, Thu, Fri, Sat, Sun };

Weekday& operator++(Weekday& w) { // prefix increment operator
    w = (w == Weekday::Sun) ? Weekday::Mon
        : Weekday(static_cast<int>(w)+1);
    return w;
}

Weekday operator++(Weekday& w, int) { // postfix increment operator
    Weekday old{w};
    ++w;
    return old;
}

// use cases ...
Weekday w = Weekday{4}; // Weekday::Thu
Weekday w2 = ++w;       // w2 is Weekday::Fri
Weekday w3 = w2++;      // w3 is Weekday::Fri
std::cout << "w3: " << static_cast<int>(w3) << "\n";
```

Summary

22

- In general, prefer scoped enumerations because they cause fewer surprises