3. The Services API

3.1. Account

The account defines a physical entity, the subscriber, through which client access to the Service Platform is enabled. The Account data model contains meta–data which describes the entity itself and entity specific preferences.

3.1.1. createAccount()

Create, to storage, an Account.

3.1.1.1. Parameters:

Index	Name	Data-type	Description
0	status	string	status of this account [INACTIVE | ACTIVE | RESTRICTED | SUSPENDED | CANCELLED]
1	title	string	account holder title
2	firstname	string	account holder's first name
3	lastname	string	account holder's last name
4	address1	string	first line of the account holder's address
5	address2	string	second line of the account holder's address
6	locality	string	locality of the account holder address
7	city	string	city of the account holders address
8	county	string	county of the account holders address
9	postcode	string	postcode of the account holders address
10	country	string	country of the account holders address
11	password	string	password for this account
12	accessPointUID	integer	Access Point UID
13	originUID	integer	Origin UID

3.1.1.2. Example argument list:

3.1.1.3. Returns:

The following is the *JavaScript* object returned a *Call* of the method with the parameter values above:

```
returnValue = {
  requestId:2016960594,
  result:642,
  resultCode:"0"
};
```

The value of *result* (642 in this example) is the *UID* of the new *Record* in the *Table*.

3.1.2. updateAccount()

Update, to storage, an Account identified by its primary key (UID).

3.1.2.1. Parameters:

Index	Name	Data-type	Description
0	uid	integer	Primary Key of the account to be updated
1	status	string	status of this account
2	title	string	account holder's title
3	firstname	string	account holder's first name
4	lastname	string	account holder's last name
5	address1	string	first line of the account holder's address
6	address2	string	second line of the account holder's address
7	locality	string	locality of the account holder address
8	city	string	city of the account holder's address
9	county	string	county of the account holder's address
10	country	string	country of the account holder's address
11	postcode	string	postcode of the account holder's address
12	password	string	password for this account
13	accessPointUID	integer	Access Point UID
14	modifiedDate	date	last time this entry was modified in the database

3.1.2.2. Example argument list:

&arg0=642&arg1=active&arg2=Mr&arg3=Jake&arg4=Gittes&arg5=123%20Central%20Avenue&arg6=%20&arg7=%20&arg8=Los%20Angeles&arg9=Los%20Angeles&arg10=%20&arg11=USA&arg12=Albacore&arg13=1&arg14=11&arg15=OriginKey

3.1.2.3. Returns:

The following is the *JavaScript* object returned a *Call* of the method with the parameter values above:

```
returnValue = {
  requestId:348227945,
  result:1,
  resultCode:"0"
};
```

The value of *result* (1 in this example) is the number of rows updated.

3.1.3. deleteAccount()

Delete, from storage, an Account identified by its primary key (UID).

3.1.3.1. Parameters:

Index	Name	Data-type	Description
0	uid	integer	Primary Key (UID) of the Account to delete

3.1.3.2. Example argument list:

arg0=642

3.1.3.3. Returns:

The following is the *JavaScript* object returned a *Call* of the method with the parameter values above:

```
returnValue = {
  requestId:1206749163,
  result:1,
  resultCode:"0"
};
```

The value of *result* (*1* in this example) is the number of rows deleted.

3.1.4. getAccByUserUID()

Gets an *Account* identified by the *UID* of a *Child*. This *Method* assumes that an *Account* (*Parent*) has one or more *Users* (*Child*).

3.1.4.1. Parameters:

Index	Name	Data-type	Description
0	usruid	integer	Primary Key (UID) of the child User of the parent Account to retrieve

3.1.4.2. Example argument list:

&arg0=21

3.1.4.3. Returns:

```
returnValue = {
  requestId:1857155926,
  result:{
    accessPointUID:1,
    status:"ACTIVE",
    postCode:"USA",
    locality:"null",
    address1:"123 Central Avenue",
    city:"Los Angeles",
    exportID:null,
    county:"Los Angeles",
    password:"Albacore",
    originKey:"OriginKey",
    firstName:"Jake",
    statusCode:"A",
    country:" ",
    changeLog:null,
    title:"Mr",
    originUID:11,
    modifiedDate:null,
    address2:" ",
    uid:661,
    creationDate:1150206238000,
    lastName:"Gittes"
  },
  resultCode:"0"
};
```

The value of *result* is – the *Account* if found, the matching object, null otherwise.

3.1.5. getByCreationDate()

Retrieve, from storage, a List of Account entities identified by their creation date.

3.1.5.1. Parameters:

Index	Name	Data-type	Description
0	starttime	string	A string representation of the start of the date range to retrieve by
1	endtime	string	A string representation of the end of the date range to retrieve by
2	dateformat	date	The date format e.g. 'dd/mm/yyyy:HH:MI:SS'

3.1.5.2. Example argument list:

&arg0=12/06/2006&arg1=14/06/2006&arg2=dd/mm/yyyy

3.1.5.3. Returns:

```
returnValue = {
  requestId:510423559,
  result:[{

    …

  },
  {
    accessPointUID:1,
    status:"ACTIVE",
    postCode:"USA",
    locality:" ",
    address1:"123 Central Avenue",
    city:"Los Angeles",
    exportID:null,
    county:"Los Angeles",
    password:"Albacore",
    originKey:"OriginKey",
    firstName:"Jake",
    statusCode:"A",
    country:" ",
    changeLog:null,
    title:"Mr",
    originUID:11,
    modifiedDate:null,
    address2:" ",
    uid:661,
    creationDate:1150206238000,
    lastName:"Gittes"
  },
  {

    …

  }],
  resultCode:"0"
};
```

The value of *result* is a *List* (the edited extract above shows the values of one *Record*) – the *List* If found, the matching objects, null otherwise.

3.1.6. getByStatus()

Retrieve, from storage, a List of Account entities identified by their status.

3.1.6.1. Parameters:

Index	Name	Data-type	Description
0	status	string	status of the Account objects to retrieve

3.1.6.2. Example argument list:

&arg0=active

3.1.6.3. Returns:

```
returnValue = {
  requestId:1598439155,
  result:[{

    …

  },
  {
    accessPointUID:1,
    status:"ACTIVE",
    postCode:"USA",
    locality:" ",
    address1:"123 Central Avenue",
    city:"Los Angeles",
    exportID:null,
    county:"Los Angeles",
    password:"Albacore",
    originKey:"OriginKey",
    firstName:"Jake",
    statusCode:"A",
    country:" ",
    changeLog:null,
    title:"Mr",
    originUID:11,
    modifiedDate:null,
    address2:" ",
    uid:661,
    creationDate:1150206238000,
    lastName:"Gittes"
  },
  {

    …
}],
  resultCode:"0"
};
```

The value of *result* is a *List* (the edited extract above shows the values of one *Record*) – the *List* If found, the matching objects, null otherwise.