





版本：V2.2

本圖面若與目錄之規格尺寸不符，以本圖面規格尺寸為主。
Below is our main specification if different from catalog.


RoHS compliant



CIRCUIT DIAGRAM



P.C.B. LAYOUT



STEM (L)	
<input type="checkbox"/>	1.5
A	4.3

IT-1127X-XXXG-G

OPERATING FORCE
160, 250

RoHS compliant

SPECIFICATION

Rating: 50mA 12V DC.

Function: OFF-(ON).

Travel: 0.2±0.1mm.

Contact resistance: 100mΩ Max.(initial)

Operating force: 160±50g.

Minimum load: 10mA 3.3V DC.(reference only)

Life: 100,000 Cycles.

Soldering temperature: 250°C Max. for 3 sec.

Soldering time: 1 time only.

Note: Unwashable, don't be immersed by epoxy and organic solvent.



EV2.1	△		
EV2.0	無	新繪製	2012.09.27
版本 VER.	符號 SYMBOL	修改內容 ALTERATION	更新日期 DATE

產品 PRODUCT		Tact Switch		型號 MODEL NO.		IT-1127-160G-G	
比例 SCALE	8 : 1	單位 UNIT	mm	<div>一綺電子企業股份有限公司</div> <div>總公司：110 台北市信義路四段415號13樓之3</div> <div>13F-3 NO. 415, SEC. 4, HSIN YI ROAD, TAIPEI, TAIWAN</div> <div>TEL：886-2-27290229 (Rep.) FAX：886-2-27582086</div> <div>URL：http://www.switronic.com.tw</div> <div>E-MAIL：switches@ms36.hinet.net</div>			
公差 TOLERANCE	.X=±0.3mm, .XX=±0.2mm						
製圖 DRAWN BY	核圖 CHECKED BY	主管 APPROVED BY					
Jay Kang	Alex Lin	Margaret Lee					

SWITRONIC[®]

INDUSTRIAL CORP.

Switches



ISO 9001:2008
Cert. No. 04-100-880142

SWITRONIC
INDUSTRIAL CORP.
Switches

