Ideal Nozzle Simulation Inputs:

a: 0.05 meter ** 2 / kilogram
n: 0.65
m: -0.2

Oxidiser:

Initial Volume: 0.41 liter
Initial Mass: 0.76 lbs

Injector Mass Flow Rate: 0.042 kilogram / second
Number of Injectors: 1
Ideal O/F Ratio: 4.83
External Temp: 50 degF
Time Step: 0.001 second

Simulation Results:

Total Burn Time: 8.256 second

Impulse: 1288.54 newton * second
Average Thrust: 156.07 newton
Motor: K156

Nozzle Results:

Suggested Throat Diameter: 0.209 inch
Suggested Exit Diameter: 0.475 inch
Suggested Diffuser Length: 0.495 inch

Fuel Grain

Port Length: 13.4 inch
Fuel Density: 3.96 kilogram / meter ** 3

Grain Diameter: 1.75 inch
Initial Port Diameter: 1.0 inch
Final Port Diameter: 1.536 inch


average fuel mass flow rate (kilogram / second) vs time (second)
0.012
0.010
0.008
0.006
0.004
0.002
0.000
0
2
4
6
8
time (second)
average fuel mass flow rate (kilogram / second)


average port diameter (inch) vs time (second)
average port diameter (inch)
1.5
1.4
1.3
1.2
1.1
1.0
0
2
4
6
8
time (second)


average regression rate (inch / second) vs time (second)
average regression rate (inch / second)
0.035
0.030
0.025
0.020
0.015
0.010
0.005
0.000
0
2
4
6
8
time (second)


average total mass flow rate (kilogram / second) vs time (second)
0.05
0.04
0.03
0.02
0.01
0.00
average total mass flow rate (kilogram / second)
0
2
4
6
8
time (second)


average total mass flux (kilogram / inch ** 2 / second) vs time (second)
average total mass flux (kilogram / inch ** 2 / second)
0.0012
0.0010
0.0008
0.0006
0.0004
0.0002
0.0000
0
2
4
6
8
time (second)


inlet mach vs time (second)
inlet mach
0.04
0.02
0.00
−0.02
−0.04
0
2
4
6
8
time (second)


inlet velocity (mph) vs time (second)
7
6
5
4
3
2
1
0
inlet velocity (mph)
0
2
4
6
8
time (second)


nozzle diffuser length (inch) vs time (second)
0.5
0.4
0.3
0.2
0.1
0.0
nozzle diffuser length (inch)
0
2
4
6
8
time (second)


nozzle exit area (inch ** 2) vs time (second)
0.175
0.150
0.125
0.100
0.075
0.050
0.025
0.000
0
2
4
6
8
time (second)
nozzle exit area (inch ** 2)


nozzle exit diameter (inch) vs time (second)
0.5
0.4
0.3
0.2
0.1
0.0
nozzle exit diameter (inch)
0
2
4
6
8
time (second)


nozzle exit mach vs time (second)
nozzle exit mach
3.00
2.95
2.90
2.85
2.80
2.75
2.70
0
2
4
6
8
time (second)


nozzle exit velocity (mph) vs time (second)
nozzle exit velocity (mph)
6900
6800
6700
6600
6500
6400
6300
0
2
4
6
8
time (second)


nozzle naught temp (degF) vs time (second)
+4.9403e3
0.036
0.035
0.034
0.033
0.032
0.031
0.030
0
2
4
6
8
time (second)
nozzle naught temp (degF)


nozzle star mach vs time (second)
nozzle star mach
1.04
1.02
1.00
0.98
0.96
0
2
4
6
8
time (second)


nozzle star pressure (pound_force_per_square_inch) vs time (second)
nozzle star pressure (pound_force_per_square_inch)
295
290
285
280
275
270
265
0
2
4
6
8
time (second)


nozzle star temp (degF) vs time (second)
+4.403e3
0.061
0.060
0.059
0.058
0.057
0.056
nozzle star temp (degF)
0
2
4
6
8
time (second)


nozzle star velocity (mph) vs time (second)
+2.192266e3
0.0082
0.0080
0.0078
0.0076
0.0074
0.0072
nozzle star velocity (mph)
0
2
4
6
8
time (second)


nozzle throat area (inch ** 2) vs time (second)
0.035
0.030
0.025
0.020
0.015
0.010
0.005
0.000
0
2
4
6
8
time (second)
nozzle throat area (inch ** 2)


nozzle throat diameter (inch) vs time (second)
0.20
0.15
0.10
0.05
0.00
0
2
4
6
8
time (second)
nozzle throat diameter (inch)


nozzle thrust (newton) vs time (second)
160
140
120
100
80
60
40
20
0
0
2
4
6
8
time (second)
nozzle thrust (newton)


oxi fuel ratio vs time (second)
oxi fuel ratio
4.1
4.0
3.9
3.8
3.7
3.6
3.5
0
2
4
6
8
time (second)


oxidiser mass (kilogram) vs time (second)
oxidiser mass (kilogram)
0.35
0.30
0.25
0.20
0.15
0.10
0.05
0.00
0
2
4
6
8
time (second)


oxidiser mass flow rate (kilogram / second) vs time (second)
0.04
0.03
0.02
0.01
0.00
oxidiser mass flow rate (kilogram / second)
0
2
4
6
8
time (second)