


# BASH Basics

Note Title

4/12/2013



# Bash Shell Programming Helps

- ▶ We use the Bash shell to orchestrate the chip building process
- ▶ Bash shell calls the other tools, does vector checking
- ▶ The shell script is a series of commands that the Bash interpreter executes

# Bash Shell Programming Helps

- ▶ Bash shell scripts begin with a "she bang" followed by the path to the bash interpreter on line one.
- ▶ This tells the interpreter that this file is a shell script and also where the script resides. For a script file named "scriptfilename":

```
#!/bin/bash  
echo "this is my first shell script"
```

- ▶ The shell script is not executable unless you make it so.
- ▶ The following adds execute permissions for the user.

```
chmod u+x <scriptfilename>
```

# Bash Shell Programming Helps - Decisions with if


```
if [ condition_to_test ] ; then
    command1
elif
    command2
else
    command3
fi
```

*- a bash.sh*



## ► File based test conditions

Condition	True If
[ -a file ]	'file' exists
[ -e file ]	'file' exists (same as -a)
[ -d directory ]	'directory' exists and is a directory
[ -f regularfile ]	'regularfile' exists and is a regular file
[ -s regularfile ]	'regularfile' exists and has size >0
[ -x executablefile ]	'executablefile' exists and is executable by the shell

# Bash Shell Programming Helps - Other test conditions



Condition	True If
[ string1 <del>=</del> string2 ]	string1 is equal to string2
[ string1 <del>!=</del> string2 ]	string1 is not equal to string2
[ numb1 -eq numb2 ]	numb1 is equal to numb2
[ numb1 -ne numb2 ]	numb1 is not equal to numb2
[ numb1 <u>-gt</u> numb2 ]	numb1 is greater than numb2



# Bash Shell Programming Helps - Running VSIM

- ▶ vsim is always invoked on the module name, not the source file
  - ▶ vsim modulename **not** vsim modulename.sy
- ▶ Typical vsim invocation for use in bash scripts:
  - ▶ vsim modulename -do dofilename -quiet -c -t 1ps
- ▶ Minimizes chatter from the tool
- ▶ Runs without the gui
- ▶ Sets simulator to run with 1pS resolution
- ▶ For more vsim command line arguments, type: vsim -help

# Bash Shell Programming Helps - File Redirection

- ▶ In BASH, there are three standard IO streams open:

stdin	file handle 0	standard input
stdout	file handle 1	standard output
stderr	file handle 2	standard error

- ▶ redirect stdout to file.txt, creating the file if necessary
  - ▶ cmd > file.txt
- ▶ forcefully redirect stdout to file.txt, even if **noclobber** is set
  - ▶ cmd >| file.txt
- ▶ redirect stdout to file.txt, appending to file.txt if it exists
  - ▶ cmd >> file.txt
- ▶ redirect stdout and stderr to file.txt
  - ▶ cmd &> file.txt
- ▶ pipe: send stdout of cmd1 to stdin of cmd2
  - ▶ cmd1 | cmd2

# Bash Shell Programming Helps - Variables, translate

- ▶ Using a string variable to shorten names
  - ▶ `OSU_SYN_LIB="/nfs/guille/a1/cadlibs/osu_lib"`
- ▶ Dereferencing the variable using the dollar sign
  - ▶ `vlog $OSU_SYN_LIB/lib_ss_1.62_125c.v -work work`
- ▶ Translate lower case to uppercase in a list file using temporary file
  - ▶ `cat listfile | tr [a-z][A-Z] > $$tempfile`
  - ▶ `mv $$tempfile listfile`
- ▶ cat sends the contents of listfile via a pipe into the translate utility tr. tr does the substitution and puts the results into a temporary file called \$\$tempfile. Then, \$\$tempfile is renamed to listfile with the altered contents.




# Bash Shell Programming Helps - Tee

- ▶ Sometimes you want to see the output of a compile on the screen and also have it sent to a file. The utility `tee` does this for you. For example:
  - ▶ `vlog my_module.sv | tee compile_transcript`
- ▶ sends the output from `vlog` to the file named `compile_transcript` and also routes it to the screen.

# Bash Shell Programming Helps - regression, diff, comments

- ▶ Check output vectors against a set of known good "golden" vectors.

```
if [ ! -s "golden_vectors" ]; then
    echo "no golden vectors found"
    exit    #bug out of shell
else
    diff listfile golden_vectors >| reports/miscompares
fi
```



- ▶ A check can then be made on the size of the miscompares file to see if there were any miscompares.

# Bash Shell Programming Helps - good links

- ▶ For more information, see:

<http://tldp.org/LDP/Bash-Beginners-Guide/html/Bash-Beginners-Guide.html>

<http://tldp.org/HOWTO/Bash-Prog-Intro-HOWTO.html>

# Makefiles

---

make 

# Block Diagram

