


docker



Objetivos

- ¿Qué son Contenedores?
- ¿Qué es Docker?
- ¿Por qué tu necesitas esto?
- ¿Qué puede hacer esto?

- Ejecutar contenedores Docker
- Crear una imagen Docker
- Redes en Docker
- Docker Compose

- Conceptos de Docker en profundidad

- Docker para Windows/Mac


- Docker Swarm
- Docker vs Kubernetes

docker

overview


¿Por qué necesitas Docker?

- Compatibilidad/Dependencias
- Tiempo de configuración excesivo
- Diferentes entornos Dev/Test/Prod




¿Qué puede hacer?

- Contenerizar Aplicaciones
- Ejecutar cada servicio con sus propias dependencias en contenedores separados



¿Qué son contenedores?



Sistemas operativos



OS

Software

Software

Software

Software

OS Kernel

Compartiendo el kernel






Docker




OS - Ubuntu

Contenedores vs Maquinas Virtuales



Containers & Virtual Machines




¿Cómo se hace esto?


```
docker run ansible  
docker run mongodb  
docker run redis  
docker run nodejs  
docker run nodejs  
docker run nodejs
```



Public Docker registry - dockerhub



Contenedor vs imagen



Docker Image

Package
Template
Plan



Docker Container #1



Docker Container #2



Docker Container #3




Primeros pasos

d o c k e r

Docker Editions



Community Edition



Enterprise Edition


Community Edition




Linux



MAC



Windows



Cloud

docker

comandos

Run – iniciar un contenedor

```
▶ docker run nginx
```

```
Unable to find image 'nginx:latest' locally
latest: Pulling from library/nginx
fc7181108d40: Already exists
d2e987ca2267: Pull complete
0b760b431b11: Pull complete
Digest:
sha256:96fb261b66270b900ea5a2c17a26abbfbe95506e73c3a3c65869a6dbe83223a
Status: Downloaded newer image for nginx:latest
```

ps – listar contenedores

```
▶ docker ps
```

CONTAINER ID	IMAGE	COMMAND	CREATED	STATUS	PORTS	NAMES
796856ac413d	nginx	"nginx -g 'daemon off..."	7 seconds ago	Up 6 seconds	80/tcp	silly_sammet

```
▶ docker ps -a
```

CONTAINER ID	IMAGE	COMMAND	CREATED	STATUS	NAMES
796856ac413d	nginx	"nginx -g 'daemon off..."	7 seconds ago	Up 6 seconds	silly_sammet
cff8ac918a2f	redis	"docker-entrypoint.s..."	6 seconds ago	Exited (0) 3 seconds ago	relaxed_aryabhata

STOP – parar un contenedor

```
▶ docker ps
```

CONTAINER ID	IMAGE	COMMAND	CREATED	STATUS	PORTS	NAMES
796856ac413d	nginx	"nginx -g 'daemon off..."	7 seconds ago	Up 6 seconds	80/tcp	silly.sammet

```
▶ docker stop silly.sammet
```

```
silly.sammet
```

```
▶ docker ps -a
```

CONTAINER ID	IMAGE	COMMAND	CREATED	STATUS	NAMES
796856ac413d	nginx	"nginx -g 'daemon off..."	7 seconds ago	Exited (0) 3 seconds ago	silly.sammet
cff8ac918a2f	redis	"docker-entrypoint.s..."	6 seconds ago	Exited (0) 3 seconds ago	relaxed_aryabhata

Rm – eliminar un contenedor

```
▶ docker rm silly_sammet
```

```
silly_sammet
```

```
▶ docker ps -a
```

CONTAINER ID	IMAGE	COMMAND	CREATED	STATUS	NAMES
cff8ac918a2f	redis	"docker-entrypoint.s..."	6 seconds ago	Exited (0) 3 seconds ago	relaxed_aryabhatta

images – Listar imágenes

► docker images

REPOSITORY	TAG	IMAGE ID	CREATED	SIZE
nginx	latest	f68d6e55e065	4 days ago	109MB
redis	latest	4760dc956b2d	15 months ago	107MB
ubuntu	latest	f975c5035748	16 months ago	112MB
alpine	latest	3fd9065eaf02	18 months ago	4.14MB

rmi – Eliminar imágenes

```
▶ docker rmi nginx
```

```
Untagged: nginx:latest
Untagged: nginx@sha256:96fb261b66270b900ea5a2c17a26abbfabe95506e73c3a3c65869a6dbe83223a
Deleted: sha256:f68d6e55e06520f152403e6d96d0de5c9790a89b4cf99f4626f68146fa1dbdc
Deleted: sha256:1b0c768769e2bb66e74a205317ba531473781a78b77feef8ea6fd7be7f4044e1
Deleted: sha256:34138fb60020a180e512485fb96fd42e286fb0d86cf1fa2506b11ff6b945b03f
Deleted: sha256:cf5b3c6798f77b1f78bf4e297b27cfa5b6caa982f04caeb5de7d13c255fd7a1e
```

! Elimina todos los contenedores dependientes para poder eliminar la imagen

Pull – bajar una imagen

```
▶ docker run nginx
```

```
Unable to find image 'nginx:latest' locally
latest: Pulling from library/nginx
fc7181108d40: Already exists
d2e987ca2267: Pull complete
0b760b431b11: Pull complete
Digest:
sha256:96fb261b66270b900ea5a2c17a26abbfbe95506e73c3a3c65869a6dbe83223a
Status: Downloaded newer image for nginx:latest
```

```
▶ docker pull nginx
```

```
Using default tag: latest
latest: Pulling from library/nginx
fc7181108d40: Pull complete
d2e987ca2267: Pull complete
0b760b431b11: Pull complete
Digest:
sha256:96fb261b66270b900ea5a2c17a26abbfbe95506e73c3a3c65869a6dbe83223a
Status: Downloaded newer image for nginx:latest
```

```
▶ docker run ubuntu
```


```
▶ docker ps
```

CONTAINER ID	IMAGE	COMMAND	CREATED	STATUS	PORTS
--------------	-------	---------	---------	--------	-------

```
▶ docker ps -a
```

CONTAINER ID	IMAGE	COMMAND	CREATED	STATUS	PORTS
45aacca36850	ubuntu	"/bin/bash"	43 seconds ago	Exited (0) 41 seconds ago	

```
▶ docker run ubuntu
```



```
▶ docker ps
```

CONTAINER ID	IMAGE	COMMAND	CREATED	STATUS	PORTS
--------------	-------	---------	---------	--------	-------

```
▶ docker ps -a
```

CONTAINER ID	IMAGE	COMMAND	CREATED	STATUS	PORTS
45aacca36850	ubuntu	"/bin/bash"	43 seconds ago	Exited (0) 41 seconds ago	

Agregar un comando

```
▶ docker run ubuntu
```

```
▶ docker run ubuntu sleep 5
```



Exec – ejecutar un comando

```
▶ docker ps -a
```

CONTAINER ID	IMAGE	COMMAND	CREATED	STATUS	NAMES
538d037f94a7	ubuntu	"sleep 100"	6 seconds ago	Up 4 seconds	distracted_mcclintock

```
▶ docker exec distracted_mcclintock cat /etc/hosts
```

```
127.0.0.1      localhost
::1      localhost ip6-localhost ip6-loopback
fe00::0 ip6-localnet
ff00::0 ip6-mcastprefix
ff02::1 ip6-allnodes
ff02::2 ip6-allrouters
172.18.0.2      538d037f94a7
```

Run – conectar y desconectar

```
▶ docker run kodekloud/simple-webapp
```

```
This is a sample web application that displays a colored background.  
* Serving Flask app "app" (lazy loading)  
* Running on http://0.0.0.0:8080/ (Press CTRL+C to quit)
```

```
▶ docker run -d kodekloud/simple-webapp
```

```
a043d40f85fefa414254e4775f9336ea59e19e5cf597af5c554e0a35a1631118
```

```
▶ docker attach a043d
```



docker
run

Run – tag

```
docker run redis
```

```
Using default tag: latest
latest: Pulling from library/redis
f5d23c7fed46: Pull complete
Status: Downloaded newer image for redis:latest

1:C 31 Jul 2019 09:02:32.624 # o000o000o000o Redis is starting o000o000o000o
1:C 31 Jul 2019 09:02:32.624 # Redis version=5.0.5, bits=64, commit=00000000, modified=0, pid=1, just started
1:M 31 Jul 2019 09:02:32.626 # Server initialized
```

```
docker run redis:4.0
```

TAG

```
Unable to find image 'redis:4.0' locally
4.0: Pulling from library/redis
e44f086c03a2: Pull complete
Status: Downloaded newer image for redis:4.0
```

```
1:C 31 Jul 09:02:56.527 # o000o000o000o Redis is starting o000o000o000o
1:C 31 Jul 09:02:56.527 # Redis version=4.0.14, bits=64, commit=00000000, modified=0, pid=1, just started
1:M 31 Jul 09:02:56.530 # Server initialized
```

RUN - STDIN

```
~/prompt-application$ ./app.sh  
Welcome! Please enter your name: Mumshad
```

```
Hello and Welcome Mumshad!
```

```
docker run kodekloud/simple-prompt-docker
```

```
Hello and Welcome !
```

```
docker run -i kodekloud/simple-prompt-docker
```

```
Mumshad
```

```
Hello and Welcome Mumshad!
```

```
docker run -it kodekloud/simple-prompt-docker
```

```
Welcome! Please enter your name: Mumshad
```

```
Hello and Welcome Mumshad!
```

Run – PORT mapping

```
docker run kodekloud/webapp
```

```
* Running on http://0.0.0.0:5000/ (Press CTRL+C to quit)
```

http://172.17.0.2:5000

Internal IP

```
docker run -p 80:5000 kodekloud/simple-webapp
```

```
docker run -p 8000:5000 kodekloud/simple-webapp
```

```
docker run -p 8001:5000 kodekloud/simple-webapp
```

```
docker run -p 3306:3306 mysql
```


```
docker run -p 8306:3306 mysql
```

```
docker run -p 8306:3306 mysql
```

```
root@osboxes:/root # docker run -p 8306:3306 -e MYSQL_ROOT_PASSWORD=pass mysql
docker: Error response from daemon: driver failed programming external connectivity on endpoint boring_bhabha (5079d342b7e8ee11c71d46): Bind for 0.0.0.0:8306 failed: port is already allocated.
```



http://192.168.1.5:80




RUN – Volume mapping

```
docker run mysql
```

```
docker stop mysql  
docker rm mysql
```

```
docker run -v /opt/datadir:/var/lib/mysql mysql
```



Inspect Container

```
▶ docker inspect blissful_hopper
```

```
[  
 {  
     "Id": "35505f7810d17291261a43391d4b6c0846594d415ce4f4d0a6ffbf9cc5109048",  
     "Name": "/blissful_hopper",  
     "Path": "python",  
     "Args": [  
         "app.py"  
     ],  
     "State": {  
         "Status": "running",  
         "Running": true,  
     },  
     "Mounts": [],  
     "Config": {  
         "Entrypoint": [  
             "python",  
             "app.py"  
         ],  
     },  
     "NetworkSettings": {...}  
 }]
```

Container Logs

```
▶ docker logs blissful_hopper
```

This is a sample web application that displays a colored background.
A color can be specified in two ways.

1. As a command line argument with --color as the argument. Accepts one of red,green,blue,blue2,pink,darkblue
2. As an Environment variable APP_COLOR. Accepts one of red,green,blue,blue2,pink,darkblue
3. If none of the above then a random color is picked from the above list.
Note: Command line argument precedes over environment variable.

No command line argument or environment variable. Picking a Random Color =blue
* Serving Flask app "app" (lazy loading)
* Environment: production
WARNING: Do not use the development server in a production environment.
Use a production WSGI server instead.
* Debug mode: off
* Running on <http://0.0.0.0:8080/> (Press CTRL+C to quit)



docker environment variables

Environment Variables

app.py

```
import os
from flask import Flask


app = Flask(__name__)

...
...

color = "red"

@app.route("/")
def main():
    print(color)
    return render_template('hello.html', color=color)

if __name__ == "__main__":
    app.run(host="0.0.0.0", port="8080")
```



▶ python app.py

Environment Variables

app.py

```
import os
from flask import Flask

app = Flask(__name__)

...
...

color = "red"

@app.route("/")
def main():
    print(color)
    return render_template('hello.html', color=color)

if __name__ == "__main__":
    app.run(host="0.0.0.0", port="8080")
```

Environment Variables

app.py

```
import os
from flask import Flask


app = Flask(__name__)

...
...

color = os.environ.get('APP_COLOR')


@app.route("/")
def main():
    print(color)
    return render_template('hello.html', color=color)

if __name__ == "__main__":
    app.run(host="0.0.0.0", port="8080")
```




▶ export APP_COLOR=blue; python app.py

ENV Variables in Docker




```
app.py
import os
from flask import Flask
app = Flask(__name__)
...
COSL
@app.route('/')
def main():
    print("Hello from DESKTOP-4CJKELD!")
    return "Hello from DESKTOP-4CJKELD!"
if __name__ == "__main__":
    app.run(host='0.0.0.0', port=8080)
```




► docker run -e APP_COLOR=bue simple-webapp-color

ENV Variables en Docker


```
▶ docker run -e APP_COLOR=blue simple-webapp-color
```



```
▶ docker run -e APP_COLOR=green simple-webapp-color
```



```
▶ docker run -e APP_COLOR=pink simple-webapp-color
```



Inspect Environment Variable

```
▶ docker inspect blissful_hopper
```

```
[  
 {  
     "Id": "35505f7810d17291261a43391d4b6c0846594d415ce4f4d0a6ffbf9cc5109048",  
     "State": {  
         "Status": "running",  
         "Running": true,  
     },  
  
     "Mounts": [],  
     "Config": {  
         "Env": [  
             "APP_COLOR=blue",  
             "LANG=C.UTF-8",  
             "GPG_KEY=0D96DF4D4110E5C43FBFB17F2D347EA6AA65421D",  
             "PYTHON_VERSION=3.6.6",  
             "PYTHON_PIP_VERSION=18.1"  
         ],  
         "Entrypoint": [  
             "python",  
             "app.py"  
         ],  
     }  
 }]
```



d o c k e r i m a g e s

¿Qué estoy contenerizando?



¿Cómo crear mi propia imagen?

Dockerfile

```
FROM Ubuntu

RUN apt-get update
RUN apt-get install python

RUN pip install flask
RUN pip install flask-mysql

COPY . /opt/source-code

ENTRYPOINT FLASK_APP=/opt/source-code/app.py flask run
```

1. OS - Ubuntu

2. Update apt repo

3. Install dependencies using apt

4. Install Python dependencies using pip

5. Copy source code to /opt folder


6. Run the web server using “flask” command

```
docker build Dockerfile -t mmumshad/my-custom-app
```

```
docker push mmumshad/my-custom-app
```

Docker
Registry

Dockerfile



Arquitectura basada en capas

Dockerfile

```
FROM Ubuntu


RUN apt-get update && apt-get -y install python

RUN pip install flask flask-mysql

COPY . /opt/source-code

ENTRYPOINT FLASK_APP=/opt/source-code/app.py flask run
```

docker build Dockerfile -t mmumshad/my-custom-app



```
root@osboxes:/root/simple-webapp-docker # docker history mmumshad/simple-webapp
IMAGE          CREATED      CREATED BY                                         SIZE        COMMENT
1a45ba829f10  About an hour ago /bin/sh -c #(nop)  ENTRYPOINT ["/bin/sh" "..."]  0B
37d37ed8fe99  About an hour ago /bin/sh -c #(nop) COPY file:29b92853d73898...  229B
d6aaebf8ded0  About an hour ago /bin/sh -c pip install flask flask-mysql    6.39MB
e4c055538e60  About an hour ago /bin/sh -c apt-get update && apt-get insta...  306MB
ccc7a11d65b1  2 weeks ago   /bin/sh -c #(nop) CMD ["/bin/bash"]           0B
<missing>      2 weeks ago   /bin/sh -c mkdir -p /run/systemd && echo '...'  7B
<missing>      2 weeks ago   /bin/sh -c sed -i 's/^#\s*/(deb.*universe\...  2.76kB
<missing>      2 weeks ago   /bin/sh -c rm -rf /var/lib/apt/lists/*       0B
<missing>      2 weeks ago   /bin/sh -c set -xe  && echo '#!/bin/sh' >...  745B
<missing>      2 weeks ago   /bin/sh -c #(nop) ADD file:39d3593ea220e68...  120MB
```

Salida del Docker build

```
root@osboxes:/root/simple-webapp-docker # docker build .
Sending build context to Docker daemon 3.072kB
Step 1/5 : FROM ubuntu
--> ccc7a11d65b1
Step 2/5 : RUN apt-get update && apt-get install -y python python-setuptools python-dev
--> Running in a7840dbfad17
Get:1 http://archive.ubuntu.com/ubuntu xenial InRelease [247 kB]
Get:2 http://security.ubuntu.com/ubuntu xenial-security InRelease [102 kB]
Get:3 http://archive.ubuntu.com/ubuntu xenial-updates InRelease [102 kB]
Get:4 http://security.ubuntu.com/ubuntu xenial-security/universe Sources [46.3 kB]
Get:5 http://archive.ubuntu.com/ubuntu xenial-backports InRelease [102 kB]
Get:6 http://security.ubuntu.com/ubuntu xenial-security/main amd64 Packages [440 kB]
Step 3/5 : RUN pip install flask flask-mysql
--> Running in a4a6c9190ba3
Collecting flask
  Downloading Flask-0.12.2-py2.py3-none-any.whl (83kB)
Collecting flask-mysql
  Downloading Flask_SQLAlchemy-1.4.0-py2.py3-none-any.whl
Removing intermediate container a4a6c9190ba3
Step 4/5 : COPY app.py /opt/
--> e7cdab17e782
Removing intermediate container faaaaaf63c512
Step 5/5 : ENTRYPOINT FLASK_APP=/opt/app.py flask run --host=0.0.0.0
--> Running in d452c574a8bb
--> 9f27c36920bc
Removing intermediate container d452c574a8bb
Successfully built 9f27c36920bc
```

failure

Layer 1. Base Ubuntu Layer

Layer 2. Changes in apt packages

Layer 3. Changes in pip packages

Layer 4. Source code

Layer 5. Update Entrypoint with “flask” command


```
docker build Dockerfile -t mmumshad/my-custom-app
```

```
root@osboxes:/root/simple-webapp-docker # docker build .
Sending build context to Docker daemon 5.12kB
Step 1/5 : FROM ubuntu
--> ccc7a11d65b1
Step 2/5 : RUN apt-get update && apt-get install -y python python-pip
--> Using cache
--> e4c055538e60
Step 3/5 : RUN pip install flask
--> Running in aacdaccd7403
Collecting flask
  Downloading Flask-0.12.2-py2.py3-none-any.whl (83kB)
Removing intermediate container aacdaccd7403
Step 4/5 : COPY app.py /opt/
--> af41ef57f6f3
Removing intermediate container a49cc8befc8f
Step 5/5 : ENTRYPOINT FLASK_APP=/opt/app.py flask run --host=0.0.0.0
--> Running in 3d745ff07d5a
--> 910416d360b6
Removing intermediate container 3d745ff07d5a
Successfully built 910416d360b6
```

¿Qué puedes contenerizar?



Conteneriza todo!!!



docker CMD vs ENTRYPOINT




```
▶ docker run ubuntu
```

```
▶ docker ps
```

CONTAINER ID	IMAGE	COMMAND	CREATED	STATUS	PORTS
--------------	-------	---------	---------	--------	-------

```
▶ docker ps -a
```

CONTAINER ID	IMAGE	COMMAND	CREATED	STATUS	PORTS
45aacca36850	ubuntu	"/bin/bash"	43 seconds ago	Exited (0) 41 seconds ago	



```
# Install Nginx.  
RUN \  
    add-apt-repository -y ppa:nginx/stable && \  
    apt-get update && \  
    apt-get install -y nginx && \  
    rm -rf /var/lib/apt/lists/* && \  
    echo "\ndaemon off;" >> /etc/nginx/nginx.conf && \  
    chown -R www-data:www-data /var/lib/nginx  
  
# Define mountable directories.  
VOLUME ["/etc/nginx/sites-enabled", "/etc/nginx/certs", "/etc/nginx/cor  
  
# Define working directory.  
WORKDIR /etc/nginx  
  
# Define default command.  
CMD ["nginx"]
```

```
ARG MYSQL_SERVER_PACKAGE_URL=https://repo.mysql.com/yum/mysql-8.0-community/docker/x86_64/  
ARG MYSQL_SHELL_PACKAGE_URL=https://repo.mysql.com/yum/mysql-tools-community/el/7/x86_64/  
  
# Install server  
RUN rpmkeys --import https://repo.mysql.com/RPM-GPG-KEY-mysql \  
    && yum install -y $MYSQL_SERVER_PACKAGE_URL $MYSQL_SHELL_PACKAGE_URL libpwquality \  
    && yum clean all \  
    && mkdir /docker-entrypoint-initdb.d  
  
VOLUME /var/lib/mysql  
  
COPY docker-entrypoint.sh /entrypoint.sh  
COPY healthcheck.sh /healthcheck.sh  
ENTRYPOINT ["/entrypoint.sh"]  
HEALTHCHECK CMD /healthcheck.sh  
EXPOSE 3306 33060  
CMD ["mysqld"]
```

```
# Pull base image.  
FROM ubuntu:14.04  
  
# Install.  
RUN \  
    sed -i 's/# \(.*multiverse$\)/\1/g' /etc/apt/sources.list && \  
    apt-get update && \  
    apt-get -y upgrade && \  
    apt-get install -y build-essential && \  
    apt-get install -y software-properties-common && \  
    apt-get install -y byobu curl git htop man unzip vim wget && \  
    rm -rf /var/lib/apt/lists/*  
  
# Add files.  
ADD root/.bashrc /root/.bashrc  
ADD root/.gitconfig /root/.gitconfig  
ADD root/.scripts /root/.scripts  
  
# Set environment variables.  
ENV HOME /root  
  
# Define working directory.  
WORKDIR /root  
  
# Define default command.  
CMD ["bash"]
```

▶ docker run ubuntu [COMMAND]

▶ docker run ubuntu sleep 5



4

```
FROM Ubuntu
```

```
CMD sleep 5
```

CMD command param1

CMD ["command", "param1"]

CMD sleep 5

CMD ["sleep", "5"]

CMD ["sleep 5"]



```
▶ docker build -t ubuntu-sleeper .
```

```
▶ docker run ubuntu-sleeper
```



```
FROM Ubuntu
```

```
CMD sleep 5
```

Command at Startup: sleep 10

```
▶ docker run ubuntu-sleeper sleep 10
```

```
FROM Ubuntu
```

```
ENTRYPOINT [ "sleep" ]
```

Command at Startup:

```
▶ docker run ubuntu-sleeper 10
```

```
▶ docker run ubuntu-sleeper
```

```
sleep: missing operand  
Try 'sleep --help' for more information.
```

Command at Startup:

```
FROM Ubuntu
```

```
ENTRYPOINT ["sleep"]
```

```
CMD ["5"]
```

Command at Startup:

```
▶ docker run ubuntu-sleeper 10
```

Command at Startup:

```
▶ docker run --entrypoint sleep2.0 ubuntu-sleeper 10
```

Command at Startup:




d o c k e r

networking


Default networks




```
docker run ubuntu
```




```
docker run Ubuntu --network=none
```



```
docker run Ubuntu --network=host
```



Networks definidas por el usuario



```
docker network create \
--driver bridge \
--subnet 182.18.0.0/16
custom-isolated-network
```

```
docker network ls
```

NETWORK ID	NAME	DRIVER	SCOPE
dba0fb9370fe	bridge	bridge	local
46d476b87cd9	customer-isolated-network	bridge	local
6de685cec1ce	docker_gwbridge	bridge	local
e29d188b4e47	host	host	local
mmrho7vsb9rm	ingress	overlay	swarm
d9f11695f0d6	none	null	local
d371b4009142	simplewebappdocker_default	bridge	local


Inspect Network

```
▶ docker inspect blissful_hopper
```

```
[  
 {  
   "Id": "35505f7810d17291261a43391d4b6c0846594d415ce4f4d0a6ffbf9cc5109048",  
   "Name": "/blissful_hopper",  
   "NetworkSettings": {  
     "Bridge": "",  
     "Gateway": "172.17.0.1",  
     "IPAddress": "172.17.0.6",  
     "MacAddress": "02:42:ac:11:00:06",  
     "Networks": {  
       "bridge": {  
         "Gateway": "172.17.0.1",  
         "IPAddress": "172.17.0.6",  
         "MacAddress": "02:42:ac:11:00:06",  
       }  
     }  
   }  
 }
```

Embedded DNS

```
mysql.connect( mysql )
```



Host	IP
web	172.17.0.2
mysql	172.17.0.3



docker storage

File system

```
/var/lib/docker  
  aufs  
  containers  
  image  
  volumes
```

Arquitectura en capas

Dockerfile

```
FROM Ubuntu

RUN apt-get update && apt-get -y install python

RUN pip install flask flask-mysql

COPY . /opt/source-code

ENTRYPOINT FLASK_APP=/opt/source-code/app.py flask run
```

```
docker build Dockerfile -t mmumshad/my-custom-app
```

Dockerfile2

```
FROM Ubuntu


RUN apt-get update && apt-get -y install python

RUN pip install flask flask-mysql

COPY app2.py /opt/source-code

ENTRYPOINT FLASK_APP=/opt/source-code/app2.py flask run
```

```
docker build Dockerfile2 -t mmumshad/my-custom-app-2
```



Arquitectura en capas

Container Layer

Read Write

Layer 6. Container Layer

```
docker run mmumshad/my-custom-app
```

Image Layers

Read Only

Layer 5. Update Entrypoint with “flask” command

Layer 4. Source code

Layer 3. Changes in pip packages

Layer 2. Changes in apt packages

Layer 1. Base Ubuntu Layer


```
docker build Dockerfile -t mmumshad/my-custom-app
```

COPY-ON-WRITE

Container Layer




Image Layers



volumenes

```
docker volume create data_volume
```




```
docker run -v data_volume:/var/lib/mysql mysql
```

```
docker run -v data_volume2:/var/lib/mysql mysql
```

```
docker run -v /data/mysql:/var/lib/mysql mysql
```

```
docker run \  
  --mount type=bind,source=/data/mysql,target=/var/lib/mysql mysql
```



Storage drivers

- AUFS
- ZFS
- BTRFS
- Device Mapper
- Overlay
- Overlay2



d o c k e r
compose

Docker compose

```
docker run mmumshad/simple-webapp  
docker run mongodb  
docker run redis:alpine  
docker run ansible
```

docker-compose.yml



```
services:  
  web:  
    image: "mmumshad/simple-webapp"  
  database:  
    image: "mongodb"  
  messaging:  
    image: "redis:alpine"  
  orchestration:  
    image: "ansible"
```

```
docker-compose up
```




Public Docker registry - dockerhub





CATS	DOGS
1	0



docker run --links

```
docker run -d --name=redis redis
```

```
docker run -d --name=db
```

```
docker run -d --name=vote -p 5000:80 --link redis:redis
```

```
docker run -d --name=result -p 5001:80 --link db:db
```

```
docker run -d --name=worker --link db:db --link redis:redis
```

```
try {  
    Jedis redis = connectToRedis("redis");  
    Connection dbConn = connectToDB("db");  
  
    System.err.println("Watching vote queue");  
}
```

Internal

The server encountered an error while attempting to handle your request.
There is an error in the configuration of the server.
Please contact the administrator of the server.

127.0.0.1 localhost	localhost ip6-localhost ip6-loopback
::1 localhost ip6-localhost ip6-loopback	fe00::0 ip6-localnet
fe00::0 ip6-mcastprefix	ff00::1 ip6-allnodes
ff02::1 ip6-allnodes	ff02::2 ip6-allrouters
172.17.0.2 redis 89cd8eb563da	172.17.0.3 ebcae9eb46bf



voting-app



result-app



in-memory DB



db



worker



Deprecation Warning


Docker compose - build

docker-compose.yml

```
redis:  
  image: redis  
  
db:  
  image: postgres:9.4  
  
vote:  
  image: voting-app  
  ports:  
    - 5000:80  
  links:  
    - redis  
  
result:  
  image: result  
  ports:  
    - 5001:80  
  links:  
    - db  
  
worker:  
  image: worker  
  links:  
    - db  
    - redis
```

docker-compose.yml

```
redis:  
  image: redis  
  
db:  
  image: postgres:9.4  
  
vote:  
  build: ./vote  
  ports:  
    - 5000:80  
  links:  
    - redis  
  
result:  
  build: ./result  
  ports:  
    - 5001:80  
  links:  
    - db  
  
worker:  
  build: ./worker  
  links:  
    - db  
    - redis
```



Docker compose - versions

docker-compose.yml

```
redis:  
    image: redis  
  
db:  
    image: postgres:9.4  
  
vote:  
    image: voting-app  
    ports:  
        - 5000:80  
    links:  
        - redis
```

version: 1

docker-compose.yml

```
version: 2  
services:  
    redis:  
        image: redis  
    db:  
        image: postgres:9.4  
    vote:  
        image: voting-app  
        ports:  
            - 5000:80  
        depends_on:  
            - redis
```

version: 2

docker-compose.yml


```
version: 3  
services:
```

version: 3

Docker compose

docker-compose.yml

```
version: 2
services:
  redis:
    image: redis
    networks:
      - back-end
  db:
    image: postgres:9.4
    networks:
      - back-end
  vote:
    image: voting-app
    networks:
      - front-end
      - back-end
  result:
    image: result
    networks:
      - front-end
      - back-end
networks:
  front-end:
  back-end:
```



d o c k e r registry

Image

```
▶ docker run nginx
```

Image

docker.io
Docker Hub

image: docker.io/nginx/nginx

Registry User/ Image/
 Account Repository

gcr.io/ kubernetes-e2e-test-images/dnsutils

Private Registry

```
▶ docker login private-registry.io
```

Login with your Docker ID to push and pull images from Docker Hub. If you don't have a Docker ID, head over to <https://hub.docker.com> to create one.

Username: registry-user

Password:

WARNING! Your password will be stored unencrypted in /home/vagrant/.docker/config.json.

Login Succeeded

```
▶ docker run private-registry.io/apps/internal-app
```

Deploy Private Registry

```
▶ docker run -d -p 5000:5000 --name registry registry:2
```

```
▶ docker image tag my-image localhost:5000/my-image
```

```
▶ docker push localhost:5000/my-image
```


```
▶ docker pull localhost:5000/my-image
```

```
▶ docker pull 192.168.56.100:5000/my-image
```




docker
engine


Docker Engine




containerization



Namespace - PID



cgroups



```
docker run --cpus=.5 ubuntu
```

```
docker run --memory=100m ubuntu
```



d o c k e r

On Windows

Docker on windows

1. Docker on Windows using Docker Toolbox
2. Docker Desktop for Windows

1. Docker toolbox




- 64-bit operating
- Windows 7 or higher.
- Virtualization is enabled



- Oracle Virtualbox
- Docker Engine
- Docker Machine
- Docker Compose
- Kitematic GUI

2. Docker Desktop for Windows



Support: Windows 10 Enterprise/Professional Edition
Windows Server 2016

Linux Containers (Default)
Or
Windows Containers

About Docker

Discover Docker Enterprise Edition

Settings

Check for Updates

Diagnose and Feedback...

Switch to Windows containers...

Docker Store

Documentation

Kitematic

Sign in / Create Docker ID...

Repositories


Kubernetes

Restart...

Quit Docker

Windows containers

Container Types:




Base Images:

- Windows Server Core
- Nano Server

Support

- Windows Server 2016
- Nano Server
- Windows 10 Professional and Enterprise (Hyper-V Isolated Containers)



VirtualBox Or Hyper-V




docker

On Mac

Docker on Mac

1. Docker on Mac using Docker Toolbox
2. Docker Desktop for Mac

1. Docker toolbox



- macOS 10.8 “Mountain Lion” or newer



- Oracle Virtualbox
- Docker Engine
- Docker Machine
- Docker Compose
- Kitematic GUI

2. Docker Desktop for Mac



Support: macOS Sierra 10.12 or newer
Mac Hardware - 2010 model or newer

Linux Containers



container orchestration

Why Orchestrate?

```
docker run nodejs  
docker run nodejs  
docker run nodejs  
docker run nodejs
```



Public Docker registry - dockerhub



Container Orchestration

```
docker service create
```


```
nodejs
```



Container Orchestration

```
docker service create
```

```
nodejs
```




KODEKLOUD

docker swarm



Solutions



Docker Swarm



kubernetes




MESOS

Docker swarm



Setup swarm



```
root@osboxes:/root/simple-webapp-docker # docker swarm init --advertise-addr 192.168.1.12
Swarm initialized: current node (0j76dum2r56p1xfne4ub1ps2c) is now a manager.
```



To add a worker to this swarm, run the following command:

```
docker swarm join --token SWMTKN-1-35va8b3fi5krpdskefqqxggtmulw3z828daucri7y526ne0sgu-2eek9qm33d4lxzoq6we9i8izp 192.16
8.1.12:2377
```

To add a manager to this swarm, run 'docker swarm join-token manager' and follow the instructions.


Docker service

```
docker run my-web-server
```




kubernetes






Nodes (Minions)




Cluster




Master



Components



Master vs Worker Nodes



kubectl

```
kubectl run hello-minikube
```

```
kubectl cluster-info
```

```
kubectl get nodes
```

```
kubectl run my-web-app --image=my-web-app --replicas=100
```



CONCLUSION



GRACIAS