

FIT1045: Algorithms and Programming Fundamentals in Python

Lecture 7

Understanding Python



COMMONWEALTH OF AUSTRALIA
Copyright Regulations 1969
WARNING

This material has been reproduced and communicated to you by or on behalf of Monash University pursuant to Part VB of the Copyright Act 1968 (the Act). The material in this communication may be subject to copyright under the Act. Any further reproduction or communication of this material by you may be the subject of copyright protection under the Act.

Do not remove this notice.

Announcements

Test 1 this week

- covers only material from Weeks 1 – 3
- questions similar to the exam
 - similar to workshop and tutorial tasks
- opens August 27 2am
- closes August 28, 1pm
- timed (45m)

Objectives


To understand

- variable and value representation in Python
- multiple assignment and tuples
- mutable versus immutable objects
- code execution in Python

This covers learning outcomes

- 3 – Analyse the behaviour of programs and data structures

What is Python?



<https://www.thrinking.com/scene/619900611055321088>

A (virtual) Machine –
The Python Interpreter

ḡḡ - ḡḡḡ
ḡḡ - ḡḡḡ
ḡḡ - ḡḡḡ
ḡḡ - ḡḡḡ
ḡḡ - ḡḡḡ
ḡḡ - ḡḡḡ

<https://www.pinterest.com.au/pin/269090146459263825/>

A Language –
The Python programming language

Today: having a closer look here



Overview


1. Objects and variables: things and names for things
2. Functions, multiple assignments, and tuples
3. Mutability: the same and the similar

What are Python *objects* and *variables*?

```
x = 1
y = 1.0
z = '1'

a = id(1)
b = id(1.0)

x2 = 1
x2 = 1.0
```




Python Tutor: <https://goo.gl/Cg3hE9>

- *objects* have: **type**, **identity**, **value** (type-specific content)
- *variable* is a **name** (identifier) and a **reference** to an object
- assignment operation **creates** variable *if necessary*
- object *potentially* created when evaluating expression (**re-using** certain immutable objects)
- variables can be **re-assigned** to another object (possibly of different type: variables don't have types themselves)

More on variables and objects

```
x = 1
y = x + 1
z = x

del x
z = y
```



Python Tutor: <https://goo.gl/e8HCrl>


- variables are **expressions** that evaluate to referenced object
- assignment operator **evaluates** right-hand-side expression
- so when assigning a variable to another, assignment operator assigns to referenced object (no reference chain)
- variables (names) can be **deleted** by del-statement
- objects **disappear** (are deleted) when no longer referenced

What defines names?

```
from math import floor

res = 0
for i in range(1, 11):
    res = res + i

print(floor(res / i))
```



Python Tutor: <https://goo.gl/Q3wWAK>

- **assignment** operation
- **import** and **for** statement
- name known until explicitly **deleted** or **frame discarded** (when leaving function execution)
- another source: **function** definitions (see below)

Exercise: swapping references

```
x = 1  
y = 2  
  
x = y  
y = x  
  
print(x)  
print(y)
```

<https://flux.qa>

Clayton: **AXXULH**
Malaysia: **LWERDE**


Exercise: swapping references

```
x = 1
y = 2

x = y
y = x

print(x)
print(y)
```

Python Tutor: <https://goo.gl/ihv8Px>




- once we lose all references to it, object is **lost**

Exercise: swapping references

```
x = 1
y = 2

tmp = x
x = y
y = tmp

print(x)
print(y)
```



Python Tutor: <https://goo.gl/U4mvcP>

- once we lose all references to it, object is **lost**
- need to keep track of it by storing **temporary reference**
- actually we already know more convenient way to swap (next section)



Overview

1. Objects and variables: things and names for things
2. Functions, multiple assignments, and tuples
3. Mutability: the same and the similar


What are Python *functions*?

```
gst_rate = 0.1
```

```
def customer_price(price):  
    gst = price * gst_rate  
    return price + gst
```

```
p1 = customer_price(135)
```

Python Tutor: <https://goo.gl/Yeu9ZV>



- *functions* are also objects with an **identifier**
- `def`-statement **creates** (or *re-assigns*) matching variable
- function execution has own frame of **local variables**
- local variables for **parameters** are created on call

What are Python *functions*?

```
gst_rate = 0.1
```


```
def customer_price(price):  
    gst = price * gst_rate  
    return price + gst
```

```
x = customer_price
```

```
del customer_price
```

```
p1 = x(135)
```

Python Tutor: <https://goo.gl/PaA3x9>



- function objects **can be assigned** to other variables
- variables referring to function **can be deleted** (including the one created by `def` statement)
- can call function object under different names via the familiar **call syntax**

Functions are things, too

```
>>> round(1.5)
2
>>> round
<built-in function round>
>>> x = round
>>> x(1.5)
2
```

Functions are “things that can be touched”, not only operations



So functions can also be parameters of other functions!

Recall: reading with type conversion

foods.txt

```
beef
potato
broccoli
apple
potato
apple
tofu
tomato
```

quantities.txt

```
300
300
200
100
250
100
120
200
```

```
def list_from_file(fname, num=False):
    file = open(fname)
    rs = []
    for l in file:
        if num:
            rs = rs+[float(l.strip())]
        else:
            rs = rs+[l.strip()]
    file.close()
    return rs
```

```
>>> foods = list_from_file('foods.txt')
>>> foods
['apple', 'broccoli', 'beef', 'lamb', 'bread', 'potato', 'tofu',
'tomato']
>>> quantities = list_from_file('quantities.txt', True)
>>> quantities
[300.0, 300.0, 200.0, 100.0, 250.0, 100.0, 120.0, 200.0]
>>>
```

Could add more cases in conditional

foods.txt

```
beef
potato
broccoli
apple
potato
apple
tofu
tomato
```

quantities.txt

```
300
300
200
100
250
100
120
200
```

```
def list_from_file(fname, typ='str'):
    file = open(fname)
    rs = []
    for l in file:
        if typ=='float':
            rs = rs+[float(l.strip())]
        elif typ=='int':
            rs = rs+[int(l.strip())]
        else:
            rs = rs+[l.strip()]
    file.close()
    return rs
```

```
>>> foods = list_from_file('foods.txt')
>>> foods
['apple', 'broccoli', 'beef', 'lamb', 'bread', 'potato', 'tofu',
'tomato']
>>> quantities = list_from_file('quantities.txt', 'float')
>>> quantities
[300.0, 300.0, 200.0, 100.0, 250.0, 100.0, 120.0, 200.0]
>>> quantities = list_from_file('quantities.txt', 'int')
>>> quantities
[300, 300, 200, 100, 250, 100, 120, 200]
```

Better solution: function parameter


foods.txt

```
beef
potato
broccoli
apple
potato
apple
tofu
tomato
```

quantities.txt

```
300
300
200
100
250
100
120
200
```

```
def list_from_file(filename, typ=str):
    file = open(filename)
    res = []
    for line in file:
        res = res + [typ(line.strip())]
    file.close()
    return res
```



higher-order function

function argument

```
>>> foods = list_from_file('foods.txt')
>>> foods
['apple', 'broccoli', 'beef', 'lamb', 'bread', 'potato', 'tofu',
'tomato']
>>> quantities = list_from_file('quantities.txt', float)
>>> quantities
[300.0, 300.0, 200.0, 100.0, 250.0, 100.0, 120.0, 200.0]
>>> quantities = list_from_file('quantities.txt', int)
>>> quantities
[300, 300, 200, 100, 250, 100, 120, 200]
```

Another example for higher order function: built-in function *map*

```
>>> map(round, [1.1, 2.7, 2.3])
```

```
<map object at 0x10da21290>
```

```
>>> m = map(round, [1.1, 2.7, 2.3])
```

```
>>> type(m)
```

```
<class 'map'>
```

```
>>> for x in m: x
```

```
1
```

```
3
```

```
2
```

function as argument

converts one Iterable to
another by applying function
to each element

Another example for higher order function: built-in function *map*

```
>>> map(round, [1.1, 2.7, 2.3])
<map object at 0x10da21290>
>>> m = map(round, [1.1, 2.7, 2.3])
>>> type(m)
<class 'map'>
>>> for x in m: x
1
3
2
```

Provides yet another solution for type conversion

```
>>> foods = list_from_file('foods.txt')
>>> foods
['apple', 'broccoli', 'beef', 'lamb', 'bread', 'potato', 'tofu',
'tomato']
>>> quantities = list_from_file('quantities.txt')
>>> quantities
['300', '300', '200', '100', '250', '100', '120', '200']
>>> list(map(int, quantities))
[300, 300, 200, 100, 250, 100, 120, 200]
```

Exercise 2: swapping via function

```
x = 1
y = 2

def swap(x, y):
    tmp = x
    x = y
    y = tmp

swap(x, y)
print(x)
print(y)
```

<https://flux.qa>


Clayton: **AXXULH**
Malaysia: **LWERDE**

Exercise 2: swapping via function

```
x = 1
y = 2

def swap(x, y):
    tmp = x
    x = y
    y = tmp

swap(x, y)
print(x)
print(y)
```



Python Tutor: <https://goo.gl/rWij55>


- local names **shadow** (hide) global names
- this function only swaps **local** variables
- functions can read **global** variables (but not directly re-assign them)

Exercise 2: swapping via function

```
x = 1
y = 2

def swap(x, y):
    tmp = x
    x = y
    y = tmp
    return x, y


x, y = swap(x, y)
print(x)
print(y)
```



Python Tutor: <https://goo.gl/soXX6e>

- comma-separated expression evaluates to **tuple**
- tuples are **immutable sequences**
- **multiple assignment** assigns elements of sequence in parallel (evaluating first complete right-hand-side expression)

Iterable type hierarchy




Can swap directly using tuple expression

```
x = 1
```

```
y = 2
```

```
def swap(x, y):  
    return y, x
```

```
x, y = swap(x, y)  
print(x)  
print(y)
```




Python Tutor: <https://goo.gl/BycpM5>

- can directly write flipped **tuple expression**
- receive by **multiple assignment**

Simple enough to not need function

```
x = 1
y = 2
x, y = y, x
print(x)
print(y)

z = y, x
print(z[0])
print(z[1])
```




Python Tutor: <https://goo.gl/9LerIt>

- can directly write flipped **tuple expression**
- receive by **multiple assignment**
- **canonical way** to swap references in Python
- sidenote: assigning to single variable yields tuple reference

Overview

1. Objects and variables: things and names for things
2. Functions, multiple assignments, and tuples
3. **Mutability: the same and the similar**


Mutable versus Immutable Collections



What are Python *lists*?

```
x = ['bread', 200]
y = x
x.extend(['eggs', 50])
x[-1] = 70

a = y[-1]
```




Python Tutor: <https://goo.gl/EuExCB>

- *lists* are objects containing **mutable** sequence of **references**
- values of variables referencing same list change simultaneously!

How are new lists created?

```
x = ['a', 'b', 'c']
y = ['a', 'b', 'c']
z = x

print(x==y and x==z)
print(id(x)==id(z))
print(id(x)==id(y))
```



Python Tutor: <https://goo.gl/J9Jl8h>

- list objects are not generally re-used: “[...]”-expression evaluates to **new list**
- but: assignment **assigns reference** to existing object (as usual)
- same objects are always equal
- equal objects don't necessarily have same **identity**

How can we copy a list?


```
from copy import copy
```

```
x = ['a', 'b', 'c']
```

```
y = x[:]
```

```
z = copy(y)
```

Python Tutor: <https://goo.gl/fAJXe5>



- certain expressions result in **copy** of list (e.g., canonical way is “slicing” of complete original list)
- **copy module** provides function *copy* for all types of objects

How can we copy a list?

```
from copy import copy

t1 = [['a', 'b'],
      ['c', 'd']]

t2 = copy(t1)
t2[0][0] = 'A'

print(t1[0][0])
```

<https://flux.qa>

Clayton: **AXXULH**
Malaysia: **LWERDE**

- certain expressions result in **copy** of list (e.g., canonical way is “slicing” of complete original list)
- **copy module** provides function *copy* for all types of objects

How can we copy a list?


```
from copy import copy

t1 = [['a', 'b'],
      ['c', 'd']]

t2 = copy(t1)
t2[0][0] = 'A'

print(t1[0][0])
```

Python Tutor: <https://goo.gl/VCnf9o>



- certain expressions result in **copy** of list (e.g., canonical way is “slicing” of complete original list)
- **copy module** provides function *copy* for all types of objects
- however, these copies are **shallow**
- remember, list is sequence of references: simple copy only **copies references** and not object referenced

How can we create a “deep” copy?


```
from copy import deepcopy
```

```
t1 = [['a', 'b'],  
      ['c', 'd']]
```

```
t2 = deepcopy(t1)  
t2[0][0] = 'A'
```

```
print(t1[0][0])
```

Python Tutor: <https://goo.gl/2fQDap>



- **copy module** provides function `deepcopy` that *recursively* copies referenced objects
- resulting **deep copy** is fully independent copy of original object

Augmented assignment statements

```
>>> x = 1
>>> x *= 2 ← short-hand for x = x * 2
>>> x
2
>>> x += 4
>>> x
6
>>> w = 'ab'
>>> w += 'c'
>>> w
'abc'
```

- short-hand for applying operator to *immutable* object referenced by variable and reassigning result

Augmented assignment statements with mutable objects

```
x = ['a']
y = x
z = y
```

short-hand for `id(x)==id(y)`


```
print(x is y and y is z)
```



```
x = x + ['b']
y += ['b']
```



```
print(x is z)
print(y is z)
```



Python Tutor: <https://goo.gl/j2CrLu>

- short-hand for applying operator to *immutable* object referenced by variable and reassigning result
- *not* equivalent for *mutable* objects: those are modified *in-place* instead of creating new object
- can be *confusing*; alternative: mutator methods (e.g. extend)

What have we learned

- **Variables** are named references to **objects**
 - can be re-assigned
 - loose object when no longer referenced
- **Functions** are objects, too
 - bound to variable on definition
 - references to them can be passed to other variables (including arguments of other functions)
- **Tuples** are immutable sequence types
 - can be used for multiple assignment
 - useful if function needs to return more than one value
- **Mutable** objects (e.g., lists) behave differently than **immutable** objects (ints, floats, strings, Booleans)
 - value of variable pointing to mutable object can be changed without being re-assigned
 - augmented assignment changes in-place

Before Next Lecture

Try out Python Tutor (e.g., examples of this lecture)

“Introduction to the design and analysis of algorithms”

Chapter 1

Coming Up

- Sorting
- Reasoning about algorithms (Invariants)