



Cybersecurity

Module 11 Challenge Submission File

Network Security Homework

Make a copy of this document to work in, and then fill out the solution for each prompt below. Save and submit this completed file as your Challenge deliverable.

Part 1: Review Questions

Security Control Types

The concept of defense in depth can be broken down into three security control types. Identify the security control type of each set of defense tactics.

1. Walls, bollards, fences, guard dogs, cameras, and lighting are what type of security control?

physical

2. Security awareness programs, BYOD policies, and ethical hiring practices are what type of security control?

administrative

3. Encryption, biometric fingerprint readers, firewalls, endpoint security, and intrusion detection systems are what type of security control?

technical

Intrusion Detection and Attack Indicators

1. What's the difference between an IDS and an IPS?

IDS only alerts of a potential threat whereas IPS will automatically take action and either block or remediate the threat

2. What's the difference between an indicator of attack (IOA) and an indicator of compromise (IOC)?

IOA is focused on the intent of the attack regardless of methods used and is a proactive approach whereas IOC is reactive and usually occurs after a suspicious incident has been reported

The Cyber Kill Chain

Name the seven stages of the cyber kill chain, and provide a brief example of each.

1. Stage 1:

Reconnaissance: searching company websites to gather information about company and infrastructure, looking for exploits or vulnerabilities within network

2. Stage 2:

Weaponization: combine exploit with backdoor into deliverable payload

3. Stage 3:

Delivery: send weaponized bundle to victim, such as a malicious link or email attachments

4. Stage 4:

Exploitation: weaponized bundle opened on destination host and executed within system

5. Stage 5:

Installation: malware/other attack vector applied or installed on system

6. Stage 6:

Command & Control (C2): assume remote control of device or entity within network, may move laterally throughout network to expand access and establish more access points for future attacks

7. Stage 7:

Actions on objectives: carry out intended goals

Snort Rule Analysis

Use the provided Snort rules to answer the following questions:

Snort Rule #1

```
alert tcp $EXTERNAL_NET any -> $HOME_NET 5800:5820 (msg:"ET SCAN Potential VNC Scan 5800-5820"; flags:S,12; threshold: type both, track by_src, count 5, seconds 60; reference:url,doc.emergingthreats.net/2002910; classtype:attempted-recon; sid:2002910; rev:5; metadata:created_at 2010_07_30, updated_at 2010_07_30;)
```

1. Break down the Snort rule header and explain what this rule does.

Alert applies to all TCP packets coming from any external IP address across any port to ports 5800:5820 on the home network

2. What stage of the cyber kill chain does the alerted activity violate?

reconnaissance

3. What kind of attack is indicated?

Vnc scan

Snort Rule #2

```
alert tcp $EXTERNAL_NET $HTTP_PORTS -> $HOME_NET any (msg:"ET POLICY PE EXE
or DLL Windows file download HTTP"; flow:established,to_client;
flowbits:isnotset,ET.http.binary; flowbits:isnotset,ET.INFO.WindowsUpdate;
file_data; content:"MZ"; within:2; byte_jump:4,58,relative,little;
content:"PE|00 00|"; distance:-64; within:4; flowbits:set,ET.http.binary;
metadata: former_category POLICY;
reference:url,doc.emergingthreats.net/bin/view/Main/2018959;
classtype:policy-violation; sid:2018959; rev:4; metadata:created_at
2014_08_19, updated_at 2017_02_01;)
```

1. Break down the Snort rule header and explain what this rule does.

Alert applies to TCP packets on HTTP ports from external network to any port on home network

2. What layer of the defense in depth model does the alerted activity violate?

Host

3. What kind of attack is indicated?

Ransomware

Snort Rule #3

Your turn! Write a Snort rule that alerts when traffic is detected inbound on port 4444 to the local network on any port. Be sure to include the `msg` in the rule option.

```
alert tcp $External_Network 4444 -> $Home_Network any {msg: "TCP packet detected through port 4444"};
```

Part 2: “Drop Zone” Lab

Set up.

Log into the Azure `firewalld` machine using the following credentials:

- Username: `sysadmin`
- Password: `cybersecurity`

Uninstall UFW.

Before getting started, you should verify that you do not have any instances of UFW running. This will avoid conflicts with your `firewalld` service. This also ensures that `firewalld` will be your default firewall.

- Run the command that removes any running instance of UFW.

```
sudo apt -y remove ufw
```

Enable and start `firewalld`.

By default, the `firewalld` service should be running. If not, then run the commands that enable and start `firewalld` upon boots and reboots.

```
$ sudo systemctl enable firewalld
$ sudo systemctl start firewalld
```

Note: This will ensure that `firewalld` remains active after each reboot.

Confirm that the service is running.

Run the command that checks whether the `firewalld` service is up and running.

```
sudo /etc/init.d/firewalld status
```

List all firewall rules currently configured.

Next, list all currently configured firewall rules. This will give you a good idea of what's currently configured and save you time in the long run by ensuring that you don't duplicate work that's already done.

- Run the command that lists all currently configured firewall rules:

```
sudo firewall-cmd --direct --get-all-rule
```

- Take note of what zones and settings are configured. You may need to remove unneeded services and settings.

List all supported service types that can be enabled.

- Run the command that lists all currently supported services to find out whether the service you need is available.

```
sudo firewall-cmd --get-services
```

- Notice that the `home` and `drop` zones are created by default.

Zone views.

- Run the command that lists all currently configured zones.

```
sudo firewall-cmd --list-all-zones
```

- Notice that the `public` and `drop` zones are created by default. Therefore, you will need to create zones for `web`, `sales`, and `mail`.

Create zones for `web`, `sales`, and `mail`.

- Run the commands that create `web`, `sales`, and `mail` zones.

```
sudo firewall-cmd --permanent --new-zone=web
sudo firewall-cmd --permanent --new-zone=sales
sudo firewall-cmd --permanent --new-zone=mail
```

Set the zones to their designated interfaces.

- Run the commands that set your `eth` interfaces to your zones.

```
sudo firewall-cmd --zone=web --add-interface=eth1
sudo firewall-cmd --zone=sales --add-interface=eth2
sudo firewall-cmd --zone=mail --add-interface=eth3
```

Add services to the active zones.

- Run the commands that add services to the `public` zone, the `web` zone, the `sales` zone, and the `mail` zone.
- `public`:

```
sudo firewall-cmd --zone=public --add-service=http --permanent
sudo firewall-cmd --zone=public --add-service=https --permanent
sudo firewall-cmd --zone=public --add-service=smtp --permanent
sudo firewall-cmd --zone=public --add-service=pop3 --permanent
```

- `web`:

```
sudo firewall-cmd --zone=web --add-service=http --permanent
```

- sales:

```
sudo firewall-cmd --zone=sales --add-service=https --permanent
```

- mail:

```
sudo firewall-cmd --zone=mail --add-service=smtp --permanent  
sudo firewall-cmd --zone=mail --add-service=pop3 --permanent
```

- What is the status of http, https, smtp and pop3?

active

Add your adversaries to the drop zone.

- Run the command that will add all current and any future blacklisted IPs to the drop zone.

```
sudo firewall-cmd --zone=drop --add-rich-rule="rule family='ipv4' source  
address='xxxxxxxxxxxxxx' reject"
```

Adversary IP addresses:

10.208.56.23
135.95.103.76
76.34.169.118

Don't understand how to do this in one command

Make rules permanent, then reload them.

It's good practice to ensure that your firewalld installation remains nailed up and retains its services across reboots. This helps ensure that the network remains secure after unplanned outages such as power failures.

- Run the command that reloads the firewalld configurations and writes it to memory:

```
sudo firewall-cmd --runtime-to-permanent
```

View active zones.

Now, provide truncated listings of all currently **active** zones. This is a good time to verify your zone settings.

- Run the command that displays all zone services.

```
sudo firewall-cmd --list-services
```

Block an IP address.

- Use a rich-rule that blocks the IP address `138.138.0.3` on your `public` zone.

```
sudo firewall-cmd --zone=public --add-rich-rule="rule family='ipv4' source address='138.138.0.3' reject"
```

Block ping/ICMP requests.

Harden your network against `ping` scans by blocking `icmp echo` replies.

- Run the command that blocks `pings` and `icmp` requests in your `public` zone.

```
sudo firewall-cmd --zone=public --add-icmp-block=echo-request
```

Rule check.

Now that you've set up your brand new firewalld installation, it's time to verify that all of the settings have taken effect.

- Run the command that lists all of the rule settings. Do one command at a time for each zone.

```
sudo firewall-cmd --zone=Web --list-all
sudo firewall-cmd --zone=Mail --list-all
sudo firewall-cmd --zone=Sales --list-all
sudo firewall-cmd --zone=public --list-all
sudo firewall-cmd --zone=drop --list-all
```

- Are all of the rules in place? If not, then go back and make the necessary modifications before checking again.

Congratulations! You have successfully configured and deployed a fully comprehensive firewalld installation.

Part 3: IDS, IPS, DiD and Firewalls

Now, you'll work on another lab. Before you start, complete the following review questions.

IDS vs. IPS Systems

1. Name and define two ways an IDS connects to a network.

Network tap - hardware device that transits inbound and outbound data streams on separate channels at the same time, offering real-time analysis

SPAN - also called port mirroring, sends mirror image of network data to another physical port for packet capture and analysis

2. Describe how an IPS connects to a network.

IPS physically connects inline with flow of data, typically between firewall and network switch

3. What type of IDS compares patterns of traffic to predefined signatures and is unable to detect zero-day attacks?

signature-based

4. What type of IDS is beneficial for detecting all suspicious traffic that deviates from the well-known baseline and is excellent at detecting when an attacker probes or sweeps a network?

Anomaly-based

Defense in Depth

1. For each of the following scenarios, provide the layer of defense in depth that applies:
 - a. A criminal hacker tailgates an employee through an exterior door into a secured facility, explaining that they forgot their badge at home.

physical

- b. A zero-day goes undetected by antivirus software.

technical

- c. A criminal successfully gains access to HR's database.

administrative

- d. A criminal hacker exploits a vulnerability within an operating system.

technical

- e. A hacktivist organization successfully performs a DDoS attack, taking down a government website.

technical

- f. Data is classified at the wrong classification level.

administrative

- g. A state-sponsored hacker group successfully firewalked an organization to produce a list of active services on an email server.

technical

- 2. Name one method of protecting data-at-rest from being readable on hard drive.

Encryption

- 3. Name one method of protecting data-in-transit.

Public Key Encryption

- 4. What technology could provide law enforcement with the ability to track and recover a stolen laptop?

GPS tracking

- 5. How could you prevent an attacker from booting a stolen laptop using an external hard drive?

Two-Factor authentication

Firewall Architectures and Methodologies

1. Which type of firewall verifies the three-way TCP handshake? TCP handshake checks are designed to ensure that session packets are from legitimate sources.

Circuit-Level Gateways

2. Which type of firewall considers the connection as a whole? Meaning, instead of considering only individual packets, these firewalls consider whole streams of packets at one time.

Stateful Firewalls

3. Which type of firewall intercepts all traffic prior to forwarding it to its final destination? In a sense, these firewalls act on behalf of the recipient by ensuring the traffic is safe prior to forwarding it.

Application Gateways

4. Which type of firewall examines data within a packet as it progresses through a network interface by examining source and destination IP address, port number, and packet type—all without opening the packet to inspect its contents?

Stateless/Packet Filtering Firewalls

5. Which type of firewall filters solely based on source and destination MAC address?

MAC Firewalls

Optional Additional Challenge Lab: “Green Eggs & SPAM”

In this activity, you will target spam, uncover its whereabouts, and attempt to discover the intent of the attacker.

- You will assume the role of a junior security administrator working for the Department of Technology for the State of California.

- As a junior administrator, your primary role is to perform the initial triage of alert data: the initial investigation and analysis followed by an escalation of high-priority alerts to senior incident handlers for further review.
- You will work as part of a Computer and Incident Response Team (CIRT), responsible for compiling **threat intelligence** as part of your incident report.

Threat Intelligence Card

Note: Log in to the Security Onion VM, and use the following **indicator of attack** to complete this portion of the assignment.

Locate the indicator of attack in Sguil based off of the following:

- **Source IP/port:** 188.124.9.56:80
- **Destination address/port:** 192.168.3.35:1035
- **Event message:** ET TROJAN JS/Nemucod.M.gen downloading EXE payload

Answer the following questions:

1. What was the indicator of an attack? (*Hint: What do the details reveal?*)

Malware downloaded

2. What was the adversarial motivation (purpose of the attack)?

Steal private information

3. Describe observations and indicators that may be related to the perpetrators of the intrusion. Categorize your insights according to the appropriate stage of the cyber kill chain, as structured in the following table:

TTP	Example	Findings
Reconnaissance	How did the attacker locate the victim?	Passive reconnaissance

Weaponization	What was downloaded?	Trojan malware
Delivery	How was it downloaded?	JavaScript file embedded in a ZIP file that is attached to an email message
Exploitation	What does the exploit do?	Steals private information
Installation	How is the exploit installed?	Malware installed in background after user opens corrupted file
Command & Control (C2)	How does the attacker gain control of the remote machine?	Connect to remote host
Actions on Objectives	What does the software that the attacker sent do to complete its tasks?	Nemucod may also open a separate document as a decoy to mislead the user.

4. What are your recommended mitigation strategies?

Install intrusion detection system to monitor inbound/outbound traffic, and a preventative control to handle threats in real-time.

5. List your third-party references.

<https://www.f-secure.com/v-descs/trojan-downloader-js-nemucod.shtml>