

Head Office:
06 Trench Road, Hyde Park Industrial Estate T +44 (0)28 9034 2655
Newtownabbey, Belfast, BT36 4TY F +44 (0)28 9034 2651

sales@fortress-sefa.com
www.fortress-sefa.com

NBS L20/480

METAL GATES

Version 01/Jan 2019/Page 1 of 2

APPENDIX 29

FORTRESS SGS15 & SGS18 STEEL MESH DOUBLE GATE

Product Reference	Fortress Double Steel Fully Mesh Gate.
Description	Flush double steel gate with a fully meshed metal infill construction, designed for general purpose industrial and commercial applications.
Size	Structural opening size: Standard 1575mm x 2100mm or 1800mm x 2100mm Frame size: 1565mm x 2095mm or 1790mm x 2095mm Door leaf size: 784mm x 2039mm or 884mm x 2039mm
Performance	Insulation Material Thermal performance: U-value N/A Door Assembly Thermal performance: Max U-value N/A. Acoustic performance: Up to Weighted Level Difference D_w value N/A. Air flow: 80% Fire performance: N/A. Security rating: N/A BS EN 12206-1 (2004) Application of architectural powder coating.
Door Leaf	50x50 angled frame 5mm thick with 2.5mm 25x25 weld mesh infill panel welded internally. Door is blanked, reinforced, drilled and tapped for mortised, templated hardware. Door reinforced, where required, for surface mounted hardware. Leading edge of the active leaf incorporates a security astragal.
Frame	50 x 50 5mm thick RHS frame fully welded for additional strength and rigidity. Strike and hinge jambs can be adjusted in length to suit finished floor levels.
Threshold	N/A
Hardware	Gate leaves are hung with 3 No. 100mm stainless steel hinges. For added security an internal dog bolt security pin hinge can be supplied which prevents the door from being removed from the opening by forced entry. High-frequency hinge reinforcement with a return bend for additional strength. As standard, doors are provided with Fortress hardware solution for architectural ease.
Finish	Door leaf and frame are supplied BS EN 12206-1 polyester power coated (PPC) to the Fortress Pro-tec range of 29 BS and RAL colours from DuPont®. Matt PPC finishes only. All finishes are applied in-house using an electrostatic process. Under normal circumstances average film thickness of 60-80µm (microns) is applied. Non-standard colours are available on request - this may increase lead times. Poly Zinc Marine grade PPC available upon request.
Options	Over panels (Solid, Weld Mesh or Louvred). Side panels (Solid, Weld Mesh or Louvred). Mullions. Transoms. Sills. Weather Bars
Accessories	Fortress Panic bolt. Fortress Panic latch. Fortress Door closer. Fortress Sash lock, Lever handle, Escutcheons & Double Euro Cylinder Fortress Deadlock, Escutcheons & Double Euro Cylinder Fortress Night Latch, Lever handle, Escutcheon and Half Cylinder Fortress Pull Handles. Fortress Kick/push plates. Fortress Friction stays. Fortress Gate slide bar lock Fortress Hasp & Staple

We reserve the right to alter specifications without prior notice. Copyright © 2016 Fortress SEFA LLP.

Belfast	Dublin	Dundee	Glasgow	Manchester	London
Uppsala	Stockholm	Göteborg	Malmö	Gdańsk	Warsaw

Head Office:

06 Trench Road, Hyde Park Industrial Estate T +44 (0)28 9034 2655
Newtownabbey, Belfast, BT36 4TY F +44 (0)28 9034 2651

sales@fortress-sefa.com
www.fortress-sefa.com

NBS L20/480

METAL GATES

Version 01/Jan2019/Page 2 of 2

APPENDIX 29

FORTRESS SGS15 & SGS18 STEEL MESH DOUBLE GATE

**Standard DuPont®
Colour Range**

BS 00A05; BS 08B29; BS 04E53; BS 12B27; BS 18B25; BS 18E53; RAL 1015;
RAL 1021; RAL 3005; RAL 3020; RAL 5003; RAL 5005; RAL 5010; RAL 5013;
RAL 5015; RAL 6005; RAL 6029; RAL 7016; RAL 7021; RAL 7031; RAL 7035;
RAL 7037; RAL 8016; RAL 9001; RAL 9005 (BLACK); RAL 9006 (SILVER);
RAL 9007; RAL 9010 (WHITE); RAL 9910.

Services

Fortress SEFA provides a full technical advice service.
NBS Specifications.
RIBA CPD.

Manufacturer

Fortress Pro-Tec Ltd. 120 Old Coach Road, Templepatrick, Ballyclare, County
Antrim, BT39 0HA.
Tel: +44 (0)28 9443 3693. Fax: +44 (0)28 9034 2651.
Email: info@fortress-sefa.com Web: www.fortress-sefa.com