

Head Office:

06 Trench Road, Hyde Park Industrial Estate  
Newtownabbey, Belfast, BT36 4TY

T +44 (0)28 9034 2655  
F +44 (0)28 9034 2651

sales@fortress-sefa.com  
www.fortress-sefa.com

## NBS L20/610

## ROLLER SHUTTERS

Version 06/Jan 2016/Page 1 of 2

## APPENDIX 08

## FORTRESS FC50 STANDARD COMMERCIAL

<b>Product Reference</b>	Fortress FC50 Commercial Roller Shutter.
<b>Description</b>	A single-skinned galvanised steel roller shutter designed to protect the building from the unwanted attentions of both the opportunist and the planned attack thief.
<b>Application</b>	Fortress FC50 is ideally suited to office, commercial and retail premises. Typical applications include exhibition halls, shopping centres, department stores, shop fronts, schools, hotels and community buildings.
<b>Size</b>	Under standard construction dimensions up to 3000mm x 3000mm. Last revision August 2008. Larger sizes by specification. Please consult Fortress SEFA for advice.
<b>Performance</b>	CE-marked: Product Standard BS EN 13241-1 2003 + A1:2011. BS EN 12604 Industrial, commercial and garage doors and gates. Mechanical aspects - Requirements. BS EN 12453 Industrial, commercial and garage doors and gates. Safety in use of power operated doors - Requirements. BS EN 12424 Industrial, commercial and garage doors and gates. Resistance to wind load: BSEN 12424:2000, Classification 5. Manufacturer's Declaration of Conformity in accordance with the Construction Products Directive 2013. Manufacturer's Declaration of Incorporation in accordance with the Machinery Directive 98/37/EC.
<b>Arrangement</b>	Vertical roller shutter for face fixing.
<b>Barrel</b>	Mild steel tube finished with one coat rust inhibitive primer.
<b>End Plates</b>	4mm-6mm (depending on curtain size/weight) mild steel plates finished with one coat rust inhibitive primer.
<b>Curtain</b>	Interlocking galvanised steel laths, 50mm in depth, with solid flat profile restrained laterally by end locks riveted to both ends on alternate laths. BS EN 12453 Galvanised steel roll-formed base bar with Fortress Anti-Catch System™ designed to avoid any lifting hazard.
<b>Guides</b>	BS EN 12424 Fortress DB50 G-channel™ 2mm/ 3mm Z-steel roll-formed guides with concealed fixing. Fortress DB50 G-channel™ patented roll-formed guide design ensures that no sharp edges are exposed.
<b>Coil Casing</b>	BS EN 12453 galvanised sheet steel coil casing as standard.
<b>Finish</b>	Standard finish is galvanised steel curtain, guides, coil casing and bottom rail, with non-galvanised components finished with one coat rust inhibitive primer.
<b>Operation</b>	BS EN 12453 Fortress FC IBM™ single-phase operator with normal day to day operation by low voltage key switch (24 Volt).

Head Office:

06 Trench Road, HydePark Industrial Estate  
Newtownabbey, Belfast, BT36 4TY

T +44 (0)28 9034 2655  
F +44 (0)28 9034 2651

sales@fortress-sefa.com  
www.fortress-sefa.com

**NBS L20/610**

**ROLLER SHUTTERS**

Version 06/Jan 2016/Page 2 of 2

**APPENDIX 08**

**FORTRESS FC50 STANDARD COMMERCIAL**

## OPTIONAL EXTRAS

### Operating Controls

BS EN 12453 Fortress 2149/ 2035 controls complete with self-checking safety Edge and photocell for applications where there are untrained door users.  
2020 Low voltage unit for 24 Volt control.  
2035 Auto remote/ Dead-man close.  
2134 Group command.  
2 button handset.  
4 button handset.  
BE Easy remote with up/down control.  
Rocker switch.  
Keyed switch system for alarm interface.

### Accessories

Self-checking safety edge (will stop and reverse the door movement immediately upon contact with an obstacle).  
Photocell (light beam sensor will detect the presence of a person or object that interrupts the light beam providing a non-contact safety system).

### Curtain

N/A

### Finishes

Door curtain and guides can be supplied BS EN 12206-1 DuPont® polyester powder coated (PPC) to the Fortress Pro-Tec range of 29 BS and RAL colours. Matt PPC finishes only. All finishes are applied in-house using an electrostatic process. Under normal circumstances average film thickness of 60-80µm (microns) is applied. Non-standard colours are available on request - this may increase lead times. Please consult Fortress SEFA for advice.

### Standard DuPont® Colour Range

BS 00A05; BS 08B29; BS 04E53; BS 12B27; BS 18B25; BS 18E53; RAL 1015; RAL 1021; RAL 3005; RAL 3020; RAL 5003; RAL 5005; RAL 5010; RAL 5013; RAL 5015; RAL 6005; RAL 6029; RAL 7016; RAL 7021; RAL 7031; RAL 7035; RAL 7037; RAL 8016; RAL 9001; RAL 9005 (BLACK); RAL 9006 (SILVER); RAL 9007; RAL 9010 (WHITE); RAL 9910.

### Services

Fortress SEFA provides a full technical advice service.  
NBS Specifications.  
RIBA CPD.

### Manufacturer

Fortress Pro-Tec Ltd. 120 Old Coach Road, Templepatrick, Ballyclare, County Antrim, BT39 0HA.  
Tel: +44 (0)28 9443 3693. Fax: +44 (0)28 9034 2651.  
Email: info@fortress-sefa.com Web: www.fortress-sefa.com