120 No. 8p
Date 18/9/211
Wheelass LAN.
Alm:
To configure usualess LAN curing ciso packet
traces.
Porcedure:
Dereate network with 3 pcs & wellers nout
2) Right click on vivieles nouter. Note IP
address. [192.168.0.1]
→ DPSable DHCP Server
- Save settings
I allak on willess on same page
-> change now to Myttome Network -> Same selling
and clack on wireless security + charge
Security mode to WEP from desabled.
tod Key 1: 0123456-189
- Then close window.
H) NOUT OLEPONO ID 1- 1800 DOL
4) Now assign IP to the PC's
Pco = 192.168.0.5 gateway = 192.168.0.1
•
PC1 = 192.168.0.6 gateway = 192.168.0.1
PC2 = 192.768.0.7
gateway = 192.168.0.1
Dow allow on Pco
-tcleck physical option

Drag the poot in the draguam to the left menu Tuom on that Now click on desktop >pc usualless click connect -> ofte Information -> connect

Type '0123456789' Pn wet kly 1

Connect 6) Repeat step 5 foor PCI & PC2.

what is a well to fit

Thus packets could be transmitted via 1915 | Lost | time | period Num

Strutation panel Event 1954

vila	tPme (sec)	Last Devices
wash k	0.001	DED.
algorit		Wheles souter o
1 (2), 1000, 100	110.008	Woolers soutes o
V9s	Pble 0.012	Care Laborate Library

Student observation

a) What is SSID of wireless Router?

Souther set identifier is name assigned to worders network, allowing dewies to connect to the connect with. This helps to distinguish one network from others in same are b) what is account in the connect with the point of the connect with the point of the connect with the helps to distinguish one network from others in same are

b) What is security key in usuales router Security key is password on code cased to protect usualess network ensuring only authorised users can connect. Common types are WEP, WPA etc.

Thus woulders IAN has been configured successfully using cisco. Packet traces.