

1 Data

Cognitive-Reframing data

Sharma et al. (2023), 600 rows
pinned commit + SHA-256

Item builder

situation + thought -> user turn
thinking-trap labels normalised

Crisis screen

deterministic, before generation
flagged items excluded

Seeded split of reframes

40 calibration
remainder held out

2 Systems under test

System prompts

neutral | MCT | MCT + boundary
identical except one paragraph
on restructuring

Models

Qwen2.5 1.5B | Llama-3 8B

Ollama, local only

3 prompts x 2 models = 6 arms
T = 0.3, top-p = 0.9, fixed seed

Authored known negatives

40 non-reframing texts

3 Scoring

Lexical scorers

content reframing [RQ1]
process orientation
metacognitive beliefs [RQ2]
technique offered [RQ3]

Judge (Mistral 7B)

not under test
REFRAMES / NO rubric

Calibration

sens. + spec. on 40 + 40
criterion fixed in advance

Held-out validation [RQ4]

sensitivity on reframes

4 Analysis

Outputs

results/table_*.csv, summary.json
figures/*.png, *.pdf

Analysis

RQ1, RQ2
exact McNemar, paired
6 fixed contrasts
Holm-corrected

RQ3
chi-square, Cramer's V

RQ4
sensitivity, specificity
Wilson 95% CI

judge vs lexical
Cohen's kappa

eligible
items

replies

40 reframes

held-out reframes