

1 | 2





NOTES:

MATERIAL:


HOUSING: HIGH THERMOPLASTIC RESIN, UL94V-0, COLOR: BLACK TERMINAL: COPPER ALLOY


SHELL: STAINLESS

2. FINISH:


CONTACT AREA: GOLD PLATED
CONTACT SOLDER AREA: GOLD FLASH
SHELL: MATTE TIN PLATED
UNDER NICKEL PLATED ALL OVER.


- 3. PRODUCT SPECIFICATION: GS-12-641.
- 4. PACKAGING SPECIFICATION: GS-14-2180.
- 5. THE 'LF' MEANS FOR LEAD FREE AND CAN WITHSTAND EXPOSE TO 260°C PEAK TEMPERATURE FOR 10 SECONDS IN IR REFLOW PROCESS.






1 |





APPU:



REFERANCE PCB LAYOUT

Item	Title	Q'TY
1	Shell	1
2	Terminal	5
3	InsertMolding	1

mat	'l. c		surface / tolerance						projection			pro	duct	fam	ily	1	ICD							
						ASME Y14.5 ✓ ASME Y14.5							5	1			USB							
ltr	ecn	o	dr	dat	e	toler	ınces	unles	s othe	rwise	specit	ied 🖰	7	コ	titl	e								
Α			LS	10/2	1/11	angl	م تو		.X±0	X±0.38		ММ			1	000	LICE		TVD	- D	-0	DT 4 C		
						lanige	uligres a .xx±0				±0.25						025	3 8	ITP	E KI	ECEPTA		CLE	
						X°±	<u>2°</u> −	.xxx±			(X±0.10		le		1									
						dr JASON HSU		05/2	1/11			dwg	no			s	heet	1 о	f 1	size				
						engr	JASON HSU JASON HSU				FC					1	Ω1	10101				١,		
						chr								10118194								A4		
		appd GARY HSIEH 05/				05/2	1/11	1	-		type CUSTOMER Drawing													
shee	et	revi	sion	Α																				
index		sheet		1																				

В

form: A4mmXLc

2

3