Started on	Monday, 28 September 2026, 9:44 PM
State	Finished
Completed on	Monday, 28 September 2026, 9:54 PM
Time taken	10 mins 4 secs
Marks	1.00/1.00
Grade	**10.00** out of 10.00 (**100**%)

Question 1 | Correct Mark 1.00 out of 1.00

Given two arrays array_One[] and array_Two[] of same size N. We need to first rearrange the arrays such that the sum of the product of pairs(1 element from each) is minimum. That is SUM (A[i] * B[i]) for all i is minimum.

For example:

Input	Result
3 1 2 3 4 5 6	28

Answer: (penalty regime: 0 %)

```
#include<stdio.h>
int main(){
    int n,i,j,temp;
    int a[100],b[100];
    int sum=0;
    scanf("%d",&n);
    for(i=0;i<n;i++)
        scanf("%d",&a[i]);
    for(i=0;i<n;i++)
    scanf("%d",&b[i]);
    for(i=0;i<n;i++){
        for(j=i+1;j<n;j++){
            if(a[i]>a[j]){
                temp=a[i];
                a[i]=a[j];
                a[j]=temp;
            }
        }
    }
    for(i=0;i<n-1;i++){
        for(j=i+1;j<n;j++){
            if(b[i]<b[j]){
                temp=b[i];
                b[i]=b[j];
                b[j]=temp;
            }
        }
    }
    for(i=0;i<n;i++){
        sum=sum+a[i]*b[i];
    }
    printf("%d",sum);
    return 0;
}
```

	Input	Expected	Got	
✔	3 1 2 3 4 5 6	28	28	✔

	Input	Expected	Got	
✔	4 7 5 1 2 1 3 4 1	22	22	✔
✔	5 20 10 30 10 40 8 9 4 3 10	590	590	✔

Passed all tests! ✔

Correct

Marks for this submission: 1.00/1.00.