




DT-Grey




DT-Green



DT-Brown



DT-Black



PDM25 V2

Connector	Pin	Role	Label	Notes
1-DT-Grey	1	Input 12	HORN	I12 HORN PDM.IN.HORN 0.75mm ² br/bl Hornknapp via slip ring Active Low, 10k Ω ext PU till busbar
1-DT-Grey	2	Input 10	WIPER_SLO	I10 WIPER SLO PDM.IN.WIPER.SLO 0.75mm ² gn E22 torkaromk. kl.53 Momentary, via busbar
1-DT-Grey	3	Input 8	WASHER	I8 WASHER PDM.IN.WASHER 0.75mm ² gn/ro Höger spak (dra) Momentary, via busbar
1-DT-Grey	4	Input 6	TURN_R	I6 TURN R PDM.IN.TURN-R 0.75mm ² sw/gn Blinkerspak höger Momentary, via busbar
1-DT-Grey	5	Input 4	BRAKE	I4 BRAKE PDM.IN.BRAKE 2.0mm ² sw/ro Broms usbrytare Momentary, batt'switch'I4
1-DT-Grey	6	Input 2	HIBEAM	I2 HIBEAM PDM.IN.HIGHBEAM 0.75mm ² ge E4 helljusspak kl.56b Latching
1-DT-Grey	7	Input 1	BLOWER	I1 BLOWER PDM.IN.BLOWER 0.75mm ² sw/ge E9 fläktvred (4.7k+4.7k) Analog, EMA 5
1-DT-Grey	8	Input 3	HAZARD	I3 HAZARD PDM.IN.HAZARD 0.75mm ² — Varningsblinkersknapp Latching, via busbar
1-DT-Grey	9	Input 5	TURN_L	I5 TURN L PDM.IN.TURN-L 0.75mm ² sw/ws Blinkerspak vänster Momentary, via busbar
1-DT-Grey	10	Input 7	PARK	I7 PARK PDM.IN.PARK 0.75mm ² — Parkljusswitch Momentary, via busbar
1-DT-Grey	11	Input 9	WIPER_FST	I9 WIPER FST PDM.IN.WIPER.FST 0.75mm ² sw/gr E22 torkaromk. kl.53b Momentary, via busbar
1-DT-Grey	12	Input 11	COOLANT	I11 COOLANT PDM.IN.COOLANT 0.75mm ² gn G2 NTC kyltemp Analog, 1k Ω PU'5V, EMA 10
2-DT-Green	1	Input 16	IGNITION	O19 REVERSE PDM.OUT.REVERSE 2.0mm ² sw/bl M16+M17 backljus Fn: I14 Status
2-DT-Green	2	Input 15	START	O23 STARTER PDM.OUT.STARTER 2.5mm ² ro/sw Startrelä terminal 50 Fn: GF1 AND I15, Stay On 0s
2-DT-Green	3	Power		O25 TURN L (F) PDM.OUT.TURN-L-F 1.5mm ² sw/ws M5 blinkers V fram Fn: T1 AND (I5 OR I3), dual-pin B3+B10
2-DT-Green	4	Output 3	IGN_COIL	O15 LOWBEAM R PDM.OUT.LOWBEAM-R 2.5mm ² ge L2 höger kl.56a Fn: GF1, Delay 3s
2-DT-Green	5	Output 2	WIPER_FST	O14 LOWBEAM L PDM.OUT.LOWBEAM-L 2.5mm ² ge/sw L1 vänster kl.56a Fn: GF1, Delay 3s
2-DT-Green	6	Output 1	BUSBAR	O13 HORN PDM.OUT.HORN 2.0mm ² sw/ge H1 signalhorn Fn: I12 Status, Peak 8A/0.5s
2-DT-Green	7	GND		O10 WIPER SLO PDM.OUT.WIPER.SLO 2.5mm ² gn V torkarmotor kl.53 Fn: I10 Status, Soft Start 1s
2-DT-Green	8	CAN-1 High		O11 BLOWER PDM.OUT.BLOWER 2.5mm ² sw/ge V2 kupéfäkt Fn: GF1 AND I1>1V, PWM, Stay On 30s
2-DT-Green	9	CAN-1 Low		O12 WASHER PDM.OUT.WASHER 1.5mm ² gn/ro V5 spolarpump Fn: I8 Status
2-DT-Green	10	5V Out		O25 TURN L (B) PDM.OUT.TURN-L-R 1.5mm ² sw/ws M6 blinkers V bak Dual-pin parallell med B3
2-DT-Green	11	Input 13	FUEL_LVL	O22 USB 12V PDM.OUT.USB12V 1.5mm ² — 12V USB-uttag Fn: GF1
2-DT-Green	12	Input 14	REVERSE	O18 RADIO MEM PDM.OUT.RADIO.MEM 1.0mm ² — Radio permanent minne Fn: Always True
3-DT-Brown	1	Output 17	RESERVE17	I16 IGNITION PDM.IN.IGNITION 2.5mm ² sw/ge Tändningsåls terminal 15 Momentary Active High
3-DT-Brown	2	Output 21	RPI	I15 START PDM.IN.START 2.5mm ² sw/ws Tändningsåls terminal 50 Momentary Active High
3-DT-Brown	3	Output 24	TURN_R	PDM POWER PDM.PWR.CTRL 4mm ² ro Startmotor kl.30 via fränskljare Batteri always-on
3-DT-Brown	4	Output 9	RESERVE_9	O3 IGN COIL PDM.OUT.IGNITION 1.5mm ² sw/li N6 seriemotstånd (tändspole) Fn: GF1, HS/L5'HS
3-DT-Brown	5	Output 8	RESERVE_8	O2 WIPER FST PDM.OUT.WIPER.FST 2.5mm ² sw/gr V torkarmotor kl.53b Fn: I9 Status, HS/L5'HS
3-DT-Brown	6	Output 7	HIBEAM_R	O1 BUSBAR PDM.OUT.BUSBAR 0.75mm ² — Signalbusbar (terminalblock) Always True, 3.0A fuse, HS/L5'HS
3-DT-Brown	7	Output 4	BRAKE	GND PDM.GND.CHASSIS 10mm ² br Chassijord punkt 12 Systemjord
3-DT-Brown	8	Output 5	FUEL	CAN HIGH PDM.CAN.H 0.75mm ² ws (vinnad) RPI CAN High 250 kbps
3-DT-Brown	9	Output 6	PARK	CAN LOW PDM.CAN.L 0.75mm ² sw (vinnad) RPI CAN Low 250 kbps, intern term. aktiv
3-DT-Brown	10	Output 24	TURN_R	5V REF PDM.5V.REF — Sensorutgång 100mA max, till I11+I13 PU
3-DT-Brown	11	Output 20	RADIO_ACC	I13 FUEL_LVL PDM.IN.FUEL_LVL 0.75mm ² li/sw G bränslegivare Analog, 100 Ω PU'5V, EMA 10
3-DT-Brown	12	Output 16	HIBEAM_L	I14 REVERSE PDM.IN.REVERSE 0.75mm ² sw/bl Backväxelkontakt Momentary, batt'switch'I14
4-DT-Black	1	Output 19	REVERSE	O17 RESERVE — — Ledig HS output
4-DT-Black	2	Output 23	STARTER	O21 RPI PDM.OUT.RPI 2.0mm ² — Raspberry Pi 5 + CAN HAT Fn: Always True, Soft Start 2s
4-DT-Black	3	Output 25	TURN_L	O24 PARK (F) PDM.OUT.PARK-F 1.5mm ² gr M1+M3 sidoljus fram Fn: I7 Status, dual-pin D3+D10
4-DT-Black	4	Output 15	LOWBEAM_R	O9 RESERVE — — Ledig HS output
4-DT-Black	5	Output 14	LOWBEAM_L	O8 RESERVE — — Ledig HS output
4-DT-Black	6	Output 13	HORN	O7 HIBEAM R PDM.OUT.HIGHBEAM-R 2.5mm ² ws L2 höger kl.56b Fn: O15 AND I2
4-DT-Black	7	Output 10	WIPER_SLO	O4 BRAKE PDM.OUT.BRAKE 2.0mm ² sw/ro M9+M10 bromsljus Fn: I4 Status, Instant trip, HS/L5'HS
4-DT-Black	8	Output 11	BLOWER	O5 FUEL PDM.OUT.FUEL 1.5mm ² sw G6 bränslepump Fn: GF1, Stay On 2s
4-DT-Black	9	Output 12	WASHER	O6 TURN R PDM.OUT.TURN-R 1.5mm ² sw/gn M7+M8 blinkers H Fn: T1 AND (I6 OR I3)
4-DT-Black	10	Output 25	TURN_L	O24 PARK (B) PDM.OUT.PARK-R 1.5mm ² gr/sw M4+M2 parkljus bak Dual-pin parallell med D3
4-DT-Black	11	Output 22	USB_12V	O20 RADIO ACC PDM.OUT.RADIO.ACC 1.5mm ² — Radio ACC Fn: GF1
4-DT-Black	12	Output 18	RADIO_MEM	O16 HIBEAM L PDM.OUT.HIGHBEAM-L 2.5mm ² ws/sw L1 vänster kl.56b Fn: O14 AND I2

