

Compiled Notes

Joseph Marino

July 14, 2017

Contents

1	Motivation	1
1.1	Intelligence	1
2	Probability & Statistics	2
2.1	Probability Basics	2
2.1.1	Definitions	2
2.1.2	Distributions	2
3	Information Theory	3
3.1	Basic Concepts	3
4	Neuroscience	5
4.1	Neurons	5
4.2	Neural Circuits	5
4.3	Brain Structures	5
5	Neural Networks	6
5.1	Basics	6
5.1.1	Linear Threshold Units	6
5.1.2	Multi-Layer Perceptrons	6
5.1.3	Backpropagation	6
6	Graphical Models	7
7	Representations & Representation Learning	8
7.1	Motivation & Definitions	8
7.2	Disentangled Representations	8
8	Programming & Experimental Practices	10
8.1	GitHub	10
8.2	Logging	11
8.3	Plotting	11
A	Appendix 1	12

Chapter 1

Motivation

1.1 Intelligence

Intelligence is a vaguely defined concept. In many situations, we often use the term to refer to the ability to perceive and understand certain concepts, such as math, art, politics, business, etc. But this narrow definition is human specific, ill-stated, and fails to capture the broad spectrum that intelligence occupies. Instead, I will use the following definition:

Intelligence is the ability of a system to perform meaningful actions within a particular environment.

Chapter 2

Probability & Statistics

2.1 Probability Basics

2.1.1 Definitions

2.1.2 Distributions

Chapter 3

Information Theory

3.1 Basic Concepts

Entropy is a measure of the uncertainty of a random variable. It tends to agree with the notion of information. Let X be a random variable, with alphabet \mathcal{X} and probability mass function $p(x) = \Pr(X = x)$, with $x \in \mathcal{X}$. The entropy of X is defined as

$$H(X) = - \sum_{x \in \mathcal{X}} p(x) \log p(x). \quad (3.1)$$

The units of entropy depend on the base of the logarithm. If the base is 2, then the units are in bits. If the base is e , then the units are in nats. To convert between different units of entropy, use $H_b(X) = (\log_b a) H_a(X)$. Note that entropy can be interpreted as the expectation of $-\log p(x)$. Also, entropy is non-negative: $H(X) \geq 0$.

The **joint entropy** of multiple random variables is defined similarly:

$$H(X, Y) = - \sum_{x \in \mathcal{X}} \sum_{y \in \mathcal{Y}} p(x, y) \log p(x, y) \quad (3.2)$$

Likewise, the **conditional entropy** is defined as

$$\begin{aligned} H(Y|X) &= \sum_{x \in \mathcal{X}} p(x) H(Y|X = x) \\ &= - \sum_{x \in \mathcal{X}} p(x) \sum_{y \in \mathcal{Y}} p(y|x) \log p(y|x) \\ &= - \sum_{x \in \mathcal{X}} \sum_{y \in \mathcal{Y}} p(x, y) \log p(y|x). \end{aligned}$$

Note that

$$H(X, Y) = H(X) + H(Y|X). \quad (3.3)$$

In words, joint entropy = individual entropy + conditional entropy. This also implies that

$$H(X, Y|Z) = H(X|Z) + H(Y|X, Z). \quad (3.4)$$

Because conditional entropy involves the conditional probability, we see that $H(Y|X) \neq H(X|Y)$. However,

$$H(X) - H(X|Y) = H(Y) - H(Y|X). \quad (3.5)$$

Relative entropy is a measure of the distance between two distributions. Put differently, it is the inefficiency of assuming the distribution of the data is $q(x)$ when the true distribution is $p(x)$. This is also referred to as the **Kullback-Leibler distance** or **divergence**.

$$D_{KL}(p(x)||q(x)) = \sum_{x \in \mathcal{X}} p(x) \log \frac{p(x)}{q(x)} = \mathbb{E}_{x \sim p(x)} \left[\log \frac{p(x)}{q(x)} \right] \quad (3.6)$$

Note that if there is a value $x \in \mathcal{X}$ such that $p(x) > 0$ and $q(x) = 0$, then $D_{KL} = \infty$. KL divergence is non-negative and is only zero when $p(x) = q(x)$. It is not symmetric, so it is not a proper distance measure.

Mutual Information is the amount of information that one random variable contains about another random variable. In other words, it is the reduction in the uncertainty of one random variable due to knowledge of the other. It is expressed as the relative entropy between the joint distribution $p(x, y)$ and the product of the marginals $p(x)p(y)$.

$$\begin{aligned} I(X; Y) &= \sum_{x \in \mathcal{X}} \sum_{y \in \mathcal{Y}} p(x, y) \log \frac{p(x, y)}{p(x)p(y)} \\ &= D_{KL}(p(x, y)||p(x)p(y)) \\ &= \mathbb{E}_{x, y \sim p(x, y)} \left[\log \frac{p(x, y)}{p(x)p(y)} \right]. \end{aligned}$$

This can also be written as

$$I(X; Y) = H(X) - H(X|Y) = H(Y) - H(Y|X). \quad (3.7)$$

Thus, *X says as much about Y as Y says about X*. In words, mutual information is the amount of information in X minus the amount of information in X after observing Y (and vice versa). This corresponds to the amount of information in X that is explained by Y (and, again, vice versa). If Y perfectly explains X , then $H(X|Y) = 0$, so $I(X; Y) = H(X)$. At the other extreme, if Y says nothing about X , then $H(X|Y) = H(X)$, so $I(X; Y) = 0$. Also,

$$I(X; Y) = H(X) + H(Y) - H(X, Y), \quad (3.8)$$

and

$$I(X; X) = H(X) - H(X|X) = H(X). \quad (3.9)$$

Thus, entropy can be considered as the amount of self-information.

Chapter 4

Neuroscience

4.1 Neurons

4.2 Neural Circuits

4.3 Brain Structures

Chapter 5

Neural Networks

5.1 Basics

5.1.1 Linear Threshold Units

5.1.2 Multi-Layer Perceptrons

5.1.3 Backpropagation

Chapter 6

Graphical Models

Chapter 7

Representations & Representation Learning

7.1 Motivation & Definitions

Overview of types of representations. How do we learn representations? What training criteria/conditions result in different representations? Are certain representations better than others? In which cases and why?

7.2 Disentangled Representations

Define disentanglement. Why are disentangled representations helpful? Trade off between disentanglement and faithfully representing the data. How do we learn disentangled representations, while at the same time, respecting the structure of the latent space? Importance of priors.

Two random variables are **independent** if their joint probability can be expressed as the product of their marginals:

$$p(\mathbf{x}, \mathbf{y}) = p(\mathbf{x})p(\mathbf{y}), \quad (7.1)$$

and they are **conditionally independent** if their conditional joint probability can be expressed as

$$p(\mathbf{x}, \mathbf{y} | \mathbf{z}) = p(\mathbf{x} | \mathbf{z})p(\mathbf{y} | \mathbf{z}). \quad (7.2)$$

Independence is related to covariance, but is a stronger property. Two variables that are independent have zero covariance and two variables that have non-zero covariance are dependent. Zero covariance implies that the variables have no *linear* dependence. Independence implies that the variables also have no *non-linear* dependence. That is, it is possible for two dependent variables to have zero covariance.

Notes:

In *Discovering Hidden Factors of Variation in Deep Networks* (2014), Chung et al. propose using a cross-covariance penalty term in the setting of semi-supervised learning of

the form:

$$C(\hat{\mathbf{y}}^{1\dots N}, \mathbf{z}^{1\dots N}) = \frac{1}{2} \sum_{ij} \left[\frac{1}{N} \sum_n (\hat{y}_i^n - \bar{\hat{y}}_i)(z_j^n - \bar{z}_j) \right]^2, \quad (7.3)$$

where $\hat{\mathbf{y}}$ is a vector of (one-hot) inferred labels and \mathbf{z} is a latent representation. N is the batch size.

In Early Visual Concept Learning with Unsupervised Deep Learning (2016), Higgins et al. propose to use a regularization weight in a VAE setting to “upweight” the amount of regularization as a means of promoting **redundancy reduction and independence** among the latent representation. They also argue for the importance of **dense sampling of the (continuous) data manifold** for disentanglement. Sparse sampling of the data manifold results in ambiguity in the manifold interpretation, requiring additional supervision for disentanglement.

In Inducing Interpretable Representations with Variational Autoencoders (2016), Sidharth et al. use supervision to impose structure on part of the latent representation in a VAE.

Dropout is a technique for preventing “fragile coadaptation” between units within a representation, effectively enforcing that they represent different (independent) quantities.

Chapter 8

Programming & Experimental Practices

This chapter contains some helpful practices for carrying out (machine learning) research projects.

8.1 GitHub

GitHub is an online platform for project source control. It is essential when collaborating on projects, as it allows you to meticulously track changes and manage conflicts between multiple versions of the code. But GitHub is also helpful when working alone on a project across multiple machines or if you just want to open source your code. The following are the basic commands for using GitHub:

Clone a repository:

```
1 | git clone <repository address>
```

Add a file to the repository:

```
1 | git add <filename>
```

Or to add everything to the repository:

```
1 | git add .
```

or

```
1 | git add -A
```

Commit changes to the repository:

```
1 | git commit -m "<message>"
```

or

```
1 | git commit
```

Note that if you run the second command, you will enter a vi interface where you can enter a multi-line message. To exit, type esc :wq

Push all committed changes to the repository:

```
1 | git push
```

Pull the repository:

```
1 | git pull
```

To create a new branch:

```
1 | git branch <branch name>
```

Switch current branch:

```
1 | git checkout <branch name>
```

Merge branch changes back into master (while currently checking out other branch):

```
1 | git merge master
```

You can send pull requests on GitHub.com. After the branch is merged, you can delete the branch on the website.

To conclude, a good workflow practice is to (1) pull the repository at the beginning of each work session, (2) push any incremental changes at regular intervals, and (3) create new branches for any major changes to be implemented.

8.2 Logging

Maintaining proper records of experiments is an essential part of conducting good research. Scientific notebooks (preferably in a digital format) are often helpful for keeping high-level notes about experiments, but one must keep experimental logs to track the different experimental set-ups that have been tested and the results. These are vital for surveying your project (what set-ups work? what set-ups should we consider trying?) and eventually communicating your results. Implementing and keeping track of these logs can seem like a hassle, but they are just as important as the experimental code itself.

8.3 Plotting

Appendix A

Appendix 1