

POST

The screenshot shows the Postman application interface. At the top, there's a header bar with the text "HTTP Morosos Api / Post". On the right side of the header are buttons for "Save", "View Documentation", and a search field containing "morosos". Below the header, the main interface has a "POST" method selected in a dropdown. The URL field contains "{{baseUrl}} {{morososPath}}". The "Body" tab is active, showing a JSON payload:

```
1 {
2   "nombre": "Joel Méndez Ruiz",
3   "dni": "12345678U",
4   "cantidad_adeudada": 4.00,
5   "fecha_alta": "2005-10-28",
6   "estado_pago": "PAGADO"
7 }
```

Below the body editor, there are tabs for "Body", "Cookies", "Headers (4)", and "Test Results". The "Test Results" tab is currently selected. It displays a status message: "Status: 500 Internal Server Error Time: 23 ms Size: 262 B". Underneath this, there are buttons for "Pretty", "Raw", "Preview", and "JSON". The "JSON" button is highlighted with a red border. The "Preview" section shows the response body:

```
1 [{"timestamp": "2025-11-20T20:01:26.634+00:00", "status": 500, "error": "Internal Server Error", "path": "/morosos"}]
```

GET

The screenshot shows a REST API testing interface with the following details:

- URL:** `HTTP Morosos Api / get`
- Method:** `GET`
- Headers:** `{baseUrl} {morososPath}`
- Params:** `Key` (Value: `Key`)
- Body:** `Body` tab selected.
- Cookies:** `Cookies` tab selected.
- Headers:** `Headers (5)` tab selected.
- Test Results:** `Status: 200 OK Time: 309 ms Size: 437 B`
- JSON Response:**

```
1 [{"id":1,"nombre":"Carlos Méndez Ruiz","dni":"12345678A","cantidad_adeudada":450.75,"fecha_alta":"2025-01-12","estado_pago":"PAGADO"}, {"id":2,"nombre":"Laura Gómez Herrera","dni":"98765432B","cantidad_adeudada":1200.0,"fecha_alta":"2025-02-05","estado_pago":"PENDIENTE"}]
```

GET BY ID

The screenshot shows the Postman interface with the following details:

- Request Method:** GET
- URL:** {{baseUrl}}/{{morososPath}}/1
- Params:** Key (Value)
- Headers:** (5)
- Body:** (Pretty, Raw, Preview, JSON)
- Response Status:** 200 OK (Time: 277 ms, Size: 297 B)
- Response Body:** [{"id":1,"nombre":"Carlos Méndez Ruiz","dni":"12345678A","cantidad_adeudada":450.75,"fecha_alta":"2025-01-12","estado_pago":"PAGADO"}]

Comprobación POST

The screenshot shows the Postman application interface. The top navigation bar includes Archivo, Editar, Selección, Ver, Ir, Ejecutar, Terminal, and Ayuda. The title bar says "morosos-app". The left sidebar shows a project named "DWES-MorososNEW" with various collection icons. The main workspace displays a "Moroso Api / get 2" collection. A "New HTTP Request" dialog is open, showing a GET method with the URL {{baseUrl}}/{{morosoPath}}/3. The "Params" tab is selected, showing a single parameter "Key" with the value "Value". Below the dialog, the "Body" tab is active, showing a JSON response:

```
1  [{"id":3,"nombre":"Joel Méndez Ruiz","dni":"12345678U","cantidad_adeudada":4.0,"fecha_alta":"2005-10-28","estado_pago":"PAGADO"}]
```

The status bar at the bottom indicates "Status: 200 OK Time: 10 ms Size: 292 B". The bottom right corner shows a terminal window titled "Run: MorosoApplication" with some log output related to Hibernate queries.

PUT

The screenshot shows the POSTMAN application interface for making a **PUT** request. The URL in the header is `PUT {{baseUrl}}/{{morososPath}}/3/estado`. The **Body** tab is selected, showing the value `PENDIENTE`. The response status is **200 OK** with a time of **35 ms** and a size of **123 B**.

PUT | {{baseUrl}}/{{morososPath}}/3/estado

Send | ▾

Params Authorization Headers (9) Body Scripts Settings

Code Cookies

none form-data x-www-form-urlencoded raw binary GraphQL Text

1 PENDIENTE

Body Cookies Headers (4) Test Results

Pretty Raw Preview Text

Status: 200 OK Time: 35 ms Size: 123 B

COMPROBACION PUT

Anteriormente estaba en pagado por lo que lo hemos cambiado

The screenshot shows the Postman application interface. At the top, there is a header bar with 'GET' selected, a dropdown for 'baseURL' and 'morososPath', and a 'Send' button. Below the header are tabs for 'Params', 'Authorization', 'Headers (7)', 'Body', 'Scripts', and 'Settings'. On the right side, there are 'Code' and 'Cookies' buttons. Under the 'Params' tab, there is a table titled 'Query Params' with one row containing 'Key' and 'Value'. In the main body area, there are tabs for 'Body', 'Cookies', 'Headers (5)', and 'Test Results'. The 'Body' tab is selected, showing a JSON response with one object. The response content is:

```
1  [{"id":3,"nombre":"Joel Méndez Ruiz","dni":"12345678U","cantidad_adeudada":4.0,"fecha_alta":"2005-10-28","estado_pago":"PENDIENTE"}]
```

At the bottom right of the main area, there are status indicators: a globe icon, 'Status: 200 OK', 'Time: 22 ms', 'Size: 295 B', and three more icons.