

Homework 4

Joseph Mulray

INFO 210

March 6, 2017

Part 1:

a.

```
select sailors.sid, name from sailors
join reserves on sailors.sid = reserves.sid
where rating >= 5 and bid=103;
```

```
SQL> select sailors.sid, name from sailors
[ 2 join reserves on sailors.sid = reserves.sid
[ 3 where rating >= 5 and bid=103;
```

SID	NAME
4	Zorba

SQL> █

b.

```
select distinct sailors.sid, sailors.name, age from sailors
join reserves on sailors.sid = reserves.sid
join boats on reserves.bid = boats.bid
where age>30 or (color='red' AND boats.bid=reserves.bid);
```

```
SQL> select distinct
  2  sailors.sid, sailors.name, age from sailors
  3  join reserves on sailors.sid = reserves.sid
  4  join boats on reserves.bid = boats.bid
  5  where age>30 or (color='red' AND
  6  boats.bid=reserves.bid);
```

SID	NAME	AGE
1	Dustin	45
2	Rusty	35
3	Horatio	35

```
SQL> █
```

c.

```
select boats.bid, color from boats
join reserves on boats.bid = reserves.bid
join sailors on reserves.sid = sailors.sid
where boats.bid=reserves.bid and name='Horatio';
```

```
SQL> select boats.bid, color from boats
  2  join reserves on boats.bid = reserves.bid
  3  join sailors on reserves.sid = sailors.sid
  4  where boats.bid=reserves.bid and
  5  name='Horatio';
```

BID	COLOR
101	blue
102	red

```
SQL> █
```

d.

```
select distinct boats.color from boats
full join reserves on boats.bid = reserves.bid
where reserves.bid is null;
```

```
SQL> select distinct boats.color from boats
  2  full join reserves on boats.bid = reserves.bid
  3  where reserves.bid is null;
```

COLOR

red

SQL> █

e.

```
select reserves.sid, reserves.bid, reserves.day
from reserves
join sailors on reserves.sid = sailors.sid
where name like '%o%';
```

```
SQL> select reserves.sid, reserves.bid, reserves.day
  2  from reserves
  3  join sailors on reserves.sid = sailors.sid
  4  where name like '%o%';
```

SID	BID	DAY
3	101	07-NOV-12
3	102	07-AUG-12
4	103	19-SEP-12

SQL> █

Part 2:

```
drop table if exists City;
drop table if exists Country;
```

```
create table Country(
Country_Name varchar(64) primary key,
Continent varchar(64) not null
);
```

```
create table City(
City_Name varchar(128),
Country_Name varchar(128),
isCapital char(3) not null,
Population number not null,
primary key(City_Name, Country_Name),
foreign key (Country_Name) references Country(Country_Name)
);
```

```
insert into Country (Country_Name, Continent) values ('US', 'North America');
insert into Country (Country_Name, Continent) values ('Canada', 'North America');
insert into Country (Country_Name, Continent) values ('England', 'Europe');
insert into Country (Country_Name, Continent) values ('Germany', 'Europe');
insert into Country (Country_Name, Continent) values ('France', 'Europe');
insert into Country (Country_Name, Continent) values ('Mali', 'Africa');
```

```
insert into City (City_Name, Country_Name, isCapital, Population) values ('New York, NY', 'US', 'y', 10000000);
insert into City (City_Name, Country_Name, isCapital, Population) values ('Washington, DC', 'US', 'y', 1000000);
insert into City (City_Name, Country_Name, isCapital, Population) values ('Philadelphia, PA', 'US', 'n', 1000000);
insert into City (City_Name, Country_Name, isCapital, Population) values ('Ottawa', 'Canada', 'n', 100000);
insert into City (City_Name, Country_Name, isCapital, Population) values ('Toronto', 'Canada', 'n', 1000000);
insert into City (City_Name, Country_Name, isCapital, Population) values ('Berlin', 'Germany', 'y', 1000000);
insert into City (City_Name, Country_Name, isCapital, Population) values ('Hamburg', 'Germany', 'n', 100000);
insert into City (City_Name, Country_Name, isCapital, Population) values ('Bonn', 'Germany', 'n', 100000);
insert into City (City_Name, Country_Name, isCapital, Population) values ('Paris', 'France', 'y', 1000000);
insert into City (City_Name, Country_Name, isCapital, Population) values ('Lyon', 'France', 'n', 100000);
insert into City (City_Name, Country_Name, isCapital, Population) values ('Bamako', 'Mali', 'y', 100000);
insert into City (City_Name, Country_Name, isCapital, Population) values ('Timbuktu', 'Mali', 'n', 100000);
insert into City (City_Name, Country_Name, isCapital, Population) values ('Mopti', 'Mali', 'y', 100000);
```

```
select Country.Country_Name from Country
full join City on Country.Country_Name = City.Country_Name
where City_Name is Null;
```

```
SQL> select Country.Country_Name from Country
2 full join City on Country.Country_Name = City.Country_Name
3 where City_Name is Null;
```

```
COUNTRY_NAME
```

```
-----
England
```

```
SQL> █
```

b.

```
select Country.Continent, Count(Country.Country_Name) as Count, Max(Population) from Country
join City on Country.Country_Name=City.Country_Name
group by Country.Continent;
```

```
SQL> select Country.Continent, Count(Country.Country_Name) as Count, Max(Population) from Country
join City on Country.Country_Name=City.Country_Name
group by Country.Continent; 2 3
```

```
CONTINENT
```

```
COUNT
```

```
-----
```

```
MAX(POPULATION)
```

```
-----
```

```
Africa 2000000 3
```

```
Europe 3500000 5
```

```
North America 8000000 5
```

```
SQL> █
```

c.

```
select City.Country_Name, AVG(Population)
from Country
join City on Country.Country_Name=City.Country_Name
group by City.Country_Name;
```

```
SQL> select City.Country_Name, AVG(Population)
from Country
join City on Country.Country_Name=City.Country_Name
group by City.Country_Name;
```

```
2      3      4
COUNTRY_NAME
```

```
-----
AVG(POPULATION)
```

```
-----
Canada
3000000
```

```
France
1350000
```

```
Germany
1933333.33
```

```
COUNTRY_NAME
```

```
-----
AVG(POPULATION)
```

```
-----
Mali
716666.667
```

```
US
3366666.67
```

```
SQL> █
```