

## NATIONAL UNIVERSITY OF SINGAPORE

## SCHOOL OF COMPUTING

## MIDTERM QUIZ

ADAPTED TO SOURCE 2021 IN 9/2020

Semester 1 AY2014/2015

## CS1101S — PROGRAMMING METHODOLOGY

1 October 2014

Time Allowed: **1 Hour 40 Minutes**

Matriculation No.:

--	--	--	--	--	--	--	--	--

**Instructions (please read carefully):**

1. Write down your **matriculation number** on the **question paper**. DO NOT WRITE YOUR NAME ON THE QUESTION SET!
2. This is an **open-sheet quiz**. You are allowed to bring one A4 sheet of notes (written or printed on both sides).
3. This paper comprises **6 questions** and **TWENTY (20)** printed pages. The time allowed for solving this quiz is **1 hour 40 minutes**.
4. The maximum score of this quiz is **60 marks**. The weight of each question is given in square brackets beside the question number.
5. All questions must be answered correctly for the maximum score to be attained.
6. All questions must be answered in the space provided in the question paper; no extra sheets will be accepted as answers.
7. The pages marked “scratch paper” in the question paper may be used as scratch paper.
8. You are allowed to use pencils or pens, as you like (no red color, please).
9. Write legibly; **UNTIDINESS will be penalized**.

**GOOD LUCK!**

Q#	1	2	3	4	5	6	Σ
MAX	5	5	7	15	11	17	60
SC							

**Question 1: Making Logical Sense [5 marks]**

Rewrite the following Source expressions without using any of the logical operators `&&`, `||`, and `!`. The result of evaluating your expression must be exactly the same as that of the original, regardless of the values of `cond_a`, `cond_b`, `do_x` and `do_y`.

**A. [1 mark]**

```
!cond_a ? do_x() : do_y()
```

**B. [2 marks]**

```
(cond_a || cond_b) ? do_x() : do_y()
```

**C. [2 marks]**

```
(cond_a && cond_b) ? do_x() : do_y()
```

**Question 2: Almost Malfunction [5 marks]****A. [4 marks]**

Consider a restricted form of Source in which functions are allowed to have at most one parameter. Rewrite the following function definition under this restriction. You must not use lists or any structure created using `pair`.

```
function myfunc(a, b, c) {  
    return a * b + c;  
}
```

**B. [1 mark]**

With your new function definition in Part A, how would you rewrite the function call `myfunc(3, 2, 1);`?

**Question 3: Function Composition Reincarnated [7 marks]**

Considered the following functions:

```
function plus_one(x) {  
    return x + 1;  
}  
  
function trans(f) {  
    return x => 2 * f(2 * x);  
}  
  
function twice(f) {  
    return x => f(f(x));  
}
```

What are the results of the following Source programs (no need for explanation)?

**A. [1 mark]**

```
trans(plus_one)(1);
```

**B. [2 marks]**

```
trans(twice(plus_one))(1);
```

**C. [2 marks]**

```
twice(trans(plus_one))(1);
```

**D. [2 marks]**

```
twice(trans)(plus_one)(1);
```

**Question 4: Binary Search Tree [15 marks]**

*[This question was posed to students with NO prior exposure to the abstraction of binary search trees. It is not the purpose of the question to properly introduce the abstraction.]*

A *binary search tree* (BST) is either null or a list with three elements: a number  $x$ , a left BST, and a right BST, where every number in the left BST is smaller than the number  $x$ , and every number in the right BST is larger than the number  $x$ .

**A. [3 mark]**

Draw the box-and-pointer diagram for the following list, which represents a BST containing the numbers 1, 2, 3 and 4.

```
list(3, list(1, null, list(2, null, null)), list(4, null, null));
```

**B. [3 marks]**

Write a Source function `BST_min` that takes a BST as its only parameter and returns the smallest number in the BST. If the BST is an empty tree, the function returns `Infinity`.

```
function BST_min(bst) {
```

```
}
```

**C. [4 marks]**

**[3 marks]** Write a Source function `BST_find` that takes a number as its first parameter and a BST as the second parameter, and returns `true` if the number is in the BST, otherwise it returns `false`.

```
function BST_find(x, bst) {
```

```
}
```

**[1 mark]** Let the number of numbers in the BST be  $n$ . Assuming that the numbers are evenly distributed to every pair of left and right BSTs, in the worst case, what would be the order of growth of runtime of `BST_find`, in  $\Theta$  notation, with respect to  $n$ ? (no need for explanation)

#### D. [5 marks]

**[4 marks]** Write a Source function `BST_to_list` that takes a BST as its only parameter and returns a list that contains only the numbers in the BST in increasing order (i.e. the smallest number appears in the front of the list). For example, applying `BST_to_list` to the BST in Part A produces the list `list(1, 2, 3, 4)`.

```
function BST_to_list(bst) {
```

**[1 mark]** Let the number of numbers in the BST be  $n$ . Assuming that the numbers are evenly distributed to every pair of left and right BSTs, what would be the order of growth of runtime of `BST_to_list`, in  $\Theta$  notation, with respect to  $n$ ? (no need for explanation)



**A. [7 marks]**

```
function find_ranks(lst) {
```

--

**B. [4 marks]**

Consider the following function:

```
function get_num(lst, ranks) {
  return rank =>
    head(ranks) === rank
    ? head(lst)
    : get_num(tail(lst), tail(ranks))(rank);
}
```

The function call `get_num(lst, ranks)(rank)` takes in `lst` (a list of unique numbers), and `ranks` (the list of ranks of the corresponding numbers in `lst`) and returns the number in `lst` that has the rank equal to `rank`.

**[3 marks]** Complete the following Source function `rank_sort`, that takes in a list of unique numbers as its only parameter and returns a list with the numbers sorted in increasing order. You must make use of the function `map`, the function `enum_list` (see Appendix) and the above `get_num` function in a correct and meaningful way.

```
function rank_sort(lst) {

  const ranks = find_ranks(lst);

}

```

**[1 mark]** Let  $n$  be the length of the input list. What is the order of growth of runtime of `rank_sort`, in  $\Theta$  notation, with respect to  $n$ ? (no need for explanation)

## Question 6: Life Skill: Writing a Cheque [17 marks]

When you use a paper-based bank cheque, you need to write out the amount in English. This exercise is about writing this number properly, without any mistakes.

For example, the number 1234 is written as “one thousand two hundred thirty four” or “one thousand two hundred and thirty four.” In this exercise, we will use the version without the word “and.”

You are to complete a Source program that takes a *positive* whole number and produces its English form.

The followings are some of the functions of the program:

```
function singles_to_english(d) {
    return list_ref(list("", "one", "two", "three",
                        "four", "five", "six",
                        "seven", "eight", "nine"), d);
}

function tens_to_english(t) {
    return list_ref(list("", "ten", "twenty", "thirty",
                        "forty", "fifty", "sixty",
                        "seventy", "eighty", "ninety"), t);
}

function ten_to_nineteen_to_english(s) {
    return list_ref(list("ten", "eleven", "twelve", "thirteen",
                        "fourteen", "fifteen", "sixteen",
                        "seventeen", "eighteen",
                        "nineteen"), s);
}

function power_of_thousand(n) {
    return list_ref(list("", "thousand", "million", "billion",
                        "trillion", "quadrillion",
                        "quintillion"), n);
}

// for each triplet of hundred/ten/single
function triplet_to_english(h, t, s) {
    const he = h > 0 ? singles_to_english(h) + " hundred" : "";
    const te = t > 0 ? tens_to_english(t) : "";
    const se = s > 0 ? singles_to_english(s) : "";
    const tese = te === "" ? se
        : t === 1 ? ten_to_nineteen_to_english(s)
        : se === "" ? te : te + " " + se;
    return he === "" ? tese
        : tese === "" ? he
        : he + " " + tese;
}
```



**C. [7 marks]**

Write a Source function `triplets_to_english` that takes a list of triplets as its only parameter, where the list has at most seven triplets, and returns a string that contains the English form of the number represented by the input list of triplets. For example, for the number 12340, the list of triplets is `list(list(0, 4, 3), list(2, 1, 0))`, and `triplets_to_english` should return the string "twelve thousand three hundred forty". Your function can call the functions `triplet_to_english` and `power_of_thousand`.

```
function triplets_to_english(triplets) {
```

```
}
```

**D. [2 marks]**

Write a Source function `number_to_english` that takes a positive whole number less than  $10^{21}$  as its only parameter and returns a string that contains the English form of the number.

```
function number_to_english(n) {
```

———— **END OF QUESTIONS** ————

## Appendix

### List Support

Source supports the following list processing functions:

- `pair(x, y)`: Makes a pair from `x` and `y`.
- `is_pair(x)`: Returns `true` if `x` is a pair and `false` otherwise.
- `head(x)`: Returns the head (first component) of the pair `x`.
- `tail(x)`: Returns the tail (second component) of the pair `x`.
- `is_null(xs)`: Returns `true` if `xs` is null and `false` if `xs` is a pair.
- `is_list(x)`: Returns `true` if `x` is a list as defined in the lectures, and `false` otherwise. Iterative process; time:  $O(n)$ , space:  $O(1)$ , where  $n$  is the length of the chain of `tail` operations that can be applied to `x`.
- `list(x1, x2, ..., xn)`: Returns a list with  $n$  elements. The first element is `x1`, the second `x2`, etc.
- `length(xs)`: Returns the length of the list `xs`. Iterative process; time:  $O(n)$ , space:  $O(1)$ , where  $n$  is the length of `xs`.
- `map(f, xs)`: Returns a list that results from list `xs` by element-wise application of `f`. Recursive process; time:  $O(n)$ , space:  $O(n)$ , where  $n$  is the length of `xs`.
- `build_list(n, f)`: Makes a list with  $n$  elements by applying the unary function `f` to the numbers 0 to  $n - 1$ . Recursive process; time:  $O(n)$ , space:  $O(n)$ .
- `for_each(f, xs)`: Applies `f` to every element of the list `xs`, and then returns `true`. Iterative process; time:  $O(n)$ , space:  $O(1)$ , where  $n$  is the length of `xs`.
- `list_to_string(xs)`: Returns a string that represents list `xs` using the box-and-pointer notation [...].
- `reverse(xs)`: Returns list `xs` in reverse order. Iterative process; time:  $O(n)$ , space:  $O(n)$ , where  $n$  is the length of `xs`. The process is iterative, but consumes space  $O(n)$  because of the result list.
- `append(xs, ys)`: Returns a list that results from appending the list `ys` to the list `xs`. Recursive process; time:  $O(n)$ , space:  $O(n)$ , where  $n$  is the length of `xs`.
- `member(x, xs)`: Returns first postfix sublist whose head is identical to `x` (`===`); returns `null` if the element does not occur in the list. Iterative process; time:  $O(n)$ , space:  $O(1)$ , where  $n$  is the length of `xs`.

- `remove(x, xs)`: Returns a list that results from `xs` by removing the first item from `xs` that is identical (`==`) to `x`. Recursive process; time:  $O(n)$ , space:  $O(n)$ , where  $n$  is the length of `xs`.
- `remove_all(x, xs)`: Returns a list that results from `xs` by removing all items from `xs` that are identical (`==`) to `x`. Recursive process; time:  $O(n)$ , space:  $O(n)$ , where  $n$  is the length of `xs`.
- `filter(pred, xs)`: Returns a list that contains only those elements for which the one argument function `pred` returns `true`. Recursive process; time:  $O(n)$ , space:  $O(n)$ , where  $n$  is the length of `xs`.
- `enum_list(start, end)`: Returns a list that enumerates numbers starting from `start` using a step size of 1, until the number exceeds ( $>$ ) `end`. Recursive process; time:  $O(n)$ , space:  $O(n)$ , where  $n$  is the length of `xs`. For example, `enum_list(2, 5)` returns the list `list(2, 3, 4, 5)`.
- `list_ref(xs, n)`: Returns the element of list `xs` at position `n`, where the first element has index 0. Iterative process; time:  $O(n)$ , space:  $O(1)$ , where  $n$  is the length of `xs`.
- `accumulate(op, initial, xs)`: Applies binary function `op` to the elements of `xs` from right-to-left order, first applying `op` to the last element and the value `initial`, resulting in  $r_1$ , then to the second-last element and  $r_1$ , resulting in  $r_2$ , etc., and finally to the first element and  $r_{n-1}$ , where  $n$  is the length of the list. Thus, `accumulate(op, zero, list(1,2,3))` results in `op(1, op(2, op(3, zero)))`. Recursive process; time:  $O(n)$ , space:  $O(n)$ , where  $n$  is the length of `xs`, assuming `op` takes constant time.

## Miscellaneous Functions

- `is_number(x)`: Returns `true` if `x` is a number, and `false` otherwise.
- `equal(x, y)`: Returns `true` if `x` and `y` have the same structure (using `pairs` and `null`), and corresponding leaves are `==`, and `false` otherwise.



(Scratch Paper: Tear off, if needed.)

(Scratch Paper: Tear off, if needed.)

(Scratch Paper: Tear off, if needed.)

(Scratch Paper: Tear off, if needed.)