

# Class 10: Structural Bioinformatics Pt.1

Joanne Wu (PID: A17060517)

## What is in the PDB database

The main repository of biomolecular structure info is the PDB < [www.rcsb.org](http://www.rcsb.org) >.

Let's see what this database contains

```
stats <- read.csv("pdb_stats.csv", row.names = 1)
stats
```

	X.ray	EM	NMR	Multiple.methods	Neutron	Other
Protein (only)	161,663	12,592	12,337	200	74	32
Protein/Oligosaccharide	9,348	2,167	34	8	2	0
Protein/NA	8,404	3,924	286	7	0	0
Nucleic acid (only)	2,758	125	1,477	14	3	1
Other	164	9	33	0	0	0
Oligosaccharide (only)	11	0	6	1	0	4
Total						
Protein (only)	186,898					
Protein/Oligosaccharide	11,559					
Protein/NA	12,621					
Nucleic acid (only)	4,378					
Other	206					
Oligosaccharide (only)	22					

Q1: What percentage of structures in the PDB are solved by X-Ray and Electron Microscopy.

```
as.numeric(stats$X.ray)
```

Warning: NAs introduced by coercion

```
[1] NA NA NA NA 164 11
```

We got to get rid of the commas, Can you find a function to get rid of the commas?

```
x <- stats$X.ray
sum( as.numeric(gsub(",", "", x)) )
```

```
[1] 182348
```

I am going to turn this into a function and then use `apply()` to work on the entire table of data.

```
sumcomma <- function(x) {
  sum( as.numeric(sub(",", "", x)) )
}

sumcomma(stats$X.ray)
```

```
[1] 182348
```

```
n.total <- sumcomma(stats$Total)
n.total
```

```
[1] 215684
```

```
sumcomma(stats$EM)
```

```
[1] 18817
```

```
apply(stats, 2, sumcomma)
```

X.ray	EM	NMR	Multiple.methods
182348	18817	14173	230
Neutron	Other	Total	
79	37	215684	

```
apply(stats, 2, sumcomma) / sumcomma(stats$Total)
```

X.ray	EM	NMR	Multiple.methods
0.8454405519	0.0872433746	0.0657118748	0.0010663749
Neutron	Other	Total	
0.0003662766	0.0001715473	1.0000000000	

About 84.54% solved by X-Ray and about 8.72% solved by Electron microscopy.

Q2: What proportion of structures in the PDB are protein?

Q3: Type HIV in the PDB website search box on the home page and determine how many HIV-1 protease structures are in the current PDB?

248,805,733 - 186,898

```
186898/248805733 * 100
```

```
[1] 0.07511804
```

## Visualizing the HIV-1 protease strcuture

Mol\* ("mol-star") viewer is now everywhere. The Mol\* homepage at: <https://molstar.org/viewer/>.

I want to insert my image from Mol\* here.

## Working with the bio3d package

```
library(bio3d)
```

```
pdb <- read.pdb("1hsg")
```

Note: Accessing on-line PDB file

```
pdb
```




Figure 1: My first molecular image

```
Call: read.pdb(file = "1hsg")
```

```
Total Models#: 1
```

```
Total Atoms#: 1686, XYZs#: 5058 Chains#: 2 (values: A B)
```

```
Protein Atoms#: 1514 (residues/Calpha atoms#: 198)
```

```
Nucleic acid Atoms#: 0 (residues/phosphate atoms#: 0)
```

```
Non-protein/nucleic Atoms#: 172 (residues: 128)
```

```
Non-protein/nucleic resid values: [ HOH (127), MK1 (1) ]
```

```
Protein sequence:
```

```
PQITLWQRPLVTIKIGGQLKEALLDTGADDTVLEEMSLPGRWKPKMIGGIGGFIKVRQYD  
QILIEICGHKAIGTVLVGPTPVNIIGRNLLTQIGCTLNFPQITLWQRPLVTIKIGGQLKE  
ALLDTGADDTVLEEMSLPGRWKPKMIGGIGGFIKVRQYDQILIEICGHKAIGTVLVGPTP  
VNIIGRNLLTQIGCTLNF
```

```
+ attr: atom, xyz, seqres, helix, sheet,  
      calpha, remark, call
```

```
head(pdb$atom)
```

	type	eleno	elety	alt	resid	chain	resno	insert	x	y	z	o	b
1	ATOM	1	N	<NA>	PRO	A	1	<NA>	29.361	39.686	5.862	1	38.10
2	ATOM	2	CA	<NA>	PRO	A	1	<NA>	30.307	38.663	5.319	1	40.62
3	ATOM	3	C	<NA>	PRO	A	1	<NA>	29.760	38.071	4.022	1	42.64
4	ATOM	4	O	<NA>	PRO	A	1	<NA>	28.600	38.302	3.676	1	43.40
5	ATOM	5	CB	<NA>	PRO	A	1	<NA>	30.508	37.541	6.342	1	37.87
6	ATOM	6	CG	<NA>	PRO	A	1	<NA>	29.296	37.591	7.162	1	38.40
	segid	elesy	charge										
1	<NA>	N	<NA>										
2	<NA>	C	<NA>										
3	<NA>	C	<NA>										
4	<NA>	O	<NA>										
5	<NA>	C	<NA>										
6	<NA>	C	<NA>										

```
pdbseq(pdb)[25]
```

25  
"D"

## Predicting functional motions of a single structure

We can do a bioinformatics prediction of functional motions (i.e. flexibility/dynamics):

```
pdb <- read.pdb("6s36")
```

Note: Accessing on-line PDB file  
PDB has ALT records, taking A only, rm.alt=TRUE

```
pdb
```

```
Call: read.pdb(file = "6s36")
```

```
Total Models#: 1
  Total Atoms#: 1898, XYZs#: 5694 Chains#: 1 (values: A)

Protein Atoms#: 1654 (residues/Calpha atoms#: 214)
Nucleic acid Atoms#: 0 (residues/phosphate atoms#: 0)

Non-protein/nucleic Atoms#: 244 (residues: 244)
Non-protein/nucleic resid values: [ CL (3), HOH (238), MG (2), NA (1) ]
```


```
Protein sequence:
MRIILLGAPGAGKGTQAQFIMEKYGIPQISTGDMRLRAAVKSGSELGKQAKDIMDAGKLV
DELVIALVKERIAQEDCRNGFLDGFPR TIPQADAMKEAGINVDYVLEFDVPDELIVDKI
VGRRVHAPSGRVYHV KFNPPKVEGKDDVTGEELTTRKDDQEETVRKRLVEYHQMTAPLIG
YYSKEAEAGNTKYAKVDGTPVAEVRADLEKILG
```

```
+ attr: atom, xyz, seqres, helix, sheet,
      calpha, remark, call
```

```
m <- nma(pdb)
```

```
Building Hessian...      Done in 0.015 seconds.
Diagonalizing Hessian... Done in 0.278 seconds.
```

```
plot(m)
```



```
mktrj(m, file="adk_m7.pdb")
```