taskvantage-admin.okta.com/admin/apps/active

Admin Console

Dashboard
Directory
Customizations
Applications
Applications
Self Service
API Service Integrations
Identity Governance
Security
Workflow
Reports
Settings

Applications

Documentation

Create App Integration | Browse App Catalog | Assign Users to App | More

Governance Labels | Search

STATUS	
ACTIVE	52
INACTIVE	0

- AD Group Access Request
- Agent0 - Cross App Access (XAA) — Client ID: 0oa22dk6fynTsZrma1d8
- Chat Assistant App — Client ID: 0oa22dfdh26QZAXGi1d8
- Claude Co-Work Request
- Claude Code Agent - MCP Client — Client ID: 0oa22dsa3musjMVnH1d8
- Databricks
- Datadog
- Example OAuth Governance App — Client ID: 0oa22dduvesqQmBKi1d8
- Figma
- GitHub Enterprise
- Google Workspace

taskvantage-admin.okta.com/admin/apps/active

Applications

Documentation

Create App Integration | Browse App Catalog | Assign Users to App | More

Governance Labels | Search

STATUS	
ACTIVE	52
INACTIVE	0

- AD Group Access Request
- Agent0 - Cross App Access (XAA) — Client ID: 0oa22dk6fynTsZrma1d8
- Chat Assistant App — Client ID: 0oa22dfdh26QZAXGi1d8
- Claude Co-Work Request
- Claude Code Agent - MCP Client — Client ID: 0oa22dsa3musjMVnH1d8
- Databricks
- Datadog
- Example OAuth Governance App — Client ID: 0oa22dduvesqQmBKi1d8
- Figma
- GitHub Enterprise
- Google Workspace

```
<!DOCTYPE html>
<html lang="en" class="wf-inactive">
  <head>…</head>
  <body id="app" class="admin-app  dstheme dstheme_rebrand is-enduser-v2">
    <noscript>…</noscript>
    <div id="container">…</div>
    <span id="st-username" class="selenium-show">joe.vanhorn@okta.com</span>
    <script nonce>…</script>
    <div data-pendo-rollback="false"></div>
    <div id="odyssey-react-overlay-component-render-ui-shell" data-odyssey-react-overlay-component>…</div>
    <div id="full-screen-overlay-admin-app-react" data-odyssey-react-overlay-component></div>
  </body>
…</html> == $0
```

html.wf-inactive

Styles | Computed | Layout | Event Listeners | DOM Breakpoints | Properties

Filter | Show all

accessKey: ""

Console | What's new

top | idx | Default levels | 2 Issues: 1 1

7 hidden

taskvantage-admin.okta.com/admin/authentication-policies

Admin Console

Directory
Customizations
Applications
Identity Governance
Security
General
HealthInsight
Authenticators
Authentication Policies
Global Session Policy
Entity Risk Policy
Identity Threat Protection
User Profile Policies
Identity Providers
Delegated Authentication
Networks
Behavior Detection
Advanced Posture Checks
Device Assurance Policies
Device Integrations

Authentication policies

Documentation

Set up user, device, and security measures to protect access to applications.

Show authentication steps

App sign-in
Define how a user must authenticate to gain access to an app.

Okta account management
Dictate what a user must validate with for authenticator enrollment, password reset, and account recovery.

© 2026 Okta, Inc. Privacy Status site OK3 Cell (US) Version 2026.04.2 E Feedback

```
<!DOCTYPE html>
<html lang="en" class="wf-inactive">
  <head></head>
  <body id="app" class="admin-app dstheme dstheme_rebrand is-enduser -v2"></body>
</html>
```

```
:root {
  --okta-app-theme-background-color: #f4f4f4;
  --okta-app-theme-surface-color: #ffffff;
}
```

```
html {
  font-size: 87.5%;
}
```

taskvantage-admin.okta.com/admin/authentication-policies/app-sign-in

NAME	DESCRIPTION	APPLIES TO
Any two factors (Default)	Require two factors to access.	20 apps
Dan C Demo - Step-up for OAG Applications	--	1 app
MFA only for External Access	--	No apps assigned
Microsoft Office 365 (Application-specific pol)	--	1 app
ODA Desktop MFA (Application-specific pol)	--	1 app
Okta Admin Console (Application-specific pol)	--	1 app
Okta Browser Plugin	--	1 app
Okta Dashboard	--	1 app
Okta End User Settings	--	1 app
Partner Admin Portal (Application-specific pol)	--	1 app

taskvantage-admin.okta.com/admin/authentication-policies/app-sign-in/rst1yr8sv84RI9lbl1d8

Admin Console

Directory
Customizations
Applications
Identity Governance
Security
General
HealthInsight
Authenticators
Authentication Policies
Global Session Policy
Entity Risk Policy
Identity Threat Protection
User Profile Policies
Identity Providers
Delegated Authentication
Networks
Behavior Detection
Advanced Posture Checks
Device Assurance Policies
Device Integrations

Based on the rules configured, Okta Verify performs device signal collection and provides user identity. To modify these settings, show device signal collection rules from the Actions menu of this policy. Learn more about enabling this feature.

Add rule

Priority	Rule	Status	Actions
1	Deny onTLA	DISABLED	Actions
	IF Group: TLA — THEN Access: Denied		
2	Allow ITP-demo password only	ENABLED	Actions
	IF User is: ITP Demo Test — THEN Access: Allowed with password Your org's authenticators that satisfy this requirement: Password Authentication methods: Allow any method that can be used to meet the requirement Re-authentication frequency is: Every 1 hours		
3	Catch-all Rule	ENABLED	Actions
	IF Any request — THEN Access: Allowed with any 2 factor types Your org's authenticators that satisfy this requirement: Knowledge / Biometric factor types Password or Okta Verify - Push[1] or Okta Verify - FastPass[1] or Passkeys (FIDO2 WebAuthn)[1]		

taskvantage-admin.okta.com/admin/authentication-policies/app-sign-in/rst1yr8sv84RI9lbl1d8

Admin Console

Directory
Customizations
Applications
Identity Governance
Security
General
HealthInsight
Authenticators
Authentication Policies
Global Session Policy
Entity Risk Policy
Identity Threat Protection
User Profile Policies
Identity Providers
Delegated Authentication
Networks
Behavior Detection
Advanced Posture Checks
Device Assurance Policies
Device Integrations

Based on the rules configured, Okta Verify performs device signal collection and provides user identity. To modify these settings, show device signal collection rules from the Actions menu of this policy. Learn more about enabling this feature.

Add rule

Priority	Rule	Status	Actions
1	Deny onTLA	DISABLED	Actions
	IF Group: TLA — THEN Access: Denied		
2	Allow ITP-demo password only	ENABLED	Actions
	IF User is: ITP Demo Test — THEN Access: Allowed with password Your org's authenticators that satisfy this requirement: Password Authentication methods: Allow any method that can be used to meet the requirement Re-authentication frequency is: Every 1 hours		
3	Catch-all Rule	ENABLED	Actions
	IF Any request — THEN Access: Allowed with any 2 factor types Your org's authenticators that satisfy this requirement: Knowledge / Biometric factor types Password or Okta Verify - Push[1] or Okta Verify - FastPass[1] or Passkeys (FIDO2 WebAuthn)[1]		

Edit
Activate
Delete

taskvantage-admin.okta.com/admin/authentication-policies/app-sign-in/rst1yr8sv84RI9lbl1d8

Edit Rule

If all of the conditions are true, the authentication settings below will apply. Otherwise, Okta will evaluate the next rule.

Rule name: Deny onTLA

IF

- IF User's user type is: Any user type
- AND User's group membership includes: At least one of the following groups: TLA
  - And none of the following groups: Enter groups to exclude...
  - Go to Groups
- AND User is: Any user
- AND Device state is: Any / Registered
  - Setup Okta Verify as Authenticator
- AND Device assurance policy is: No policy
- AND Device platform is: Any platform
  - Device platform is securely verified for registered devices. For unregistered devices, it's determined by the user-agent and can be modified. Learn more about Device platform security
- AND User's IP is: Any IP
- AND Risk is: Any

taskvantage-admin.okta.com/admin/authentication-policies/app-sign-in/rst1yr8sv84RI9lbl1d8

And none of the following groups: Enter groups to exclude...
Go to Groups
AND User is: Any user
AND Device state is: Any / Registered
Setup Okta Verify as Authenticator
AND Device assurance policy is: No policy
AND Device platform is: Any platform
Device platform is securely verified for registered devices. For unregistered devices, it's determined by the user-agent and can be modified. Learn more about Device platform security
AND User's IP is: Any IP
AND Risk is: Any

- AND The following custom expression is true
  - This is an optional advanced setting. If the expression is formatted incorrectly or conflicts with conditions set above, the rule may not match any users.
  - Expression language reference

THEN

- THEN Access is: Denied / Allowed after successful authentication

Save Cancel