NH-L9i bar — lga115x

Order ready: no — confirm the unverified dimensions before ordering

Formed bar

End-hole span (motherboard): 75.000 mm
Center-hole spacing (heatsink): 23.000 mm
Arm, center hole to end hole: 26.000 mm
Distance between the two bars, set by the heatsink: 75.000 mm
Thickness: 3.175 mm
Width: 16.000 mm
Bend: 20.000 deg up, inside radius 1.587 mm
Ear height, web midplane to ear-hole midplane: 3.348 mm
Flat blank: 92.025 x 16.000 mm
Upload files use plain through-holes. Countersinks and threads are services.

Hole table

Role	Flat X (mm)	Drawn dia (mm)	Shop operation
center left	-11.500	3.300	90 deg M3 countersink, major 6.500 mm, depth 1.600 mm
center right	11.500	3.300	90 deg M3 countersink, major 6.500 mm, depth 1.600 mm
ear left	-38.013	2.500	M3x0.5 through tap
ear right	38.013	2.500	M3x0.5 through tap

Countersink side: Top face of the flat web, the face on the inside of the upward bends.
The tapped hole is perpendicular to the ear, so its axis is tilted by the bend angle.

Flat pattern. Dashed lines are bend centers. Holes are plain diameters.

Unverified: center_spacing_mm, web_width_mm, ear_diameter_mm, bend_angle_deg, ear_height_mm, inside_bend_radius_mm