

R32 DAIKIN FIT SERIES

NA	Information Not Available
Green	Daikin better
Red	Comp. better
White	Equal or no significant difference.

Features	DH6VS FIT DAIKIN	DH7VS FIT DAIKIN	DH9VS FIT DAIKIN	37MUHA CARRIER/MIDEA	EVOX MIDEA	INFINITY 27VNA3	DCS SERIES	SIGNATURE SL22KLV	ELITE EL18KSLV	FLEEX ECO R32 GREE	FLEEX Ultra R32 GREE	IDS Ligh/PLUS BOSCH	IDS PREMIUM BOSCH	IDS Ultra HP BOSCH	KUSXA/B LG	Hi-Pro HISENSE	Hi-Ultra HISENSE	HH8 YORK	RD16AY RHEEM	RD18AY RHEEM	RD19AY RHEEM	STWV0 TRANE	Comments	Comments Enhanced	
Initial Cost	\$5	\$5	\$5	\$5	\$5	\$5	\$5	\$5	\$5	\$5	\$5	\$5	\$5	\$5	\$5	\$55	\$5	\$5	\$5	\$5	\$5	\$5	More Tonnage options considered better due to more ratings and matchups being possible. More options account for varying duct and/or home sizes.	More Tonnage options considered better due to more ratings and matchups being possible. More options account for varying duct and/or home sizes.	
Sizing options (Tons)	1.5, 2, 2.5, 3, 3.5, 4, 5	2, 3, 3.5, 4	2,3	1.5, 2, 2.5, 3, 4, 5	1.5, 2, 2.5, 3, 4, 5	3, 4, 5	1.5, 2, 2.5, 3, 4, 5	2, 3, 4, 5	2, 3, 4, 5	2.5, 3, 5	2, 3, 4, 5	2, 3, and 5	(2,3), (4,5)	One SKU (4,5)	1, 1.5, 2, 3, 3.5, 4, 5	2, 3, 4, 5	2, 3, 4, 5	2, 3, (4, 5)	2, 3, 4, 5	2, 3, 4, 5	2, 3, 4, 5	2, 3, 4, 5	At least 2 dimensions better or worse	At least 2 dimensions better or worse	
Chassis Type	SD	SD	SD	SD	SD	Cube	SD	Cube	SD	SD	SD	Cube Style	Cube Style	Cube Style	SD	SD	SD	SD	SD	SD	SD	CUBE	CUBE	At least 2 dimensions better or worse	At least 2 dimensions better or worse
Smallest footprint available (inches) D x W x H	13 x 39 x 37	13 x 36 x 27	12 x 37 x 56	13 x 35 x 26	14 x 21 x 49	31 3/16 x 31 3/16 x 36	16.34 x 38.58 x 38.39	39 x 35 x 46	15 x 36 x 30	21-1/4 x 21-1/4 x 48 3/16	21-1/4 x 48-3/16 x 21-1/4	28 x 28 x 24	29 x 29 x 24	29 x 29 x 43	13 x 37 x 32	12-1/4 x 33-7/8 x 26-3/8	12-1/4 x 33-7/8 x 26-3/8	13 x 35 x 29	19.8 x 40.4 x 31.8	22.8 x 42.3 x 46.4	36.13 x 36.13 x 51.17	34 x 37 x 51	At least 2 dimensions better or worse	At least 2 dimensions better or worse	
Air Handler Matchup	115V* / 240V R-32	115V* / 240V R-32	115V* / 240V R-32	115V* / 240V R-454B	115V* / 240V R-454B	230V R-454B	115V/230V R-454B	230V R-454B	230V R-454B	230V R-32	230V R-32	240V R-454B	240V R-454B	240V R-454B	240V R-32	240V R-454B	240V R-454B	240V R-454B	240V R-454B	240V R-454B	240V R-454B	240V R-454B	Daikin is the only one with 115V AH with SD Inverter	Daikin is the only one with 115V AH with SD Inverter	
Refrigerant	VS Rotary (Swing)	VS Rotary (Swing)	VS Rotary (Swing)	VS Rotary	VS Rotary	VS Rotary	Twin-Rotary	Variable Capacity	VS Rotary	VS Rotary	VS Rotary	VS Rotary	VS Rotary	VS Rotary	VS Rotary	VS Rotary	VS Rotary	VS Rotary	VS Rotary	VS Rotary	VS Rotary	VS Scroll	VS Scroll	Swing Compressor provides true modulation versus others having multiple steps	Swing Compressor provides true modulation versus others having multiple steps
Compressor Type	Yes	Yes	Yes	NA	NA	Yes	No	Yes	No	NA	NA	Yes	Yes	Yes	NA	No	No	Yes	Yes	Yes	Yes	Yes	Yes	Swing Compressor provides true modulation versus others having multiple steps	Swing Compressor provides true modulation versus others having multiple steps
Compressor Sound Blanket	Extremely Quiet, ~45dBA	Extremely Quiet, ~45 dBA	Extremely Quiet, ~47 dBA	Extremely Quiet, ~59dBA	Extremely Quiet, ~37dBA	Extremely Quiet, ~55dBA	Extremely Quiet, ~62.5dBA	Extremely Quiet, ~58dBA	Extremely Quiet, ~54dBA	Extremely Quiet, ~59dBA	Extremely Quiet, ~60dBA	Extremely Quiet, ~59dBA	Extremely Quiet, ~53.4dBA	Extremely Quiet, ~59.9dBA	Extremely Quiet, ~54dBA	Extremely Quiet, ~54dBA	Extremely Quiet, ~54dBA	Extremely Quiet, ~54dBA	Extremely Quiet, ~50dBA	Extremely Quiet, ~50dBA	Extremely Quiet, ~50dBA	~60dBA	Extremely Quiet, ~55dBA	Quiet Mode dBAs is not included	Quiet Mode dBAs is not included
Coil Only Matchup	Yes	Yes	Yes	Yes	Yes	No	Yes	No	Yes	Yes	No	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Whether unit can pair up with 3rd party Furnace (Daikin AC is capable through D24V gateway -- will launch O1CY25)	Whether unit can pair up with 3rd party Furnace	
Straight Cool Version	Yes	No	No	No	No	No	NA	No	No	No	No	No	No	No	No	No	No	No	No	No	No	Yes	Yes		
Controls	Primary Thermostat Type	Smart Communicating Thermostat	Smart Communicating Thermostat	Smart Communicating Thermostat	24vac & Communicating	Smart Communicating Thermostat	24V Thermostat	Smart Communicating Thermostat	Smart Communicating Thermostat	Smart Communicating Thermostat	Smart Communicating Thermostat	24vac thermostats	24vac thermostats	Smart Communicating Thermostat	Smart Communicating Thermostat	24vac thermostats	24vac thermostats	24vac thermostats	Smart Communicating Thermostat	Smart Communicating Thermostat	Smart Communicating Thermostat	Smart Communicating Thermostat			
	24V Thermostat Option	No	No	No	Yes	Yes	No	Yes	No	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	No			
Installation Features	Regional equipment profiles for optimal comfort & efficiency (Quality Install)	Yes	Yes	Yes	No	No	No	No	No	No	No	No	No	No	NA	No	No	No	No	No	No	No	Preconfigured profile that includes proper airflow to optimize humidity control.	Preconfigured profile that includes proper airflow to optimize humidity control.	
	Customizable & re-usable equipment configurations, "Profiles," (Quality Install)	Yes	Yes	Yes	No	No	No	No	No	No	No	No	No	No	NA	No	No	No	No	No	No	No	All systems settings and parameters are preconfigured in a single file (system profile) that can be downloaded to thermostat at the touch of a button.	All systems settings and parameters are preconfigured in a single file (system profile) that can be downloaded to thermostat at the touch of a button.	
	Charge verification without tools (Quality Install)	Yes	Yes	Yes	No	No	No	No	No	No	No	No	No	No	NA	No	No	No	No	No	No	Yes	Allows the technician to calculate amount of refrigerant to be added and verifies if the charge is correct.	Allows the technician to calculate amount of refrigerant to be added and verifies if the charge is correct.	
	Slow loss of charge alerting (Charge Integrity)	Yes	Yes	Yes	No	No	No	No	No	No	No	No	No	No	NA	No	No	No	No	No	No	No	Alerts contractor in instances of slow refrigerant leak.	Alerts contractor in instances of slow refrigerant leak.	
	Real-time, cloud-connected, Alerts & Diagnostics (Cloud Services)	Yes	Yes	Yes	No	No	No	Yes	Yes	No	No	Yes	Yes	Yes	NA	No	No	No	Yes	Yes	No	Yes	Cloud services provides contractor with real time alerts, troubleshooting, and diagnostic information.	Cloud services provides contractor with real time alerts, troubleshooting, and diagnostic information.	
Features	Humidity Control (true Dehum, VS indoor Fan)	Yes	Yes	Yes	Yes	Yes	NA	Yes	Yes	NA	NA	No	No	NA	NA	NA	NA	NA	Yes	Yes	Yes	Yes	True humidification happens when you are able to keep compressor speed high and fan speed low.	True humidification happens when you are able to keep compressor speed high and fan speed low.	
	Factory Installed Base pan Heater	No	No	Yes	Yes	Yes	NA	Yes	Yes	Yes	Yes	No	No	No	Yes	Yes	Yes	Yes	No	No	No	No			
	3-Stage Heater Kit (Optional)	No	No	Yes	No	Yes	NA	NA	No	NA	NA	No	No	Yes	NA	NA	NA	NA	No	No	No	No			
	Intelligent Defrost	Yes	Yes	Yes	Yes	Yes	NA	Yes	No	Yes	Yes	Limited	Limited	Limited	NA	NA	NA	Limited	No	Limited	No	No	Allows for heating during defrost cycle	Allows for heating during defrost cycle	
	Anti-corrosive film coating	Yes	Yes	Yes	Yes	Yes	NA	Yes	No	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	No	Yes	No	Yes	Blue Fin Corrosion Coating. Hydrophilic coating to help keep the coil clean.	Blue Fin Corrosion Coating. Hydrophilic coating to help keep the coil clean.	
Efficiency and Performance	ENERGY STAR®	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes		
	ENERGY STAR® cchP	Yes	Yes	Yes	1.5, 2	Yes	Yes	Yes	Yes	No	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	No	Yes	Yes	Yes	Yes		
	CEE 2025	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes		
	SEER2	Up to 17.5	Up to 18	Up to 21.1	Up to 18	Up to 19.3	Up to 23	Up to 17.4	Up to 21.1	Up to 19	Up to 19	Up to 18	Up to 20	Up to 19	Up to 17.5	Up to 20	Up to 18	Up to 19	Up to 17	Up to 19	Up to 20	Up to 22.4			
	EEER2	Up to 10.9	Up to 10	Up to 12	Up to 12	Up to 12.5	Up to 13	Up to 11.7	Up to 13.6	Up to 12.3	Up to 11.7	Up to 11.8	Up to 13	Up to 12	Up to 11.8	Up to 12	Up to 10	Up to 12	Up to 10.5	Up to 13	Up to 12.5	Up to 13			
	HSPF2	Up to 9	Up to 8.6	Up to 10	Up to 10.3	Up to 10.8	Up to 9.5	Up to 10.3	Up to 10.5	Up to 10	Up to 10	Up to 9	Up to 9.5	Up to 10	Up to 9.5	Up to 11	Up to 9	Up to 9.5	Up to 8.5	Up to 10	Up to 8.5	Up to 10.5			
	COP@5F	2.1	2.0	2.4	1.91	2.1	1.9	1.9	2.4	1.95	2.0	2.1	1.9	2.0	2.1	1.8	2.2	2.1	2.3	2.3	2.1	2.2			
	Max Capacity at 5F	20,000	29,000	34,200	39,000	32,600	47,000	54,000	46,500	43,000	21,600	45,000	24,400	24,400	55,000	33,000	31,000	26,000	27,600	20,000	28,200	29,600	25,400		
	Max Capacity at 47F	34,200	35,000	34,200	38,000	36,000	34,200	37,000	56,000	56,000	34,000	48,000	34,200	34,200	55,000	37,000	34,000	35,000	35,000	33,800	33,000	34,200	33,800		
	Max Capacity at 95F	34,200	35,000	36,000	36,000	36,000	32,200	36,000	56,000	55,500	34,000	54,000	34,600	34,200	53,500	34,400	32,000	34,000	35,000	34,200	32,800	34,200	36,200		
	Max Capacity at 115F	28,000	29,000	31,500	26,855	NA	28,800	NA	NA	NA	NA	23,500	25,800	38,830	NA	24,800	26,000	29,000	NA	NA	NA	NA	NA		
	Cooling Operating Range Min/Max F	0F/115F	0F/115F	0F/115F	-22F/130F	-22F/122F	125F	-22F/122F	NA	5F/125F	+5F/118F	+5F/130F	40F/120F	15F/125F	5F/118F	5F/125F	5F/115F	35F/122F	50F/125F	50F/125F	60F/110F	55F/150F			
	Heating Operating Range Min/Max F	-10F/70F	-10F/70F	-10F/70F	-22F/86F	-22F/86F	-13F	-22F/75F	As low as -20F	-22F/86F	3F/86F	-22F/75F	-10F/75F	-4F/86F	-13F/75F	-13F/75F	-10F/75F	-22F/80F	-22F/70F	-22F/70F	-10F/60F	0F/66F			
	Line Lengths up to	100ft	100ft	150 ft	213ft	213ft	250ft	246ft	150 ft	150 ft	98ft	98ft	100ft	100ft	100ft	164ft - 246ft	164ft - 246ft	164ft - 246ft	164ft - 246ft	150ft	150ft	200ft			
	Pre-charge	15ft	15ft	15ft	25ft	25ft	15ft	NA	15 ft	25ft	25ft	15ft	15ft	15ft	15ft	24.6ft	15ft	15ft	25ft	15ft	15ft	10ft			
	Elevation	100ft	100ft	100ft	98ft	65ft	NA	NA	50 ft	50 ft	49ft	49ft	50 ft	50 ft	50 ft	98.4ft	98ft	98ft	98ft	50ft	50ft	50ft			
Warranty	Warranty	12y parts & 12y Repl.	12y parts & 12y Repl.	12y parts & 12y Repl.	10y parts & 10y Comp	10y parts & 10y Comp	10y parts & 10y Comp	10y parts & 10y Comp	10y parts & 10y Comp	10y parts & 10y Comp	10y parts & 10y Comp	10y parts & 10y Comp	10y parts & 10y Comp	10y parts & 10y Comp	5y parts & 7y Comp	10y parts & 10y Comp	10y parts & 10y Comp	10y parts & 10y Comp	10y parts & 10y Comp	10y parts & 10y Comp	10y parts & 10y Comp	10y parts & 12y Comp	Daikin has the best in class warranty	Daikin has the best in class warranty	