

The First Law of Thermodynamics

Contents

1	Historical Foundation of the First Law of Thermodynamics	2
1.1	Introduction	2
1.2	Early Concepts of Heat	3
1.3	Joule's Paddle-Wheel Experiment (1843)	3
1.3.1	Apparatus Description	3
1.3.2	Experimental Procedure	4
1.3.3	Key Results	4
1.4	Development of the Energy Concept	5
1.4.1	Equivalence of Heat and Work	5
1.4.2	The State Function Concept	5
2	Statement of the First Law	6
3	Internal Energy as a State Function	7
4	Work and Generalized Forces	7
4.1	Mechanical Work in a Compressible System	7
4.2	Generalized Work	8
4.3	Key Points and Sign Conventions	8

5 Path Dependence of Heat and Work	9
---	----------

Appendices	9
-------------------	----------

A Exact Differentials and Chain Rules in Thermodynamics	9
--	----------

A.1 Introduction	9
A.2 Exact Differentials in Two Variables	9
A.3 Condition for Exactness (Clairaut–Schwarz Theorem)	10
A.4 Generalization to Three Variables	10
A.5 Inexact Differentials and Integrating Factors	12
A.6 Thermodynamic Summary Table	14
A.7 Key Chain Rules and Partial Derivative Identities	14
A.7.1 Reciprocity Relation	15
A.7.2 Cyclic Relation (Triple Product Rule)	15
A.7.3 Implicit Differentiation Rule	16
A.7.4 Chain Rule involving an Intermediate Variable	16
A.7.5 Application Examples	17
A.8 Summary of Useful Partial Derivative Identities	18

1 Historical Foundation of the First Law of Thermodynamics

1.1 Introduction

The formulation of the First Law of Thermodynamics emerged from centuries of investigation into the nature of heat and its relationship to mechanical work. Early studies of heat, initially regarded as a material substance (*caloric*), gradually revealed its intimate connection with motion and energy transfer. Through careful experiments and theoretical advances—most notably those of Joule, Mayer, and Helmholtz—it became clear that heat and mechanical work are interchangeable mechanisms of energy transfer.

This section traces the key conceptual and experimental developments that led to the modern statement of the First Law, which asserts the conservation of energy in thermodynamic processes. By examining the historical path from caloric theory to the energy principle, we gain insight into both the physical meaning of internal energy and the broader unifying role of energy conservation across physics.

1.2 Early Concepts of Heat

- **Caloric Theory (18th century):** Heat was regarded as a weightless, indestructible fluid called *caloric* that flowed from hotter to colder bodies. Within this framework, heat transfer was understood as the transport of caloric, and thermal equilibrium corresponded to a uniform distribution of this substance. Despite its eventual failure, caloric theory successfully explained many qualitative thermal phenomena and dominated scientific thinking throughout the eighteenth century.
- **Count Rumford's Observations (1798):** In his famous experiments on the boring of cannon barrels, Count Rumford (Benjamin Thompson) observed that the heat generated by friction appeared to be inexhaustible, increasing without bound as long as mechanical work was supplied. This behavior was incompatible with the notion of heat as a conserved material substance and provided strong empirical evidence against caloric theory.
- **Conceptual Shift:** Rumford's results, together with later work by Davy and others, initiated a gradual shift toward viewing heat as a manifestation of microscopic motion. This transition laid the groundwork for the mechanical theory of heat and ultimately for the identification of heat as a mode of energy transfer rather than a material entity.

1.3 Joule's Paddle-Wheel Experiment (1843)

The crucial experiment that established the mechanical equivalent of heat:

1.3.1 Apparatus Description

Joule's apparatus consisted of:

- A falling weight of known mass attached to a string
- The string wrapped around an axle connected to paddle wheels
- The paddles immersed in an insulated water bath
- A precise thermometer to measure temperature changes




Figure 1: Schematic of Joule’s paddle-wheel experiment demonstrating the mechanical equivalent of heat. Image from Wikipedia: “Mechanical equivalent of heat”

1.3.2 Experimental Procedure

1. The weight was allowed to fall a measured height
2. The rotating paddles agitated the water, converting:

Gravitational potential energy $\rightarrow$ Kinetic Energy $\rightarrow$ Heat

3. The temperature change of water was recorded
4. The process was repeated to verify consistency

1.3.3 Key Results

The mechanical work input is

$$W = Mgh,$$

where M is the falling weight’s mass, h is the vertical distance the weight descends (m), and g is the acceleration due to gravity.

The heat produced in the water is

$$Q = m_w c \Delta T$$

where Q = heat energy (J), m_w = mass of the water in the insulated chamber (kg), c = specific heat capacity (J/kg·°C), and ΔT = temperature change (°C).

Joule found the constant ratio:

$$W_Q \equiv \frac{W}{Q} = J \quad (4.184 \text{ J/cal})$$

1.4 Development of the Energy Concept

The work of Joule and others led to several critical realizations:

1.4.1 Equivalence of Heat and Work

- Heat and work are different forms of *energy transfer*
- They can be converted into one another
- Conversion occurs at a fixed rate (mechanical equivalent)

1.4.2 The State Function Concept

- The net effect (ΔU) depends only on initial and final states
- Different combinations of Q and W can produce the same ΔU
- Implies the existence of an internal energy function U

Table 1: Key Contributors to the First Law

Scientist	Contribution
Count Rumford (1798)	Discredited caloric theory
J.R. Mayer (1842)	Proposed energy conservation
J.P. Joule (1843-78)	Measured mechanical equivalent
H. Helmholtz (1847)	Generalized energy concept

Remark 1. *The equation*

$$W_Q = J = 4.184 \text{ J/cal}$$

*is not a thermodynamic law, but rather a **unit conversion factor**. It expresses that*

$$1 \text{ calorie of heat} = 4.184 \text{ joules of energy.}$$

Historically, J is known as the mechanical equivalent of heat, which connects the traditional heat unit (calorie) with the mechanical (SI) energy unit (joule). In contrast, the first law of thermodynamics (see below),

$$dU = \delta Q - \delta W,$$

is a statement of energy conservation. All quantities involved— U , Q , and W —must be expressed in the same energy units (typically joules).

2 Statement of the First Law

The First Law of Thermodynamics formalizes the principle of **energy conservation** for thermodynamic systems. It asserts that the change in a system's internal energy U is equal to the net energy transferred to the system as heat minus the work done by the system on its surroundings. In differential form, this is written as

$$dU = \delta Q - \delta W, \tag{1}$$

where

- dU is the infinitesimal change in the **internal energy** of the system, a state function that depends only on the current state,
- δQ is the infinitesimal amount of **heat added to the system**, and
- δW is the infinitesimal amount of **work done by the system on its surroundings**.

Key points to note:

- Unlike internal energy, δQ and δW are *inexact differentials*, reflecting the fact that heat and work are *process-dependent* energy transfers rather than state functions.
- The First Law provides a rigorous framework for *bookkeeping of energy*: any energy added to a system as heat or work changes its internal energy, and energy cannot be created or destroyed.
- This principle generalizes the classical conservation of mechanical energy by including heat as a form of energy transfer, reconciling the observations of Joule, Mayer, and others with a unified energy concept.

Remark 2. In practical applications, the sign convention is important: heat flowing into the system and work done by the system on the environment are taken as positive. Other conventions exist, but the physical content of the First Law remains the same.

3 Internal Energy as a State Function

The **internal energy** U of a system is a **state function**, meaning that its value depends only on the current thermodynamic state of the system, typically specified by variables such as temperature T , pressure P , and volume V , and *not* on the specific process or path used to reach that state. This property distinguishes internal energy from heat and work, which are process-dependent forms of energy transfer.

- **Path-independence:** The change in internal energy ΔU between two states is independent of the specific process connecting them. Whether the system is heated, compressed, or allowed to expand freely, ΔU depends only on the initial and final states.
- **Exact differential:** Mathematically, dU is an exact differential:

$$\oint dU = 0 \quad \text{for any cyclic process,}$$

which means that if a system undergoes a cyclic transformation returning to its original state, the net change in internal energy is zero.

- **Physical interpretation:** Internal energy represents the total microscopic energy contained in the system, including kinetic energy of particle motion, potential energy of interactions, chemical energy, and other forms of internal energy. Its state function property ensures that all energy exchanges via heat or work ultimately contribute consistently to U .

Remark 3. *The state function property of internal energy underlies the formulation of the First Law of Thermodynamics and allows a consistent definition of other state functions, such as enthalpy, Helmholtz free energy, and Gibbs free energy.*

4 Work and Generalized Forces

In thermodynamics, **work** is understood as the energy transferred to or from a system via generalized forces acting through their conjugate displacements. Unlike internal energy, work is *path-dependent* and hence is represented by an inexact differential, δW .

4.1 Mechanical Work in a Compressible System

In the simplest case of a compressible system, such as a gas confined in a cylinder with a movable piston, the infinitesimal work done by the system during a small change in volume is

$$\delta W = P dV, \tag{2}$$

where P is the pressure (generalized force) and dV is the infinitesimal change in volume (generalized displacement). Here:

- $dV > 0$ corresponds to expansion of the system, in which case the system does positive work on its surroundings.
- $dV < 0$ corresponds to compression, where work is done *on* the system and $\delta W < 0$.

4.2 Generalized Work

In more general contexts, thermodynamic work can be associated with various types of generalized forces and their conjugate coordinates. The total work in a process involving multiple generalized coordinates is expressed as

$$\delta W = \sum_i X_i dx_i, \quad (3)$$

where:

- X_i denotes a generalized force, such as pressure, surface tension, magnetic field, or electrical potential, and
- x_i denotes the corresponding generalized displacement, such as volume, surface area, magnetization, or electric charge displacement.

4.3 Key Points and Sign Conventions

- Work is **process-dependent** (an inexact differential). Its magnitude and direction depend on the specific path taken in the space of generalized coordinates.
- **Sign convention:** By standard thermodynamic convention:
 - Work done *by the system* on the surroundings is positive ($\delta W > 0$),
 - Work done *on the system* by the surroundings is negative ($\delta W < 0$).
- This framework allows thermodynamic analysis of diverse systems, from simple gases to magnetic, elastic, or electrical systems, using a unified formalism of generalized forces and displacements.

5 Path Dependence of Heat and Work

Unlike internal energy U , both heat Q and work W are **path-dependent** quantities. That is, the amount of heat transferred or work done depends not only on the initial and final states, but also on the specific process connecting them. Over a closed cyclic process (e.g., a heat engine cycle):

$$\oint \delta Q \neq 0, \quad \oint \delta W \neq 0, \quad \text{but} \quad \oint dU = 0$$

since the internal energy, being a state function, returns to its original value at the end of the cycle.

Appendices

A Exact Differentials and Chain Rules in Thermodynamics

A.1 Introduction

In thermodynamics, state functions such as internal energy U , entropy S , and volume V have the property that their differentials are **exact**. This contrasts with path-dependent quantities like heat δQ and work δW , which are **inexact differentials**. To make this distinction rigorous, we present the mathematical theory of exact differentials and related identities involving partial derivatives.

A.2 Exact Differentials in Two Variables

Let $f(x, y)$ be a scalar function with continuous partial derivatives. Its total differential is

$$df = \frac{\partial f}{\partial x} dx + \frac{\partial f}{\partial y} dy.$$

This is an **exact differential** because it arises from a well-defined scalar function. In general, a differential form

$$\omega = M(x, y) dx + N(x, y) dy$$

is said to be **exact** if there exists a function $f(x, y)$ such that $df = \omega$. This implies:

$$\frac{\partial f}{\partial x} = M, \quad \frac{\partial f}{\partial y} = N.$$

A.3 Condition for Exactness (Clairaut–Schwarz Theorem)

Let $\omega = M(x, y) dx + N(x, y) dy$ be a differential 1-form. If M and N have continuous first partial derivatives on a simply connected domain, then ω is *exact* if and only if

$$\frac{\partial M}{\partial y} = \frac{\partial N}{\partial x}.$$

This equality of mixed partial derivatives is a consequence of the **Clairaut–Schwarz theorem**, which states that

$$\frac{\partial^2 f}{\partial x \partial y} = \frac{\partial^2 f}{\partial y \partial x}$$

whenever these second-order partial derivatives are continuous.

Under this condition, there exists a scalar potential function $f(x, y)$ such that

$$df = \omega, \quad \text{i.e.,} \quad M = \frac{\partial f}{\partial x}, \quad N = \frac{\partial f}{\partial y}.$$

A.4 Generalization to Three Variables

Consider the differential 1-form

$$\omega = M(x, y, z) dx + N(x, y, z) dy + P(x, y, z) dz.$$

The form ω is said to be *exact* if there exists a scalar potential function $f(x, y, z)$ such that

$$df = \omega, \quad \text{i.e.,} \quad M = \frac{\partial f}{\partial x}, \quad N = \frac{\partial f}{\partial y}, \quad P = \frac{\partial f}{\partial z}.$$

If M , N , and P have continuous first partial derivatives on a simply connected domain in $\mathbb{R}^3$, exactness is equivalent to the equality of the appropriate mixed partial derivatives:

$$\frac{\partial M}{\partial y} = \frac{\partial N}{\partial x}, \quad \frac{\partial M}{\partial z} = \frac{\partial P}{\partial x}, \quad \frac{\partial N}{\partial z} = \frac{\partial P}{\partial y}.$$

These conditions follow from the **Clairaut–Schwarz theorem** applied to the potential f , and ensure that the gradient field ∇f is well-defined.

Geometrically, this means that the corresponding vector field

$$\mathbf{F} = \langle M, N, P \rangle$$

is *conservative*, or equivalently, that its curl vanishes:

$$\nabla \times \mathbf{F} = \mathbf{0}.$$

Example: An Exact Differential in Three Variables

Consider the differential 1-form

$$\omega = (yz + 2x) dx + (xz + 3y^2) dy + (xy + 4z^3) dz.$$

Step 1: Identify the components

$$M(x, y, z) = yz + 2x, \quad N(x, y, z) = xz + 3y^2, \quad P(x, y, z) = xy + 4z^3.$$

Step 2: Check the exactness conditions:

$$\begin{aligned} \frac{\partial M}{\partial y} &= z, & \frac{\partial N}{\partial x} &= z & \Rightarrow & \frac{\partial M}{\partial y} = \frac{\partial N}{\partial x}, \\ \frac{\partial M}{\partial z} &= y, & \frac{\partial P}{\partial x} &= y & \Rightarrow & \frac{\partial M}{\partial z} = \frac{\partial P}{\partial x}, \\ \frac{\partial N}{\partial z} &= x, & \frac{\partial P}{\partial y} &= x & \Rightarrow & \frac{\partial N}{\partial z} = \frac{\partial P}{\partial y}. \end{aligned}$$

Since all mixed partial derivatives are equal, ω is an *exact differential*.

Step 3: Find the potential function $f(x, y, z)$:

Start from

$$M(x, y, z) = \frac{\partial f}{\partial x}.$$

Integrate M with respect to x , treating y and z as constants:

$$f(x, y, z) = \int M(x, y, z) dx = \int (yz + 2x) dx = xyz + x^2 + g(y, z),$$

where $g(y, z)$ is an arbitrary function of y and z , accounting for the fact that the “constant of integration” may depend on the other variables.

Next, impose $\frac{\partial f}{\partial y} = N = xz + 3y^2$:

$$\frac{\partial f}{\partial y} = xz + \frac{\partial g}{\partial y} = xz + 3y^2 \quad \Rightarrow \quad \frac{\partial g}{\partial y} = 3y^2.$$

Integrate with respect to y :

$$g(y, z) = y^3 + h(z),$$

where $h(z)$ is a function of z only.

Finally, impose $\frac{\partial f}{\partial z} = P = xy + 4z^3$:

$$\frac{\partial f}{\partial z} = xy + h'(z) = xy + 4z^3 \quad \Rightarrow \quad h'(z) = 4z^3.$$

Integrate:

$$h(z) = z^4 + \text{constant}.$$

Step 4: Write the potential function:

$$f(x, y, z) = x^2 + xyz + y^3 + z^4 + C.$$

Thus, $\omega = df$ and is exact.

■

A.5 Inexact Differentials and Integrating Factors

Not all differential expressions are exact. However, multiplying ω by a suitable **integrating factor** $\mu(x, y)$ may render it exact:

$$\mu(x, y) \omega = \text{exact differential}.$$

In thermodynamics, heat δQ is inexact, but

$$\frac{\delta Q}{T} = dS$$

is exact. The integrating factor here is $\frac{1}{T}$, and S is the state function (entropy).

Example: Finding an Integrating Factor

Consider the differential form

$$\omega = (y) dx + (2x) dy.$$

Now,

$$\frac{\partial M}{\partial y} = 1, \quad \frac{\partial N}{\partial x} = 2,$$

so ω is *not* exact.

We look for an *integrating factor* $\mu(x)$ that depends only on x . Multiplying through:

$$\mu(x)\omega = \mu(x)y dx + 2\mu(x)x dy.$$

The exactness condition becomes

$$\frac{\partial}{\partial y}[\mu(x)y] = \mu(x), \quad \frac{\partial}{\partial x}[2\mu(x)x] = 2\mu'(x)x + 2\mu(x).$$

Exactness requires:

$$\mu(x) = 2\mu'(x)x + 2\mu(x).$$

Simplifying:

$$0 = 2x \mu'(x) + \mu(x),$$

which is a first-order ODE for μ . Solving:

$$\frac{\mu'(x)}{\mu(x)} = -\frac{1}{2x} \Rightarrow \mu(x) = C x^{-1/2}.$$

We can take $C = 1$ for simplicity, so:

$$\mu(x) = x^{-1/2}.$$

Multiplying the original form by $\mu(x)$ gives

$$x^{-1/2}y \, dx + 2x^{1/2} \, dy,$$

which now satisfies the exactness condition. Thus, there exists $f(x, y)$ such that

$$df = x^{-1/2}y \, dx + 2x^{1/2} \, dy.$$

Integrating $f_x = x^{-1/2}y$ with respect to x :

$$f(x, y) = 2x^{1/2}y + h(y).$$

Differentiating with respect to y :

$$f_y = 2x^{1/2} + h'(y),$$

and matching $f_y = 2x^{1/2}$ gives $h'(y) = 0$, so h is constant.

Therefore, the potential function is

$$f(x, y) = 2x^{1/2}y + C.$$

■

Exact Form $\Rightarrow$ Solution

Given a differential equation

$$\omega = M dx + N dy = 0,$$

if an integrating factor μ is found such that $\mu\omega$ is exact, then

$$\mu\omega = 0 \quad \Longrightarrow \quad df = 0,$$

where f is the potential function of $\mu\omega$.

Since $df = 0$ implies f is constant along solution curves, the general solution is

$$f(x, y) = C.$$

Example: For $\omega = y dx + 2x dy$, $\mu(x) = x^{-1/2}$ makes it exact, with potential

$$f(x, y) = 2\sqrt{x} y.$$

Thus the solution set of $\omega = 0$ is

$$2\sqrt{x} y = C.$$

A.6 Thermodynamic Summary Table

Quantity	Differential	Exact?
Internal Energy U	dU	Yes
Entropy S	dS	Yes
Work W	δW	No
Heat Q	δQ	No

A.7 Key Chain Rules and Partial Derivative Identities

Consider three variables x, y, z which depend on each other such that

$$x = x(y, z), \quad y = y(z, x), \quad z = z(x, y).$$

The total differentials of x and y can be written as

$$\begin{aligned} dx &= \left(\frac{\partial x}{\partial y} \right)_z dy + \left(\frac{\partial x}{\partial z} \right)_y dz, \\ dy &= \left(\frac{\partial y}{\partial z} \right)_x dz + \left(\frac{\partial y}{\partial x} \right)_z dx. \end{aligned}$$

Substituting the expression for dy into the differential for dx , we have

$$dx = \left(\frac{\partial x}{\partial y}\right)_z \left[\left(\frac{\partial y}{\partial z}\right)_x dz + \left(\frac{\partial y}{\partial x}\right)_z dx \right] + \left(\frac{\partial x}{\partial z}\right)_y dz.$$

Rearranging terms gives

$$dx = \left[\left(\frac{\partial x}{\partial y}\right)_z \left(\frac{\partial y}{\partial z}\right)_x + \left(\frac{\partial x}{\partial z}\right)_y \right] dz + \left(\frac{\partial x}{\partial y}\right)_z \left(\frac{\partial y}{\partial x}\right)_z dx.$$

Since x and z are independent variables, equating the coefficients of dx and dz on both sides yields

$$1 = \left(\frac{\partial x}{\partial y}\right)_z \left(\frac{\partial y}{\partial x}\right)_z, \quad (\text{A.1})$$

and

$$0 = \left(\frac{\partial x}{\partial y}\right)_z \left(\frac{\partial y}{\partial z}\right)_x + \left(\frac{\partial x}{\partial z}\right)_y. \quad (\text{A.2})$$

From these results, we derive the following fundamental identities:

A.7.1 Reciprocity Relation

Equation (A.1) immediately implies the *reciprocity relation*

$$\boxed{\left(\frac{\partial x}{\partial y}\right)_z = \frac{1}{\left(\frac{\partial y}{\partial x}\right)_z}}.$$

This relation expresses the inverse nature of partial derivatives when the same variable is held fixed.

A.7.2 Cyclic Relation (Triple Product Rule)

Using the reciprocal relation

$$\left(\frac{\partial x}{\partial z}\right)_y = \frac{1}{\left(\frac{\partial z}{\partial x}\right)_y},$$

and substituting it into Eq. (A.2), we obtain

$$\boxed{\left(\frac{\partial x}{\partial y}\right)_z \left(\frac{\partial y}{\partial z}\right)_x \left(\frac{\partial z}{\partial x}\right)_y = -1}.$$

This identity is known as the *cyclic relation*, or the *triple product rule*, and holds for any three interdependent variables x , y , and z .

A.7.3 Implicit Differentiation Rule

By combining the reciprocity relation with the cyclic (triple product) relation, we obtain

$$\boxed{\left(\frac{\partial y}{\partial x}\right)_z = -\frac{\left(\frac{\partial z}{\partial x}\right)_y}{\left(\frac{\partial z}{\partial y}\right)_x}}.$$

This identity provides a convenient rule for evaluating partial derivatives when the variables are related implicitly by an equation of state.

A.7.4 Chain Rule involving an Intermediate Variable

Suppose we have three variables (x, y, z) related by the constraint

$$f(x, y, z) = 0,$$

and another variable w that depends on two of them, say

$$w = w(x, y).$$

Assuming that this equation can be inverted to solve for x in terms of y and w , we write

$$x = x(y, w).$$

Substituting into the constraint equation yields

$$f(x(y, w), y, z) = 0,$$

from which we can solve for y as a function of z and w :

$$y = y(z, w).$$

We now differentiate x and y :

$$\begin{aligned} dx &= \left(\frac{\partial x}{\partial y}\right)_w dy + \left(\frac{\partial x}{\partial w}\right)_y dw, \\ dy &= \left(\frac{\partial y}{\partial z}\right)_w dz + \left(\frac{\partial y}{\partial w}\right)_z dw. \end{aligned}$$

Substituting the expression for dy into the equation for dx , we obtain:

$$dx = \left(\frac{\partial x}{\partial y}\right)_w \left(\frac{\partial y}{\partial z}\right)_w dz + \left[\left(\frac{\partial x}{\partial w}\right)_y + \left(\frac{\partial x}{\partial y}\right)_w \left(\frac{\partial y}{\partial w}\right)_z \right] dw.$$

On the other hand, since $x = x(z, w)$ indirectly through the composition $x(y(z, w), w)$, we can also write

$$dx = \left(\frac{\partial x}{\partial z} \right)_w dz + \left(\frac{\partial x}{\partial w} \right)_z dw.$$

Comparing the two expressions for dx , we identify the partial derivatives:

$$\boxed{\left(\frac{\partial x}{\partial z} \right)_w = \left(\frac{\partial x}{\partial y} \right)_w \left(\frac{\partial y}{\partial z} \right)_w}$$

and

$$\left(\frac{\partial x}{\partial w} \right)_z = \left(\frac{\partial x}{\partial w} \right)_y + \left(\frac{\partial x}{\partial y} \right)_w \left(\frac{\partial y}{\partial w} \right)_z$$

The second identity can also be obtained by differentiating the composed function

$$x = x(y, w) = x(y(z, w), w)$$

with respect to w , while keeping z fixed.

A.7.5 Application Examples

Suppose $S = S(T, V)$ represents entropy as a function of temperature T and volume V . Then the partial derivative of volume with respect to temperature at constant entropy is

$$\left(\frac{\partial V}{\partial T} \right)_S = - \frac{\left(\frac{\partial S}{\partial T} \right)_V}{\left(\frac{\partial S}{\partial V} \right)_T}.$$

Consider pressure $P = P(V, T)$ as a function of volume and temperature. Then, the derivative of temperature with respect to volume at constant pressure can be expressed as

$$\left(\frac{\partial T}{\partial V} \right)_P = - \frac{\left(\frac{\partial P}{\partial V} \right)_T}{\left(\frac{\partial P}{\partial T} \right)_V}.$$

Let the chemical potential $\mu = \mu(T, P)$ depend on temperature and pressure. The derivative of pressure with respect to temperature at constant chemical potential satisfies

$$\left(\frac{\partial P}{\partial T} \right)_\mu = - \frac{\left(\frac{\partial \mu}{\partial T} \right)_P}{\left(\frac{\partial \mu}{\partial P} \right)_T}.$$

A.8 Summary of Useful Partial Derivative Identities

Name	Identity
Reciprocity	$\left(\frac{\partial x}{\partial y}\right)_z = \frac{1}{\left(\frac{\partial y}{\partial x}\right)_z}$
Cyclic Rule	$\left(\frac{\partial x}{\partial y}\right)_z \left(\frac{\partial y}{\partial z}\right)_x \left(\frac{\partial z}{\partial x}\right)_y = -1$
Implicit Function Rule	$\left(\frac{\partial y}{\partial x}\right)_z = -\frac{\left(\frac{\partial z}{\partial x}\right)_y}{\left(\frac{\partial z}{\partial y}\right)_x}$
Chain Rule	$\left(\frac{\partial x}{\partial z}\right)_w = \left(\frac{\partial x}{\partial y}\right)_w \left(\frac{\partial y}{\partial z}\right)_w$

These mathematical tools are essential when working with thermodynamic identities, Maxwell relations, and potentials like Helmholtz or Gibbs free energy. Mastery of these rules enables clear and efficient manipulation of thermodynamic expressions.